

# EMF TEST REPORT

**Test Report No.** : OT-237-RWD-045

**Reception No.** : 2306001870

**Applicant** : Westcom Wireless Inc.

**Address** : 2773 Leechburg Road, Lower Burrell, Pennsylvania, 15068, United States

**Manufacturer** : Westcom Wireless Inc.

**Address** : 2773 Leechburg Road, Lower Burrell, Pennsylvania, 15068, United States

**Type of Equipment** : ProCom

**FCC ID.** : 2AO37ATLASLOUD

**Model Name** : ATLAS LM

**Multiple Model Name** : N/A

**Serial number** : N/A

**Total page of Report** : 7 pages (including this page)

**Date of Incoming** : July 17, 2023

**Date of issue** : July 25, 2023

## SUMMARY

The equipment complies with the regulation; *FCC CFR 47 PART 2.1091*

This test report only contains the result of a single test of the sample supplied for the examination.

It is not a generally valid assessment of the features of the respective products of the mass-production.

This report is not correlated with the "KS Q ISO/IEC 17025 and KOLAS accreditation" of Korean Laboratory Accreditation Scheme.



Tested by  
Su-Min, You / Sr. Engineer  
ONETECH Corp.

Reviewed by  
Tae-Ho, Kim / Chief Engineer  
ONETECH Corp.

Approved by  
Jae-Ho, Lee / Chief Engineer  
ONETECH Corp.

## CONTENTS

	<b>Page</b>
<b>1. VERIFICATION OF COMPLIANCE .....</b>	<b>4</b>
<b>2. GENERAL INFORMATION .....</b>	<b>5</b>
<b>2.1 Product Description .....</b>	<b>5</b>
<b>2.2 Alternative type(s)/model(s); also covered by this test report.....</b>	<b>5</b>
<b>3. EUT MODIFICATIONS.....</b>	<b>5</b>
<b>4. MAXIMUM PERMISSIBLE EXPOSURE .....</b>	<b>6</b>
<b>4.1 RF Exposure Calculation .....</b>	<b>6</b>
<b>4.2 EUT Description .....</b>	<b>6</b>
<b>4.3 Calculated MPE Safe Distance for Sig Fox .....</b>	<b>7</b>

**Revision History**

Rev. No.	Issue Report No.	Issued Date	Revisions	Section Affected
0	OT-237-RWD-045	July 25, 2023	Initial Release	All

### 1. VERIFICATION OF COMPLIANCE

Applicant : Westcom Wireless Inc.  
 Address : 2773 Leechburg Road, Lower Burrell, Pennsylvania, 15068, United States  
 Contact Person : Frank Girardi / President  
 Telephone No. : +1-724-337-1400  
 FCC ID : 2AO37ATLASLOUD  
 Model Name : ATLAS LM  
 Brand Name : N/A  
 Serial Number : N/A  
 Date : July 25, 2023

EQUIPMENT CLASS	DSS – PART 15 SPREAD SPECTRUM TRANSMITTER
E.U.T. DESCRIPTION	ProCom
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	KDB 447498 D01 General RF Exposure Guidance v06
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	Certification
Modifications on the Equipment to Achieve Compliance	None

- The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

## 2. GENERAL INFORMATION

### 2.1 Product Description

The Westcom Wireless Inc., Model ATLAS LM (referred to as the EUT in this report) is a ProCom. The product specification described herein was obtained from product data sheet or user's manual.

DEVICE TYPE	ProCom	
Temperature Range	-10 °C ~ 50 °C	
OPERATING FREQUENCY	902 MHz ~ 928 MHz	
MODULATION TYPE	GFSK	
RF OUTPUT POWER	Mode 1_Normal	22.73 dBm
	Mode 2_Long	28.73 dBm
	Mode 3_Repeat	28.17 dBm
ANTENNA TYPE	Helical Antenna	
ANTENNA GAIN	-0.65 dBi	
List of each Osc. or crystal Freq.(Freq. >= 1 MHz)	48 MHz	

### 2.2 Alternative type(s)/model(s); also covered by this test report.

-. None

## 3. EUT MODIFICATIONS

-. None

## 4. MAXIMUM PERMISSIBLE EXPOSURE

### 4.1 RF Exposure Calculation

According to the FCC rule 1.1310 table 1B, the limit for the maximum permissible RF exposure for an uncontrolled environment are  $f/1500$  mW/cm<sup>2</sup> for the frequency range between 300 MHz and 1 500 MHz and 1.0 mW/cm<sup>2</sup> for the frequency range between 1 500 MHz and 100 000 MHz.

The electric field generated for a 1 mW/cm<sup>2</sup> exposure is calculated as follows:

$$E = \sqrt{(30 * P * G) / d}, \text{ and } S = E^2 / Z = E^2 / 377, \text{ because } 1 \text{ mW/cm}^2 = 10 \text{ W/m}^2$$

Where

S = Power density in mW/cm<sup>2</sup>, Z = Impedance of free space, 377 Ω

E = Electric field strength in V/m, G = Numeric antenna gain, and d = distance in meter

Combining equations and rearranging the terms to express the distance as a function of the remaining variable

$$d = \sqrt{(30 * P * G) / (377 * 10 S)}$$

Changing to units of mW and cm, using P (mW) = P (W) / 1 000, d (cm) = 0.01 \* d (m)

$$d = 0.282 * \sqrt{(P * G) / S}$$

Where

d = distance in cm, P = Power in mW, G = Numeric antenna gain, and S = Power density in mW/cm<sup>2</sup>

### 4.2 EUT Description

Kind of EUT	ProCom
Device Category	<input type="checkbox"/> Portable (< 20 cm separation) <input checked="" type="checkbox"/> Mobile (> 20 cm separation) <input type="checkbox"/> Others
Exposure Evaluation Applied	<input checked="" type="checkbox"/> MPE <input type="checkbox"/> SAR <input type="checkbox"/> N/A

### 4.3 Calculated MPE Safe Distance for Sig Fox

According to above equation, the following result was obtained.

Operating Freq. (MHz)	Operating Mode	Target Power W/tolerance (dBm)	Max tune up power		Antenna Gain		Safe Distance (cm)	Power Density (mW/cm <sup>2</sup> ) @ 20 cm Separation	Limit (mW/cm <sup>2</sup> )
			(dBm)	(mW)	Log	Linear			
902.5	Normal	22.73 ± 0.5	23.23	210.38	-0.65	0.86	4.86	0.036 1	0.601 7
902.4	Long	28.73 ± 0.5	29.23	837.53			9.70	0.143 5	0.601 6
902.5	Repeat	28.17 ± 0.5	28.67	736.21			9.09	0.126 2	0.601 7

According to above table, for 902.4 MHz(Long Mode) , safe distance,

$$D = 0.282 * \sqrt{(837.53 * 0.86)/0.60} = 9.70 \text{ cm.}$$

For getting power density at 20 cm separation in above table, following formula was used.

$$S = P * G / (4\pi * R^2) = 837.53 * 0.86 / (4 * \pi * 20^2) = 0.143 5$$

Where:

S = Power Density,

P = Power input to the external antenna (Output power from the EUT antenna port (dBm) – cable loss (dB)),

G = Gain of Transmit Antenna (linear gain), R = Distance from Transmitting Antenna