STORM SEASON is here again!



is your Shelter from the storm

Add Tripp Lite power protection to every purchase to prevent equipment downtime, damage and data loss caused by severe weather

YOU BOUGHT...

Servers, switches, networking equipment



NOW ADD...

Tripp Lite rack-mount UPS systems, PDUs, rack enclosures, KVM switches and cooling



YOU BOUGHT...

PCs, workstation, computer peripherals and accessories



NOW ADD...

Tripp Lite desktop UPS systems and surge protectors



YOU BOUGHT...

Tablets, Chromebooks



NOW ADD...

Tripp Lite USB and AC charging stations and carts



YOU BOUGHT..

TVs, digital displays, monitors



NOW ADD...

Tripp Lite digital signage and connectivity solutions







SURGE PROTECTORS

Tripp Lite Model	Outlets/Cord
TLP606B	6/6 ft.
TLP606USB	6 + USB/6 ft.
TLP606DMUSB	6 + USB (with mounting clamp)/6 ft.
TLP608RUSBB	6 + USB/8 ft.
TLP712B	7/12 ft.
TLP725	7/25 ft.
SUPER7	7/7 ft.
SUPER7TEL15	7 + RJ11/15 ft.
TLP808	8/8 ft.
TLP810NET	8 + RJ11/RJ45/Coax/10 ft.
ISOBAR4ULTRA	4/6 ft.
ISOBAR6ULTRA	6/6 ft.
ISOBAR8ULTRA	8/12 ft.
IBAR12	12/15 ft.
IBAR12-20ULTRA*	12/15 ft.

POWER DISTRIBUTION UNITS (PDUs)

*20A circuit breaker.

SRCOOL7KRM

SRCOOL12K

SRCOOL18K

SRCOOL24K

SRCOOLNET



_						
Tripp Lite Model	Mounting	Nominal Voltage	Input Type/Plug	Outlet (Qty.) Type		
Basic						
PDU1215	Horiz./Vert.	120V	5-15P	(13) 5-15R		
PDU1220	Horiz./Vert.	120V	5-20P	(13) 5-15/20R		
Metered						
PDUMH15AT (ATS)	Horizontal	120V	2 x 5-15P	(8) 5-15R		
PDUMH20AT (ATS)	Horizontal	120V	2 x 5-20P, L5-20P	(16) 5-15/20R		
Monitored						
PDUMNH30HV	Horizontal	208/240V	L6-30P	(4) C19, (12) C13		
PDUMNV30HV2	Vertical	208/240V	L6-30P	(6) C19, (36) C13		
Switched						
PDUMH20HVATNET (ATS)	Horizontal	200-240V	2 x IEC-320-C20	(8) C13, (2) C19		
PDUMH30HVATNET (ATS)	Horizontal	208/240V	2 x L6-30P	(16) C13, (2) C19, (1) L6-30R		

RACK ENCLOSURES AND COOLING SOLUTIONS

COOLING SOLO HONS					
Tripp Lite Model	Size	Туре	Capacity		
Enclosures					
SR12UB	12U	Extended Depth	1,000 lbs.		
SR18UB	18U	Extended Depth	1,000 lbs.		
SR24UB	24U	Standard	1,000 lbs.		
SR25UB	25U	Standard	3,000 lbs.		
SR42UB	42U	Standard	3,000 lbs.		
SR48UB	48U	Standard	3,000 lbs.		
Wall-Mount I	Enclosures				
SRW6U	6U	Non-Swinging	200 lbs.		
SRW9U	9U	Non-Swinging	200 lbs.		
SRW10US	10U	Swinging	200 lbs.		
SRW12U	12U	Non-Swinging	200 lbs.		
SRW12US	12U	Swinging	200 lbs.		
SRW12U13	12U	Non-Swinging	200 lbs.		
SRW18US	18U	Swinging	250 lbs.		
Open Frame	Racks				
SRWO12UHD	12U	Wall-Mount	200 lbs.		
SRWO8U22	8U/12U/22U	Expandable Wall-Mount	150 lbs.		
SR2POST	45U	2-Post Rack	800 lbs.		
SR4POST	45U	4-Post Rack	1,000 lbs.		
Cooling Solu					

Rack-Mount Air-Conditioning Unit, 7,000 BTU, 120V, 60Hz

Portable Air-Conditioning Unit, 18,000 BTU, 208/240V, 60Hz

Web card for remote cooling management and monitoring of SRCOOL12K

Portable Air-Conditioning Unit, 24,000 BTU, 208/240V, 60Hz

Portable Air-Conditioning Unit, 12,000 BTU, 120V, 60Hz

UPS SYSTEMS

	Tripp Lite Model	Outlets	½ Load Runtime*	
Com	npact UPS Systems			
	BC350	6	10	133
*	INTERNET550U	8	5.6	
	INTERNET750U	12	9.4	4
	AVR550U	8	5.5	
*	AVR750U	12	8.6	
	AVR900U	12	8.4	
Digi	ital Tower and Rackn	nount UPS	Systems	- 6
	SMART1300LCDT	0	10	120

,,,,,,,,,,		0				
igital Tower and Rackm	ount UPS	Systems		th.	OF	
SMART1300LCDT	8	10		150		Į
OMNI1500LCDT	10	7.5		Same of		
SMART1500LCDT	10	10		- 1		
OMNI900LCD	8	10				
SMART1000LCD	8	10				
SMART1200LCCD	8	12				
SMART1500LCD	8	11.8				
SMC10002URM	6	15.6				
SMC15002URM	8	17.7			- 2	
martPro Rackmount UP	S Systems		100		0	

	SMC15002URM	8	17.7	
Sma	artPro Rackmount UPS	Systems		(A) (B)
	SMART500RT1U	7	14.6	
	SMART750RM1U	6	16.2	
	SMART1000RM1U	6	13.2	
	SMART1500RM2U	8	13	
	SMART1500RMXL2UA	8	14+	
	SMART2200RM2U	8	12	
	SMART2200RMXL2U	8	12+	
*	SMART3000RM2U	9	10+	
*	SMART3000RMXL2U	9	10+	
	SMART5000RT3U	14	38+	
Sma	artOnline Rackmount L	JPS Syste	ms	

	311171111300011130		301	
Sm	artOnline Rackmoun	t UPS Syst	tems	F 157-16
	SU750RTXL2U	6	11+	
	SU1000RTXL2UA	6	14+	2000
*	SU1000RTXLCD2U	6	14+	
	SU1500RTXL2UA	6	14+	
*	SU1500RTXLCD2U	6	14+	
	SU2200RTXL2UA	7	14+	
*	SU2200RTXLCD2U	7	12+	
	SU3000RTXL2U	7	15+	
	SU3000RTXL3U	9	14+	
*	SU3000RTXLCD3U	9	11+	
SN	MP Card for Remote <i>F</i>	Access		
	SNMPWEBCARD			
	esented in minutes, may vary			

*Represented in minutes, may vary based on load and battery condition. + Features expandable runtime with optional external battery packs.





ENERGY STAR®





Your World