

EV-UMBRA-PRO-IP65-600-S

Professional IP65 Weatherproof Batten

FEATURES

- Power monitoring (DT51)
- Tuneable white (DT8-Tc) controlled by DALI
- Flicker-free dimming controlled by DALI
- IP65 weatherproof rating and IK08 impact rating
- LED Lifetime >120,000 hours
- 10 Years Design Life at max. ambient
- Self-test (AS2293/IEC62034)
- DALI (IEC62386)
- Microwave sensor suitable for DALI-2 supporting IEC 62386-303
- Corridor mode function in standalone operation



| MECHANICAL | |
|-------------------|---------------|
| Body Material | Polycarbonate |
| Diffuser Material | Polycarbonate |
| Fitting Colour | Grey |
| IK Rating | IK08 |
| Installation Type | Surface mount |
| IP Rating | IP65 |

| ELECTRICAL | |
|---|---------|
| Electrical Rating | Class I |
| Input Frequency | 50 Hz |
| Input voltage | 230Vac |
| In Australia the Input voltage is defined as 230Vac -6%/+10%. This effectively means that the voltage range of these products are 216Vac - 253Vac or 240V +6% | |
| Maximum Wattage | 20 W |
| Power Factor | 0.95 |
| Standby Power | 0.3 W |

Standby power for maintained emergency devices is measured when the light is on and the charger is in standby. Typically charging occurs for the first 16 hours after the device is powered or after a discharge. For non-maintained emergency devices or DALI controlled devices this is measured when the light is off and charger is in standby mode.

| | |
|--|---------------------------------|
| Switch Type | Inbuilt Mains Rated DALI Switch |
| A Terminal input has been provided to allow the wiring of a Main rated switch input. This input can be programmed to switch any controlled area when using a DALI-2 compliant control system. This input supports IEC62386-301 (momentary or rocker switches), IEC62386-302 (on /off switches) and IEC62386-303 (mains rated sensor inputs). | |

| | |
|--------------------|------------|
| Working Temp Range | 0 to 40 °C |
|--------------------|------------|

| LAMP | |
|--|------------------------|
| Macadam Steps (SDCM) | 3-step MacAdam Ellipse |
| CCT Configuration | TUNEABLE WHITE |
| Full support for DALI-2 DT8 has been provided which allows White colour control on a compliant DALI-2 control system. This function can be used to set a desired colour or to transition between colours depending on the time of day. | |
| CRI | >84 |
| Lamp/LED Current | 650 mA |
| Lamp/LED voltage | 24 V |

| LED LIFETIME | | |
|---|-------------|-------------|
| LED Lifetime | >120000 hrs | |
| This is the Reported LED Lifetime in Hours based on TM-21. Ektor does not list the projected or calculated LED lifetime, which is normally longer as TM-21 Addendum B explicitly states "The Calculated and Projected Lp(Dk) are not to be reported". This Lifetime refers to the life of a single LED however the system life is longer since the probability and binomial distribution of all LEDs in the system means that the average led is performing above the specification and compensates for the LEDs falling below. | | |
| Ambient Temp (°C) | 25 °C | 40 °C |
| L90B10 | 43000 hrs | 43000 hrs |
| L80B10 | 90000 hrs | 90000 hrs |
| L70B10 | >120000 hrs | >120000 hrs |
| L70B50 | >120000 hrs | >120000 hrs |

This rating defines the performance of the led within its lifetime. L relates to lumen depreciation, where the proceeding number gives the resultant lumen output at the end of it reported lifetime. L70, would mean 30% lumen depreciation which means 70% of its initial output and is tested accordingly to TM-21. The B part refers to failures, which can be define as the percentage of LEDs which fall below the L value in the projected lifetime. A value of B10 refers to 10% failure and a value of B50 refers to 50% failure. After the defined lifetime, the system will reach the defined lumen depreciation and the average led



failures is defined by the B rating. The B rating is defined in and tested to IEC62717.

TM-21 Test Hours 20000 hrs

COLOUR TEMPERATURE

CCT 3000K to 6500K

CCT Colour Tunable White

System Lumens >2000 lm

DRIVER

Dimmable Yes

Driver Included Yes

Integrated Driver No

Driver Type DALI DT8 Dimmable

DALI DT8 ~ Includes DALI-2 Driver with full support for DT6 and DT8-tc allowing flicker free dimming and colour control with compliant DALI-2 Application controllers.

Power Monitoring DALI Device type 51 power monitoring

Inbuilt DALI-2 support for Device type 51 - Power monitoring for use with DALI-2 compliant control systems which allows the reporting of the products total power consumption for power aggregation and measurements.

Wiring Type Re-wireable terminal block (6 pin)

SENSOR (S SUFFIX)

Adjustable Detection Area / Sensitivity Yes

Adjustable Hold Time Yes

Adjustable Standby Level Yes

Adjustable Standby Period Yes

Corridor Function Yes

Dawn Reset No

Detection Range 10 m

Dusk Mode No

Lux Adjustment No

Manual Override Yes

Sensor Communication DALI 2

Inbuilt DALI-2 Sensor for use with DALI-2 Compliant control systems. Some features and functions are only available for use with DALI-2 Application controllers which support the features. This product also supports a standalone mode for limited use without a DALI-2 application controller.

Sensor Type Microwave

Switched Output No

Time Delay Via DALI mins

COMPLIANCE

Product Design Life 100000 hrs

The product design life relates to the total product life which includes LEDs, drivers and the enclosure. This is different to the LED lifetime which only refers to the lifetime of the LEDs. The product design life is calculated at the maximum ambient or working temperature of the product and takes into account the Maximum Daily Use.

Standards AS/NZS 60598.1
AS/NZS 60598.2.1
AS CISPR 15
AS/NZS 61347.1
AS/NZS 61347.2.13

WARRANTY

Commercial Use Warranty 2 Onsite, 3 RTB (Total 5 Years)

This product is covered with our extended commercial use warranty, which covers the product for up to 5-years. The first 2-years of the warranty is provided onsite within our terms and conditions and the remaining 3-year period is covered by a return to base warranty.

DIMENSIONS

Product Height 93 mm

Product Length 650 mm

Product Width 130 mm

ORDERING INFORMATION

Order code 12090

Description UMBRA PRO 600mm
Weatherproof LED batten with sensor

Item Code EV-UMBRA-PRO-IP65-600-S

LINE DRAWINGS

EV/UMBRA/PRO/IP65

