

Panasonic

Panasonic
LED Lighting
Solutions

The true essence of light





E14 LED Lamp

LDCCH03LG1E4 - LDCCH03WG1E4 - LDCCH03DG1E4

220-240V AC, E14 Type 3W LED Lamp

*Excellent LED Lamp within gorgeous classic appearance




Thanks to its cutting edge technology, E14 type LED lamp is able to emit light with clean and panoramic angle, creating alight and homey space.

Product benefits:

- Low energy consumption
- Easy replacement of classic lamps
- Instant light with no warm-up time

Areas of application:

- Domestic applications
- General illumination
- Suitable to use with chandeliers



TECHNICAL SPECIFICATIONS

	LDCCH03LG1E4	LDCCH03WG1E4	LDCCH03DG1E4
Model Name:	C37 3.0W 2700K E14	C37 3.0W 4000K E14	C37 3.0W 6500K E14
Stock Code:	LDCCH03LG1E4	LDCCH03WG1E4	LDCCH03DG1E4
Input Voltage (AC) (V)	230V	230V	230V
Tolerance Voltage Range:	220-240V	220-240V	220-240V
Power Consumption (typical) (W)	3.0W	3.0W	3.0W
Wattage equivalent compared to incandescent	25W	25W	25W
Input Frequency (Hz)	50/60Hz	50/60Hz	50/60Hz
Life (h)	15000H	15000H	15000H
CCT (Correlated color temp.) (K)	2700K	4000K	6500K
Lumen (lm)	270lm	290lm	290lm
Enegy label	A++	A++	A++
Optic Angle	200°	200°	200°
CRI (color rendering index)	CRI80	CRI80	CRI80
Standard deviation of color matching	≤6	≤6	≤6
Startup time	<0.5S	<0.5S	<0.5S
IP rating	IP20	IP20	IP20
Fixture Dimension (mm)	100*37	100*37	100*37
Total Weight (Kg)	0.03Kg	0.03Kg	0.03Kg
Humidity (Non condensing)	<90%	<90%	<90%
Operating Temperature range °C	-20-40°	-20-40°	-20-40°
Storage Temperature Range	-20-60°	-20-60°	-20-60°
Product Material	Plastic	Plastic	Plastic
Diffuser material	PC	PC	PC
Base Type	E14	E14	E14
RoHS compliant	YES	YES	YES
Mercury free, no IR or UV radiation	YES	YES	YES
Certificates	CE, ERP, LVD, RoHS, SEPRO, EAC	CE, ERP, LVD, RoHS, SEPRO, EAC	CE, ERP, LVD, RoHS, SEPRO, EAC





E14 LED Lamp

LDCCH05LG1E4 - LDCCH05WG1E4- LDCCH05DG1E4

220-240V AC, E14 Type 5W LED Lamp

*Excellent LED Lamp within gorgeous classic appearance




Thanks to its cutting edge technology, E14 type LED lamp is able to emit light with clean and panoramic angle, creating alight and homey space.

Product benefits:

- Low energy consumption
- Easy replacement of classic lamps
- Instant light with no warm-up time

Areas of application:

- Domestic applications
- General illumination
- Suitable to use with chandeliers



TECHNICAL SPECIFICATIONS

	LDCCH05LG1E4	LDCCH05WG1E4	LDCCH05DG1E4
Model Name:	C37 5.0W 2700K E14	C37 5.0W 4000K E14	C37 5.0W 6500K E14
Stock Code:	LDCCH05LG1E4	LDCCH05WG1E4	LDCCH05DG1E4
Input Voltage (AC) (V)	230V	230V	230V
Tolerance Voltage Range:	220-240V	220-240V	220-240V
Power Consumption (typical) (W)	5.0W	5.0W	5.0W
Wattage equivalent compared to incandescent	40W	40W	40W
Input Frequency (Hz)	50/60Hz	50/60Hz	50/60Hz
Life (h)	15000H	15000H	15000H
CCT (Correlated color temp.) (K)	2700K	4000K	6500K
Lumen (lm)	440lm	455lm	455lm
Eney label	A+	A+	A+
Optic Angle	200°	200°	200°
CRI (color rendering index)	CRI80	CRI80	CRI80
Standard deviation of color matching	≤6	≤6	≤6
Startup time	<0.5S	<0.5S	<0.5S
IP rating	IP20	IP20	IP20
Fixture Dimension (mm)	100*37	100*37	100*37
Total Weight (Kg)	0.03Kg	0.03Kg	0.03Kg
Humidity (Non condensing)	<90%	<90%	<90%
Operating Temperature range °C	-20-40°	-20-40°	-20-40°
Storage Temperature Range	-20-60°	-20-60°	-20-60°
Product Material	Plastic	Plastic	Plastic
Diffuser material	PC	PC	PC
Base Type	E14	E14	E14
RoHS compliant	YES	YES	YES
Mercury free, no IR or UV radiation	YES	YES	YES
Certificates	CE, ERP, LVD, RoHS, SEPRO, EAC	CE, ERP, LVD, RoHS, SEPRO, EAC	CE, ERP, LVD, RoHS, SEPRO, EAC





E14 LED Lamp

LDCCH07LG1E4 - LDCCH07WG1E4 - LDCCH07DG1E4

220-240V AC, E14 Type 6.5W LED Lamp

*Excellent LED Lamp within gorgeous classic appearance




Thanks to its cutting edge technology, E14 type LED lamp is able to emit light with clean and panoramic angle, creating alight and homey space.

Product benefits:

- Low energy consumption
- Easy replacement of classic lamps
- Instant light with no warm-up time

Areas of application:

- Domestic applications
- General illumination
- Suitable to use with chandeliers



TECHNICAL SPECIFICATIONS

	LDCCH07LG1E4	LDCCH07WG1E4	LDCCH07DG1E4
Model Name:	C37 6.5W 2700K E14	C37 6.5W 4000K E14	C37 6.5W 6500K E14
Stock Code:	LDCCH07LG1E4	LDCCH07WG1E4	LDCCH07DG1E4
Input Voltage (AC) (V)	230V	230V	230V
Tolerance Voltage Range:	220-240V	220-240V	220-240V
Power Consumption (typical) (W)	6.5W	6.5W	6.5W
Wattage equivalent compared to incandescent	50W	50W	50W
Input Frequency (Hz)	50/60Hz	50/60Hz	50/60Hz
Life (h)	15000H	15000H	15000H
CCT (Correlated color temp.) (K)	2700K	4000K	6500K
Lumen (lm)	630lm	650lm	650lm
Eney label	A+	A+	A+
Optic Angle	200°	200°	200°
CRI (color rendering index)	CRI80	CRI80	CRI80
Standard deviation of color matching	≤6	≤6	≤6
Startup time	<0.5S	<0.5S	<0.5S
IP rating	IP20	IP20	IP20
Fixture Dimension (mm)	107*37	107*37	107*37
Total Weight (Kg)	0.03Kg	0.03Kg	0.03Kg
Humidity (Non condensing)	<90%	<90%	<90%
Operating Temperature range °C	-20-40°	-20-40°	-20-40°
Storage Temperature Range	-20-60°	-20-60°	-20-60°
Product Material	Plastic	Plastic	Plastic
Diffuser material	PC	PC	PC
Base Type	E14	E14	E14
RoHS compliant	YES	YES	YES
Mercury free, no IR or UV radiation	YES	YES	YES
Certificates	CE, ERP, LVD, RoHS, SEPRO, EAC	CE, ERP, LVD, RoHS, SEPRO, EAC	CE, ERP, LVD, RoHS, SEPRO, EAC

