

LFX/FL/80W/BRZ/50K LED FLOOD LIGHT FIX SUNLITE

Item: 49172-SU



Fixture Life Hours 50000 Hours Material Metal Lens Finish Clear

Bulb Integrated LED

Finish Bronze Lumens Per Watt (LPW) 117.09 Life (based on 3hr/day) 45.7

Safety Rating ETL Listed - Wet Location

Dimmable True Dimming Type 0-10V DLC True

Fixture Characteristics

Number of Lights 1 - Light Mounting Pole **Use Location** Outdoor

Electrical Characteristics

Watts 80 Volts 120-277 250-400 **Equivalent Watts** LED Chip Manufacturer Seoul COB

Number of LEDs 3 Power Factor 0.92

Operating Temperature -40° to 40° C

Light Characteristics

Brightness 9367 Lumens

Color Accuracy (CRI) 70

Light Appearance Super White 5000K Color Temperature Beam Angle 100°-80°

Product Dimensions

Item Dimensions (in) (W) 9.45 (H) 7.87 (D) 13.78 Package Dimensions (in) (W) 14.64 (H) 10.23 (D) 13.70

Product Data

Item Number 49172-SU Barcode on SKU 653703491721 **Brand** SUNLITE

LFX/FL/80W/BRZ/50K Description

DLC File Number PTBF4LPQ



Sunlite 49172-SU LED Outdoor Floodlight Fixture, 50K - Super White, 9367 Lumen, 80 Watt, Bronze Finish

- LED TECHNOLOGY Sunlite LED Floodlight Fixtures provide ample illumination for outdoor spaces while saving energy. Each fixture contains 3 high output LEDs and an adjustable conduit mount base so it can be positioned it for optimal coverage.
- o ENERGY EFFICIENT Each fixture uses only 80 of energy. Estimated yearly energy cost is a low \$9.64. (Based on 3 hours/day use at \$0.11/kWh) With a 50,000 hour lifespan these fixtures will provide significant savings in electricity over their lifetime and require no maintenance.
- o HIGH LUMEN OUTPUT Each fixture contains only 3 LEDs but gives off a bright 9367 lumen with 5000K super white color temperature.
- o TASK AND SECURITY LIGHTING These commercial grade fixtures are made from die-cast aluminum. Ideal for activity space lighting like walking paths, sports venues, backyards and playgrounds. Use for landscape lighting, security lighting or outdoor task lighting in residential or commercial locations.
- ETL AND DLC LISTED These fixtures are ETL Listed for wet location installation and DLC Listed for quality and efficiency. They operate on 120-277 volt service.





