

Power It! Power Strip with 6 Right-Angle Outlets and 15-ft. Cord

MODEL NUMBER: TLM615NCRA



Description

Tripp Lite's Power It! TLM615NCRA power strip offers reliable, convenient and cost-effective power distribution for appliances, power tools, lighting and other electrical equipment. Includes 6 right-angle NEMA 5-15R outlets, 15-foot AC power cord and keyhole mounting slots. Multi-outlet strip reduces cable clutter and enables the connection of multiple electrical devices to a single AC wall socket. Features rugged metal case to stand up to the most demanding environments, illuminated power switch with transparent cover to prevent accidental shutoff and 15A integrated circuit breaker to prevent dangerous overloads.

INPUT/OUTPUT: Input: NEMA 5-15P/Output: 6 NEMA 5-15R

ELECTRICAL: 120V AC, 50/60Hz, 15A

FORMAT: Corded power distribution strip with right-angle outlets

Features

- Multi-outlet power strip offers reliable, convenient and cost-effective power distribution for appliances, power tools, lighting and other electrical equipment
- Includes 6 right-angle NEMA 5-15R outlets
- Illuminated on/off switch provides one-touch power control for connected equipment
- Transparent switch cover snaps tight to prevent accidental shutoff
- · Convenient keyhole slots provide secure mounting options for a wide variety of surfaces and applications
- 15A power handling capacity with integrated circuit breaker
- 120V AC, 50/60Hz electrical compatibility
- 15-foot AC power cord
- Rugged metal case provides extra safety and durability
- UL certification

Specifications

Highlights

- 6 right-angle outlets
- Illuminated on/off switch with cover
- 15-amp circuit breaker
- 15 ft. power cord
- Rugged metal case
- Keyhole mounting slots

Applications

- Offers a reliable, convenient and cost-effective method of power distribution for appliances, power tools, lighting and other electrical equipment in home, office or worksite.
- Unfiltered electrical pass-through makes the power strip ideal for distributing alternate waveform UPS or generator power to connected equipment.

Package Includes

- TLM615NCRA power strip
- Warranty information
- Instruction manual



OVERVIEW		
Intended Application	Computer Networks	
ОИТРИТ		
Frequency compatibility	50 / 60 Hz	
Output watts	1800	
Circuit Breaker (amps)	15	
Overload protection	15A circuit breaker	
Outlet quantity / type	6 NEMA 5-15R	
Transformer accommodation	Right-angle outlets provide superior accommodation for transformers	
Outlet orientation	Single row of 6 (right-angle)	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	15A 120V	
Input connection type	NEMA 5-15P	
Input cord length (ft.)	15	
Input cord length (m)	4.5	
Input cord gauge, type	SJT 14AWG	
Voltage compatibility (VAC)	120	
LEDS ALARMS & SWITCHES		
Switches	Illuminated on/off switch controls power to all outlets	
Locking switch cover	Transparent switch cover snaps tight to prevent accidental shutoff	
PHYSICAL		
Shipping Dimensions (HWD/in)	15.5 x 6.5 x 2.25	
Shipping Dimensions (HWD/cm)	39.4 x 16.5 x 5.7	
Shipping weight (lbs)	3	
Shipping weight (kg)	1.4	
Unit Dimensions (HWD/in)	13.75 x 2.5 x 2	
Unit Dimensions (HWD/cm)	35 x 6.35 x 5.1	
Unit weight (lbs)	2.8	
Unit weight (kg)	1.3	
Material of construction	Metal case	



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Integrated keyhole mounting tabs	Keyhole slots enable mounting to a variety of surfaces	
Receptacle Color	Light Gray	
AC line cord color	Light Gray	
Style	Strip	
Outlets center to center measurement	41.3mm	
Keyhole slot center to center measurement	Distance between mounting tabs = 203.20mm; Distance between end tabs = 330.17mm	
CERTIFICATIONS		
Additional International Approvals	Complies with RoHS (Restriction of Hazardous Substances Directive)	
UL1363 (Power Tap)	UL1363	
cUL / CSA (Canada)	cUL	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2014 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.