ThinkCentre M630e Tiny 10YM006GAC

Product

ThinkCentre M630e Tiny

Region

LA

Country/Region

Argentina

Machine Type

10YM

TopSeller

No

Processor

Intel Core i3-8145U (2C / 4T, 2.1 / 3.9GHz, 4MB)

Chipset

Intel SoC Platform

Graphics

Integrated Intel UHD Graphics 620

Memory

1x 8GB DDR4-2666

Storage

1x 128GB SSD M.2 2242 PCIe 3.0x2 NVMe

Optical

None

Speaker

1.5Wx1

Ethernet

Integrated 100/1000M

WLAN + Bluetooth

Intel 3165 11ac. 1x1 + BT4.2

Optional Rear Ports

None

Chassis Intrusion Switch

Chassis Intrusion Switch

Kensington Cable Lock

None

Adapter Cage

None

Toolless Chassis Screw

None

Dust Filter

None

VESA Mount

None

Color Black

Stand None

Kevboard

USB Calliope Keyboard, Black, Spanish (LA)

USB Calliope Mouse

Power Supply

65W 88% Adapter

Additional Certificates

None

Monitor Cable

None

System Management

None

Operating System

None

Bundled Software

None

Base Warrantv

1-year, Onsite

Bundled Service

None

EAN/UPC/JAN

195235922590

End of Support

N/A

Announce Date

2020-08-04

Recommended Services

5Y Premier Support Upgrade from 1Y Onsite (5WS0T36190)

Better

4Y Premier Support Upgrade from 1Y Onsite (5WS0T36168)

3Y Premier Support Upgrade from 1Y Onsite (5WS0T36147)



WWW.LENOVO.COM

Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area.

Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. Lenovo provides this publication "as is" without warranty of any kind, either express or implied, including the implied warranties of merchantability or fitness for a particular purpose.



https://psref.lenovo.com

Visit psref website for the latest version of Product specifications Reference. © Lenovo, 2020. All rights reserved.



ThinkCentre M630e Tiny Platform Specifications

Processor	Intel® Pentium®, or 8th Generation Intel Core™ i3 / i5 Processor						Security chip	None					
	Processor	Cores / Threads	Frequency Base/Max(GHz)	Cache	Memory Support (Up to)	Integrated Graphics	Security features	Firmware TPM 2.0, integrated in chipset					
	Pentium Gold 5405U	2 / 4	2.3G	2 MB	DDR4-2133	UHD 610			 Security slot (in rear for optional Kensington® MicroSaver® cable) Boot sequence control Boot without keyboard and mouse 				
	Core i3-8145U	2/4	2.1G / 3.9G	4 MB	DDR4-2400	UHD 620		Chassis intrusion switch Power-on password Administrator password					
	Core i5-8265U	4/8	1.6G / 3.9G	6 MB	DDR4-2400	UHD 620							
Memory	16GB max, DDR4-266 * System automaticall	ets, non-ECC with lower memo	orv controller	Keyboard	Hard disk password Some: Lenovo Calliope Keyboard (USB connector), black								
Storage	* System automatically clocks down for the processors with lower memory controller Some: Hard Drive / SATA 6.0Gb/s, 2.5", 5400 rpm or 7200 rpm Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Some: M.2 SSD (2280) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: M.2 SSD (2242) / PCIe NVMe, PCIe 3.0 x 2, 16Gb/s One onboard SATA 6.0Gb/s connector						Mouse	Some: Lenovo Calliope Keyboard (USB connector), black Some: Lenovo Calliope Mouse (USB connector), black					
Onboard SATA							Mechanical	1 //					
Graphics	Intel HD Graphics 610/620 in processor, uses main memory, DirectX [®] 12, one DisplayPort™, one HDMI, up to 2 independent displays; Max resolution: 4096x2304 (DP)@60Hz; 4096x2304 (HDMI)@24Hz Optional DP to VGA dongle or DP to HDMI 1.4 dongle						1			Dimens	ions (WxDxH)	Weight (Approx.)	
Monitor cable								Tiny on	ly	179mm X 183n	" (1.5" with rubber feet) nm X 34.5mm (37mm rubber feet)	2.91 lb (1.32 kg), vary by config	
Chipset	Intel SoC (System on Chip) platform						VESA mount Floor Stand	Optional VESA mount bracket kit, supports VESA 75mm and 100mm					
Front ports* (Std.) One USB 3.1 Gen1, one USB 3.1 Type-C Gen 1, one microphone (3.5mm),						. 1001 Otalia	Optional system floor stand for vertical orientation						
one headphone / microphone combo jack (3.5mm)					Power supply	Some: 65 watts adapter, autosensing, 88% PSU							
Rear ports* (Std.) Two USB 3.1 Gen1, two USB 2.0, one ethernet (RJ-45), one DisplayPort, one HDM Rear ports* (Opt.) None						Limited warranty							
* Depending on many factors, actual data transfer speed may be lower than theoretical speed									, ,		e / service upgrades ava	allable	
Audio support	Realtek ALC233VB / internal speaker (1.5 watt)						Preload	Preloaded operating system Some: Windows® 10 Pro 64-bit Some: Windows 10 Home 64-bit Preloaded applications (only some listed) Lienovo Vantage Microsoft Office preloaded; purchase a product key to activate LinkedIn					
WLAN													
							Environment	ENERGY STAR® 8.0, EPEAT™ Silver rating, ErP Lot 3, TCO, RoHS-compliant, WEEE, REACH					
Bluetooth													
Ethernet								MIL-STD-810G (Low Pressure [Altitude], High Temperature, Low Temperature, Temperature Shock, Humidity, Sand and Dust, Vibration, Shock, Fungus, Solar Radiation)					
]						
Ethernet (Opt.) Manageability	None							Radiation	on)	-			

















