

DisplayPort to HDMI Adapter Cable (M/M), 20 ft. (6.1 m)

MODEL NUMBER: P582-020



Converts a DisplayPort audio/video signal for display on an HDMI monitor, projector or television.

Description

The P582-020 DisplayPort to HDMI Adapter Cable connects a DisplayPort computer to the HDMI port on a monitor, projector or television. With a DisplayPort male connector on one end and an HDMI male connector on the other, this cable requires no separate adapter. It lets you use your existing HDMI display instead of buying a new DisplayPort monitor.

Ideal for displaying crystal-clear video on a large monitor or digital sign, this 20-ft. (6.09 m) cable supports high-definition video resolutions up to 1920 x 1080 (1080p), as well as rich, full audio (if your DisplayPort card supports audio passthrough) and HDCP (High-Definition Content Protection). This in-line passive adapter is designed for use with Dual-Mode (DP++) DisplayPort graphics cards.

Nickel-plated connectors and gold-plated contacts ensure excellent conductivity. Integral strain relief ensures the cable and molded connectors last a long time. Flexible PVC jacket makes the cable easy to install in tight corners and other areas where space is restricted.

Features

Sends High-Definition DisplayPort Audio/Video Signals to an HDMI Display

- Connects DisplayPort computer to HDMI-enabled monitor, projector or TV
- Ideal for displaying video on large monitor or digital sign
- DisplayPort and HDMI male connectors
- · No separate adapter required

Vibrant Video and Sound Quality

- Supports high-definition video resolutions up to 1920 x 1080 (1080p)
- Supports audio and HDCP
- This product is a passive adapter and requires that the connected computer has a DP++ (DisplayPort ++) dual-mode port

Superior Materials for Superior Performance

- Nickel-plated connectors and gold-plated contacts for excellent conductivity
- · Integral strain relief for long life

Highlights

- Supports video resolutions up to 1920 x 1080 (1080p)
- · Supports audio and HDCP
- No separate adapter required
- Designed for Dual-Mode DisplayPort graphics cards
- · Gold-plated contacts
- This product is a passive adapter and requires that the connected computer has a DP++ (DisplayPort ++) dualmode port

System Requirements

 Not for use with MST Hubs. For compatibility with MST Hubs, use a Displayport 1.2 compliant product such as P582-020-HD-V2A

Package Includes

 P582-020 DisplayPort to HDMI Adapter Cable (M/M), 20-ft. (6.09 m)



• Flexible PVC jacket for easy installation in tight corners

Specifications

OVERVIEW		
UPC Code	037332192875	
Product Type	Passive Cable	
Technology	HDMI; DisplayPort	
Cable Type	Passive	
VIDEO		
Max Supported Video Resolution	1920 x 1200 (1080p)	
Wax Supported Video Resolution	1525 X 1256 (1666P)	
PHYSICAL		
Color	Black	
Cable Jacket Color	Black	
Cable Jacket Material	PVC	
Cable Jacket Rating	VW-1	
Cable Outer Diameter (OD)	6.5mm	
Wire Gauge (AWG)	28	
Cable Length (ft.)	20	
Cable Length (m)	6.10	
Cable Length (in.)	240	
Shipping Dimensions (hwd / in.)	1.25 x 10.70 x 5.20	
Shipping Dimensions (hwd / cm)	3.18 x 27.18 x 13.21	
Shipping Weight (lbs.)	0.80	
Shipping Weight (kg)	0.36	
Unit Dimensions (hwd / in.)	1.250 x 10.700 x 5.200	
CONNECTIONS		
Side A - Connector 1	DISPLAYPORT (MALE)	
Side B - Connector 1	HDMI (MALE)	
STANDARDS & COMPLIANCE		
Product Compliance	Trade Agreements Act (TAA)	
WARRANTY & SUPPORT		
WARRANTI & OUT ON		



Product Warranty Period (Worldwide)	3-year limited warranty
--	-------------------------



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.