Panasonic



INSPIRING LIGHTNESS - CX10 | X1500 | X2000

All-round Brilliance

Panasonic's 4K camcorders combine the latest technologies to a single device. Overleaf you will see how the three models compare. Whichever you go for, you're getting a great low light sensor, the peace of mind of dual card recording, superb codecs, live streaming, 5-axis stabilisation for super steady shots, and super slow-motion recording. Add ND filters, a 24x zoom and InfraRed filming and for a superb all-round package.

Multi-purpose Workhorse

Streaming and recording are standard on all versions. Removing the XLR adapter / handle unit (optional with the X1500) means that it's also

fantastic as a low-profile multi-camera production camera, great for YouTube studios, fly-on-the-wall documentaries and even theatre production.

Tomorrow's Workflows

While all models offer the future-proofed HEVC recording, CX10 gives you features never seen before on such a small and inexpensive camera. P2 recording offers the codecs used by news teams to shoot and share high quality footage at low bitrates. You also get wired IP networking and the option of NDI. With these technologies, you can plug the camera into Ethernet networks for multi-camera productions without the need for expensive HDMI or SDI cabling.

- COMPARISON MATRIX -AG-CX10 HC-X2000 HC-X1500 - SYSTEM -Sensor 1/2.5-type (inch) MOS Sensor | 8.29 megapixels Incorporates the ON/OFF control function IR Filter 3.5" LCD Monitor & LED Video Light Body: approx. 0.9kg (1.98lb) (excl. handle, lens hood, battery, & accessories) Weight Shooting: approx. 1.5kg (3.31lb) (incl. handle, lens hood, battery, & eyecup) **Power Supply** 7.28V (5,900mAh battery) / 12V (AC Adaptor) - LEICA DICOMAR LENS -F Value F18-40 Optical Zoom 24x (25-600 mm) with 62mm filter diameter **ND Filter** 1/4, 1/16, 1/64, OFF Image Stabiliser Ball O.I.S., 5-Axis HYBRID O.I.S. - RECORDER -Recording Media SDHC/SDXC Memory Card Super Slow Recording HD Frame Rate 120/100 fps Video Compression H.264 | H.265 / HEVC | H.264 AVCHD P2 LongG 50 / LongG 25 X X - VIDEO OUTPUT -3G-SDI X HDMI (UHD/HD) Full Size - AUDIO -Stereo Microphone Built-in stereo microphone | Microphone Input: 3.5mm stereo mini jack VW-HU1 Detachable Handle Unit Included Optional XLR Input with 48v phantom power Dual X - LIVE STREAMING -Unicast, Multicast | RTSP/RTP/RTMP/RTMPS **IP Streaming** 2.4GHz Wi-Fi IEEE 802.11b/g/n USB LAN Conversion Adaptor (VW-UEA1)



NDI licence option

Holdan Limited

X