# **TVW-300**



# 4-Monitor Tower Standalone TV Wall

- 4-bay Tower Standalone TV Wall
- Location-based management with e-Map
- Intel Core i7-8700K, 16GB
- Independent Graphics Card

# Specifications

# **Device**

Product Type	Standalone TV Wall
Maximum number of Monitors	4

### **Hardware**

Haldwale	
CPU	Intel Core i7-8700K
RAM	16GB
Graphics Card or GPU	NVIDIA GeForce GTX1650 x 2

#### License

License required	No

#### **Live View**

Maximum display layout	64 (per monitor)
Embedded websites in Live View	Display and connect to pre-configured embedded website


Local Display performance	1 monitor: recommended total up to 64 channels (720P/15fps, 480P/15fps), 53 channels (720P/30fps), 43 channels (1080P/15fps), 23 channels (1080P/30fps) 2 monitors: recommended total up to 128 channels (720P/15fps, 480P/15fps), 106 channels (720P/30fps), 86 channels (1080P/15fps), 46 channels (1080P/30fps) 4 monitors: recommended total up to 128 channels (1080P/15fps), 96 channels (720P/30fps), 84 channels (1080P/15fps), 44 channels (1080P/30fps) *The performance was tested on the camera settings: H.264 3Mbps
	*Recommended one monitor per graphic card via HDMI/DVI/DP, maximum two graphic cards per TV Wall Server *The display performance may vary depending on camera settings, the number of channels, current layout, CPU performance and internet infrastructure
Мар	
е-Мар	Yes
Google Map	Yes
Video	
Compression	H.265, H.264, MPEG-4, MJPEG
Hardware Accelerated Decoding	H.264, H.265
Audio	
Audio Type	2-way, Mic-in, Line-in, Line-out
Network	
Ethernet Port	Non-PoE: 1 port(s), Ethernet (1000 Base-T), RJ-45 connector
System	
Client PC Operating System	Windows 7 SP1, Windows 8.1, Windows 10, Windows Server 2008 R2 SP1, Windows Server 2012 R2, Windows Server 2016
Server Operating System	Windows 10 IoT
USB	2-Port USB 2.0, 6-Port USB 3.0, 1-Port USB 3.1
Integration	
Web Browser	IE 11 (Please verify that your computer meets the minimum system requirements for Internet Explorer from Microsoft website.)
Third-party Integration	Point of Sale (POS), Access Control, Network I/O
Storage	
System Drive	SSD, 256GB
Storage Bay	SATA, Max. 4 Disk(s) (without storage disks)
HDD Size	3.5"
Interface	
Expansion Slots Available	1 x PCle 3.0 (x4) 3 x PCle 3.0 (x1)
Local Access	USB keyboard & mouse
Local Display Interface	HDMI x 3, DVI x 3, Display Port x 3
General	
Power Source	AC 100-240V
Power Consumption	650 W (AC)





# Standalone TV Wall

Power Supply	650W
Dimensions	(W x H x D): 177mm x 424mm x 527mm (6.97" x 16.69" x 20.75")
Bundled Accessories	Power cord
Fan	Yes
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)
Operating Humidity	0% - 85% RH
Warranty	3 Year(s). For extended warranty offering, see http://www.acti.com/support/warranty

# Dimension Diagram







Unit: mm [inch]

# Related Products

# Network & Storage Peripherals - Hard Disk

PHDD-1E16



2.5" 256G SATA SSD System drive with Windows 10 and TV Wall Server 1 for TVW-300