

Tripp Lite

1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

Android devices will require a USB Host Mode (OTG) cable (Tripp Lite U052-06N) to connect the U209-005-DB25 to the device.

USB-to-Serial Cable Adapter (USB-A to DB25 M/M)

MODEL NUMBER: U209-005-DB25







Description

If you need to connect a PDA, digital camera, modem or anISDN terminal with a serial port to your laptop or tablet, then Tripp Lite'sU209-005-DB25 USB-to-Serial Cable Adapter is a great choice. The U209-005-DB25allows you to connect legacy RS232 peripherals with either a 9-pin DB9 or25-pin DB25 connector to your computer's USB port. The U209-005-DB25 comes withUSB A (Male) and DB9 (Male) connectors; the included DB9-to-DB25 cable adaptercan be inserted onto the DB9 connector for use in USB-to-DB25 (M/M) connections. The cable is plug-and-play and requires no external power. The U209-005-DB25supports data transfer rates up to 230 kbps and has a 5 ft. overall length. Itis compatible with Windows, Mac and Linux operating systems, as well as Androidtablets / phones with a USB Host Mode (OTG) cable (Tripp Lite U052-06N) and OS version 3.2 and above.

Features

- Connect a RS232 serial device to the USB port on your computer
- Connectors: USB-A (M); DB25 (M); DB9 (M)
- . No external power is required
- Supports data transfer rates up to 230 kbps
- Premium double-shielded cable with gold-plated contacts, tinned copper braid and an aluminum Mylar foil shield that eliminates cross-talk and reduces
 EMI/RFI interference
- Compatible with Windows, Mac and Linux computers
- Compatible with Android tablets / phones with USB Host Mode (OTG) support and OS version 3.2 and above

Specifications

OVERVIEW

Highlights

- 5 ft. cable length
- · No external power is required
- Compatible with Windows, Mac and Linux computers, and Android tablets / phones (See System Requirements)
- Need drivers? Click on the "SUPPORT" tab below

System Requirements

- Compatible with Windows 2000, XP, Server 2003, Vista, 7, Server 2008, 8, 8.1, and Server 2012
- Compatible with Mac OS X 10.6 through 10.10
- Compatible with Linux Redhat 7.3, 8.0 and 9.0 (Linux Kernel 2.4.31 and above; already includes built-in drivers)
- Android devices will require a USB Host Mode (OTG) cable (Tripp Lite's U052-06N) to connect the U209-005-DB25 to the device.

Package Includes

- U209-005-DB25 USB-to-DB25
 Serial Cable Adapter
- DB9-to-DB25 Adapter
- Owner's manual



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Intended Application	Connecting Peripherals
Style	USB
Model Type	Adapters
Cable Types	USB
INPUT	
Cable Length (ft.)	5
Cable Length (m)	1.52
PHYSICAL	
Color	Black
CONNECTIONS	
Connector A	USB A (MALE)
Connector B	DB9 (MALE)
Connector C	DB25 (MALE)
WARRANTY	
Product Warranty Period (Worldwide)	2-year limited warranty

© 2014 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.