

RF Exposure Evaluation

Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

Friis transmission formula: $Pd = (Pout \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

Pd = power density in mW/cm², **Pout** = output power to antenna in mW;

G = gain of antenna in linear scale, **Pi** = 3.1416;

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

Test Result of RF Exposure Evaluation

	Modulation	Frequency MHz	Output power to antenna (dBm)	Target power W/tolerance (dBm)	Max Output power to antenna (dBm)	Max Output power to antenna (mW)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
BLE	GFSK	2402	-2.69	-2±1	-1	0.7943	0.000284	1.0	PASS
		2440	-2.58	-2±1	-1	0.7943	0.000284	1.0	PASS
		2480	-2.78	-2±1	-1	0.7943	0.000284	1.0	PASS
Wifi 2.4g	802.11b	2412	15.91	16±1	17	50.1187	0.017936	1.0	PASS
		2437	16.80	16±1	17	50.1187	0.017936	1.0	PASS
		2462	16.83	16±1	17	50.1187	0.017936	1.0	PASS
	802.11g	2412	19.86	20±1	21	125.8925	0.045054	1.0	PASS
		2437	20.50	20±1	21	125.8925	0.045054	1.0	PASS
		2462	20.58	20±1	21	125.8925	0.045054	1.0	PASS
	802.11n (20)	2412	19.70	20±1	21	125.8925	0.045054	1.0	PASS
		2437	20.36	20±1	21	125.8925	0.045054	1.0	PASS
		2462	20.24	20±1	21	125.8925	0.045054	1.0	PASS
	802.11n (40)	2422	20.63	20±1	21	125.8925	0.045054	1.0	PASS
		2437	20.44	20±1	21	125.8925	0.045054	1.0	PASS
		2452	19.91	20±1	21	125.8925	0.045054	1.0	PASS

	Modulation	Frequency MHz	Output power to antenna (dBm)	Target power W/tolerance (dBm)	Max Output power to antenna (dBm)	Max Output power to antenna (mW)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
Wifi 5.8g	802.11a	5745	-1.75	-1±1	0	1.0000	0.000438	1.0	PASS
		5785	-0.72	-1±1	0	1.0000	0.000438	1.0	PASS
		5825	-0.35	-1±1	0	1.0000	0.000438	1.0	PASS
	802.11n(20)	5745	-1.32	-0.5±1	0.5	1.1220	0.000492	1.0	PASS
		5785	-0.34	-0.5±1	0.5	1.1220	0.000492	1.0	PASS
		5825	0.04	-0.5±1	0.5	1.1220	0.000492	1.0	PASS
	802.11ac(20)	5745	-1.40	-0.5±1	0.5	1.1220	0.000492	1.0	PASS
		5785	-0.42	-0.5±1	0.5	1.1220	0.000492	1.0	PASS
		5825	0.06	-0.5±1	0.5	1.1220	0.000492	1.0	PASS
	802.11n(40)	5755	-1.74	-1±1	0	1.0000	0.000438	1.0	PASS
		5795	-1.19	-1±1	0	1.0000	0.000438	1.0	PASS
	802.11ac(40)	5755	-1.74	-1±1	0	1.0000	0.000438	1.0	PASS
		5795	-1.08	-1±1	0	1.0000	0.000438	1.0	PASS
	802.11ax(80)	5775	-0.53	-1±1	0	1.0000	0.000438	1.0	PASS

	Modulation	Frequency MHz	Output power to antenna (dBm)	Target power W/tolerance (dBm)	Max Output power to antenna (dBm)	Max Output power to antenna (mW)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
Wifi 5.2g	802.11a	5180	6.11	6±1	7	5.0119	0.001798	1.0	PASS
		5200	6.01	6±1	7	5.0119	0.001798	1.0	PASS
		5240	5.73	6±1	7	5.0119	0.001798	1.0	PASS
	802.11n(20)	5180	6.81	6±1	7	5.0119	0.001798	1.0	PASS
		5200	6.35	6±1	7	5.0119	0.001798	1.0	PASS
		5240	6.01	6±1	7	5.0119	0.001798	1.0	PASS
	802.11ac(20)	5180	6.72	6±1	7	5.0119	0.001798	1.0	PASS
		5200	6.27	6±1	7	5.0119	0.001798	1.0	PASS
		5240	5.88	6±1	7	5.0119	0.001798	1.0	PASS
	802.11n(40)	5190	5.83	6±1	7	5.0119	0.001798	1.0	PASS
		5230	5.34	6±1	7	5.0119	0.001798	1.0	PASS
	802.11ac(40)	5190	6.04	6±1	7	5.0119	0.001798	1.0	PASS
		5230	5.06	6±1	7	5.0119	0.001798	1.0	PASS
	802.11ac(80)	5210	5.79	6±1	7	5.0119	0.001798	1.0	PASS

Remark:

1. BT/wifi2.4g Antenna gain is 2.55 dBi, wifi5.2g Antenna gain is 2.56 dBi, wifi5.8g Antenna gain is 3.43 dBi
2. In the case of simultaneous launches for wifi and BT:

The Max Calc. Thresholds : BLE: 0.000284, Wifi2.4g: 0.045054, Wifi5g:0.001798

$$\text{BT and Wifi: } 0.000284 + 0.045054 + 0.001798 = 0.047136 \leq 1$$

So a SAR test is not required