



# PON ONT User Guide

V1.0

## Copyright Statement

© 2022 Shenzhen Tenda Technology Co., Ltd. All rights reserved.

**Tenda** is a registered trademark legally held by Shenzhen Tenda Technology Co., Ltd. Other brand and product names mentioned herein are trademarks or registered trademarks of their respective holders. Copyright of the whole product as integration, including its accessories and software, belongs to Shenzhen Tenda Technology Co., Ltd. No part of this publication can be reproduced, transmitted, transcribed, stored in a retrieval system, or translated into any language in any form or by any means without the prior written permission of Shenzhen Tenda Technology Co., Ltd.

## Disclaimer

Pictures, images and product specifications herein are for references only. To improve internal design, operational function, and/or reliability, Tenda reserves the right to make changes to the products without obligation to notify any person or organization of such revisions or changes. Tenda does not assume any liability that may occur due to the use or application of the product described herein. Every effort has been made in the preparation of this document to ensure accuracy of the contents, but all statements, information and recommendations in this document do not constitute a warranty of any kind, express or implied.

# Preface

Thank you for choosing Tenda!

This user guide walks you through all functions of the PON ONT products (HG9 used for illustration). All the screenshots herein, unless otherwise specified, are taken from HG9.

This user guide is applicable to the following ONTs.

Product model	Description
HG9	AC1200 Dualband Wi-Fi GPON ONT
HG9 xPON+Easymesh	
HG7c	AC1200 Dualband Wi-Fi xPON ONT
HG7	
HG6	N300 Wi-Fi GPON ONT
HG1	GPON ONT





Web UI of different models may differ. The Web UI displayed shall prevail.

## Conventions

The typographical elements that may be found in this document are defined as follows.

Item	Presentation	Example
Cascading menus	>	<b>System &gt; Live Users</b>
Parameter and value	Bold	Set <b>User Name</b> to <b>Tom</b> .
Variable	Italic	Format: <i>XX:XX:XX:XX:XX:XX</i>
UI control	Bold	On the <b>Policy</b> page, click the <b>OK</b> button.
Message	“ ”	The “Success” message appears.

The symbols that may be found in this document are defined as follows.

Symbol	Meaning
 NOTE	This format is used to highlight information of importance or special interest. Ignoring this type of note may result in ineffective configuration, loss of data or damage to devices.
 TIP	This format is used to highlight a procedure that will save time or resources.

## For more documents




If you want to get more documents of the device, visit [www.tendacn.com](http://www.tendacn.com) and search for the corresponding product model.

The related documents are listed as below.

Document	Description
Data Sheet	It introduces the basic information of the device, including product overview, selling points, and specifications.
Quick Installation Guide	It introduces how to set up the device quickly for internet access, the descriptions of LED indicators, ports, and buttons, FAQ, statement information, and so on.
User Guide	It introduces how to set up more functions of the device for more requirements, including all functions on the web UI of the device.

## Technical Support

If you need more help, contact us by any of the following means. We will be glad to assist you as soon as possible.

	Global: (86) 755-27657180 (China Time Zone)		support@tenda.com.cn
	United States: 1-800-570-5892 (Toll Free: 7 x 24 hours)		
	Canada: 1-888-998-8966 (Toll Free: Mon - Fri 9 am - 6 pm PST)		
	Hong Kong: 00852-81931998		
	<a href="http://www.tendacn.com">www.tendacn.com</a>		

## Revision History

Tenda is constantly searching for ways to improve its products and documentation. The following table indicates any changes that might have been made since this guide was first published.

Version	Date	Description
V1.0	2022-03-15	Original publication.

# Contents

1	Get to know your device .....	1
1.1	Overview .....	1
1.2	Appearance .....	1
1.2.1	Indicators, ports, and buttons .....	1
1.2.2	Label .....	9
2	Web UI .....	11
2.1	Login .....	11
2.2	Logout.....	13
2.3	Web UI layout .....	13
2.4	Common buttons .....	14
3	Status .....	15
3.1	Device status .....	15
3.2	IPv6 status .....	17
3.3	PON status.....	18
4	LAN .....	19
5	WLAN .....	20
5.1	Basic settings.....	20
5.1.1	Overview .....	20
5.1.2	Customize the main Wi-Fi name .....	23
5.1.3	Enable multiple wireless networks .....	23
5.2	Advanced settings.....	25
5.2.1	Overview .....	25
5.2.2	Hide the main Wi-Fi name.....	26
5.3	Security.....	27
5.3.1	Overview .....	27

5.3.2	Customize the Wi-Fi password .....	28
5.4	Access control .....	29
5.4.1	Overview .....	29
5.4.2	Allow certain clients to access the Wi-Fi network .....	29
5.5	WPS.....	31
5.5.1	Overview .....	31
5.5.2	Connect to the Wi-Fi network using the WPS button .....	31
5.5.3	Connect to the Wi-Fi network using PBC on the web UI .....	33
5.5.4	Connect to the Wi-Fi network by entering PIN code of clients on the ONT .....	35
5.5.5	Connect to the Wi-Fi network by entering PIN code of the ONT on clients .....	37
5.6	Status .....	38
6	WAN .....	39
6.1	Overview .....	39
6.2	Bridge mode.....	46
6.2.1	Configure internet access on a computer .....	46
6.2.2	Configure internet access on a router .....	48
6.3	Router mode .....	49
6.3.1	Set up a fixed IP connection .....	49
6.3.2	Set up a dynamic IP connection .....	50
6.3.3	Set up a PPPoE connection .....	52
6.3.4	Set up a 6rd connection.....	54
7	Services .....	56
7.1	Service .....	56
7.1.1	DHCP .....	56
7.1.2	Dynamic DNS .....	58
7.1.3	IGMP Proxy .....	62
7.1.4	UPnP .....	63
7.1.5	Samba.....	63

7.2 Firewall .....	64
7.2.1 ALG .....	64
7.2.2 IP/Port filtering .....	65
7.2.3 MAC filtering .....	67
7.2.4 Port forwarding .....	69
7.2.5 URL Blocking .....	73
7.2.6 DMZ .....	74
8 VoIP .....	78
8.1 Set VoIP proxy .....	78
8.2 Change advanced SIP settings .....	80
8.3 Set the forward mode .....	82
8.4 Set speed dial rules .....	83
8.5 Abbreviated dial .....	84
8.6 Set a dial plan .....	85
8.7 Set coding type .....	86
8.8 Set a hotline .....	87
8.9 Set the Don't Disturb mode .....	88
8.10 Set an alarm .....	89
9 Advance .....	90
9.1 Advanced settings .....	90
9.1.1 ARP table .....	90
9.1.2 Routing .....	90
9.1.3 SNMP .....	94
9.2 IPv6 settings .....	96
9.2.1 IPv6 status .....	96
9.2.2 RADVD .....	96
9.2.3 DHCPv6 .....	98
9.2.4 MLD proxy .....	100



9.2.5 MLD snooping .....	101
10 Diagnostics .....	102
10.1 Overview .....	102
10.2 Execute Ping to test connectivity .....	104
10.3 Execute Traceroute to test routing .....	105
10.4 Manual inform report .....	105
11 Admin .....	106
11.1 GPON/EPON settings .....	106
11.2 Multicast VLAN .....	107
11.2.1 Overview .....	107
11.2.2 Set multicast VLAN to watch IPTV programs .....	107
11.3 OMCI information .....	108
11.4 Commit/Reboot .....	108
11.5 Backup/Restore .....	108
11.5.1 Back up the configuration of the ONT .....	109
11.5.2 Restore previous configuration of the ONT .....	109
11.5.3 Reset the ONT .....	109
11.6 Password .....	110
11.7 Firmware upgrade .....	111
11.8 ACL .....	112
11.9 Time Zone .....	114
11.10 TR-069 .....	115
11.11 Logout .....	116
12 Statistics .....	117
Appendixes .....	118
A.1 Configure the computer to obtain an IPv4/IPv6 address automatically .....	118
A.1.1 Windows 10 .....	118
A.1.2 Windows 8 .....	121

A.1.3 Windows 7 .....	123
A.2 Acronyms and abbreviations .....	125

## 1

# Get to know your device

## 1.1 Overview


The ONTs of HG1, HG6, HG7, HG7c and HG9 are Fiber to the Home (FTTH) devices that provide internet access and other services with a fiber cord connected. With HG6, HG7, HG7c and HG9, you can enjoy internet access, watch IPTV program, make phone calls simultaneously by connecting you devices, IPTV STBs (set-top boxes) and landline phones to the ONT.

## 1.2 Appearance

### 1.2.1 Indicators, ports, and buttons

#### HG1

##### ■ LED indicators



LED indicator	Color	Status	Description
LAN	Green	Solid on	The LAN port is connected properly, but no data is being transmitted over the port.
		Blinking	The LAN port is connected properly, and data is being transmitted over the port.

LED indicator	Color	Status	Description
LOS	Red	Off	No Ethernet device is connected or the Ethernet device is not connected to the LAN port properly.
		Blinking	The received optical power is lower than the optical receiver sensitivity, or no fiber cord is connected.
		Off	The received optical power is within the optical receiver sensitivity.
PON	Green	Solid on	The ONT is registered successfully.
		Blinking	The registration is not completed (unregistered or registering).
		Off	The received optical power is lower than the optical receiver sensitivity, or no fiber cord is connected.
PWR	Green	Solid on	The ONT is powered on properly.
		Off	The ONT is powered off or not powered on properly.


## Ports & buttons



Jack/Port/Button	Description
PWR	Power jack. Please use the included power adapter to connect the ONT to a power source.
LAN	Gigabit LAN port. Used to connect to a router, switch or computer.
FIBER	SC/APC optical fiber port. Used to connect to the optical network.
RST	Reset button. After the ONT completes startup, use an object with a spike to hold the button down for more than 10 seconds and then release it. All LED indicators light off in a few seconds. When the PWR LED indicator lights solid on again, the ONT is reset.


## HG6

### LED indicators



LED indicator	Color	Status	Description
PWR	Green	Solid on	The ONT is powered on properly.
		Off	The ONT is powered off or not powered on properly.
PON	Green	Solid on	The ONT is registered successfully.
		Blinking	The registration is not completed (unregistered or registering).
		Off	The received optical power is lower than the optical receiver sensitivity, or no fiber cord is connected.
LOS	Red	Blinking	The received optical power is lower than the optical receiver sensitivity, or no fiber cord is connected.
		Off	The received optical power is within the optical receiver sensitivity.
LAN1/2/3/4	Green	Solid on	The LAN port is connected properly, but no data is being transmitted over the corresponding port.
		Blinking	The LAN port is connected properly, and data is being transmitted over the corresponding port.
		Off	No Ethernet device is connected or the Ethernet device is not connected to the LAN port properly.
TEL	Green	Solid on	The ONT is registered with the IMS (IP Multimedia Subsystem), but no data is being transmitted.
		Blinking	The ONT is registered with the IMS, and data is being transmitted.
		Off	The ONT is not registered with the IMS.
WLAN	Green	Solid on	The Wi-Fi network is enabled, but no data is being transmitted wirelessly.
		Blinking	The Wi-Fi network is enabled, and data is being transmitted wirelessly.
		Off	The Wi-Fi network is disabled.
WPS	Green	Solid on for 2 minutes	A WPS connection is established.
		Blinking	The ONT is performing WPS negotiation.
		Off	The ONT is not performing WPS negotiation.
USB	Green	Solid on	The USB device is connected to the USB port properly, but no data is being transmitted over the port.
		Blinking	The USB device is connected to the USB port properly, and data is being transmitted over the port.
		Off	The USB port is disconnected or not connected properly.

## Ports & buttons




Port/Button	Description
ON/OFF	Power on/off button. Press the button to turn on or off the ONT.
PWR	Power jack. Please use the included power adapter to connect the ONT to a power source.
PON	SC/APC optical fiber port. You can find it on the bottom of the ONT, which is used to connect to a fiber cord.
USB	USB 2.0 port. Used to connect to a USB storage device for resource sharing.
WPS	WPS button. Press the button to start the WPS negotiation process of the ONT. The WPS LED indicator blinks. Within 2 minutes, enable the WPS function on a WPS-supported device to establish a WPS connection.
WLAN	Wi-Fi network button. Press the button to enable or disable the Wi-Fi network of the ONT.
TEL	Telephone port. Used to connect to a telephone for voice service.
LAN1/2/3/4	One gigabit (LAN4) and three fast LAN ports. Used to connect to a router, switch, computer, or IPTV STB.
RESET	Reset button. After the ONT completes startup, use an object with a spike to hold down the button for more than 10 seconds and then release it. All LED indicators light off in a few seconds. When the <b>PWR</b> LED indicator lights solid on again, the ONT is restored to the configurations preset by the ISP.
LED	LED indicator on/off button. Press the button to turn on or off the LED indicators of the ONT.

## HG7 & HG7c

The appearance of HG7 and HG7c is quite similar, except that HG7c does not have the TEL indicator and port. The following figures show the appearance of HG7 as an example.


### LED indicators



### HG7

LED indicator	Color	Status	Description
PWR	Green	Solid on	The ONT is powered on properly.
		Off	The ONT is powered off or not powered on properly.
PON	Green	Solid on	The ONT is registered successfully.
		Blinking	The registration is not completed (unregistered or registering).
		Off	The received optical power is lower than the optical receiver sensitivity, or no fiber cord is connected.
LOS	Red	Blinking	The received optical power is lower than the optical receiver sensitivity, or no fiber cord is connected.
		Off	The received optical power is within the optical receiver sensitivity.
LAN	Green	Solid on	There is at least one LAN port connected properly, but no data is being transmitted over the corresponding port.
		Blinking	There is at least one LAN port connected properly, and data is being transmitted over the corresponding port.
		Off	No Ethernet device is connected or the Ethernet device is not connected to any LAN port properly.
2.4G/5G	Green	Solid on	The 2.4 GHz/5 GHz Wi-Fi network is enabled, but no data is being transmitted wirelessly.
		Blinking slowly (0.5s)	The 2.4 GHz/5 GHz Wi-Fi network is enabled, and data is being transmitted wirelessly.
		Blinking quickly (0.25s)	The ONT is performing or pending for WPS negotiation.
		Off	The 2.4 GHz/5 GHz Wi-Fi network is disabled.
TEL	Green	Solid on	The ONT is registered with IMS, but no data is being transmitted.
		Blinking	The ONT is registered with IMS, and data is being transmitted.
		Off	The ONT is not registered with IMS.

■ Ports & buttons



HG7

Port/Button	Description
PON	Optical fiber port. You can find it on the bottom of the ONT, which is used to connect to a fiber cord.
PWR	Power jack. Please use the included power adapter to connect the ONT to a power source.
TEL	Telephone port. Used to connect to a telephone for voice service using a telephone cable, which needs to be prepared by yourself.
LAN1/LAN2	Gigabit LAN ports. Used to connect to a router, switch, computer or IPTV set-top box.
WPS/RST	WPS/Reset button. <ul style="list-style-type: none"><li><b>WPS:</b> Wi-Fi-enabled devices can connect to the Wi-Fi networks of the ONT without entering the password through WPS negotiation. Press the button for 1 to 3 seconds to start the WPS negotiation process of the ONT. The <b>2.4G</b> and <b>5G</b> LED indicators blink quickly. Within 2 minutes, enable the WPS function on a WPS-supported device to establish a WPS connection.</li><li><b>Reset:</b> Reset the ONT to factory settings. After the ONT completes startup, press the button for more than 10 seconds and release it. All LED indicators will light off in a few seconds. When the <b>PWR</b> LED indicator lights solid on again, the ONT is restored to the configurations preset by the ISP.</li></ul>



## HG9


### LED indicators



LED indicator	Color	Status	Description
POWER	Green	Solid on	The ONT is powered on properly.
		Off	The ONT is powered off or not powered on properly.
INET	Green	Solid on	Internet access is available via the ONT.
		Blinking	Data is being transmitted via the ONT.
		Off	No internet access is available via the ONT.
PON	Green	Solid on	The ONT is registered successfully.
		Blinking	The registration is not completed (unregistered or registering).
		Off	The received optical power is lower than the optical receiver sensitivity, or no fiber cord is connected.
LOS	Red	Blinking	The received optical power is lower than the optical receiver sensitivity, or no fiber cord is connected.
		Off	The received optical power is within the optical receiver sensitivity.
LAN1/2/3/4	Green	Solid on	The LAN port is connected properly, but no data is being transmitted over the corresponding port.
		Blinking	The LAN port is connected properly, and data is being transmitted over the corresponding port.
		Off	No Ethernet device is connected or the Ethernet device is not connected to the LAN port properly.
TEL	Green	Solid on	The ONT is registered with IMS, but no data is being transmitted.
		Blinking	The ONT is registered with IMS, and data is being transmitted.
		Off	The ONT is not registered with IMS.
2.4G/5G	Green	Solid on	The Wi-Fi network of the corresponding frequency is enabled, but no data is being transmitted wirelessly.

LED indicator	Color	Status	Description
		Blinking	The Wi-Fi network of the corresponding frequency is enabled, and data is being transmitted wirelessly.
		Off	The Wi-Fi network of the corresponding frequency is disabled.
WPS	Green	Solid on for 2 minutes	A WPS connection is established.
		Blinking	The ONT is performing WPS negotiation.
		Off	The ONT is not performing WPS negotiation.
USB	Green	Solid on	The USB device is connected to the USB port properly, but no data is being transmitted over the port.
		Blinking	The USB device is connected to the USB port properly, and data is being transmitted over the port.
		Off	The USB port is disconnected or not connected properly.

## Ports & buttons




Port/Button	Description
TEL	Telephone port. Used to connect to a telephone for voice service.
PON	SC/APC optical fiber port. Used to connect to a fiber cord.
LAN1/2/3/4	Gigabit LAN ports. Used to connect to a router, switch, computer, or IPTV STB.

Port/Button	Description
POWER	Power jack. Please use the included power adapter to connect the ONT to a power source.
ON/OFF	Power on/off button. Press the button to turn on or off the ONT.
LED	LED indicator on/off button. Press the button to turn on or off the LED indicators of the ONT.
WPS	WPS button. Press the button to start the WPS negotiation process of the ONT. The WPS LED indicator blinks. Within 2 minutes, enable the WPS function on a WPS-supported device to establish a WPS connection.
WLAN	Wi-Fi network button. Press the button to enable or disable the Wi-Fi network of the ONT.
RESET	Reset button. After the ONT completes startup, use an object with a spike to hold down the button for more than 10 seconds and then release it. All LED indicators light off in a few seconds. When the POWER LED indicator lights solid on again, the ONT is restored to the configurations preset by the ISP.
USB	USB 2.0 port. Used to connect to a USB storage for resource sharing.

## 1.2.2 Label

The label is located on the bottom panel of the ONT. See the following figure for details.



**Model:** Model of the ONT

**IP Address:** Default IP address used to log in to the web UI of the ONT

**Username & Password:** Default user name and password used to log in to the web UI of the ONT

**SSID & Key:** Default Wi-Fi name and password of the ONT

**GPON SN:** GPON serial number of the ONT

**MAC Address:** MAC address of the ONT

**Product S/N:** Product serial number

## 2 Web UI

### 2.1 Login

**Step 1** Connect the ONT to a power source using the provided power adapter.


**Step 2** Press the ON/OFF button to turn on the ONT.



TIP

Skip this step if your ONT has no ON/OFF button.

**Step 3** Connect a computer to a LAN port of the ONT using an Ethernet cable, or connect your smartphone to the Wi-Fi network of the ONT.



**Step 4** Start a web browser on a connected device and visit the IP address of the ONT (**192.168.1.1** by default). Enter your **User Name** and **Password** (both are **admin** by default), and click **Login**.



User Name:

Password:

-----End




TIP

If the above page does not appear, try the following solutions:

- Ensure that the ONT is powered on properly.
- If a wired device, such as a computer, is used for configuration, ensure that the wired device is connected to a LAN port of the router properly, and is set to obtain an IP address automatically.
- If a wireless device, such as a smartphone, is used for configuration, ensure that the wireless device is connected to the Wi-Fi network of the ONT and the cellular network (mobile data) of the client is disabled.
- Restore the ONT to factory settings and try again.

The following page appears.



[Logout](#) HG9

Status	LAN	WLAN	WAN	Services	VoIP	Advance	Diagnostics	Admin	Statistics																																													
<div style="display: flex;"> <div style="width: 20%;"> <p><b>Status</b></p> <ul style="list-style-type: none"> <li>Device</li> <li>IPv6</li> <li>PON</li> </ul> </div> <div style="width: 80%;"> <p><b>Device Status</b></p> <p>This page shows the current status and some basic settings of the device.</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2" style="background-color: #f2f2f2;">System</th> </tr> </thead> <tbody> <tr><td>Device Name</td><td>HG9</td></tr> <tr><td>Uptime</td><td>33 min</td></tr> <tr><td>Software version</td><td>v1.0.0</td></tr> <tr><td>Hardware Version</td><td>v1.0</td></tr> <tr><td>CPU Usage</td><td>5%</td></tr> <tr><td>Memory Usage</td><td>45%</td></tr> </tbody> </table> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2" style="background-color: #f2f2f2;">LAN Configuration</th> </tr> </thead> <tbody> <tr><td>IP Address</td><td>192.168.1.1</td></tr> <tr><td>Subnet Mask</td><td>255.255.255.0</td></tr> <tr><td>DHCP Server</td><td>Enabled</td></tr> <tr><td>MAC Address</td><td>502B73FF0189</td></tr> </tbody> </table> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="7" style="background-color: #f2f2f2;">WAN Configuration</th> </tr> <tr> <th>Interface</th> <th>VLAN ID</th> <th>Connection Type</th> <th>Protocol</th> <th>IP Address</th> <th>Gateway</th> <th>Status</th> </tr> </thead> <tbody> <tr> <td>nas0_0</td> <td>10</td> <td>INTERNET</td> <td>Bridged</td> <td></td> <td></td> <td>down</td> </tr> </tbody> </table> <p><input type="button" value="Refresh"/></p> </div> </div>										System		Device Name	HG9	Uptime	33 min	Software version	v1.0.0	Hardware Version	v1.0	CPU Usage	5%	Memory Usage	45%	LAN Configuration		IP Address	192.168.1.1	Subnet Mask	255.255.255.0	DHCP Server	Enabled	MAC Address	502B73FF0189	WAN Configuration							Interface	VLAN ID	Connection Type	Protocol	IP Address	Gateway	Status	nas0_0	10	INTERNET	Bridged			down
System																																																						
Device Name	HG9																																																					
Uptime	33 min																																																					
Software version	v1.0.0																																																					
Hardware Version	v1.0																																																					
CPU Usage	5%																																																					
Memory Usage	45%																																																					
LAN Configuration																																																						
IP Address	192.168.1.1																																																					
Subnet Mask	255.255.255.0																																																					
DHCP Server	Enabled																																																					
MAC Address	502B73FF0189																																																					
WAN Configuration																																																						
Interface	VLAN ID	Connection Type	Protocol	IP Address	Gateway	Status																																																
nas0_0	10	INTERNET	Bridged			down																																																


## 2.2 Logout

The ONT logs you out when you:

- Click the **Logout** button on the upper-right corner of the web UI, or click **Logout** in **Admin > Logout**.
- Perform no operation within 20 minutes.

## 2.3 Web UI layout

The web UI of the ONT is composed of 4 parts, including the level-1 navigation tree, level-2 navigation tree, tab page area, and configuration area. See the following figure.



No.	Name	Description
①	Level-1 navigation tree	The navigation bars and tab pages display the function menu of the ONT. When you select a function in the navigation bar, the configuration of the function appears in the configuration area.
②	Level-2 navigation tree	
③	Tab page area	
④	Configuration area	It enables you to view and modify the configuration.

## 2.4 Common buttons

Some buttons are commonly used in the web UI of the ONT, and their functions are listed as follows.

Button	Description
<b>Refresh</b>	It is used to refresh the statistics shown on the page.
<b>Add</b>	It is used to add the information that you entered.
<b>Reset</b>	It is used to restore the information that you entered on the page.
<b>Delete</b>	
<b>Delete Selected</b>	They are used to delete the information that you selected.
<b>Delete All</b>	
<b>Modify</b>	It is used to modify the information that you selected.
<b>Remove</b>	It is used to remove the information that you selected.
<b>Apply</b>	
<b>Apply Changes</b>	They are used to apply the settings configured on the page.



# 3 Status

In this module, you can:

- View [device status](#) of the ONT.
- View [IPv6 status](#) of the ONT.
- View [PON status](#) of the ONT.

## 3.1 Device status

On this page, you can view the basic system information, LAN configuration and WAN configuration of the ONT.

To access the page, log in to the web UI of the ONT and choose **Status > Device**.

System						
Device Name			HG9			
Uptime			51 min			
Software version			v1.0.0			
Hardware Version			v1.0			
CPU Usage			3%			
Memory Usage			44%			
LAN Configuration						
IP Address			192.168.1.1			
Subnet Mask			255.255.255.0			
DHCP Server			Enabled			
MAC Address			502B73FF0189			
WAN Configuration						
Interface	VLAN ID	Connection Type	Protocol	IP Address	Gateway	Status
nas0_0	10	INTERNET	Bridged			down

## Parameter description

Parameter		Description
System		It displays the basic system information of the ONT, including the device name, uptime, software version, hardware version, CPU usage and memory usage.
LAN Configuration	IP Address	It specifies the LAN IP address of the ONT, which is also the IP address used to log in to the web UI of the ONT.
	Subnet Mask	It specifies the LAN subnet mask of the ONT.
	DHCP Server	It specifies whether the DHCP server of the ONT is enabled.
	MAC Address	It specifies the MAC address of the ONT's LAN port.
WAN Configuration	Interface	It specifies the name of the interface/WAN connection when IPv4 is enabled.
	VLAN ID	It specifies the VLAN ID of the WAN connection.
	Connection Type	It specifies the WAN connection type.
	Protocol	It specifies the channel mode used by the WAN port.
	IP Address	They specify the IP address and gateway address that the ONT obtains after you set up a WAN connection successfully.
	Gateway	
	Status	<p>It specifies the connection status of the WAN connection.</p> <ul style="list-style-type: none"> <li>• <b>up</b>: The WAN connection is successful and currently available.</li> <li>• <b>down</b>: The WAN connection failed and is currently unavailable.</li> </ul>

## 3.2 IPv6 status

On this page, you can view the IPv6 connection status of the ONT.

To access the page, log in to the web UI of the ONT and choose **Status > IPv6**.

LAN Configuration					
IPv6 Address		240e:fa:c662:ce3b:ca3a:35ff:fe80:3e68/64			
IPv6 Link-Local Address		fe80::1/64			
Prefix Delegation					
Prefix		240e:fa:c662:ce3b::/64			
WAN Configuration					
Interface	VLAN ID	Connection Type	Protocol	IP Address	Status
ppp0_nas0_0	47	INTERNET	PPPoE	240e:fa:c662:ce3a:ca3a:35ff:fe80:3e6f/64	up

### Parameter description

Parameter	Description	
LAN Configuration	IPv6 Address	It specifies the LAN IPv6 address of the ONT.
	IPv6 Link-Local Address	It specifies the IPv6 link-local address of the ONT. A link-local address is an IPv6 unicast address that is automatically configured on any interface and is valid only for communications within the network segment.
Prefix Delegation	Prefix	It specifies the IPv6 prefix of the LAN port of ONT.
WAN Configuration	Interface	It specifies the name of the interface/WAN when IPv6 is enabled.
	VLAN ID	It specifies the VLAN ID of the WAN connection.
	Connection Type	It specifies the WAN connection type.
	Protocol	It specifies the channel mode used by the WAN port.
	IP Address	They specify the IP address and gateway address that the ONT obtains after you set up a WAN connection successfully.
	Gateway	
	Status	It specifies the connection status of the WAN connection. <ul style="list-style-type: none"> <li>• <b>up</b>: The WAN connection is successful and currently available.</li> <li>• <b>down</b>: The WAN connection failed and is currently unavailable.</li> </ul>

## 3.3 PON status

On this page, you can view the PON status and GPON/EPON connection status of the ONT.

To access the page, log in to the web UI of the ONT and choose **Status > PON**.

PON Status	
Vendor Name	
Temperature	43.105469 C
Voltage	3.329700 V
Tx Power	-inf dBm
Rx Power	-inf dBm
Bias Current	6.250000 mA
GPON Status	
ONU State	O1

### Parameter description

Parameter	Description	
PON Status	Vendor Name	It specifies the vendor name of the ONT.
	Temperature	It specifies the current chip temperature of the ONT.
	Voltage	It specifies the current voltage of the optical module of the ONT.
	Tx Power	It specifies the transmitted and received optical power of the ONT over the PON port.
	Rx Power	
	Bias Current	It specifies the current bias current of the optical module of the ONT.
GPON Status	ONU State	It specifies the state of the ONT, ranging from O1 to O7.
		<ul style="list-style-type: none"> <li>• <b>O1 to O4</b>: The ONT is registering.</li> <li>• <b>O5</b>: The ONT registered successfully and is under normal operation.</li> <li>• <b>O6/O7</b>: The ONT is in abnormal state and stops transmitting signals.</li> </ul>
		ONU ID
EPON Status (HG7/HG6)	Auth state	It specifies the state of the ONT.

# 4 LAN

In this module, you can configure the LAN IPv4 and IGMP/MLD Snooping settings of the ONT.

To access the page, log in to the web UI and choose **LAN**.

<b>InterfaceName:</b>	br0
<b>IP Address:</b>	<input type="text" value="192.168.1.1"/>
<b>Subnet Mask:</b>	<input type="text" value="255.255.255.0"/>
<b>IGMP/MLD Snooping:</b>	<input type="radio"/> Disabled <input checked="" type="radio"/> Enabled

## Parameter description

Parameter	Description
InterfaceName	It specifies the LAN interface name of the ONT.
IP Address	It specifies the IPv4 LAN address of the ONT, which is also the IPv4 address for logging in to the web UI of the ONT.
Subnet Mask	It specifies the IPv4 LAN subnet mask of the ONT.
IGMP Snooping	<p>When Internet Group Management Protocol (IGMP) snooping is enabled, multicast data from known IPv4 multicast groups are multicast to the specified LAN ports only, instead of all LAN ports, thus saving link bandwidth.</p> <ul style="list-style-type: none"> <li>Standard mode: If no member joins a multicast group, the data of that multicast group is broadcast. If a member joins a multicast group, the data of that multicast group is only forwarded to the LAN port of the member.</li> <li>Blocking mode: If no member joins a multicast group, the data of that multicast group is discarded. If a member joins a multicast group, the data of that multicast group is only forwarded to the LAN port of the member.</li> </ul>
MLD Snooping (HG6)	MLD is used by IPv6 routers for discovering multicast listeners on a directly attached link. If disabled on layer2 devices, IPv6 multicast data packets will be broadcast on the entire layer2; if enabled, these packets will be multicast to only specified recipient instead of being broadcast on the entire layer2.

# 5 WLAN



- WLAN settings are only available on ONTs with the wireless function, and WLAN (5 GHz) settings are not available for single-band ONTs.
- WLAN (2.4 GHz) and WLAN (5 GHz) configurations are similar. WLAN (2.4 GHz) is used for illustration in this part.

In this module, you can customize your Wi-Fi network, including:

- [Customize Wi-Fi name and other basic settings](#)
- [Hide Wi-Fi name and set other advanced functions](#)
- [Customize Wi-Fi password](#)
- [Allow certain clients to access the Wi-Fi network](#)

## 5.1 Basic settings

### 5.1.1 Overview

On this page, you can set basic parameters of the Wi-Fi network of the ONT, such as enabling/disabling the Wi-Fi network and setting band and SSID (Wi-Fi name).

To access the page, log in to the web UI of the ONT and choose **WLAN > wlan1 (2.4 GHz) > Basic Settings**.

<input type="checkbox"/> <b>Disable WLAN Interface</b>	
<b>Band:</b>	2.4 GHz (B+G+N) ▼
<b>Mode:</b>	AP ▼ <span>Multiple AP</span>
<b>SSID:</b>	Tenda-FF0189
<b>Channel Width:</b>	40MHz ▼
<b>Channel Number:</b>	7 ▼
<b>Radio Power (%):</b>	100% ▼
<b>Associated Clients:</b>	<span>Show Active WLAN Clients</span>

## Parameter description

Parameter	Description
Disable WLAN Interface	<p>It specifies whether to enable the Wi-Fi network.</p>
Band	<p>It specifies the wireless band and protocol of the Wi-Fi network.</p> <p>The dual-band ONT supports both 2.4 GHz and 5 GHz, and the single-band ONT supports 2.4 GHz.</p> <ul style="list-style-type: none"> <li>• <b>2.4 GHz(B)</b>: In this mode, the 2.4 GHz wireless devices compliant with IEEE 802.11b protocol can connect to the 2.4 GHz wireless network of the ONT. The maximum wireless rate is 11 Mbps.</li> <li>• <b>2.4 GHz(G)</b>: In this mode, the 2.4 GHz wireless devices compliant with IEEE 802.11g protocol can connect to the 2.4 GHz wireless network of the ONT. The maximum wireless rate is 54 Mbps.</li> <li>• <b>2.4 GHz(B+G)</b>: In this mode, the 2.4 GHz wireless devices compliant with IEEE 802.11b or IEEE 802.11g protocol can connect to the 2.4 GHz wireless network of the ONT.</li> <li>• <b>2.4 GHz(N)</b>: In this mode, the 2.4 GHz wireless devices compliant with IEEE 802.11n protocol can connect to the 2.4 GHz wireless network of the ONT. The maximum wireless rate is 300 Mbps.</li> <li>• <b>2.4 GHz(G+N)</b>: In this mode, the 2.4 GHz wireless devices compliant with IEEE 802.11g or IEEE 802.11n protocol can connect to the 2.4 GHz wireless network of the ONT.</li> <li>• <b>2.4 GHz(B+G+N)</b>: In this mode, the 2.4 GHz wireless devices compliant with IEEE 802.11b, IEEE 802.11g or IEEE 802.11n protocol can connect to the 2.4 GHz wireless network of the ONT.</li> <li>• <b>5 GHz(A)</b>: In this mode, the 5 GHz wireless devices compliant with IEEE 802.11a protocol can connect to the 5 GHz wireless network of the ONT. The maximum wireless rate is 54 Mbps.</li> <li>• <b>5 GHz(N)</b>: In this mode, the 5 GHz wireless devices compliant with IEEE 802.11n protocol can connect to the 5 GHz wireless network of the ONT. The maximum wireless rate is 300 Mbps.</li> <li>• <b>5 GHz(A+N)</b>: In this mode, the 5 GHz wireless devices compliant with IEEE 802.11a or IEEE 802.11n protocol can connect to the 5 GHz wireless network of the ONT.</li> <li>• <b>5 GHz(AC)</b>: In this mode, the 5 GHz wireless devices compliant with IEEE 802.11ac protocol can connect to the 5 GHz wireless network of the ONT. The maximum wireless rate is 867 Mbps.</li> <li>• <b>5 GHz(N+AC)</b>: In this mode, the 5 GHz wireless devices compliant with IEEE 802.11n or IEEE 802.11ac protocol can connect to the 5 GHz wireless network of the ONT.</li> <li>• <b>5 GHz(A+N+AC)</b>: In this mode, the 5 GHz wireless devices compliant with IEEE 802.11a, IEEE 802.11n or IEEE 802.11ac protocol can connect to the 5 GHz wireless network of the ONT.</li> </ul>
Mode	<p>It specifies the wireless operation mode of the ONT.</p> <p><b>AP</b>: The ONT serving as a wireless access point provides a wireless network for wireless clients.</p>

Parameter	Description
Multiple AP	<p>You can click <b>Multiple AP</b> to create more wireless networks of the same band.</p> <ul style="list-style-type: none"> <li>• <b>No.:</b> It specifies the No. of the AP Wi-Fi network.</li> <li>• <b>Enable:</b> It specifies whether to enable the AP Wi-Fi network.</li> <li>• <b>Band:</b> It specifies the wireless band and protocol of the AP Wi-Fi network.</li> <li>• <b>SSID:</b> It specifies the Wi-Fi name of the AP Wi-Fi network.</li> <li>• <b>Broadcast SSID:</b> It specifies whether to hide the SSID of the AP Wi-Fi network. <b>Enabled</b> means that the SSID is displayed. <b>Disabled</b> means that the SSID is hidden, and you need to enter the SSID of the Wi-Fi network manually to connect to it.</li> <li>• <b>Active Client List:</b> You can click it to view the information of clients connected to the Wi-Fi network.</li> <li>• <b>Reset:</b> You can click it to discard the unsaved modifications on this page.</li> </ul>
SSID	It specifies the Wi-Fi name of the main Wi-Fi network.
Channel Width	<p>It specifies the bandwidth of the wireless channel of the Wi-Fi network. The following values may vary with the ONT models. Please refer to the actual product for details.</p> <ul style="list-style-type: none"> <li>• <b>20MHz:</b> It indicates that the channel bandwidth used by the ONT is 20 MHz.</li> <li>• <b>40MHz:</b> It indicates that the channel bandwidth used by the ONT is 40 MHz.</li> <li>• <b>20/40MHz:</b> It specifies that the ONT can switch its channel bandwidth between 20 MHz and 40 MHz based on the ambient environment.</li> <li>• <b>80:</b> It indicates that the channel bandwidth used by the ONT is 80 MHz. This option is available only at 5 GHz.</li> <li>• <b>20/40/80:</b> It specifies that the ONT can switch its channel bandwidth among 20 MHz, 40 MHz, and 80 MHz based on the ambient environment. This option is available only at 5 GHz.</li> </ul>
Channel Number	<p>It specifies the channel in which the Wi-Fi network works.</p> <p>You are recommended to choose a channel with less interference for better wireless transmission efficiency. You can use a third-party tool to scan the Wi-Fi signals nearby to understand the channel usage situations.</p> <ul style="list-style-type: none"> <li>• <b>Auto:</b> It indicates that the ONT automatically adjusts its operating channel according to the ambient environment.</li> <li>• <b>Auto (DFS):</b> Dynamic Frequency Selection. With this function enabled, the ONT will automatically detect the frequency of the radar system. When the ONT detects radar signals in the same frequency with the ONT itself, the ONT will automatically switch to another frequency to avoid interference with the radar system.</li> </ul>
Radio Power (%)	You can set the intensity of the radio power of the ONT. A higher radio power brings a wider coverage of Wi-Fi coverage.



Parameter	Description
Associated Clients	You can view the clients that connect to the Wi-Fi network by clicking <b>Show Active WLAN Clients</b> .
	<ul style="list-style-type: none"> <li>• <b>MAC Address:</b> It specifies the MAC address of the client connected to the Wi-Fi network.</li> </ul>
	<ul style="list-style-type: none"> <li>• <b>Tx Packets:</b> It specifies the number of transmitted packets of the client through the Wi-Fi network.</li> </ul>
	<ul style="list-style-type: none"> <li>• <b>Rx Packets:</b> It specifies the number of received packets of the client through the Wi-Fi network.</li> </ul>
	<ul style="list-style-type: none"> <li>• <b>Tx Rate (Mbps):</b> It specifies the transmitting rate of the Wi-Fi network.</li> <li>• <b>RSSI:</b> It specifies the signal strength of the client received by the AP.</li> </ul>

## 5.1.2 Customize the main Wi-Fi name

**Step 1** Choose **WLAN > wlan1 (2.4 GHz) > Basic Settings** on the web UI.

**Step 2** Set **SSID**.

**Step 3** Click **Apply Changes**.

---End

After completing the configuration, you can search the SSID(s) on your Wi-Fi-enabled devices and connect to it to access the internet.

## 5.1.3 Enable multiple wireless networks

**Step 1** Choose **WLAN > wlan1 (2.4 GHz) > Basic Settings** on the web UI.

**Step 2** Click **Multiple AP**. Select **Enable** to enable any Wi-Fi network as required, set **SSID** (Wi-Fi name), and click **Apply Changes**.

No.	Enable	Band	SSID	Data Rate	Broadcast SSID	WMM	Relay Blocking	Active Client List	Multicast to Unicast
AP1	<input checked="" type="checkbox"/>	2.4 GHz (B+G+N)	AP-1	Auto	Enabled	Enabled	Disabled	Show	Enabled
AP2	<input type="checkbox"/>	2.4 GHz (B+G+N)	AP-2	Auto	Enabled	Enabled	Disabled	Show	Enabled
AP3	<input type="checkbox"/>	2.4 GHz (B+G+N)	AP-3	Auto	Enabled	Enabled	Disabled	Show	Enabled
AP4	<input type="checkbox"/>	2.4 GHz (B+G+N)	AP-4	Auto	Enabled	Enabled	Disabled	Show	Enabled

---End

After completing the configuration, you can search the SSID(s) on your Wi-Fi-enabled devices and connect to it to access the internet.

## 5.2 Advanced settings

### 5.2.1 Overview

On this page, you can configure more advanced settings of your Wi-Fi network.

To access the page, log in to the web UI of the ONT and choose **WLAN > wlan1 (2.4 GHz) > Advanced Settings**.



You are recommended to retain the default settings if without professional guidance.

<b>RTS Threshold:</b>	<input type="text" value="2347"/> (0-2347)
<b>Beacon Interval:</b>	<input type="text" value="100"/> (20-1024 ms)
<b>DTIM Period:</b>	<input type="text" value="1"/> (1-255)
<b>Broadcast SSID:</b>	<input type="radio"/> Enabled <input checked="" type="radio"/> Disabled

#### Parameter description

Parameter	Description
RTS Threshold	<p>It specifies the frame length threshold for triggering the RTS/CTS mechanism in the unit of byte. If a frame exceeds this threshold, the RTS/CTS mechanism is triggered to reduce conflicts.</p> <p>Set the RTS threshold based on the actual situation. An excessively small value increases the RTS frame transmission frequency and bandwidth requirement. A higher RTS frame transmission frequency enables a wireless network to recover from conflicts quicker. For a wireless network with high user density, you can lower this threshold to reduce conflicts.</p> <p>The RTS mechanism requires some network bandwidth. Therefore, it is triggered only when frames exceed this threshold.</p>
Beacon Interval	<p>It specifies the interval at which this device sends Beacon frames.</p> <p>Beacon frames are sent at the interval to announce the existence of a wireless network. Generally, a smaller interval allows wireless clients to connect to this device sooner, while a larger interval allows the wireless network to transmit data quicker.</p>
DTIM Period	<p>It specifies the countdown before this device transmits broadcast and multicast frames in its cache. The unit is Beacon interval.</p> <p>For example, if <b>DTIM Interval</b> is set to <b>1</b>, this device transmits all cached frames at one Beacon interval.</p> <p>It is used when the client is in power-saving mode, and the ONT informs the client about the presence of buffered multicast/broadcast data on the ONT at the specified interval. A proper value helps improve the power efficiency of clients.</p>

Parameter	Description
Broadcast SSID	<p>It specifies whether to broadcast or hide the SSID (Wi-Fi name) of the main Wi-Fi network.</p> <p>If the SSID is hidden, it cannot be found on clients and clients need to enter the information of the Wi-Fi network manually to connect to it.</p>

## 5.2.2 Hide the main Wi-Fi name

**Step 1** Choose **WLAN > wlan1 (2.4 GHz) > Advanced Settings** on the web UI.

**Step 2** Select **Disabled** for **Broadcast SSID**.

<b>RTS Threshold:</b>	<input type="text" value="2347"/>	(0-2347)
<b>Beacon Interval:</b>	<input type="text" value="100"/>	(20-1024 ms)
<b>DTIM Period:</b>	<input type="text" value="1"/>	(1-255)
<b>Broadcast SSID:</b>	<input type="radio"/> Enabled <input checked="" type="radio"/> Disabled	

**Step 3** Click **Apply Changes**.

---End

After the configuration is completed, the SSID (Wi-Fi name) of the 2.4 GHz network is hidden, but you can connect to the Wi-Fi network by entering its SSID and other required parameters.

## 5.3 Security

### 5.3.1 Overview

On this page, you can perform password settings to secure your Wi-Fi network.

To access the page, log in to the web UI of the ONT and choose **WLAN > wlan1 (2.4 GHz) > Security**.

SSID Type:	Root AP - CMCC-V4.0-5G ▼
Encryption:	WPA/WPA2-PSK ▼
Authentication Mode:	<input checked="" type="radio"/> Personal (Pre-Shared Key)
WPA Cipher Suite:	<input type="checkbox"/> TKIP <input checked="" type="checkbox"/> AES
WPA2 Cipher Suite:	<input type="checkbox"/> TKIP <input checked="" type="checkbox"/> AES
Pre-Shared Key Format:	Passphrase ▼
Pre-Shared Key:	.....

#### Parameter description

Parameter	Description
SSID Type	It specifies the Wi-Fi network to be configured.
Encryption	<p>It specifies the encryption mode of the Wi-Fi network.</p> <ul style="list-style-type: none"> <li>• <b>NONE</b>: It indicates that the Wi-Fi network is not encrypted and clients can connect to it without password.</li> <li>• <b>WEP</b>: It indicates that the Wi-Fi network is encrypted using WEP, an old security algorithm for IEEE 802.11 wireless networks. The maximum rate in this mode is 54 Mbps.</li> <li>• <b>WPA-PSK</b>: It indicates that the Wi-Fi network is encrypted using WPA-PSK, which has better compatibility than WPA2-PSK.</li> <li>• <b>WPA2-PSK</b>: It indicates that the Wi-Fi network is encrypted using WPA2-PSK, which has a higher security level than WPA-PSK.</li> <li>• <b>WPA/WPA2-PSK</b>: It indicates that the Wi-Fi network is encrypted using both WPA-PSK and WPA2-PSK, providing both security and compatibility.</li> </ul>
Authentication Mode	<p>It specifies the authentication mode used when clients connect the Wi-Fi network if encryption is enabled.</p> <p>When the Wi-Fi network is encrypted with WEP, the authentication modes include:</p> <ul style="list-style-type: none"> <li>• <b>Open System</b>: There is no authentication performed when clients connect to the Wi-Fi network, and the key is only required during data transmission.</li> <li>• <b>Shared Key Auto</b>: The key is required for clients to connect to the Wi-Fi network.</li> </ul> <p>When the Wi-Fi network is encrypted with other encryption modes, <b>Personal (Pre-Shared Key)</b> is required to connect to the Wi-Fi network.</p>

Parameter	Description
WPA Cipher Suite	They specify the encryption algorithms used for WPA, including <b>TKIP</b> and <b>AES</b> . When selected, clients adopting the corresponding encryption algorithm(s) can connect to the Wi-Fi network.
WPA2 Cipher Suite	
Key Length	It specifies the key length of the password and is only required when WEP is used to encrypt the Wi-Fi network.
Key Format/Pre-Shared Key Format	It specifies the password format and the required number of characters, including <b>ASCII</b> (only for WEP), <b>Hex</b> (except for WEP) and <b>Passphrase</b> .
Pre-Shared Key	It specifies the password for connecting to the Wi-Fi network.

## 5.3.2 Customize the Wi-Fi password

- Step 1** Choose **WLAN > wlan1 (2.4 GHz) > Security** on the web UI.
- Step 2** Select SSID (Wi-Fi name) for which you want to customize the password in **SSID Type**.
- Step 3** Select **WPA-PSK**, **WPA2-PSK** and **WPA/WPA2-PSK**.
- Step 4** Set password-related options, such as **Encryption**, **WPA Cipher Suite**, **Pre-Shared Key Format**.
- Step 5** Enter the Wi-Fi password in **Pre-Shared Key**.

<b>SSID Type:</b>	Root AP - 111aaa2 ▼
<b>Encryption:</b>	WPAWPA2-PSK ▼
<b>Authentication Mode:</b>	<input checked="" type="radio"/> Personal (Pre-Shared Key)
<b>WPA Cipher Suite:</b>	<input checked="" type="checkbox"/> TKIP <input checked="" type="checkbox"/> AES
<b>WPA2 Cipher Suite:</b>	<input checked="" type="checkbox"/> TKIP <input checked="" type="checkbox"/> AES
<b>Pre-Shared Key Format:</b>	Passphrase ▼
<b>Pre-Shared Key:</b>	●●●●●●●●

- Step 6** (Optional) Repeat **Step 2** to **Step 6** to set the Wi-Fi password for other SSIDs.
- Step 7** Click **Apply Changes**.
- End

After completing the configuration, you can connect the Wi-Fi networks using the Wi-Fi password you set.

## 5.4 Access control

### 5.4.1 Overview

On this page, you can add and delete access control rules to decide which clients can or cannot connect to all the Wi-Fi networks in the frequency band.

To access the page, log in to the web UI of the ONT and choose **WLAN > wlan1 (2.4 GHz) > Access Control**. Rules added are shown in **Current Access Control List**.

**Mode:** Allow Listed Apply Changes

**MAC Address:**  (ex. 00E086710502)

Add Reset

Current Access Control List		
Mode	MAC Address	Select

#### Parameter description

Parameter	Description
Mode	It specifies the control mode.
	<ul style="list-style-type: none"> <li>• <b>Disabled:</b> It indicates that the access control function is disabled.</li> </ul>
	<ul style="list-style-type: none"> <li>• <b>Allow Listed:</b> It indicates that only clients with the MAC addresses added to the list can connect to the Wi-Fi network.</li> </ul>
	<ul style="list-style-type: none"> <li>• <b>Deny Listed:</b> It indicates that clients with the MAC addresses added to the list cannot connect to the Wi-Fi network.</li> </ul>
MAC Address	It specifies the MAC address of the client to be controlled.

### 5.4.2 Allow certain clients to access the Wi-Fi network

Assume that you only want to enable a smartphone and a tablet to access your Wi-Fi network and prevent misuse of others. The MAC addresses of smartphone and tablet are:

- Smartphone: 8E:5B:54:F6:E1:00
- Tablet: 8C:EC:4B:B3:04:92

#### Configuring procedure:

**Step 1** Choose **WLAN > wlan1 (2.4 GHz) > Access Control** on the web UI.

**Step 2** Select **Allow Listed** for **Mode**, and click **Apply Changes**.

**Mode:** Allow Listed Apply Changes

**Step 3** Enter **8E5B54F6E100** in **MAC Address**, and click **Add**.

<b>MAC Address:</b>	<input type="text" value="8E5B54F6E100"/> (ex. 00E086710502)
<input type="button" value="Add"/>	<input type="button" value="Reset"/>

**Step 4** Enter **8CEC4BB30492** in **MAC Address**, and click **Add**.

---End

After the configuration is completed, the added devices are listed in **Current Access Control List**, and only the smartphone and tablet can connect to the Wi-Fi network.

Current Access Control List		
Mode	MAC Address	Select
Allow	8e:5b:54:f6:e1:00	<input type="checkbox"/>
Allow	8c:ec:4b:b3:04:92	<input type="checkbox"/>



If the MAC address of a device is added in the **Deny Listed** mode, the device will fail to access the Wi-Fi network and a message indicating incorrect password will be displayed on the device.



## 5.5 WPS

### 5.5.1 Overview

The Wi-Fi Protected Setup (WPS) function enables wireless clients that support WPS, such as smartphones, to connect to the Wi-Fi network of the ONT quickly and easily.


There are four methods to connect to the Wi-Fi network of the ONT through WPS.


- [Connect to the Wi-Fi network using the WPS button](#)
- [Connect to the Wi-Fi network using PBC on the web UI](#)
- [Connect to the Wi-Fi network by entering PIN code of clients on the ONT](#)
- [Connect to the Wi-Fi network by entering PIN code of the ONT on clients](#)

To access the page, log in to the web UI of the ONT and choose **WLAN > wlan1 (2.4 GHz) > WPS**.


<input type="checkbox"/> <b>Disable WPS</b>	
<b>Self-PIN Number:</b>	<input type="text" value="12345670"/> <input type="button" value="Regenerate PIN"/>
<b>Push Button Configuration:</b>	<input type="button" value="Start PBC"/>
<input type="button" value="Apply Changes"/> <input type="button" value="Reset"/>	
<b>Client PIN Number:</b>	<input type="text"/> <input type="button" value="Start PIN"/>

### 5.5.2 Connect to the Wi-Fi network using the WPS button

- Step 1** Find the **WPS** button on the ONT. Press it once and you can see the WPS LED indicator blinks.
- Step 2** Configure the WPS function on your wireless devices **within 2 minutes**. Configuration on various devices may differ (Example: HUAWEI P10 smartphone).
1. Find **Settings** on the phone.
  2. Choose **WLAN**.
  3. Tap , and choose **WLAN settings**.



4. Choose **WPS connection**.




---End

Wait a moment until the WPS negotiation is completed, and the smartphone is connected to the Wi-Fi network.



TIP


- If multiple wireless networks are enabled in a frequency band, the main network is connected by default.
- To use the WPS function, the encryption mode of the wireless network must be WAP2 or not encrypted.




### 5.5.3 Connect to the Wi-Fi network using PBC on the web UI

**Step 1** Get the ONT ready for WPS negotiation.


1. Log in to the web UI of the ONT.
2. Choose **WLAN > WPS**.
3. Click Start PBC.




If the following message is displayed, the PBC is started successfully.




**Step 2** Configure the WPS function on your wireless devices **within 2 minutes**. Configuration on various devices may differ (Example: HUAWEI P10 smartphone).

1. Find **Settings** on the phone.
2. Choose **WLAN**.
3. Tap , and choose **WLAN settings**.



4. Choose **WPS connection**.




---End

Wait a moment until the WPS negotiation is completed, and the phone is connected to the Wi-Fi network.





- If multiple wireless networks are enabled in a frequency band, the main network is connected by default.
- To use the WPS function, the encryption mode of the wireless network must be WAP2 or not encrypted.




## 5.5.4 Connect to the Wi-Fi network by entering PIN code of clients on the ONT

**Step 1** Find the PIN code of the client. (The method differs with devices. HUAWEI P10 smartphone is used for illustration here.)

1. Find **Settings** on the phone.
2. Choose **WLAN**.
3. Tap , and choose **WLAN settings**.



4. Choose **WPS PIN connection**, and record the PIN code of the client.



**Step 2** Start WPS connection on the ONT.

1. Log in to the web UI of the ONT.
2. Choose **WLAN > wlan1 (2.4 GHz) > WPS**.
3. Enter the PIN code in **Client PIN Number** and click **Start PIN**.

---End

After the ONT and the client finish WPS negotiation, the client connects to the Wi-Fi network of the ONT successfully.



- If multiple wireless networks are enabled in a frequency band, the main network is connected by default.
- To use the WPS function, the encryption mode of the wireless network must be WAP2 or not encrypted.

### 5.5.5 Connect to the Wi-Fi network by entering PIN code of the ONT on clients



This method is usually used on WiFi network adapters. Please refer to the user guide of the WiFi network adapter for configuration details.

#### Configuring procedure:

- Step 1** Choose **WLAN > wlan (2.4GHz) > WPS** on the web UI. Find and record the **Self-PIN Number** of the ONT.

<input type="checkbox"/> Disable WPS	
Self-PIN Number:	12345670 <span>Regenerate PIN</span>
Push Button Configuration:	<span>Start PBC</span>

- Step 2** Enter the PIN code on the wireless device that supports WPS connection using PIN code.
- End

Wait a moment until the WPS negotiation is completed, and the wireless device is connected to the WiFi network.



- If multiple wireless networks are enabled in a frequency band, the main network is connected by default.
- To use the WPS function, the encryption mode of the wireless network must be WAP2 or not encrypted.

## 5.6 Status

On this page, you can check the information and status of the Wi-Fi network you set up, including those virtual AP Wi-Fi networks.

To access the page, log in to the web UI of the ONT and choose **WLAN > wlan1 (2.4 GHz) > Status**.

WLAN Configuration	
Mode	AP
Band	2.4 GHz (B+G+N)
SSID	Tenda- [REDACTED]
Channel Number	3
Encryption	WPA2 Mixed
BSSID	[REDACTED]
Associated Clients	0

### Parameter description

Parameter	Description
Mode	It specifies the mode of the Wi-Fi network.
Band	It specifies the wireless band and protocol of the Wi-Fi network.
SSID	It specifies the Wi-Fi name of the Wi-Fi network.
Channel Number	It specifies the channel in which the Wi-Fi network works.
Encryption	It specifies the encryption mode of the Wi-Fi network.
BSSID	Basic Service Set Identifier (BSSID) is used to describe sections of a wireless local area network. This service set is the MAC address of the AP's radio for clients to identify and connect to.
Associated Clients	It specifies the number of connected clients.



# 6 WAN

## 6.1 Overview

After you have [registered the ONT](#) successfully, you can set up the WAN connection.



You can set up WAN connections to access different types of services or a combination of them, including internet, TR069, voice, and others. Internet is used for illustration in this chapter unless specified.

The ONT can work under the following two modes:

- [Bridge mode](#): The channel mode is set to **Bridged**. To access the internet, you can set up an internet connection (PPPoE, DHCP, or static IP) on a computer or router connected to the ONT.
- [Router mode](#): The channel mode is set to **IPoE**, **PPPoE** or **6rd**. To access the internet, you can set up WAN connections on the ONT.



Under the bridge mode, you can only access the internet through the LAN ports of the ONT. Under the router mode, you can access the internet through both the LAN ports and Wi-Fi networks of the ONT.

To access the configuration page, log in to the web UI of the ONT and choose **WAN > WAN > PON WAN**. Required settings for WAN connections differ with the channel modes, connection types and IP protocols that you choose.

## Common WAN settings

This part shows the common settings in all types of WAN connections.

nas0_0 ▾	
Enable VLAN:	<input checked="" type="checkbox"/>
VLAN ID:	10
802.1p_Mark	▾
Channel Mode:	PPPoE ▾
Enable NAPT:	<input type="checkbox"/>
Admin Status:	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Connection Type:	INTERNET ▾
MTU:	1492
Enable IGMP-Proxy:	<input checked="" type="checkbox"/>
Enable MLD-Proxy:	<input checked="" type="checkbox"/>
IP Protocol:	IPv4 ▾

### Parameter description

Parameter	Description
nas0_0	<p>It specifies the WAN connection name which you set up.</p> <p>You can add multiple WAN connections by clicking the drop-down list and choose <b>new link</b>. After configuring required parameters, you can click <b>Apply Change</b> to save the connections.</p> <p>This parameter is generated automatically after you create a new link and cannot be customized. A maximum of eight links can be created here.</p>
Enable VLAN	If the WAN connection you want to set up includes VLAN information, you can select <b>Enable VLAN</b> and set the <b>VLAN ID</b> as required.
VLAN ID	
802.1p_Mark	This parameter is available only when the <b>Enable VLAN</b> function is enabled. It specifies the 802.1P priority. Data with a larger priority value takes a higher priority to be processed.
Multicast Vlan ID: [1-4094] (HG6)	This VLAN ID must already exist in 802.1Q VLAN and only ports in this VLAN can forward multicast packets.

Parameter	Description
Channel Mode	<p>It specifies the mode that you used to set up the WAN connection, including <b>Bridged</b>, <b>IPoE</b>, <b>PPPoE</b> and <b>6rd</b>.</p> <ul style="list-style-type: none"> <li>• <b>Bridged</b>: Select this type when this device only serves as a modem, and you want to set up a dial-up connection or enter other internet parameters directly on your computer for internet access.</li> <li>• <b>IPoE</b>: Select <b>DHCP</b> if your ISP does not provide any parameters to you for internet access, and select <b>Fixed IP</b> if your ISP provides a static IP address and other related information to you for internet access.</li> <li>• <b>PPPoE</b>: Select this type if your ISP provides a user name and password to you for internet access.</li> <li>• <b>6rd</b>: Select this type when you want to deploy the IPv6 network rapidly based on IPv4 infrastructures.</li> </ul>
Enable NAPT	<p>It specifies whether to enable the Network Address Port Translation (NAPT) function. NAPT is a technique in which port numbers and private IP addresses are mapped from multiple internal hosts to one public IP address and enable hosts within the LAN to access the internet with the same public IP address. If multiple devices need to share the WAN in the router mode, you need to enable NAPT.</p>
Admin Status	<p>It specifies whether to enable this WAN connection.</p>
Connection Type	<p>It specifies the WAN connection type. Choose the proper connection type as required by your ISP.</p> <ul style="list-style-type: none"> <li>• Other</li> <li>• TR069</li> <li>• INTERNET</li> <li>• INTERNET_TR069</li> <li>• VOICE</li> <li>• VOICE_TR069</li> <li>• VOICE_INTERNET</li> <li>• VOICE_INTERNET_TR069</li> </ul>
MTU	<p>Maximum Transmission Unit (MTU) is the largest data packet transmitted by a network device. When the channel mode is PPPoE, the default MTU value is 1492. When the channel mode is IPoE, the default MTU value is 1500. Do not change the value unless necessary.</p>
Enable IGMP-Proxy	<p>It specifies whether to enable the Internet Group Management Protocol (IGMP) Proxy. If you are not sure, keep the default setting or consult your ISP.</p> <p>IGMP Proxy is used to manage multicast data and reduce traffic replication. IGMP proxy enables a device to issue IGMP host messages on behalf of its users, reducing IGMP messages and the load for the uplink device.</p>
Enable MLD-Proxy	<p>It specifies whether to enable the Multicast Listener Discovery (MLD) Proxy. If you are not sure, keep the default setting or consult your ISP.</p> <p>MLD is the IPv6 equivalent of IGMP.</p>
IP Protocol	<p>It specifies the adopted IP protocol version.</p> <ul style="list-style-type: none"> <li>• <b>IPv4</b>: Select this option if IPv4 is used for communication.</li> <li>• <b>IPv6</b>: Select this option if IPv6 is used for communication.</li> <li>• <b>IPv4/IPv6</b>: Select this option if both IPv4 and IPv6 are used for communication.</li> </ul>


## WAN IP settings

You can configure the WAN IPv4 address information in this part.

This part needs to be configured only when **Channel Mode** is set to **IPoE** and **IP Protocol** is set to **IPv4** or **IPv4/IPv6** or when **Channel Mode** is set to **6rd**.

WAN IP Settings:	
Type:	<input checked="" type="radio"/> Fixed IP <input type="radio"/> DHCP
Local IP Address:	<input type="text" value="0.0.0.0"/>
Remote IP Address:	<input type="text" value="0.0.0.0"/>
Subnet Mask:	<input type="text" value="0.0.0.0"/>
IP Unnumbered	<input type="checkbox"/>
Request DNS:	<input type="radio"/> Enable <input checked="" type="radio"/> Disable
Primary DNS Server:	<input type="text"/>
Secondary DNS Server:	<input type="text"/>

### Parameter description

Parameter	Description
Type	<p>It specifies the method used by the ONT to obtain WAN IP address information.</p> <ul style="list-style-type: none"> <li>• <b>Fixed IP:</b> You need to configure the local IP address, remote IP address (gateway address) and other related information manually.</li> <li>• <b>DHCP:</b> The ONT obtains WAN IP address information automatically. Choose this type if your ISP does not provide related parameters.</li> </ul>
Local IP Address	
Remote IP Address	If you select <b>Fixed IP</b> for <b>Type</b> , you should manually enter the IP address and related information provided by your ISP.
Subnet mask	
IP Unnumbered	<p>It specifies whether to enable the IP unnumbered function.</p> <p>With it enabled, you can enable IP processing on a serial interface without assigning it a unique IP address. The IP unnumbered interface can "borrow" the IP address of another interface already configured on the router, which conserves network and address space. If it cannot be enabled on the web UI, this function is not supported.</p>
Request DNS	If the IP address is obtained through DHCP, you can select <b>Request DNS</b> to obtain the DNS server address automatically.
Primary DNS Server	If the IP address obtaining type is <b>Fixed IP</b> or <b>Request DNS</b> function is disabled when the IP address obtaining type is <b>DHCP</b> , you should enter the DNS server address provided by your ISP.
Secondary DNS Server	<p> <b>TIP</b></p> <p>If the ISP only provides one DNS server address, you can leave the secondary DNS blank.</p>

## IPv6 WAN settings

You can configure the WAN IPv6 address information in this part.

When **IP Protocol** is set to **IPv6** or **IPv4/IPv6**, and **Channel Mode** is set to **IPoE** or **PPPoE**, these parameters are required.

IPv6 WAN Setting:	
Address Mode:	<input type="checkbox"/> Slaac <input checked="" type="checkbox"/> Static
IPv6 Address:	<input type="text"/> / <input type="text"/>
IPv6 Gateway:	<input type="text"/>
Enable DHCPv6 Client:	<input checked="" type="checkbox"/>
Request Options:	<input checked="" type="checkbox"/> Request Address <input checked="" type="checkbox"/> Request Prefix
Request DNS:	<input type="radio"/> Enable <input checked="" type="radio"/> Disable
Primary IPv6 DNS:	<input type="text"/>
Secondary IPv6 DNS:	<input type="text"/>

### Parameter description

Parameter	Description
Address Mode	<p>It specifies how the WAN IPv6 address of the ONT is obtained, including:</p> <ul style="list-style-type: none"> <li>• <b>Slaac</b>: Stateless Address Autoconfiguration (SLAAC) is a dynamic allocation method of IPv6 address, which enables the ONT to auto-generate IPv6 addresses with local information and those from the router advertisement.</li> <li>• <b>Static</b>: You need to enter parameters related to IPv6 address manually.</li> </ul>
IPv6 Address	It specifies the IPv6 address and prefix length provided by your ISP when you select <b>Static</b> for <b>Address Mode</b> .
IPv6 Gateway	It specifies the IPv6 gateway address of the ONT when you select <b>Static</b> for <b>Address Mode</b> .
Enable DHCPv6 Client	It specifies whether the ONT acts as a client to receive configuration information from the DHCPv6 server.
Request Options	You can enable the ONT to obtain the IPv6 address and prefix as a DHCPv6 client when <b>Enable DHCPv6 Client</b> is selected.
Request DNS	When <b>Request DNS</b> is set to <b>Enable</b> , the ONT obtains the IPv6 DNS server address from the DHCPv6 server.
Primary IPv6 DNS	When <b>Request DNS</b> is set to <b>Disable</b> , you need to set the primary and secondary DNS server addresses manually.
Secondary IPv6 DNS	



## PPP settings

You can configure the PPPoE parameters to access the internet in this part.

When **Channel Mode** is set to **PPPoE**, these parameters are required.

PPP Settings:	
UserName:	<input type="text"/>
Password:	<input type="password"/>
Type:	Continuous ▼

### Parameter description

Parameter	Description
UserName	They specify the PPPoE user name and password for settings up the WAN connection.
Password	
Type	<p>It specifies the PPPoE connection type.</p> <ul style="list-style-type: none"> <li>• <b>Continuous:</b> The ONT keeps connected to the internet.</li> <li>• <b>Connect on Demand:</b> The ONT disconnects from the internet after a certain period and establishes the connection as soon as you attempt to access the internet.</li> <li>• <b>Manual:</b> Users should manually connect and disconnect the network connection.</li> </ul>
AC-Name (HG6)	<p>It specifies the PPPoE server name, for the ONT to verify the legitimacy of the PPPoE server.</p> <p> <b>TIP</b></p> <p>If your ISP did not provide a service name, leave this field blank. Otherwise, a dial failure may occur.</p>
Service-Name (HG6)	<p>It specifies the PPPoE service name used by the PPPoE server to verify the legitimacy of the ONT.</p> <p> <b>TIP</b></p> <p>If your ISP did not provide a service name, leave this field blank. Otherwise, a dial failure may occur.</p>

## 6rd configuration

When you want to access a certain IPv6 network or service of your service provider through an IPv4 network and you are provided with related parameters, you can set up a 6rd connection.

When **Channel Mode** is set to **6rd**, these parameters are required.

6rd Config:	
Board Router v4 Address:	<input type="text"/>
6rd IPv4 Mask Len:	<input type="text"/>
6rd Prefix (EX:"2001:db8::"):	<input type="text"/>
6rd Prefix length:	<input type="text"/>

## Parameter description

Parameter	Description
Board Router v4 Address	It specifies the IPv4 address of the remote border relay router.
6rd IPv4 Mask Len	It specifies the length of the IPv4 subnet mask used for 6rd connection. The WAN IPv4 addresses of both ends must be in the same segment.
6rd Prefix (EX:"2001:db8::")	<p>It specifies the IPv6 prefix of the current network.</p> <ul style="list-style-type: none"> <li>• If the 6rd channel is used for communication between IPv6 islands, you can customize the IPv6 prefix here.</li> <li>• If the 6rd channel is used for accessing the ISP's IPv6 network, the IPv6 prefix must be provided by the ISP.</li> </ul>
6rd Prefix length	It specifies the 6rd prefix length.

## Port mapping

You can configure the port mapping options in this part. When certain interfaces are selected for the WAN connection, devices connected to these interfaces use the WAN connection to access the internet preferentially.

Port Mapping:	
<input type="checkbox"/> LAN_1	<input type="checkbox"/> LAN_2
<input type="checkbox"/> LAN_3	<input type="checkbox"/> LAN_4
<input type="checkbox"/> WLAN0	
<input type="checkbox"/> WLAN0-AP1	<input type="checkbox"/> WLAN0-AP2
<input type="checkbox"/> WLAN0-AP3	<input type="checkbox"/> WLAN0-AP4
<input type="checkbox"/> WLAN1	
<input type="checkbox"/> WLAN1-AP1	<input type="checkbox"/> WLAN1-AP2
<input type="checkbox"/> WLAN1-AP3	<input type="checkbox"/> WLAN1-AP4

## 6.2 Bridge mode


If you have a router and want to set up internet access on it, or you only want to access the internet on a certain computer, you can use the ONT under bridge mode.



When the ONT is under bridge mode, you can only access the internet through the downstream device used for setting up internet access.

Under bridge mode, the ONT acts as a bridging device between your LAN and your ISP. The ONT works under bridge mode by default.

The network topology of the scenario is shown as follows.




### 6.2.1 Configure internet access on a computer




Configure your computer to access the internet according to the parameters provided by your ISP. PPPoE is used for illustration here.


#### Configuring procedure:

- Step 1** Connect your computer to a LAN port of the ONT.
- Step 2** Right-click  on the desktop and choose **Network Connections**.
- Step 3** Choose **Dial-up** and click **Set up a new connection**.







**Step 4** Click **Connect to the Internet** and click **Next**.



**Step 5** Click **Broadband (PPPoE)**.



**Step 6** Enter the PPPoE **User name** and **Password** provided by your ISP and click **Connect**.



---End


After the configuration, you can access the internet on the computer.

## 6.2.2 Configure internet access on a router

Assume that your ISP provides you with the PPPoE user name and password.

**Configuring procedure:**

**Step 1** Connect the WAN port of router to a LAN port of the ONT using an Ethernet cable.



**Step 2** Refer to the quick installation guide or user guide of your router to configure the internet access.

---End

After the configuration, you can access the internet through the router.

## 6.3 Router mode

If you want to set up WAN connections for one or multiple services on the ONT, and access the WAN connection through both the Wi-Fi networks of the ONT and LAN ports, you can set the ONT to router mode. Based on the information provided by your ISP, you need to complete different configurations on the web UI.

### 6.3.1 Set up a fixed IP connection

When your ISP provides fixed IP address (IPv4 or IPv6, or both) information, which may include the IP address, subnet mask and DNS server, you can set up a fixed IP connection.

#### Configuring procedure:

- Step 1** Log in to the web UI of the ONT.
- Step 2** Choose **WAN > PON WAN**.
- Step 3** Set **Channel Mode** to **IPoE**.
- Step 4** Set other common WAN parameters as required by your ISP.

nas0_0 ▾	
Enable VLAN:	<input checked="" type="checkbox"/>
VLAN ID:	<input type="text"/>
802.1p_Mark	<input type="text"/>
Channel Mode:	IPoE ▾
Enable NAPT:	<input type="checkbox"/>
Admin Status:	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Connection Type:	INTERNET ▾
MTU:	<input type="text" value="1500"/>
Enable IGMP-Proxy:	<input type="checkbox"/>
Enable MLD-Proxy:	<input type="checkbox"/>
IP Protocol:	IPv4 ▾

- Step 5** Configure **WAN IP Settings** or/and **IPv6 WAN Setting** based on the IP protocol you choose.
  - In the **WAN IP Settings** part, set **Type** to **Fixed IP** and configure other parameters as required.
  - In the **IPv6 WAN Setting** part, set **Address Mode** to **Static** and configure other parameters as required.

WAN IP Settings:	
Type:	<input checked="" type="radio"/> Fixed IP <input type="radio"/> DHCP
Local IP Address:	<input type="text" value="0.0.0.0"/>
Remote IP Address:	<input type="text" value="0.0.0.0"/>
Subnet Mask:	<input type="text" value="255.255.255.0"/>
IP Unnumbered:	<input type="checkbox"/>
Request DNS:	<input type="radio"/> Enable <input checked="" type="radio"/> Disable
Primary DNS Server:	<input type="text"/>
Secondary DNS Server :	<input type="text"/>

IPv6 WAN Setting:	
Address Mode:	<input type="text" value="Static"/>
IPv6 Address:	<input type="text"/> / <input type="text"/>
IPv6 Gateway:	<input type="text"/>
Request DNS :	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Primary IPv6 DNS:	<input type="text"/>
Secondary IPv6 DNS:	<input type="text"/>

**Step 6** (Optional) Configure **Port Mapping** as required.

Port Mapping:	
<input type="checkbox"/> LAN_1	<input type="checkbox"/> LAN_2
<input type="checkbox"/> LAN_3	<input type="checkbox"/> LAN_4
<input type="checkbox"/> WLAN0	
<input type="checkbox"/> WLAN0-AP1	<input type="checkbox"/> WLAN0-AP2
<input type="checkbox"/> WLAN0-AP3	<input type="checkbox"/> WLAN0-AP4
<input type="checkbox"/> WLAN1	
<input type="checkbox"/> WLAN1-AP1	<input type="checkbox"/> WLAN1-AP2
<input type="checkbox"/> WLAN1-AP3	<input type="checkbox"/> WLAN1-AP4

**Step 7** Click **Apply Changes**.

---End

After the configuration, you can access the internet through the LAN ports or Wi-Fi networks of the ONT, or by connecting a router (connection type: DHCP/dynamic IP) to a LAN port of the ONT.

## 6.3.2 Set up a dynamic IP connection

If your ISP does not provide any parameters, you can try to set up a DHCP connection.

**Configuring procedure:**

- Step 1** Log in to the web UI of the ONT.
- Step 2** Choose **WAN > PON WAN**.
- Step 3** Set **Channel Mode** to **IPoE**.
- Step 4** Set other common WAN parameters as required by your ISP.

nas0_0 ▼	
Enable VLAN:	<input checked="" type="checkbox"/>
VLAN ID:	<input type="text"/>
802.1p_Mark	<input type="text" value="0"/>
Channel Mode:	IPoE ▼
Enable NAPT:	<input type="checkbox"/>
Admin Status:	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Connection Type:	INTERNET ▼
MTU:	<input type="text" value="1500"/>
Enable IGMP-Proxy:	<input type="checkbox"/>
Enable MLD-Proxy:	<input type="checkbox"/>
IP Protocol:	IPv4 ▼

- Step 5** Configure **WAN IP Settings** or/and **IPv6 WAN Setting** based on the IP protocol you choose.
- In the **WAN IP Settings** part, set **Type** to **DHCP** and configure other parameters as required.
  - In the **IPv6 WAN Setting** part, set **Type** to **Slaac** and configure other parameters as required.

WAN IP Settings:	
Type:	<input type="radio"/> Fixed IP <input checked="" type="radio"/> DHCP
Local IP Address:	<input type="text" value="0.0.0.0"/>
Remote IP Address:	<input type="text" value="0.0.0.0"/>
Subnet Mask:	<input type="text" value="255.255.255.0"/>
IP Unnumbered:	<input type="checkbox"/>
Request DNS:	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Primary DNS Server:	<input type="text"/>
Secondary DNS Server :	<input type="text"/>
IPv6 WAN Setting:	
Address Mode:	Stateless DHCPv6(SLAAC) ▼
Request Options:	<input checked="" type="checkbox"/> Request Prefix
Request DNS :	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Primary IPv6 DNS:	<input type="text"/>
Secondary IPv6 DNS:	<input type="text"/>

**Step 6** (Optional) Configure **Port Mapping** as needed.

Port Mapping:	
<input type="checkbox"/> LAN_1	<input type="checkbox"/> LAN_2
<input type="checkbox"/> LAN_3	<input type="checkbox"/> LAN_4
<input type="checkbox"/> WLAN0	
<input type="checkbox"/> WLAN0-AP1	<input type="checkbox"/> WLAN0-AP2
<input type="checkbox"/> WLAN0-AP3	<input type="checkbox"/> WLAN0-AP4
<input type="checkbox"/> WLAN1	
<input type="checkbox"/> WLAN1-AP1	<input type="checkbox"/> WLAN1-AP2
<input type="checkbox"/> WLAN1-AP3	<input type="checkbox"/> WLAN1-AP4

**Step 7** Click **Apply Changes**.

---End

After the configuration, you can access the internet through the LAN ports or Wi-Fi networks of the ONT, or by connecting a router (connection type: DHCP/dynamic IP) to a LAN port of the ONT.

### 6.3.3 Set up a PPPoE connection

If your ISP provides the PPPoE user name, password, and other related parameters (if any), you can set up a PPPoE connection.

**Configuring procedure:**

**Step 1** Log in to the web UI of the ONT.

**Step 2** Choose **WAN > PON WAN**.

**Step 3** Set **Channel Mode** to **PPPoE**.

**Step 4** Choose an **IP Protocol** in the drop-down list.

**Step 5** Set other common WAN parameters as required by your ISP.

nas0_0 ▾	
Enable VLAN:	<input checked="" type="checkbox"/>
VLAN ID:	<input type="text"/>
802.1p_Mark	<input type="text" value=""/>
Channel Mode:	PPPoE ▾
Enable NAPT:	<input type="checkbox"/>
Admin Status:	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Connection Type:	INTERNET ▾
MTU:	<input type="text" value="1492"/>
Enable IGMP-Proxy:	<input type="checkbox"/>
Enable MLD-Proxy:	<input type="checkbox"/>
IP Protocol:	IPv4 ▾

**Step 6** Enter the PPPoE **UserName** and **Password** provided by your ISP in **PPP Settings**.

PPP Settings:	
UserName:	<input type="text"/>
Password:	<input type="text"/>
Type:	Continuous ▾

**Step 7** (Optional) If you set **IP Protocol** to **IPv6** or **IPv4/IPv6**, enter required parameters in **IPv6 WAN Setting**.

**Step 8** (Optional) Configure **Port Mapping** as needed.

Port Mapping:	
<input type="checkbox"/> LAN_1	<input type="checkbox"/> LAN_2
<input type="checkbox"/> LAN_3	<input type="checkbox"/> LAN_4
<input type="checkbox"/> WLAN0	
<input type="checkbox"/> WLAN0-AP1	<input type="checkbox"/> WLAN0-AP2
<input type="checkbox"/> WLAN0-AP3	<input type="checkbox"/> WLAN0-AP4
<input type="checkbox"/> WLAN1	
<input type="checkbox"/> WLAN1-AP1	<input type="checkbox"/> WLAN1-AP2
<input type="checkbox"/> WLAN1-AP3	<input type="checkbox"/> WLAN1-AP4

**Step 9** Click **Apply Changes**.

---End

After the configuration, you can access the internet through the LAN ports or Wi-Fi networks of the ONT, or by connecting a router (connection type: DHCP/dynamic IP) to a LAN port of the ONT.

## 6.3.4 Set up a 6rd connection

When you want to access a certain IPv6 network or service of your service provider through an IPv4 network and you are provided with related parameters, you can set up a 6rd connection.

### Configuring procedure:

- Step 1** Log in to the web UI of the ONT.
- Step 2** Choose **WAN > PON WAN**.
- Step 3** Set **Channel Mode** to **6rd**.
- Step 4** Set other common WAN parameters as required by your ISP.

nas0_0 ▼	
Enable VLAN:	<input checked="" type="checkbox"/>
VLAN ID:	<input type="text"/>
802.1p_Mark	<input type="text"/>
Channel Mode:	6rd ▼
Enable NAPT:	<input type="checkbox"/>
Admin Status:	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Connection Type:	INTERNET ▼
MTU:	1500
Enable IGMP-Proxy:	<input type="checkbox"/>
Enable MLD-Proxy:	<input type="checkbox"/>

- Step 5** Set parameters in the **WAN IP Settings** part using the parameters provided by your ISP.

WAN IP Settings:	
Type:	<input type="radio"/> Fixed IP <input checked="" type="radio"/> DHCP
Local IP Address:	<input type="text"/>
Remote IP Address:	<input type="text"/>
Subnet Mask:	<input type="text"/>
IP Unnumbered	<input type="checkbox"/>
Request DNS:	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Primary DNS Server:	<input type="text"/>
Secondary DNS Server:	<input type="text"/>

- Step 6** Set parameters in the **6rd Config** part using the parameters provided by your ISP.



6rd Config:	
Board Router v4 Address:	<input type="text"/>
6rd IPv4 Mask Len:	<input type="text"/>
6rd Prefix (EX:"2001:db8::"):	<input type="text"/>
6rd Prefix length:	<input type="text"/>

**Step 7** (Optional) Configure **Port Mapping** as required.

Port Mapping:	
<input type="checkbox"/> LAN_1	<input type="checkbox"/> LAN_2
<input type="checkbox"/> LAN_3	<input type="checkbox"/> LAN_4
<input type="checkbox"/> WLAN0	
<input type="checkbox"/> WLAN0-AP1	<input type="checkbox"/> WLAN0-AP2
<input type="checkbox"/> WLAN0-AP3	<input type="checkbox"/> WLAN0-AP4
<input type="checkbox"/> WLAN1	
<input type="checkbox"/> WLAN1-AP1	<input type="checkbox"/> WLAN1-AP2
<input type="checkbox"/> WLAN1-AP3	<input type="checkbox"/> WLAN1-AP4

**Step 8** Click **Apply Changes**.

---End

After the configuration, you can access the internet through the LAN ports or Wi-Fi networks of the ONT, or by connecting a router (connection type: DHCP/ dynamic IP) to a LAN port of the ONT.

# 7 Services

## 7.1 Service

### 7.1.1 DHCP

#### Overview


The DHCP server can automatically assign IP addresses, subnet masks, gateway addresses and DNS to LAN clients. When it is disabled, you need to manually configure the IP address information on the LAN device to access the internet. Disable it only when necessary.

To access the configuration page, log in to the web UI of the ONT and choose **Services > Service > DHCP**.

<b>DHCP Mode:</b>	<input type="radio"/> NONE <input checked="" type="radio"/> DHCP Server	
Enable the DHCP Server if you are using this device as a DHCP server. This page lists the IP address pools available to hosts on your LAN. The device distributes numbers in the pool to hosts on your network as they request Internet access.		
LAN IP Address: 192.168.1.1 Subnet Mask: 255.255.255.0		
<b>IP Pool Range:</b>	192.168.1.2 - 192.168.1.254	<a href="#">Show Client</a>
<b>Subnet Mask:</b>	255.255.255.0	
<b>Max Lease Time:</b>	86400 seconds (-1 indicates an infinite lease)	
<b>Gateway Address:</b>	192.168.1.1	
<b>DNS option:</b>	<input checked="" type="radio"/> Use DNS Relay <input type="radio"/> Set Manually	

#### Parameter description

Parameter	Description
DHCP Mode	<p>It specifies the status of the DHCP server.</p> <ul style="list-style-type: none"> <li><b>NONE:</b> The DHCP server is disabled.</li> <li><b>DHCP Server:</b> The DHCP server is enabled.</li> </ul>
LAN IP address	It specifies the current LAN IP address of the ONT, which is also the IP address used to log in to the web UI of the ONT.
Subnet Mask	It specifies the current subnet mask of the LAN.
IP Pool Range	It specifies the range of IP addresses that a DHCP server can assign to LAN clients.

Parameter	Description
Show Client	<p>It shows information of the active DHCP clients, including:</p> <ul style="list-style-type: none"> <li>• <b>IP Address:</b> It specifies the IP address assigned to the DHCP leased client.</li> <li>• <b>MAC Address:</b> It specifies the MAC address of the DHCP leased client.</li> <li>• <b>Expired Time (sec):</b> It specifies the time expired for the DHCP leased client.</li> </ul>
Subnet Mask	It specifies the subnet mask of the DHCP clients.
Max Lease Time	It specifies the valid time of the IP addresses assigned by the DHCP server of the ONT to the DHCP clients.
Gateway Address	It specifies the gateway IP address of DHCP clients.
DNS option	<p>It specifies how the ONT assigns DNS server addresses to LAN clients.</p> <ul style="list-style-type: none"> <li>• <b>Use DNS Relay:</b> The ONT forwards the DNS query packets from LAN clients to an external DNS server.</li> <li>• <b>Set Manually:</b> You need to set the DNS server address manually. You can set three DNS servers at most, and at least one is required.</li> </ul>
MAC-Based Assignment	<p>It is used to assign fixed IP addresses to certain LAN clients based on their MAC addresses. Devices with the MAC address connected to the ONT get the same IP address every time.</p> <p> <b>TIP</b></p> <p>Please note the format of the MAC address. Use “-” to separate every two characters in the MAC address.</p>

## Reserve IP addresses for certain devices

**Scenario:** You have an FTP server at home under the LAN of the ONT.

**Requirement:** You want to visit resources on the FTP server when you are not at home and avoid instability of services resulted from the dynamic IP address assigned by the ONT.

**Solution:** You can reserve a fixed IP address for the FTP server to reach the goal.

Assume that:

- Fixed IP address reserved for the FTP server: 192.168.1.136
- MAC address of the FTP server host: D4:61:DA:1B:CD:89

### Configuring procedure:

**Step 1** Log in to the web UI of the ONT.

**Step 2** Choose **Services > Service > DHCP**.

**Step 3** Click **MAC-Based Assignment**.

**Step 4** Set **MAC Address** in the format of **D4-61-DA-1B-CD-89**.

**Step 5** Enter **192.168.1.136** in **Assigned IP Address**.

**Step 6** Click **Assign IP**.

### MAC-Based Assignment

This page is used to configure the static IP base on MAC Address. You can assign/delete the static IP. The Host MAC Address, please input a string with hex number. Such as 00-d0-59-c6-12-43. The Assigned IP Address, please input a string with digit. Such as 192.168.1.100 .

<b>Enable:</b>	<input type="checkbox"/>
<b>MAC Address (xx-xx-xx-xx-xx-xx):</b>	<input type="text" value="D4-61-DA-1B-CD-89"/>
<b>Assigned IP Address (xxx.xxx.xxx.xxx):</b>	<input type="text" value="192.168.1.136"/>

MAC-Based Assignment Table			
Select	Enable	MAC Address	Assigned IP Address

-----End

Now you can access resources on the FTP server free from the influence of the dynamic IP address.

## 7.1.2 Dynamic DNS

### Overview

The Dynamic DNS (DDNS) maps the WAN IP address (changeable public IP address) of the ONT to a domain name for dynamic domain name resolution. This ensures proper operation of functions that involve the WAN IP address of the ONT, such as port forwarding and DMZ.

To access the configuration page, log in to the web UI of the ONT and choose **Services > Service > Dynamic DNS**.

<b>Enable:</b>	<input checked="" type="checkbox"/>
<b>DDNS Provider:</b>	<input type="text" value="DynDNS.org"/>
<b>Hostname:</b>	<input type="text"/>
<b>Interface</b>	<input type="text" value="v"/>
<b>DynDns Settings</b>	
<b>UserName:</b>	<input type="text"/>
<b>Password:</b>	<input type="text"/>
<b>TZO Settings</b>	
<b>Email:</b>	<input type="text"/>
<b>Key:</b>	<input type="text"/>
<input type="button" value="Add"/>	<input type="button" value="Modify"/> <input type="button" value="Remove"/>
<b>Dynamic DNS Table</b>	
<b>Select State</b>	<b>Hostname</b>
	<b>UserName</b>
	<b>Service</b>
	<b>Status</b>

### Parameter description

Parameter		Description
Enable		It specifies whether the rule takes effect after being added.
DDNS Provider		It specifies the DDNS service provider. The ONT supports <b>DynDNS.org</b> , <b>TZO</b> and <b>NO-IP</b> . You need to register and purchase services from one of these service providers and use the parameters provided by the service provider to configure the function on the ONT.
Hostname		It specifies the hostname registered with the DDNS service.
Interface		It specifies the WAN interface on which the dynamic DNS rule takes effect.
DynDns Settings	UserName	They specify the user name and password registered on a DDNS service provider for logging in to the DDNS service.
	Password	These fields are only available when the service provider is set to <b>DynDNS.org</b> and <b>NO-IP</b> .
TZO Settings	Email	They specify the Email and key you registered with the DDNS service provider.
	Key	
Add/Modify/Remove		<ul style="list-style-type: none"> <li>• <b>Add:</b> It is used to add a new dynamic DNS rule.</li> <li>• <b>Modify:</b> It is used to modify existing dynamic DNS rules.</li> <li>• <b>Remove:</b> It is used to delete existing dynamic DNS rules.</li> </ul>

## Enable internet users to access LAN resources using a domain name

**Scenario:** You have set up an FTP server within your LAN.

**Goal:** Open the FTP server to internet users and enable yourself to access the resources of the FTP server from the internet using a domain name when you are not at home.

**Solution:** You can configure the DDNS plus port forwarding functions to reach the goal.

Assume that the information of the FTP server includes:


- IP address: 192.168.1.136
- Service port: 21

The information of the registered DDNS service:

- Service provider: DynDNS.org
- User name: JohnDoe
- Password: JohnDoe123
- Domain name: o2849z7222.zicp.vip



Please ensure that the ONT obtains a public IP address. This function may not work on a host with an IP address of a private network or an intranet IP address assigned by ISPs that start with 100. Common IPv4 addresses are classified into class A, class B and class C. Private IP addresses of class A range from 10.0.0.0 to 10.255.255.255. Private IP addresses of class B range from 172.16.0.0 to 172.31.255.255. Private IP addresses of class C range from 192.168.0.0 to 192.168.255.255.



### Configuring procedure:

**Step 1** Log in to the web UI of the ONT.

**Step 2** Add a Dynamic DNS rule.

1. Choose **Services > Service > Dynamic DNS**.
2. Select **Enable**.
3. Choose a service provider in **DDNS Provider**, which is **DynDNS.org** in this example.
4. Enter the **Hostname**, which is **o2849z7222.zicp.vip** in this example.
5. Select the WAN interface that the port forwarding rule applies to.

6. Enter the user name and password in the **DynDns Settings** part, which are **JohnDoe** and **JohnDoe123456** in this example.
7. Click **Add**.

<b>Enable:</b>	<input checked="" type="checkbox"/>
<b>DDNS Provider:</b>	DynDNS.org ▼
<b>Hostname:</b>	o2849z7222.zicp.vip
<b>Interface</b>	ppp0 ▼
<b>DynDns Settings</b>	
<b>UserName:</b>	JohnDoe
<b>Password:</b>	.....

**Step 3** Configure the port forwarding function (refer to [port forwarding](#)).


---End

After the configuration, users from the internet can access the FTP server by visiting “*Intranet service application layer protocol name://Domain name*”. If the remote port number is not the same as the default intranet service port number, the accessing address should be: “*Intranet service application layer protocol name://Domain name:Remote port number*”.


In this example, the address is **ftp://o2849z7222.zicp.vip**.

**To access the FTP server from the internet with a domain name:**

Open the file explorer on a computer that can access the internet, and visit **ftp://o2849z7222.zicp.vip**.



Enter the user name and password to access the resources on the FTP server.



After the configuration, if internet users still cannot access the FTP server, try the following methods:

- Ensure that the local port number configured in the port forwarding function is the same as the intranet service port number set on the server.
- Close the firewall, antivirus software and security guards on the host of the FTP server and try again.

### 7.1.3 IGMP Proxy

IGMP proxy enables a device to issue IGMP host messages on behalf of its users, and reduces IGMP messages and the load for uplink device. The ONT with IGMP proxy enabled intercepts and processes the IGMP messages of its users, and then forward them to its uplink device. It assumes the role of router on the user side, queries user information regularly, and assumes the role of client on the network routing side, and sends the current user information to it when needed. Therefore, a multicast routing table is formed in the ONT with IGMP Proxy enabled.

To access the configuration page, log in to the web UI of the ONT and choose **Services > Service > IGMP Proxy**.



The IGMP proxy function can only be edited when there is at least one WAN connection with IGMP proxy enabled.

<b>IGMP Proxy:</b>	<input type="radio"/> Disable <input checked="" type="radio"/> Enable
<input type="button" value="Apply Changes"/>	



### 7.1.4 UPnP

UPnP is short for Universal Plug and Play. This function enables the ONT to open port automatically for UPnP-based programs. It is generally used for P2P programs, such as BitComet and AnyChat, and helps increase the download speed.

To access the configuration page, log in to the web UI of the ONT and choose **Services > Service > UPnP**.

UPnP:	<input type="radio"/> Disable <input checked="" type="radio"/> Enable
<input type="button" value="Apply Changes"/>	

### 7.1.5 Samba

Samba enables computers using different operating systems in the same LAN to share resources.

To access the configuration page, log in to the web UI of the ONT and choose **Services > Service > Samba**.

Samba:	<input type="radio"/> Disable <input checked="" type="radio"/> Enable
Server String :	<input type="text" value="Tenda Samba Server"/>
<input type="button" value="Apply Changes"/>	

## 7.2 Firewall

### 7.2.1 ALG

Application Layer Gateway (ALG) is a software component that manages specific application protocols such as Session Initiation Protocol (SIP) and File Transfer Protocol (FTP). The ALG acts as an intermediary between the internet and an application server and allows or denies traffic of certain types to the application server. It does this by intercepting and analyzing the specified traffic, allocating resources, and defining dynamic policies to allow traffic to pass through.

To access the configuration page, log in to the web UI of the ONT and choose **Service > Firewall > Dynamic DNS**.

ALG Type		
ftp	<input checked="" type="radio"/> Enable	<input type="radio"/> Disable
tftp	<input checked="" type="radio"/> Enable	<input type="radio"/> Disable
h323	<input checked="" type="radio"/> Enable	<input type="radio"/> Disable
rtsp	<input checked="" type="radio"/> Enable	<input type="radio"/> Disable
l2tp	<input checked="" type="radio"/> Enable	<input type="radio"/> Disable
ipsec	<input checked="" type="radio"/> Enable	<input type="radio"/> Disable
sip	<input checked="" type="radio"/> Enable	<input type="radio"/> Disable
pptp	<input checked="" type="radio"/> Enable	<input type="radio"/> Disable

#### Parameter description

Parameter	Description
ftp	The File Transfer Protocol (FTP) is a standard network protocol used for the transfer of computer files between a client and server on a computer network. The users on LAN can share resources on the FTP server on WAN only when it is selected.
tftp	The Trivial File Transfer Protocol (TFTP) is a simple file transfer protocol that allows a client to get a file from or put a file onto a remote host.
h323	H.323 is a recommendation from the ITU Telecommunication Standardization Sector (ITU-T) that defines the protocols to provide audio-visual communication sessions on any packet network. The H.323 standard addresses call signaling and control, multimedia transport and control, and bandwidth control for point-to-point and multi-point conferences. The IP phone and network conference function can be used on the computers connected to the ONT only when this function is enabled.
rtsp	The Real Time Streaming Protocol (RTSP) is a network control protocol designed for use in entertainment and communications systems to control streaming media servers. The protocol is used for establishing and controlling media sessions between end points. The users on LAN can view videos on demand when this function is enabled.

Parameter	Description
l2tp	<p>The Layer Two Tunneling Protocol (L2TP) is an extension of the Point-to-Point Tunneling Protocol (PPTP) used by an Internet Service Provider (ISP) to enable the operation of a Virtual Private Network (VPN) over the Internet.</p> <p>If you select L2TP protocol when you create a VPN connection on your computer in the LAN of the ONT, it takes effect only when this function is enabled.</p>
ipsec	<p>The Internet Protocol Security (IPsec) is a secure network protocol suite that authenticates and encrypts the packets of data to provide secure encrypted communication between two computers over an IP network. It is used in Virtual Private Networks (VPNs).</p> <p>If you select IPsec protocol when you create a VPN connection on your computer in the LAN of the ONT, it takes effect only when this function is enabled.</p>
sip	<p>The Session Initiation Protocol (SIP) is a signaling protocol used for signaling and controlling multimedia communication sessions in applications of internet telephony for voice and video calls, in private IP telephone systems, in instant messaging over IP networks as well as mobile phone calling over LTE (VoLTE).</p> <p>The IP phone function can be used on the computers connected to the ONT only when this function is enabled.</p>
pptp	<p>The Point-to-Point Tunneling Protocol (PPTP) is an obsolete method for implementing virtual private networks. PPTP has many well-known security issues.</p> <p>If you select the PPTP protocol when you create a VPN connection on your computer in the LAN of the ONT, it takes effect only when this function is enabled.</p>

## 7.2.2 IP/Port filtering

In this section, you can configure filtering rules to restrict certain types of data packets from passing through the ONT. The use of such filters can be helpful in securing or restricting your local network.


- LAN→WAN: By default, all outgoing traffic from LAN is allowed, but some can be blocked by specific filtering rules. Outgoing filtering rules can block outgoing traffic by some conditions.
- WAN→LAN: By default, all incoming traffic is blocked. However, some traffic can access by specific filtering rules. The incoming filtering rules allow traffic to pass in some conditions.

To access the configuration page, log in to the web UI of the ONT and choose **Services > Firewall > IP/Port Filtering**. The rules added are shown in the **Current Filter Table**.

<b>FilteringDirection:</b>	LAN -> WAN ▼					
<b>Default Action:</b>	<input type="radio"/> Deny <input checked="" type="radio"/> Allow		<input type="button" value="Apply Changes"/>			
<b>Protocol:</b> TCP ▼	<b>Rule Action:</b> <input checked="" type="radio"/> Deny <input type="radio"/> Allow					
<b>Source IP Address:</b> <input type="text"/>	<b>Subnet Mask:</b> <input type="text"/>	<b>Port:</b> <input type="text"/> - <input type="text"/>				
<b>Destination IP Address:</b> <input type="text"/>	<b>Subnet Mask:</b> <input type="text"/>	<b>Port:</b> <input type="text"/> - <input type="text"/>				
<input type="button" value="Add"/>						
<b>Current Filter Table</b>						
<b>Select</b>	<b>Protocol</b>	<b>Source IP Address</b>	<b>Source Port</b>	<b>Destination IP Address</b>	<b>Destination Port</b>	<b>Rule Action</b>

### Parameter description

Parameter	Description
FilterDirection Direction (HG6)	It specifies the forwarding direction of data to be filtered.
Default Action	<p>It specifies the default action for the outgoing(LAN→WAN) or incoming(WAN→LAN) data.</p> <ul style="list-style-type: none"> <li>• <b>Deny:</b> Denies traffic which does not match the filter rule in the <b>Current Filter Table</b>.</li> <li>• <b>Allow:</b> Allows traffic which does not match the filter rule in the <b>Current Filter Table</b>.</li> </ul>
Protocol	<p>It specifies the protocol adopted by data to be filtered.</p> <ul style="list-style-type: none"> <li>• <b>TCP:</b> TCP protocol.</li> <li>• <b>UDP:</b> UDP protocol.</li> <li>• <b>ICMP:</b> ICMP protocol.</li> <li>• <b>TCP/UDP:</b> TCP protocol and UDP protocol.</li> <li>• <b>ANY:</b> Any protocol.</li> </ul>
Rule Action	<p>It specifies whether to deny or allow the data to pass through.</p> <ul style="list-style-type: none"> <li>• <b>Deny:</b> Packets that comply with the rule are denied, while others are perform the default action.</li> <li>• <b>Allow:</b> Only packets that comply with the rule are allowed, while others are perform the default action.</li> </ul>
Source IP Address	<p>It specifies the source IP address of the packets. The settings of <b>Source IP Address</b> and <b>Subnet Mask</b> determine which computers are affected by this rule.</p> <ul style="list-style-type: none"> <li>• When <b>Filtering Direction</b> is set to <b>LAN→WAN</b>, this parameter specifies the LAN computer's IP address to be affected.</li> <li>• When <b>Filtering Direction</b> is set to <b>WAN→LAN</b>, this parameter specifies the internet computer's IP address to be affected.</li> <li>• When this parameter is left blank, all IP addresses are covered.</li> </ul>
Subnet Mask	It specifies the subnet mask of the source IP address.

Parameter	Description
Port	<p>It specifies the source port of the packets.</p> <p>The source port is only available for the TCP/UDP protocol. If <b>ICMP</b> or <b>ANY</b> is selected for <b>Protocol</b>, this field is not required.</p> <p> <b>TIP</b></p> <p>Since the source port of the data packet is changeable, it is recommended that the port be set to 1 to 65535 or left blank.</p>
Destination IP Address	<p>It specifies the destination IP address of the packets. The settings of <b>Destination IP Address</b> and <b>Subnet Mask</b> determine which servers are affected by this rule.</p> <ul style="list-style-type: none"> <li>• When <b>Filtering Direction</b> is set to <b>LAN→WAN</b>, this parameter specifies the internet server's IP address to be affected.</li> <li>• When <b>Filtering Direction</b> is set to <b>WAN→LAN</b>, this parameter specifies the LAN server's IP address to be affected.</li> <li>• When this parameter is left blank, all IP addresses are covered.</li> </ul>
Subnet Mask	<p>It specifies the subnet mask of the destination IP address. The settings of <b>Destination IP Address</b> and <b>Subnet Mask</b> determine which servers are affected by this rule.</p>
Port	<p>It specifies the destination port of the packets. Its setting determines which services are affected by this rule.</p> <p>The destination port is only for TCP and UDP protocol.</p>

## 7.2.3 MAC filtering


### Overview

The MAC filtering function enables you to filter data packets from your local network to the internet to disallow clients with certain MAC addresses to access the internet and helps you to manage your network.

To access the configuration page, log in to the web UI of the ONT and choose **Services > Firewall > MAC Filtering**. The rule added are shown in **Current Filter Table**.

<b>MAC Filtering:</b>	<input type="radio"/> Disable <input checked="" type="radio"/> Enable	<button>Apply Changes</button>
<b>Mode:</b>	<input type="radio"/> Whitelist <input checked="" type="radio"/> BlackList	<button>Apply Changes</button>
Source MAC Address:	<input type="text"/>	Destination MAC Address: <input type="text"/> <button>Add</button>
<b>Current Filter Table</b>		
Select	Source MAC Address	Destination MAC Address

## Parameter description

Parameter	Description
MAC Filtering	It specifies whether to enable the MAC filtering function.
Mode	<p>It specifies the mode of the MAC filtering function.</p> <ul style="list-style-type: none"> <li>• <b>Whitelist:</b> Only data packets whose source or destination MAC addresses are added in the current filter table can access the internet.</li> <li>• <b>Blacklist:</b> Data packets from the LAN whose source or destination MAC addresses are added in the current filter table cannot pass through the ONT.</li> </ul>
Source MAC Address	<p>They specify the source and destination MAC addresses of data packets.</p> <p>You can only enter one source MAC address and destination MAC address in one MAC filtering rule.</p>
Destination MAC Address	<p> <b>TIP</b></p> <p>The MAC address cannot contain any special characters. An example in the correct format is cc3a61711b6e.</p>

## Allow only specified devices to access the internet

**Scenario:** The Wi-Fi network at your home is misused by unknown users sometimes.

**Goal:** Only allow certain devices of family members to access the internet.

**Solution:** You can configure the MAC address filter function to reach the goal.

Assume that:

Device	MAC address	Status
Your own phone	8C:EC:4B:B3:04:93	Connected
Family member's phone 1	94:C6:91:29:C2:12	Disconnected
Family member's phone 2	98:9C:57:19:D0:1B	Disconnected

### Configuring procedure:

**Step 1** Log in to the web UI of the ONT.

**Step 2** Choose **Services > Firewall > MAC Filtering**.

**Step 3** Set **MAC Filtering** to **Enable**, and click **Apply Changes**.

**Step 4** Set **Mode** to **Whitelist**, and click **Apply Changes**.

MAC Filtering:	<input type="radio"/> Disable <input checked="" type="radio"/> Enable	<input type="button" value="Apply Changes"/>
Mode:	<input checked="" type="radio"/> Whitelist <input type="radio"/> BlackList	<input type="button" value="Apply Changes"/>

**Step 5** Enter **8CEC4BB30493** in the **Source MAC Address** field, and click **Add**.

Source MAC Address:	<input type="text" value="8CEC4BB30493"/>	Destination MAC Address:	<input type="text"/>	<input type="button" value="Add"/>
---------------------	---	--------------------------	----------------------	------------------------------------

**Step 6** Repeat **Step 5** to add the other two MAC addresses.

After the MAC addresses are added, they are displayed in **Current Filter Table**.

Current Filter Table		
Select	Source MAC Address	Destination MAC Address
<input type="checkbox"/>	8c-ec-4b-b3-04-93	-----
<input type="checkbox"/>	94-c6-91-29-c2-12	-----
<input type="checkbox"/>	98-9c-57-19-d0-1b	-----

---End

In this example, after the configuration is completed, only the three devices added can access the internet through the ONT.

## 7.2.4 Port forwarding

### Overview

By default, internet users cannot access any service on any of their local hosts. The port forwarding function enables you to open certain ports of a local host to internet users and allow them to access the corresponding services. This function can allow access and prevent the local network from being attacked at the same time.

To access the configuration page, log in to the web UI of the ONT and choose **Services > Firewall > Port Forwarding**. The rules added are shown in **Current Port Forwarding Table**.

<b>Port Forwarding:</b>		<input type="radio"/> Disable <input checked="" type="radio"/> Enable		<button>Apply Changes</button>				
Enable <input checked="" type="checkbox"/>		Application: <span>Active Worlds</span> ▼						
Comment	Local IP	Local Port from	Local Port to	Protocol	Remote IP	Remote Port from	Remote Port to	Interface
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	Both ▼	<input type="text"/>	<input type="text"/>	<input type="text"/>	Any ▼

### Parameter description

Parameter	Description
Port Forwarding	It specifies whether to enable the port forwarding function.
Enable	It specifies whether the port forwarding rule takes effect after being added.
Application	It includes some common services. When you choose a service from the list, some parameters of the rule are filled automatically, including <b>Comment</b> , <b>Local Port from</b> , <b>Local Port to</b> , <b>Remote Port from</b> and <b>Remote Port to</b> .
Comment	You can specify a comment for the rule for easy retrieval.
Local IP	It specifies the IP address of the LAN host which runs the service to be accessed.

Parameter	Description
Local Port from Local Port to	They specify a port or a range of ports used for the LAN service.
Protocol	It specifies the service protocol. Select <b>Both</b> if you are uncertain about the service type.
Remote IP	It specifies the IP address of the host which needs to access the local service. When it is left blank, users with any IP address can access the local server.
Remote Port from Remote Port to	They specify a port or a range of ports that internet users use to access the local service.
interface	It specifies the WAN interface through which internet users access the local service.

## Enable internet users to access local services

**Scenario:** You have set up an FTP server within your LAN.

**Goal:** Open the FTP server to internet users and enable family members who are not at home to access the resources of the FTP server from the internet.

**Solution:** You can configure the port forwarding function to reach the goal.


Assume that the information of the FTP server includes:

- IP address: 192.168.1.136
- MAC address: D4:61:DA:1B:CD:89
- Service port: 21
- The WAN IP address of the router: 102.33.66.88.



- Please ensure that the router obtains an IP address from the public network. This function may not work on a host with an IP address of a private network or an intranet IP address assigned by ISPs that start with 100. Common IPv4 addresses are classified into class A, class B and class C. Private IP addresses of class A range from 10.0.0.0 to 10.255.255.255. Private IP addresses of class B range from 172.16.0.0 to 172.31.255.255. Private IP addresses of class C range from 192.168.0.0 to 192.168.255.255.
- ISPs may block unreported web services to be accessed with the default port number 80. Therefore, when the default LAN port number is 80, please manually change it to an uncommon port number (1024–65535), such as 9999.
- The LAN port number can be different from the WAN port number.





### Configuring procedure:

**Step 1** Log in to the web UI of the ONT.

**Step 2** Add a port forwarding rule.

1. Choose **Services > Firewall > Port Forwarding**.
2. Set **Port Forwarding** to **Enable**, and click **Apply Changes**.
3. Select **Enable** and select **FTP Server** from the **Application** drop-down list.
4. (Optional) Modify **Comment** for the rule, which is **FTP server** in this example.
5. Set **Local IP**, which is **192.168.1.136** in this example, and leave **Remote IP** blank.

<b>Port Forwarding:</b>		<input type="radio"/> Disable <input checked="" type="radio"/> Enable		<button>Apply Changes</button>				
Enable <input checked="" type="checkbox"/>		Application: FTP Server						
Comment	Local IP	Local Port from	Local Port to	Protocol	Remote IP	Remote Port from	Remote Port to	Interface
FTP Server	192.168.1.136	21	21	TCP		21	21	Any

**Step 3** Assign a fixed IP address to the host where the server locates.

6. Choose **Services > Service > DHCP**.
7. Click **MAC-Based Management**.
8. Set **MAC Address** of the host of the server, which is **D4-61-DA-1B-CD-89** in this example.
9. Set **Assigned IP Address** for the server host, which is **192.168.1.136** in this example.

<b>MAC Address</b> (xx-xx-xx-xx-xx-xx):	D4-61-DA-1B-CD-89
<b>Assigned IP Address</b> (xxx.xxx.xxx.xxx):	192.168.1.136


10. Click **Assign IP**.

---End


After the configuration, users from the internet can access the FTP server by visiting “*Intranet service application layer protocol name://WAN IP address of the ONT*”. If the remote port number is different from the default intranet service port number, the visiting address should be: “*Intranet service application layer protocol name://WAN IP address of the ONT:Remote port number*”. In this example, the address is “**ftp://102.33.66.88**”. You can find the WAN IP address of the ONT in [Device status](#).

### To access the FTP server from the internet:

Open the file explorer on a computer that can access the internet, and visit **ftp://102.33.66.88**.



Enter the user name and password to access the resources on the FTP server.



If you want to access the server within a LAN using a domain name, refer to the solution [Dynamic DNS + Port Forwarding](#).



After the configuration, if internet users cannot access the FTP server, try the following methods:

- Ensure that the LAN port number configured in the port forwarding function is the same as the service port number set on the server.
- Close the firewall, antivirus software and security guards on the host of the FTP server and try again.

## 7.2.5 URL Blocking

### Overview

The URL blocking function enables you to block LAN clients from accessing certain websites by specifying a Fully Qualified Domain Name (FQDN) or keyword.

To access the configuration page, log in to the web UI of the ONT and choose **Services > Firewall > URL Blocking**. The rule added are shown in the **URL Blocking Table**.

The screenshot shows the URL Blocking configuration interface. At the top, there's a 'URL Blocking:' label followed by two radio buttons: 'Disable' (which is selected) and 'Enable'. To the right of these is an 'Apply Changes' button. Below this, there's an 'FQDN:' label followed by a text input field and an 'Add' button. At the bottom, there's a table titled 'URL Blocking Table' with two columns: 'Select' and 'FQDN'.

### Parameter description

Parameter	Description
URL Blocking	It specifies whether to enable the URL blocking function.
FQDN	It specifies the domain name that you want to block LAN clients from accessing. An FQDN, sometimes also referred to as an absolute domain name, is a domain name that specifies its exact location in the tree hierarchy of the Domain Name System (DNS). It specifies all domain levels, including the top-level domain and the root zone.

### Block clients from accessing certain websites

Assume that you use the ONT to provide internet access at your home. You want your children to focus on study rather than social media, such as Facebook, Twitter, or Instagram. You can use URL blocking to reach the goal.

#### Configuring procedure:

- Step 1** Log in to the web UI of the ONT.
- Step 2** Choose **Service > Firewall > URL Blocking**.
- Step 3** Select **Enable** for **URL Blocking**, and click **Apply Changes**.

**Step 4** Enter **facebook** in **FQDN** and click **Add**. Repeat this step for blocking twitter and instagram.

---End

After the configuration, Facebook, Twitter, and Instagram are not accessible through the ONT.

## 7.2.6 DMZ

### Overview

A DMZ host on a LAN is free from restrictions in communicating with the internet. It is useful for getting better and smoother experiences in video conferences and online games. You can also set the host of a server within the LAN as a DMZ host when in need of accessing the server from the internet.



NOTE

- A DMZ host is not protected by the firewall of the router. Hackers may leverage the DMZ host to attack your LAN. Therefore, enable the DMZ function only when necessary.
- Hackers may leverage the DMZ host to attack the local network. Do not use the DMZ host function randomly.
- Security software, antivirus software, and the built-in OS firewall of the computer may cause DMZ function failures. Disable them when using the DMZ function. If the DMZ function is not required, you are recommended to disable it and enable your firewall, security, and antivirus software.

To access the configuration page, log in to the web UI of the ONT and choose **Services > Firewall > DMZ**.

### Parameter description

Parameter	Description
DMZ Host	It specifies whether to enable the DMZ host function.
DMZ Host IP Address	It specifies the IP address of the LAN host to be set as the DMZ host.

## Enable internet users to access LAN resources

**Scenario:** You have set up an FTP server within your LAN.

**Goal:** Open the FTP server to internet users and enable family members who are not at home to access the resources of the FTP server from the internet.

**Solution:** You can configure the DMZ host function to reach the goal.


Assume that the information of the FTP server includes:

- IP address: 192.168.1.136
- MAC address: D4:61:DA:1B:CD:89
- Service port: 21
- WAN IP address of the router: 102.33.66.88



TIP

Please ensure that the router obtains a public IP address public. This function may not work on a host with an IP address of a private network or an intranet IP address assigned by ISPs that start with 100. Common IPv4 addresses are classified into class A, class B and class C. Private IP addresses of class A range from 10.0.0.0 to 10.255.255.255. Private IP addresses of class B range from 172.16.0.0 to 172.31.255.255. Private IP addresses of class C range from 192.168.0.0 to 192.168.255.255.



### Configuring procedure:

**Step 1** Log in to the web UI of the ONT.

**Step 2** Set the server host as the DMZ host.

1. Choose **Services > Firewall > DMZ**.
2. Select **Enable** for **DMZ Host**.
3. Enter the IP address of the server host, which is **192.168.1.136** in this example.
4. Click **Apply Changes**.

<b>DMZ Host:</b>	<input type="radio"/> Disable <input checked="" type="radio"/> Enable
<b>DMZ Host IP Address:</b>	<input type="text" value="192.168.1.136"/>

**Step 3** Assign a fixed IP address to the host where the server locates.

1. Choose **Services > Service > DHCP**.

2. Click **MAC-Based Management**.
3. Enter the MAC Address of the host of the server, which is **D4-61-DA-1B-CD-89** in this example.
4. Enter the assigned IP Address for the server host, which is **192.168.1.136** in this example.

<b>MAC Address</b> (xx-xx-xx-xx-xx-xx):	D4-61-DA-1B-CD-89
<b>Assigned IP Address</b> (xxx.xxx.xxx.xxx):	192.168.1.136

5. Click **Assign IP**.

---End

After the configuration, users from the internet can access the FTP server by visiting “*Intranet service application layer protocol name://WAN IP address of the ONT*”. If the intranet service port number is not the default number, the accessing address should be: “*Intranet service application layer protocol name://WAN IP address of the ONT:Intranet service port number*”.




If the default intranet service port number is 80, please change the service port number to an uncommon one (1024–65535), such as 9999.


In this example, the address is “**ftp://102.33.66.88**”. You can find the WAN IP address of the ONT in [Device status](#).

**To access the FTP server from the internet:**

Open the file explorer on a computer that can access the internet, and visit **ftp://102.33.66.88**.



Enter the user name and password to access the resources on the FTP server.



If you want to access the server within a LAN using a domain name, refer to the solution [DMZ + Dynamic DNS](#).



After the configuration, if internet users still cannot access the FTP server, close the firewall, antivirus software and security guards on the host of the FTP server and try again.

# 8 VoIP

The VoIP function enables telephone calls to be made and received over an IP network.

To access the configuration page, log in to the web UI of the ONT and choose **VoIP > Port1**.

## 8.1 Set VoIP proxy

Before you can make phone calls on the phone connected to the ONT, you need to complete registration with the SIP server.

Navigate to the **Main Proxy** and **Backup Proxy** part, which can be both used to complete the registration. After the parameters are properly configured, click **Apply** on the bottom of the page to enable the settings to take effect.

Main Proxy	
Display Name	<input type="text"/>
Number	<input type="text"/>
Login ID	<input type="text"/>
Password	<input type="password"/>
Proxy	<input type="checkbox"/> Enable
Proxy Addr	<input type="text"/>
Proxy Port	<input type="text" value="5060"/>
SIP Subscribe	<input type="checkbox"/> Enable
SIP Domain	<input type="text"/>
Reg Expire (sec)	<input type="text" value="3600"/>
Outbound Proxy	<input type="checkbox"/> Enable
Outbound Proxy Addr	<input type="text"/>
Outbound Proxy Port	<input type="text" value="5060"/>
Enable Session timer	<input checked="" type="checkbox"/> Enable
Session Expire (sec)	<input type="text" value="1800"/>
Register Status	Disabled



## Parameter description

Parameter	Description
Display Name	It specifies the caller name that will be displayed on the peer side.
Number	It specifies the phone number of your telephone.
Login ID	They specify the login ID and password to register with the SIP server.
Password	
Proxy	You can choose to enable the SIP proxy server function as required. When enabled, you need to enter the IP address and port of the SIP proxy server.
Proxy Addr	
Proxy Port	
SIP Subscribe	It is used to create a subscription between the client application that wishes to obtain service information and the information provider.
SIP Domain	It specifies the domain name for SIP service registration.
Reg Expire (sec)	It specifies the period after which the SIP registration expires.
Outbound Proxy	When it is enabled, all outgoing requests will be sent to this outbound proxy server.
Outbound Proxy Addr	They specify the IP address and port number of the SIP Outbound Proxy server.
Outbound Proxy Port	
Enable Session timer	When it is enabled, the ONT periodically checks the status of a SIP session.
Session Expire (sec)	It specifies the interval at which the ONT checks the status of a SIP session.
Register Status	It specifies the SIP registration status.

## 8.2 Change advanced SIP settings

To change advanced SIP settings, navigate to the **SIP Advanced** part.

Change the parameters as required by your ISP, or keep the default value if you are not sure. After the parameters are properly configured, click **Apply** on the bottom of the page to enable the settings to take effect.

SIP Advanced	
SIP Port	<input type="text" value="5060"/>
Media Port	<input type="text" value="9000"/>
DTMF Relay	<input type="text" value="DTMF_delete"/>
DTMF RFC2833 Payload Type	<input type="text" value="96"/>
DTMF RFC2833 Packet Interval	<input type="text" value="10"/> (msec) (Must be multiple of 10msec)
Use DTMF RFC2833 PT as Fax/Modem RFC2833 PT	<input type="checkbox"/> Enable
Fax/Modem RFC2833 Payload Type	<input type="text" value="101"/>
Fax/Modem RFC2833 Packet Interval	<input type="text" value="10"/> (msec) (Must be multiple of 10msec)
SIP INFO Duration (ms)	<input type="text" value="250"/>
Call Waiting	<input type="checkbox"/> Enable
Call Waiting Caller ID	<input type="checkbox"/> Enable
Reject Direct IP Call	<input type="checkbox"/> Enable
Send Caller ID hidden	<input type="checkbox"/> Enable
call transfer	<input checked="" type="checkbox"/> Enable
3 way conference	<input checked="" type="checkbox"/> Enable
conference on server/CPE	<input type="radio"/> server <input checked="" type="radio"/> CPE
conference-uri	<input type="text"/>

### Parameter description

Parameter	Description
SIP Port	It specifies the port used for SIP calls.
Media Port	It specifies the port for voice streams using the Real-time Transport Protocol (RTP).
DTMF Relay	Dual-tone Multi-frequency (DTMF) Relay enables the ONT to send DTMF digits over IP. You can choose the DTMF relay type here, which includes <b>RFC2833</b> , <b>SIP INFO</b> , <b>Inband</b> and <b>DTMF_delete</b> .

Parameter	Description
DTMF RFC2833 Payload Type	When <b>DTMF Relay</b> is set to <b>RFC2833</b> , you need to specify these five parameters. If you are not sure, keep the default values.
DTMF RFC2833 Packet Interval	
Use DTMF RFC2833 PT as Fax/Modem RFC2833 PT	
Fax/Modem RFC2833 Payload Type	
Fax/Modem RFC2833 Packet Interval	
SIP INFO Duration (ms)	When <b>DTMF Relay</b> is set to <b>SIP INFO</b> , you need to specify the SIP INFO duration.
Call Waiting	It specifies whether to enable the call waiting function, which allows you to suspend a telephone call already in progress to accept a second call, or switch between calls.
Call Waiting Caller ID	It specifies whether to display the caller ID of the waiting call.
Reject Direct IP Call	It specifies whether to reject or accept direct IP calls.
Send Caller ID hidden	It specifies whether to hide your caller ID when making phone calls.
call transfer	It specifies whether to enable the call transfer function, which allows you to relocate an existing telephone call to another phone.
3 way conference	It specifies whether to enable the 3-way conference function, which allows you to talk with 2 people at the same time using your telephone.
conference on server/CPE	It specifies the location of conferences.
conference-uri	It specifies the URI where the conference is made.

## 8.3 Set the forward mode

By setting the forward mode, incoming phone calls can be forwarded to another phone number under different circumstances.

To configure the forward mode, navigate to the **Forward Mode** part. After the parameters are properly configured, click **Apply** on the bottom of the page to enable the settings to take effect.

Forward Mode	
Immediate Forward to	<input type="radio"/> off <input checked="" type="radio"/> VoIP
Immediate Number	<input type="text"/>
Busy Forward to	<input type="radio"/> off <input checked="" type="radio"/> VoIP
Busy Number	<input type="text"/>
No Answer Forward to	<input type="radio"/> off <input checked="" type="radio"/> VoIP
No Answer Number	<input type="text"/>
No Answer Time (sec)	<input type="text" value="0"/>

### Parameter description

Parameter	Description
Immediate Forward to	You can enable or disable Immediate Forward. Immediate Forward prevails Busy Forward and No Answer Forward.
Immediate Number	<ul style="list-style-type: none"> <li>• <b>off</b>: Immediate Forward is disabled.</li> <li>• <b>VoIP</b>: Immediate Forward is enabled, and phone calls will be forwarded immediately to the phone number you specified in <b>Immediate Number</b>.</li> </ul>
Busy Forward to	You can enable or disable Immediate forward. To enable Busy Forward, disable Immediate Forward first.
Busy Number	<ul style="list-style-type: none"> <li>• <b>off</b>: Busy Forward is disabled.</li> <li>• <b>VoIP</b>: Busy Forward is enabled, and phone calls will be forwarded to the phone number you specified in <b>Busy Number</b> when the line is busy.</li> </ul>
No Answer Forward to	You can enable or disable No Answer Forward. To enable No Answer Forward, disable Immediate Forward and Busy Forward first.
No Answer Number	<ul style="list-style-type: none"> <li>• <b>off</b>: No Answer Forward is disabled.</li> <li>• <b>VoIP</b>: No Answer Forward is enabled, and phone calls will be forwarded to the phone number you specified in <b>No Answer Number</b> when the calls are not answered after the time set in <b>No Answer Time (sec)</b> is reached.</li> </ul>
No Answer Time (sec)	

## 8.4 Set speed dial rules

By adding speed dial rules, you can make phone calls quickly by pressing the speed name plus # instead of the original numbers on the keypad of the telephone.

To set speed dial rules, navigate to the **Speed Dial** part. After the parameters are properly configured, click **Apply** on the bottom of the page to enable the settings to take effect.

Speed Dial			
Position	Speed Name	Phone Number	Select
0	<input type="text"/>	<input type="text"/>	<input type="checkbox"/>
1	<input type="text"/>	<input type="text"/>	<input type="checkbox"/>
2	<input type="text"/>	<input type="text"/>	<input type="checkbox"/>
3	<input type="text"/>	<input type="text"/>	<input type="checkbox"/>
4	<input type="text"/>	<input type="text"/>	<input type="checkbox"/>
5	<input type="text"/>	<input type="text"/>	<input type="checkbox"/>
6	<input type="text"/>	<input type="text"/>	<input type="checkbox"/>
7	<input type="text"/>	<input type="text"/>	<input type="checkbox"/>
8	<input type="text"/>	<input type="text"/>	<input type="checkbox"/>
9	<input type="text"/>	<input type="text"/>	<input type="checkbox"/>

### Parameter description

Parameter	Description
Speed Name	You can set <b>Speed Name</b> for each commonly used number to facilitate making phone calls. You only need to press the speed name plus # on the telephone to dial a certain phone number that you specify in <b>Phone Number</b> .
Phone Number	

# 8.5 Abbreviated dial

By adding abbreviated dial rules, you can make phone calls by dialing the abbreviated number rather than the full number.

To set abbreviated dial rules, navigate to the **Abbreviated Dial** part. After the parameters are properly configured, click **Apply** on the bottom of the page to enable the settings to take effect.

Abbreviated Dial	
Abbreviated Name	Phone Number
<input type="text"/>	<input type="text"/>
<input type="text"/>	<input type="text"/>
<input type="text"/>	<input type="text"/>
<input type="text"/>	<input type="text"/>
<input type="text"/>	<input type="text"/>

## 8.6 Set a dial plan

The dial plan function is used to analyze the number dialed by the call participant and decides which number should be dialed or which function should be selected. With the help of the dial plan, the telephone network, or the telephone system itself analyses and recognizes the dialed number and generates the proper connection request.

To set a dial plan, navigate to the **Dial plan** part. After the parameters are properly configured, click **Apply** on the bottom of the page to enable the settings to take effect.

Dial plan	
Enable Dialplan	<input type="radio"/> on <input checked="" type="radio"/> off
Dial plan	<input type="text"/>

### Parameter description

Parameter	Description
Enable Dialplan	It specifies whether to enable a dial plan.
Dial plan	It specifies the name of dial plan.

## 8.7 Set coding type

Codecs enable the ONT to compress digital voice data to reduce bandwidth usage per call. Change the settings only when necessary.

To set the codec type, navigate to the **Codec** part. After the parameters are properly configured, click **Apply** on the bottom of the page to enable the settings to take effect.

Codec											
RTP Redundant (First precedence)		Codec		Disabled ▾							
		Payload Type		121							
Type	Packetization	Precedence									Disable
		1	2	3	4	5	6	7	8	9	
G711-ulaw	20 ms ▾	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
G711-alaw	20 ms ▾	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
G729	20 ms ▾	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
G723	30 ms ▾	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
G726-16k	20 ms ▾	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
G726-24k	20 ms ▾	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
G726-32k	20 ms ▾	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
G726-40k	20 ms ▾	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
G722	10 ms ▾	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Option		G726 Packing Order		Right ▾							
		G723 Bit Rate		6.3k ▾							

### Parameter description

Parameter	Description
Codec	It specifies the coding type used to compress digital voice data, which has higher priority over other coding types.
Payload Type	It specifies the payload type value for digital voice data coding.
Type	It specifies the coding type used to compress digital voice data.
Packetization	It specifies the packetization rate of digital voice data.
Disable	It is used to disable the selected codec type.
G726 Packing Order	It specifies the packing order when the G726 codec type is used.
G723 Bit Rate	It specifies the bit rate when G723 codec type is used.



## 8.8 Set a hotline

By setting a hotline for the telephone, the telephone dials the phone number you set if there is no dialing action within a period after you pick up the phone set.

To set a hotline, navigate to the **Hot Line** part. After the parameters are properly configured, click **Apply** on the bottom of the page to enable the settings to take effect.

Hot Line	
Use Hot Line	<input type="checkbox"/> Enable
Hot Line Number	<input type="text"/>

### Parameter description

Parameter	Description
Use Hot Line	It specifies whether the hotline is enabled.
Hot Line Number	It specifies the hotline number to be dialed when no dialing action is performed within a specific period after you pick up the phone set.

## 8.9 Set the Don't Disturb mode

If you enable the Don't Disturb (DND) mode, incoming calls will be denied during the specified period.

To set the Don't Disturb mode, navigate to the **DND (Don't Disturb)** part. After the parameters are properly configured, click **Apply** on the bottom of the page to enable the settings to take effect.

Choose a desired mode for your phone:

- **Always:** All phone calls are denied all the time.
- **Enable:** Phone calls are denied during the specified period.
- **Disable:** The DND mode is disabled, and all phone calls are accepted.

DND (Don't Disturb)	
DND Mode	<input checked="" type="radio"/> Always <input type="radio"/> Enable <input type="radio"/> Disable
From	<input type="text" value="00"/> : <input type="text" value="00"/> (hh:mm)
To	<input type="text" value="00"/> : <input type="text" value="00"/> (hh:mm)

### Parameter description

Parameter	Description
DND Mode	It specifies whether the DND mode is enabled.
From	They specify the period during which the DND mode is enabled when <b>Enable</b> is selected for <b>DND Mode</b> .
To	

## 8.10 Set an alarm

You can set an alarm on and the telephone will ring at the specified time.

Navigate to the **Alarm** part. After the parameters are properly configured, click **Apply** on the bottom of the page to enable the settings to take effect.

Alarm	
Enable	<input type="checkbox"/>
Time	<input type="text" value="0"/> : <input type="text" value="0"/> (hh:mm)

### Parameter description

Parameter	Description
Enable	It specifies whether the alarm is enabled.
Time	It specifies the time at which the telephone rings.

# 9 Advance

## 9.1 Advanced settings

### 9.1.1 ARP table

On this page, you can view the IP address and MAC address of devices connected to the ONT in a wireless and wired manner.

To access the page, log in to the web UI of the ONT and choose **Advance > Advance > ARP Table**.

IP Address	MAC Address
192.168.1.2	8c-ec-4b-b3-04-92

### 9.1.2 Routing

#### Overview

On this page, you can add, modify, and delete static route rules. In addition, you can view the route table of the ONT.

Routing is the act of choosing an optimal path to transfer data from a source address to a destination address. A static route is a special route that is manually configured and has the advantages of simplicity, efficiency, and reliability. Proper static routing can reduce routing problems and overload of routing data flow, and improve the forwarding speed of data packets.

After the static route is established, all data whose destination address is the destination network of the static route are directly forwarded to the next hop through the static route interface.

To access the page, log in to the web UI of the ONT and choose **Advance > Advance > Routing**.

<b>Enable:</b>	<input checked="" type="checkbox"/>
<b>Destination:</b>	<input type="text"/>
<b>Subnet Mask:</b>	<input type="text"/>
<b>Next Hop:</b>	<input type="text"/>
<b>Metric:</b>	<input type="text"/>

Static Route Table						
Select	State	Destination	Subnet Mask	Next Hop	Metric	Interface

### Parameter description

Parameter	Description
Add Route	It is used to add a new static route rule.
Update	It is used to update your modification to an existing rule.
Delete Selected	It is used to delete the selected rule.
Show Routes	It is used to display the commonly used routes of the ONT.
Select	Select existing rules to update or delete them.
State	It specifies the status of a rule, including <b>Enable</b> and <b>Disable</b> .
Destination	It specifies the IP address of the destination network.
Subnet Mask	It specifies the subnet mask of the destination network.
Next Hop	It specifies the ingress IP address of the next hop route after the data packet exits from the WAN interface of the ONT.
Metric	It specifies the priority of the routing rule. The smaller the number, the higher the priority. When the destination networks of two rules are the same, packets will be forwarded according to the rule with smaller metric.
Interface	It specifies the interface of the ONT that the packet exits from.

### Add a new static route rule

- Step 1** Log in to the web UI of the ONT.
- Step 2** Choose **Advance > Advance > Routing**.
- Step 3** Select **Enable** as required.
- Step 4** Set **Destination**, **Subnet Mask**, **Next Hop**, **Metric**, and **Interface**.
- Step 5** Click **Add Route**.

Enable:	<input checked="" type="checkbox"/>
Destination:	<input type="text"/>
Subnet Mask:	<input type="text"/>
Next Hop:	<input type="text"/>
Metric:	<input type="text"/>
Interface:	Any ▼

---End

After the configuration succeeds, the static rule will be displayed in **Static Route Table**.

## Modify a static rule

**Step 1** Log in to the web UI of the ONT.

**Step 2** Choose **Advance > Advance > Routing**.

**Step 3** Select a static route rule, and it will appear in the configuring part.

Enable:	<input checked="" type="checkbox"/>
Destination:	<input type="text" value="192.168.1.2"/>
Subnet Mask:	<input type="text" value="255.255.255.255"/>
Next Hop:	<input type="text" value="192.168.10.1"/>
Metric:	<input type="text" value="12"/>

Add Route
Update
Delete Selected
Show Routes

Static Route Table					
Select	State	Destination	Subnet Mask	Next Hop	Metric
<input checked="" type="radio"/>	Enable	192.168.1.2	255.255.255.255	192.168.10.1	12

**Step 4** Modify the parameters of the rule as required.

Enable:	<input checked="" type="checkbox"/>
Destination:	<input type="text" value="192.168.1.2"/>
Subnet Mask:	<input type="text" value="255.255.255.255"/>
Next Hop:	<input type="text" value="192.168.10.10"/>
Metric:	<input type="text" value="12"/>

**Step 5** Click **Update**.

---End

After the configuration succeeds, the updated parameters of the static rule will be displayed in **Static Route Table**.

Static Route Table					
Select	State	Destination	Subnet Mask	Next Hop	Metric
<input type="radio"/>	Enable	192.168.1.2	255.255.255.255	192.168.10.10	12

## Delete an existing rule

To delete an existing rule, select the rule in **Static Route Table** and click **Delete Selected**.

Enable:	<input checked="" type="checkbox"/>
Destination:	<input type="text" value="192.168.0.10"/>
Subnet Mask:	<input type="text" value="255.255.255.255"/>
Next Hop:	<input type="text" value="192.168.10.10"/>
Metric:	<input type="text" value="12"/>

Add Route
Update
Delete Selected
Show Routes

Static Route Table						
Select	State	Destination	Subnet Mask	Next Hop	Metric	Interface
<input checked="" type="radio"/>	Enable	192.168.0.10	255.255.255.255	192.168.10.10	12	---
<input type="radio"/>	Disable	192.168.1.1	255.255.255.255	192.168.10.1	12	---

## Show commonly used routes

Click **Show Routes**, and you will find the commonly used routes in the prompt window.

Destination	Subnet Mask	Next Hop	Metric	Interface
0.0.0.0	0.0.0.0	*	0	ppp0
10.11.122.1	255.255.255.255	*	0	ppp0



- The route with 0.0.0.0 as both destination and subnet mask is the default route. When no perfectly matched route is found for a packet, the packet will be forwarded through the default route.
- 0.0.0.0 as the next hop indicates that the ONT is directly connected to the destination network.

### 9.1.3 SNMP

The Simple Network Management Protocol (SNMP) is the most widely used network management protocol in TCP/IP networks. SNMP enables you to remotely manage all your network devices compliant with this protocol, such as monitoring the network status, changing network device settings, and receiving network event alarms.

SNMP allows automatic management of devices from various vendors regardless of physical differences among the devices.

#### SNMP management framework

The SNMP management framework consists of the SNMP manager, SNMP agent, and Management Information Base (MIB).

- **SNMP manager:** It is a system that controls and monitors network nodes using the SNMP protocol. The SNMP manager most widely used in network environments is Network Management System (NMS). An NMS can be a dedicated network management server, or an application that implements management functions in a network device.
- **SNMP agent:** It is a software module in a managed device. The module is used to manage data about the device and report the management data to an SNMP manager.
- **MIB:** It is a collection of managed objects. It defines a series of attributes of managed objects, including names, access permissions, and data types of objects. Each SNMP agent has its MIB. An SNMP manager can read and/or write objects in the MIB based on the permissions assigned to the SNMP manager.

#### SNMP operations

There are mainly three operations based on SNMP:

- **Get:** The SNMP manager sends a request to retrieve the value of a variable or list of variables.
- **Set:** The SNMP manager sends a request to change the value of a variable or list of variables.
- **Trap:** The SNMP agent notifies the SNMP manager of significant events by an unsolicited SNMP message.

An SNMP manager manages SNMP agents in an SNMP network. The SNMP manager exchanges management information with the SNMP agents using the SNMP protocol. The ONT functions as an SNMP agent.

The ONT is compatible with SNMP V1 and SNMP V2C and adopts the community authentication mechanism.

To access the page, log in to the web UI of the ONT and choose **Advance > Advance > SNMP**.



<b>SNMP:</b>	<input type="radio"/> Disable <input checked="" type="radio"/> Enable
<b>System Description:</b>	<input type="text" value="System Description"/>
<b>System Contact:</b>	<input type="text" value="System Contact"/>
<b>SystemName:</b>	<input type="text" value="HG9"/>
<b>System Location:</b>	<input type="text" value="System Location"/>
<b>System Object ID:</b>	<input type="text" value="1.3.6.1.4.1.16972"/>
<b>Trap IP Address:</b>	<input type="text" value="192.168.1.254"/>
<b>Community name (read-only):</b>	<input type="text" value="public"/>
<b>Community name (write-only):</b>	<input type="text" value="public"/>

### Parameter description

Parameter	Description
SNMP	It specifies whether to enable the SNMP agent function.
System Description	It specifies a description of the ONT, which can be anything you like and is used for identification.
System Contact	It specifies the contact information of the ONT.
SystemName	It specifies the name of ONT.
System Location	It specifies the place where the ONT is located.
System Object ID	It specifies the object ID of the ONT in the MIB, which can be used by the SNMP manager to identify and manage the ONT.
Trap IP Address	It specifies the destination IP address of the SNMP trap. Make sure that the ONT and the SNMP manager are reachable to each other.
Community name (read-only)	They specify the community names which act as passwords for the interaction between the SMNP manager and SNMP agent.
Community name (write-only)	<ul style="list-style-type: none"> <li>• <b>Community name (read-only):</b> It is used to authenticate the Get request.</li> <li>• <b>Community name (write-only):</b> It is used to authenticate the Set request.</li> </ul>

## 9.2 IPv6 settings

The ONT supports both IPv4 and IPv6 for internet access. In this module, you can enable and disable IPv6 of the ONT, and perform other IPv6-related configurations on the ONT.

### 9.2.1 IPv6 status

On this page, you can enable or disable the IPv6 function of the ONT.

To access the page, log in to the web UI of the ONT and choose **Advance > IPv6 > IPv6 Enable/Disable**. Select **Enable** or **Disable** and click **Apply Changes**.

IPv6: ☐ Disable ☒ Enable

### 9.2.2 RADVD

The Router Advertisement Daemon (RADVD) is used by system administrators in stateless auto-configuration methods of network hosts on IPV6 networks.



When IPv6 hosts configure their network interfaces, they broadcast Router Solicitation (RS) requests onto the network to discover available devices. The RADVD software answers requests with Router Advertisement (RA) messages. In addition, RADVD periodically broadcasts RA packets to the attached link to update network hosts.

To access the page, log in to the web UI of the ONT and choose **Advance > IPv6 > RADVD**.

MaxRtrAdvInterval:	<input type="text" value="600"/>
MinRtrAdvInterval:	<input type="text" value="198"/>
AdvManagedFlag:	<input type="radio"/> off <input checked="" type="radio"/> on
AdvOtherConfigFlag:	<input type="radio"/> off <input checked="" type="radio"/> on
Prefix Mode:	<input type="text" value="Manual"/>
Prefix:	<input type="text" value="3ffe:501:ffff:100::"/>
Prefix Length:	<input type="text" value="64"/>
AdvValidLifetime:	<input type="text" value="2592000"/>
AdvPreferredLifetime:	<input type="text" value="604800"/>
AdvOnLink:	<input type="radio"/> off <input checked="" type="radio"/> on
AdvAutonomous:	<input type="radio"/> off <input checked="" type="radio"/> on
RDNSS 1:	<input type="text"/>
RDNSS 2:	<input type="text"/>
Enable ULA:	<input type="radio"/> off <input checked="" type="radio"/> on
ULA Prefix:	<input type="text" value="fc01::"/>
ULA Prefix Length:	<input type="text" value="64"/>
ULA Prefix Valid Lifetime:	<input type="text" value="2592000"/>
ULA Prefix Preferred Lifetime:	<input type="text" value="604800"/>

### Parameter description

Parameter	Description
MaxRtrAdvInterval	They specify the Maximum and Minimum Router Advertisement Intervals. They are the intervals between each router advertisement message. The router sends these messages periodically. The actual interval used is randomly selected from a value between the minimum and maximum values.
MinRtrAdvInterval	
AdvManagedFlag	They specify the Advertisement Managed Flag and Advertisement Other Configuration Flag. <ul style="list-style-type: none"> <li>• <b>Advertisement Managed Flag:</b> This flag indicates that hosts retrieve managed IPv6 addresses from a DHCPv6 server for their interfaces.</li> <li>• <b>Advertisement Other Configuration Flag:</b> This flag indicates that hosts use SLAAC to generate their IPv6 address and obtain other configuration information using DHCPv6, such as DNS information.</li> </ul>
AdvOtherConfigFlag	
Prefix Mode	It specifies the configuring mode of the prefix which is assigned to the IPv6 host, including <b>Auto</b> and <b>Manual</b> . <ul style="list-style-type: none"> <li>• <b>Auto:</b> The ONT automatically assigns a prefix to the IPv6 host.</li> <li>• <b>Manual:</b> You need to set the prefix manually.</li> </ul>

Parameter	Description
Prefix	They specify the prefix information included in the RA message to hosts for generating their IPv6 address.
Prefix Length	
AdvValidLifetime	They specify the Advertisement Valid Lifetime and Advertisement Preferred Lifetime. When the preferred lifetime expires, the use of the prefix is not encouraged, but not prohibited. When the valid lifetime expires, the prefix becomes invalid.
AdvPreferredLifetime	
	 <b>TIP</b> The valid lifetime must be greater than or equal to the preferred lifetime.
AdvOnLink	It specifies whether the router advertisement is on the link.
AdvAutonomous	It specifies whether the prefix in the router advertisement can be used to generate IPv6 address.
RDNSS 1/2	They specify the Recursive DNS Server (RDNSS) addresses assigned to IPv6 hosts for DNS information configuration.
Enable ULA	It specifies whether to enable the Unique Local Address (ULA). The purpose of ULA resembles that of the private network address in IPv4. It is only used within the private network and increases stability for the IPv6 host and its use of services.
ULA Prefix	They specify the ULA prefix information advertised by the ONT to hosts for generating unique local addresses.
ULA Prefix Length	
ULA Prefix Valid Lifetime	They specify the valid lifetime and preferred lifetime of ULA prefix. When the preferred lifetime expires, the use of the ULA prefix is not encouraged, but not prohibited. When the valid lifetime expires, the ULA prefix becomes invalid.
ULA Prefix Preferred Lifetime	
	 <b>TIP</b> The valid lifetime must be greater than or equal to the preferred lifetime.

### 9.2.3 DHCPv6

IPv6 hosts may automatically generate IP addresses internally using Stateless Address Autoconfiguration (SLAAC), or they may be assigned configuration with Dynamic Host Configuration Protocol version 6 (DHCPv6). When the DHCPv6 server is enabled, the ONT can assign IPv6 hosts with IP addresses, IP prefixes and other configurations required for IPv6 internet access.

To access the page, log in to the web UI of the ONT and choose **Advance > IPv6 > DHCPv6**.

**DHCPv6 Mode:** ☐ NONE ☒ DHCPv6Server(Manual) ☐ DHCPv6Server(Auto)

Enable the DHCPv6 Server if you are using this device as a DHCPv6 server. This page lists the IP address pools available to hosts on your LAN. The device distributes numbers in the pool to hosts on your network as they request Internet access.

<b>IP Pool Range:</b>	<input type="text" value="3ffe:501:ffff:100::10"/> - <input type="text" value="3ffe:501:ffff:100::11"/>	<input type="button" value="Show Client"/>
<b>Prefix Length:</b>	<input type="text" value="64"/>	
<b>Valid Lifetime:</b>	<input type="text" value="20000"/> seconds	
<b>Preferred Lifetime:</b>	<input type="text" value="10000"/> seconds	
<b>Renew Time:</b>	<input type="text" value="5000"/> seconds	
<b>Rebind Time:</b>	<input type="text" value="16000"/> seconds	
<b>Client DUID:</b>	<input type="text" value="00:01:00:01:00:04:93:e0:00:00:00:00:a2:a2"/>	

**Domain:**

Domain Search Table	
Select	Domain
<input type="button" value="Delete Selected"/> <input type="button" value="Delete All"/>	

**Name Server IP:**

Name Server Table	
Select	Name Server

### Parameter description

Parameter	Description
DHCPv6 Mode	<p>You can select a DHCPv6 server mode or disable it.</p> <ul style="list-style-type: none"> <li>• <b>NONE:</b> The DHCPv6 server of the ONT is disabled.</li> <li>• <b>DHCPv6Server(Manual):</b> You need to define the IP address pool, prefix length and other required parameters for IPv6 addresses to be assigned to IPv6 hosts.</li> <li>• <b>DHCPv6Server(Auto):</b> The ONT defines the IPv6 addresses to be assigned to the IPv6 host automatically.</li> </ul>
IP Pool Range	It specifies the IP address range within which the ONT can assign IPv6 addresses to the IPv6 host.
Show Client	<p>It shows information of the active DHCPv6 clients, including:</p> <ul style="list-style-type: none"> <li>• <b>IP Address:</b> It specifies the IP address assigned to the DHCP leased client.</li> <li>• <b>MAC Address:</b> It specifies the MAC address of the DHCP leased client.</li> <li>• <b>Expired Time (sec):</b> It specifies the time expired for the DHCP leased client.</li> </ul>
Prefix Length	It specifies the length of IPv6 prefix.

Parameter	Description
Valid Lifetime	They specify the valid lifetime and preferred lifetime of the IPv6 address assigned to IPv6 hosts.
Preferred Lifetime	When the preferred lifetime expires, communication using the IPv6 address is not encouraged, but allowed. When the valid lifetime expires, the IPv6 address becomes invalid.
Renew Time	It specifies the time before expiration when the host is expected to contact the DHCPv6 server that did the assignment to renew the lifetimes of the addresses assigned to the client.
Rebind Time	It specifies the new valid time after the IPv6 address is renewed.
Client DUID	It specifies the DHCP Unique Identifier (DUID) assigned to clients. The DUID is used by a client to get an IP address from a DHCPv6 server, and the server compares the DUID with its database and delivers configuration data (such as the address and DNS servers) to the client.
Domain	It is used to configure the domain.
Domain Search Table	It displays all domain settings.
Name Server IP	You can add a DNS server address to obtain DNS information for address resolution.
Name Server Table	

## 9.2.4 MLD proxy

MLD (Multicast Listener Discovery) is a Layer 2 multicast protocol running on IPv6 networks. The MLD proxy enables a device to issue MLD host messages on behalf of its users, reduces MLD messages and the load for uplink device. The device with MLD proxy enabled intercepts and processes the MLD messages of its users, and then forwards them to its uplink device. It assumes the role of router on the user side, queries user information regularly, and assumes the role of client on the network routing side, and sends the current user information to it when needed. Therefore, a multicast routing table is formed in the device with MLD Proxy enabled.

To access the page, log in to the web UI of the ONT and choose **Advance > IPv6 > MLD Proxy**.

**MLD Proxy:**
☐ Disable
 ☒ Enable

Apply Changes

## 9.2.5 MLD snooping

MLD (Multicast Listener Discovery) is a Layer 2 multicast protocol running on IPv6 networks. With MLD snooping enabled, the ONT listens to the multicast conversations and maintains a map of the relationship between links and IP multicast which the link needs. Multicasts may be filtered from the links which do not need them, conserving bandwidth on those links.

To access the page, log in to the web UI of the ONT and choose **Advance > IPv6 > MLD Snooping**.

<b>MLD Snooping:</b>	<input type="radio"/> Disable <input checked="" type="radio"/> Enable
<input type="button" value="Apply Changes"/>	

# 10 Diagnostics

## 10.1 Overview

The ONT provides connectivity diagnosis tools, which include Ping and Tracert. You can use these tools to test the connectivity to the internet, a certain IP address or domain name.

- **Ping:** It is a utility that helps to check if an IP address or domain name is accessible or not. Ping works by sending a packet to the specified address and waits for the reply. It also measures round trip time and reports errors.
- **Tracert:** It is a utility that traces a packet from your computer to the host, and will also show the number of steps (hops) required to reach there, along with the time by each step.

To access the page, log in to the web UI of the ONT and choose **Diagnostics**. Both tools include IPv4 (**Ping/Tracert**) and IPv6 (**Ping6/Tracert6**) versions. The IPv4 version is used for illustration.

### Ping

Host Address:	<input type="text"/>
WAN Interface:	Any ▼
<input type="button" value="Go"/>	

#### Parameter description

Parameter	Description
Host Address	It specifies the IP address or domain name whose connectivity with the ONT is to be diagnosed.
WAN Interface	It specifies the WAN interface through which the packet for diagnosis is forwarded.

### Tracert

Host Address:	<input type="text"/>
NumberOfTries:	<input type="text" value="3"/>
MaxHopCount:	<input type="text" value="30"/>
<input type="button" value="Go"/>	



**Parameter description**

Parameter	Description
Host Address	It specifies the IP address or domain name of the tracert target.
NumberOfTries	<p>It specifies the maximum number of times that the host tries to reach the host address.</p> <p>If all the attempts fail, it denotes network congestion and a reason for slow loading Web pages and dropped connections.</p>
MaxHopCount	<p>It specifies the hops of the packet for diagnosis.</p> <p>When a packet cannot reach the destination and expires at an intermediate step, that node returns the packet and identifies itself. It denotes network congestion and a reason for slow loading web pages and dropped connections.</p>

## 10.2 Execute Ping to test connectivity

- Step 1** Log in to the web UI of the ONT.
- Step 2** Choose **Diagnostics > Ping**.
- Step 3** Enter the IP address or domain name in Host Address, such as **www.google.com**.
- Step 4** Choose any interface from **WAN Interface**.
- Step 5** Click **Go**.

Host Address:	<input type="text" value="www.google.com"/>
WAN Interface:	<input type="text" value="Any"/>
<input type="button" value="Go"/>	

Wait a moment. The result appears when the diagnosis finishes.

---End

## 10.3 Execute Traceroute to test routing

- Step 1** Log in to the web UI of the ONT.
- Step 2** Choose **Diagnostics > Tracert** or **Diagnosis > Tracert**.
- Step 3** Enter the IP address or domain name in **Host Address**, such as **www.google.com**.
- Step 4** Specify the number of attempts in **NumberOfTries**.
- Step 5** Specify the number of hops in **MaxHopCount**.
- Step 6** Click **Go**.

<b>Host Address:</b>	<input type="text" value="www.google.com"/>
<b>NumberOfTries:</b>	<input type="text" value="3"/>
<b>MaxHopCount:</b>	<input type="text" value="30"/>
<input type="button" value="Go"/>	

Wait a moment. The result appears when the diagnosis finishes.

---End

## 10.4 Manual inform report

On this page, you can manually inform reports to the Auto-Configuration Server (ACS). To access this page, log in to the web UI of the ONT and choose **Diagnosis > Inform report**.

**Inform report Diagnostics**  
 This page is used to manual inform report to acs server. The diagnostic result will then be displayed.

<b>Inform report status:</b>	<input type="text" value="Not Report"/>
<input type="button" value="Inform report"/>	

# 11 Admin

## 11.1 GPON/EPON settings

On this page, you can register your ONT for internet access.

The ONT may register itself automatically after you connect a fiber cord to it and power it on. Under some circumstances, you may need to manually register the ONT with parameters provided by your ISP on this page.

To access the page, log in to the web UI of the ONT and choose **Admin > GPON Settings** (or **EPON Settings** for HG7). Enter the parameters provided by your ISP and click **Apply Changes** to register the ONT.

You can view the registration status of the ONT on the [PON status](#) page.

<b>LOID:</b>	<input type="text"/>
<b>LOID Password:</b>	<input type="password"/>
<b>PLOAM Password:</b>	<input type="password" value="....."/>
<b>Serial Number:</b>	<input type="text" value=""/>
<b>OMCI OLT Mode:</b>	<input type="text" value="Default Mode"/> ▼

## 11.2 Multicast VLAN

### 11.2.1 Overview

On this page, you can configure multicast VLAN values for certain WAN interfaces to access certain network or services, such as IPTV services.


To access the page, log in to the web UI of the ONT and choose **Admin > Multicast Vlan**.

Setup Multicast Vlan (empty means not to setup)		
Interface	Multicast Vlan	Modify
ppp0		

### 11.2.2 Set multicast VLAN to watch IPTV programs

Assume that you have subscribed to the IPTV service from your ISP and it is included in your broadband service, and the VLAN ID of the IPTV service is 10. When you want to watch IPTV programs on the TV, you can configure the multicast VLAN function to reach the goal.

#### Configuring procedure:

- Step 1** Log in to the web UI of the ONT.
- Step 2** Choose **Admin > Multicast Vlan**.
- Step 3** Choose the WAN interface that includes the IPTV service, click  in the line of the interface, and enter **10** in **Setup Multicast Vlan (empty means not to setup)**.
- Step 4** Click **Apply**.

Setup Multicast Vlan (empty means not to setup)	
	<input type="text" value="10"/>
<input type="button" value="Apply"/> <input type="button" value="Undo"/>	

---End

When the multicast VLAN is set successfully, the multicast VLAN ID you set is displayed under **Multicast Vlan**. You can watch IPTV programs on the TV through the set-top box connected to a port of the ONT.

## 11.3 OMCI information

ONU Management Control Interface (OMCI) defines a mechanism and message format that is used by the Optical Line Termination (OLT) to configure, manage, and monitor ONTs.

To access the page, log in to the web UI of the ONT and choose **Admin > OMCI Information**. You can click **Refresh** to update the information.

OMCI software version 1:	v1.0.0
OMCI software version 2:	v1.0.0
OMCC version:	0x80
Traffic Managment option:	2
CWMP Product Class:	IGD
HW version:	RTL960x

## 11.4 Commit/Reboot

This page is used to commit any configuration changes you have made and reboot the ONT to put the changes into effect. Click **Commit and Reboot** to save settings and reboot the ONT.

To access the page, log in to the web UI of the ONT and choose **Admin > Commit/Reboot**.

<b>Commit and Reboot:</b>	<input type="button" value="Commit and Reboot"/>
---------------------------	--

## 11.5 Backup/Restore

On this page, you can back up the configuration of the ONT, restore the configuration from a backup file, and reset the ONT.

To access the page, log in to the web UI of the ONT and choose **Admin > Backup/Restore**.

<b>Backup Settings to File:</b>	<input type="button" value="Backup..."/>
<b>Restore Settings from File:</b>	<input type="button" value="Choose File"/> <span>No file chosen</span> <input type="button" value="Restore"/>
<b>Reset Settings to Default:</b>	<input type="button" value="Reset"/>

## 11.5.1 Back up the configuration of the ONT


You can back up the configuration of the ONT at a certain time for future restoration after you change the settings or reset the ONT.

**Configuring procedure:**

**Step 1** Log in to the web UI of the ONT.

**Step 2** Choose **Admin > Backup/Restore**.

**Step 3** Click **Backup....**



The configuration file (**config.xml**) is automatically downloaded to the local host.

---End

## 11.5.2 Restore previous configuration of the ONT


You can restore the previous configuration of the ONT using the backup file that you have downloaded.

**Configuring procedure:**


**Step 1** Log in to the web UI of the ONT.

**Step 2** Choose **Admin > Backup/Restore**.

**Step 3** Click **Choose File**, and select the configuration file.



**Step 4** Click **Restore**.



The ONT reboots to enable the configuration to take effect.

---End

## 11.5.3 Reset the ONT

When the ONT malfunctions and you cannot find a solution, you can try to reset the ONT. If your ISP has preset the ONT, the ONT will be restored to the configurations preset by the ISP. Otherwise, the ONT will be restored to factory settings.



TIP

Resetting the ONT will clear all previous personalized configurations. It is recommended to back up the configuration of the ONT in advance.

**Configuring procedure:**

- Step 1** Log in to the web UI of the ONT.
- Step 2** Choose **Admin > Backup/Restore**.
- Step 3** Click **Reset**.

Reset Settings to Default:	Reset
----------------------------	-------

The ONT starts rebooting. Wait until it finishes rebooting, and then you can log in to the ONT again and perform settings.

---End

## 11.6 Password

On this page, you can change the login password for the ONT. The default login user name and password are **admin**. You can only change the password, and the original password is required during the process.

**Configuring procedure:**

- Step 1** Log in to the web UI of the ONT.
- Step 2** Choose **Admin > Password**.
- Step 3** Enter the original password in **Old Password**.
- Step 4** Enter your new password in **New Password** and **Confirmed Password**.
- Step 5** Click **Apply Changes**.

UserName:	admin ▼
Old Password:	<input type="password"/>
New Password:	<input type="password"/>
Confirmed Password:	<input type="password"/>

The following message is displayed, indicating that the password is changed successfully.

<p><b>Change setting successfully!</b></p> <p>OK</p>
--

---End



## 11.7 Firmware upgrade

To get new features and improve performance and operating stability, you can upgrade the firmware of the ONT when a new version is available.

### Configuring procedure:

- Step 1** Go to [www.tendacn.com](http://www.tendacn.com). Download an applicable firmware of the ONT to your local computer and unzip it.
- Step 2** Log in to the web UI of the ONT.
- Step 3** Choose **Admin > Firmware Upgrade**.
- Step 4** Click **Choose File**, and select the upgrade file.
- Step 5** Click **Upgrade**.



The screenshot shows a web interface for firmware upgrade. At the top, there is a button labeled 'Choose File' and the text 'No file chosen'. Below this, there are two buttons: 'Upgrade' and 'Reset'.

The ONT reboots automatically.

---End

## 11.8 ACL

Access Control List (ACL) is a collection of permit and deny rules that ensure security by blocking unauthorized users from and allowing authorized users to access ONT.

To access the page, log in to the web UI of the ONT and choose **Admin > ACL**.

<b>ACL Capability:</b>	<input type="radio"/> Disable <input checked="" type="radio"/> Enable <button>Apply Changes</button>
<b>Enable:</b>	<input checked="" type="checkbox"/>
<b>Interface:</b>	LAN ▼
<b>Start IP Address:</b>	<input type="text"/>
<b>End IP Address:</b>	<input type="text"/>

ServiceName	LAN
Any	<input type="checkbox"/>
TELNET	<input type="checkbox"/>
FTP	<input type="checkbox"/>
TFTP	<input type="checkbox"/>
HTTP	<input type="checkbox"/>
HTTPS	<input type="checkbox"/>
SNMP	<input type="checkbox"/>
PING	<input checked="" type="checkbox"/>

Add

ACL Table					
Select	State	Interface	IP Address	Services	Port
<input type="checkbox"/>	Enable	LAN	N/A	ftp,tftp,web,https,snmp,ping	21,69,80,443,161,162,-
<input type="checkbox"/>	Enable	WAN	N/A	web,https	80,443

Delete Selected

### Parameter description

Parameter	Description
ACL Capability	It specifies whether to enable the ACL function of the ONT.
Enable	<p>It specifies the control mode of the function.</p> <ul style="list-style-type: none"> <li>When <b>Enable</b> is selected, traffic that meets the criteria of the rule can pass through the specified port of the ONT.</li> <li>When <b>Disable</b> is selected, traffic that meets the criteria of the rule is discarded at the specified port of the ONT.</li> </ul>

Parameter	Description
Interface	<p>It specifies the interface that the access control rule applies to, including LAN and WAN.</p> <ul style="list-style-type: none"> <li>• <b>LAN:</b> The ONT checks traffic from the LAN side according to the rule and decides to pass it or discard it.</li> <li>• <b>WAN:</b> The ONT checks traffic from the WAN side according to the rule and decides to pass it or discard it.</li> </ul>
Start IP Address	They specify the IP address range or a certain IP address that is controlled by the rule.
End IP Address	
ServiceName	<p>It specifies the protocol adopted by the traffic, or the types of traffic.</p> <ul style="list-style-type: none"> <li>• <b>Any:</b> It indicates that all types of traffic are under the control of this rule.</li> <li>• <b>TELNET:</b> Telnet is a protocol that provides a command line interface for communication with a remote device or server, sometimes employed for remote management but also for initial device setup like network hardware.</li> <li>• <b>FTP:</b> File Transfer Protocol (FTP) is a standard network protocol used for the transfer of computer files between a client and server on a computer network.</li> <li>• <b>TFTP:</b> Trivial File Transfer Protocol (TFTP) is a simple file transfer protocol that allows a client to get a file from or put a file onto a remote host.</li> <li>• <b>HTTP:</b> Hypertext Transfer Protocol (HTTP) is an application protocol and the foundation of data communication for the World Wide Web, where hypertext documents include hyperlinks to other resources that the user can easily access.</li> <li>• <b>HTTPS:</b> Hypertext Transfer Protocol Secure (HTTPS) is an extension of HTTP. SNMP is used for secure communication over a computer network, and is widely used on the Internet.</li> <li>• <b>SNMP:</b> Simple Network Management Protocol (SNMP) is the most widely used network management protocol in TCP/IP networks, which enables you to remotely manage all your network devices compliant with this protocol.</li> <li>• <b>PING:</b> Ping is a computer network administration software utility used to test the reachability of a host on an IP network.</li> </ul>
WAN/LAN	It specifies the interface to which the rule applies. It changes as you choose an interface.
ACL Table	It displays all the ACL rules that are added.
Select	It is used to select multiple ACL rules.
State	It specifies the control mode of the rule. If you deselect <b>Enable</b> when setting an ACL rule, the <b>State</b> shows <b>Disable</b> .
Interface	It specifies the interface that the access control rule applies to, including LAN and WAN.
IP Address	It specifies the IP address range or a certain IP address that is controlled by the rule.
Services	It specifies the protocols adopted by the traffic, or the types of traffic.
Port	It specifies the default ports adopted by the corresponding services.

## 11.9 Time Zone

On this page, you can change the system time of the ONT, or enable the ONT to update its system time with the Simple Network Time Protocol (SNTP) server.

To access the page, log in to the web UI of the ONT and choose **Admin > Time Zone**.

<b>Current Time :</b>	Year <input type="text" value="2020"/> Mon <input type="text" value="1"/> Day <input type="text" value="1"/> Hour <input type="text" value="2"/> Min <input type="text" value="35"/> Sec <input type="text" value="54"/>
<b>Time Zone Select :</b>	<input type="text" value="Asia/Singapore (UTC+08:00)"/> ▼
<b>Enable Daylight Saving Time</b>	<input checked="" type="checkbox"/>
<b>Enable SNTP Client Update</b>	<input type="checkbox"/>
<b>WAN Interface:</b>	<input type="text" value="Any"/> ▼
<b>SNTP Server :</b>	<input checked="" type="radio"/> <input type="text" value="203.117.180.36 - Asia Pacific"/> ▼ <input type="radio"/> <input type="text" value="220.130.158.52"/> (Manual Setting)

### Parameter description

Parameter	Description
Current Time	It specifies the current system time of the ONT. You can change it manually.
Time Zone Select	It specifies the time zone where the ONT locates.
Enable Daylight Saving Time	<p>Daylight Saving Time (DST) is the practice of advancing clocks during warmer months so that darkness falls later each day according to the clock.</p> <p>With it is enabled, the ONT sets the time forward by one hour in the spring ("spring forward") and set the time back by one hour in autumn ("fall back") to return to standard time. In other words, there is one 23-hour day in late winter or early spring and one 25-hour day in the autumn.</p>
Enable SNTP Client Update	<p>It specifies whether to enable automatic update of system time through synchronization with SNTP server.</p> <p>The SNTP is a time synchronization protocol of the TCP/IP protocol family. It is based on the connectionless User Datagram Protocol (UDP) and can be used on all supporting devices to synchronize system time in IP networks.</p>
WAN Interface	It specifies the interface through which the ONT updates its system time with the SNTP server.
SNTP Server	You can choose a preset SNTP server, or manually set the IP address for updating system time.

## 11.10 TR-069

The Customer Premise Equipment (CPE) WAN Management Protocol (TR-069) allows an ACS (Auto-Configuration Server) to perform auto-configuration, provision, collection, and diagnostics to the ONT from the internet. Generally, it is used by the ISP to manage the ONT.

To access the page, log in to the web UI of the ONT and choose **Admin > TR-069**.

<b>TR069 Daemon:</b>	<input checked="" type="radio"/> Enabled <input type="radio"/> Disabled
<b>EnableCWMPParamete:</b>	<input checked="" type="radio"/> Enabled <input type="radio"/> Disabled
<b>ACS</b>	
<b>URL:</b>	<input type="text" value="http://"/>
<b>UserName:</b>	<input type="text" value="username"/>
<b>Password:</b>	<input type="text" value="password"/>
<b>Periodic Inform:</b>	<input type="radio"/> Disabled <input checked="" type="radio"/> Enabled
<b>Periodic Inform Interval:</b>	<input type="text" value="300"/>
<b>Connection Request</b>	
<b>Authentication:</b>	<input type="radio"/> Disabled <input checked="" type="radio"/> Enabled
<b>UserName:</b>	<input type="text"/>
<b>Password:</b>	<input type="text"/>
<b>Path:</b>	<input type="text" value="/tr069"/>
<b>Port:</b>	<input type="text" value="7547"/>

### Parameter description

Parameter	Description
TR069 Daemon	It specifies whether to enable the TR069 function.
Enable CWMP Parameter	It specifies whether to enable the CPE WAN management protocol.
ACS	URL
	UserName
	Password
	Periodic Inform
	Periodic Inform Interval
	It specifies the URL of the ACS.
	They specify the user name and password used to authenticate the ONT when the ONT connects to the ACS using the CPE WAN management protocol.
	It is used to enable or disable the ONT to periodically inform ACS.
	It specifies the interval that the ONT to inform the ACS.

Parameter	Description	
Connection Request	Authentication	It specifies whether to authenticate the connection request sent by the ACS.
	UserName	They specify the user name and password used to authenticate the ACS when it sends the connection request to the CPE.
	Password	
	Path	It specifies the path used to receive the connection request sent by the ACS. Keep the default value if you are not sure.
	Port	It specifies the port used to receive the connection request sent by the ACS.

## 11.11 Logout

To access the page, choose **Admin > Logout**.

You can log out of the web UI of the ONT by clicking **Logout** on this page, or click **Logout** at the upper-right corner of the web UI.

### Logout

This page is used to logout from the Device.

Logout

# 12 Statistics

In this part, you can view the packet statistics of the ports and interfaces of the ONT.

## Interface statistics

This page displays the received and transmitted packets statistics, including the received packets (Rx pkt), received packets error (Rx err), dropped received packets (Rx drop), transmitted packets (Tx pkt), transmitted packets error (Tx err), dropped transmitted packets (Tx drop).

To access the page, log in to the web UI of the ONT and choose **Statistics > Interface**.

Interface	Rx pkt	Rx err	Rx drop	Tx pkt	Tx err	Tx drop
LAN1	1128	0	0	1122	0	0
LAN2	0	0	0	0	0	0
LAN3	0	0	0	0	0	0
LAN4	0	0	0	0	0	0
wlan0	1009913	0	0	0	0	0
wlan1	1136	0	0	20	0	0
ppp0_nas0_0	0	0	0	0	0	0

## PON statistics

The page displays the data statistics transmitted and received through the PON port.

To access the page, log in to the web UI of the ONT and choose **Statistics > PON Statistics**.


Bytes Sent:	0
Bytes Received:	0
Packets Sent:	0
Packets Received:	0
Unicast Packets Sent:	0
Unicast Packets Received:	0
Multicast Packets Sent:	0
Multicast Packets Received:	0
Broadcast Packets Sent:	0
Broadcast Packets Received:	0
FEC Errors:	0
HEC Errors:	0
Packets Dropped:	0
Pause Packets Sent:	0
Pause Packets Received:	0

# Appendixes

## A.1 Configure the computer to obtain an IPv4/IPv6 address automatically


Perform the configuration procedure in [Windows 10](#), [Windows 8](#) and [Windows 7](#) as required. A computer installed with a wired network adapter is used as an example to describe the procedure. The procedures for configuring computers installed with WiFi network adapters are similar.

### A.1.1 Windows 10

**Step 1** Click  in the bottom right corner of the desktop and choose **Network settings**.




**Step 2** Click **Change adapter options**.







**Step 3** Right-click on the connection in use, and then click **Properties**.



**Step 4** Double-click **Internet Protocol Version 4 (TCP/IPv4)** or **Internet Protocol Version 6 (TCP/IPv6)**.




**Step 5** Select **Obtain an IP address automatically** and **Obtain DNS server address automatically**, and click **OK**.




**Step 6** Click **OK** in the **Ethernet Properties** window.


---End

## A.1.2 Windows 8


**Step 1** Right-click  in the bottom right corner of the desktop and choose **Open Network and Sharing Center**.




**Step 2** Click **Ethernet** and then **Properties**.



**Step 3** Double-click **Internet Protocol Version 4 (TCP/IPv4)** or **Internet Protocol Version 6 (TCP/IPv6)**.




**Step 4** Select **Obtain an IP address automatically** and **Obtain DNS server address automatically**, and click **OK**.




**Step 5** Click **OK** in the **Ethernet Properties** window.


**---End**

## A.1.3 Windows 7


**Step 1** Click  in the bottom right corner of the desktop and choose **Open Network and Sharing Center**.




**Step 2** Click **Local Area Connection** and then **Properties**.



**Step 3** Double-click **Internet Protocol Version 4 (TCP/IPv4)** or **Internet Protocol Version 6 (TCP/IPv6)**.



**Step 4** Select **Obtain an IP address automatically** and **Obtain DNS server address automatically**, and click **OK**.



**Step 5** Click **OK** in the **Local Area Connection Properties** window.

**---End**

## A.2 Acronyms and abbreviations

Acronym or Abbreviation	Full Spelling
ACL	Access control list
ACS	Auto-Configuration Server
AES	Advanced Encryption Standard
ALG	Application Layer Gateway
AP	Access Point
APC	Angled Physical Contact
ARP	Address Resolution Protocol
ASCII	American Standard Code for Information Interchange
BSSID	Basic Service Set Identifiers
CPE	Customer Premise Equipment
CPU	Central processing unit
CTS	Clear To Send
CWMP	CPE WAN Management Protocol
DDNS	Dynamic Domain Name System
DHCP	Dynamic Host Configuration Protocol
DHCPv6	Dynamic Host Configuration Protocol version 6
DMZ	Demilitarized zone
DND	Don't Disturb
DNS	Domain Name System
DTMF	Dual tone multi-frequency
DUID	DHCP unique identifier
FQDN	Fully qualified domain name
FTP	File Transfer Protocol
FTTH	Fiber to the Home
HTTP	Hypertext Transfer Protocol
HTTPS	Hypertext Transfer Protocol Secure

Acronym or Abbreviation	Full Spelling
IGMP	Internet Group Management Protocol
IMS	IP Multimedia Subsystem
IP	Internet Protocol
IPsec	Internet Protocol Security
IPTV	Internet Protocol television
IPv4	Internet Protocol version 4
IPv6	Internet Protocol version 6
ISP	Internet service provider
ITU	International Telecommunication Union
L2TP	Layer 2 Tunneling Protocol
LAN	Local Area Network
MAC	Medium access control
MIB	Management information base
MLD	Multicast Listener Discovery
MPPE	Microsoft Point-to-Point Encryption
MTU	Maximum Transmission Unit
NAPT	Network Address Port Translation
NMS	Network Management System
OLT	Optical line termination
OMCI	ONU Management Control Interface
ONT	Optical Network Terminal
ONU	Optical network unit
OS	Operating system
P2P	Peer-to-peer
PIN	Personal Identification Number
PON	Passive optical network
PPP	Point-to-Point Protocol



Acronym or Abbreviation	Full Spelling
PPPoE	Point-to-Point Protocol over Ethernet
PPTP	Point-to-Point Tunneling Protocol
RA	Router Advertisement
RADVD	Router Advertisement Daemon
RDNSS	Recursive DNS Server
RS	Router Solicitation
RSSI	Received Signal Strength Indicator
RTP	Real-time Transport Protocol
RTS	Request To Send
RTSP	Real Time Streaming Protocol
SC	Subscriber connector
SIP	Session Initiation Protocol
SLAAC	Stateless address autoconfiguration
SNMP	Simple Network Management Protocol
SNTP	Simple Network Time Protocol
SSID	Service set identifier
STB	Set-top box
TCP	Transmission Control Protocol
TFTP	Trivial File Transfer Protocol
TKIP	Temporal Key Integrity Protocol
TR-069	Technical Report - 069
UDP	User Datagram Protocol
UI	User interface
ULA	Unique Local Address
UPnP	Universal Plug and Play
URI	Uniform Resource Identifier
URL	Uniform Resource Locator

<b>Acronym or Abbreviation</b>	<b>Full Spelling</b>
VLAN	Virtual Local Area Network
VPN	Virtual Private Network
VoIP	Voice over IP
VoLTE	Voice over Long-Term Evolution
WAN	Wide Area Network
WEP	Wired Equivalent Privacy
WLAN	Wireless Local Area Network
WPA	Wi-Fi Protected Access
WPA-PSK	WPA-Preshared Key
WPS	WiFi Protected Setup