

## RF EXPOSURE EVALUATION

FCC ID: 2AB7K-A7721

According to KDB 447498:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances*  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f_{\text{(GHz)}}}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR,<sup>16</sup> where

- $f_{\text{(GHz)}}$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum *test separation distance* is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by §2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

The maximum output power for low channel is: 0.70dBm= 1.17mW

Tune up tolerance is:  $0.70 \pm 1$  dBm

The Max. Tune up Power = 1.70dBm= 1.48mW

The calculation results=  $1.48/5 \cdot \sqrt{2.402} = 0.4588 < 3$

The maximum output power for middle channel is: 0.72dBm= 1.18mW

Tune up tolerance is:  $0.72 \pm 1$  dBm

The Max. Tune up Power = 1.72dBm= 1.49mW

The calculation results=  $1.49/5 \cdot \sqrt{2.441} = 0.4655 < 3$

The maximum output power for high channel is: 1.01dBm= 1.26mW

Tune up tolerance is:  $1.01 \pm 1$  dBm

The Max. Tune up Power = 2.01dBm= 1.59mW

The calculation results=  $1.59/5 \cdot \sqrt{2.480} = 0.5000 < 3$

Test Results: **The EUT is not need to conduct SAR measurement.**

