



a Motorola Solutions Company

Product Specification

VideoXpert Storage Server T-Series

Enterprise 2U 12-Bay Rackmount

Enterprise, High Performance and Video Processing

Benefit from scalable storage performance and video processing with this Enterprise server. This 2U platform brings you scalability and performance to adapt to a variety of the most demanding and process intensive video surveillance applications.

Up to 144TB of raw storage allows for long term video storage and archiving. Paired with the latest Intel® Xeon® Scalable processor, this provides high density storage with Enterprise throughput for the most demanding applications.

Better performance is provided with dual SSDs for accelerated boot and application load times. Remote management, provided by iDRAC, allows for constant system status and critical resource monitoring. RAID 6 storage, in addition to redundant 750W power supplies, provide system reliability and high availability, while a five-year, on-site, next business day, Keep Your Hard Drive warranty, ensures peace of mind.



KEY FEATURES

- Up to 144TB of Raw Storage
- Intel® Xeon® Silver Scalable Processor
- Operating System: Windows Server 2019
- iDRAC features include:
 - Remote Management
 - Disaster Recovery
 - Critical Resource Monitoring



SSD & 24/7 Duty Cycle SATA Drives



Redundant Power



RAID 6



**5-Year, On-site, NBD,
Keep Your Hard Drive Warranty**

SKU	DESCRIPTION
VXS2-T0-N	VXS RAID STORAGE SVR 00TB
VXS2-T96-N8	VXS RAID STORAGE SVR 96TB
VXS2-T144-N12	VXS RAID STORAGE SVR 144TB
VX-S2-HDTRAY	HD carrier tray for VxStorage v2.



a Motorola Solutions Company

VideoXpert Storage Server T-Series

Enterprise 2U 12-Bay Rackmount

Product Specification

CERTIFIED | PURPOSE BUILT | GUARANTEED

SYSTEM		
Processor	(1)Intel® Xeon® Silver 4210 Scalable Processor (10 Cores, 20 Threads, 2.20 GHz)	
Processor Passmark	Intel® Xeon® Silver 4210: 12,020	
Maximum Storage	Up to 144TB	
Operating System	Windows Server 2019	
Memory	32GB (4x 8GB)	
RAID	OS RAID 1; Data RAID 6	
RAID Controller	PERC H740P (8GB NV Cache, RAID 6)	
Networking	(2) 1GbE RJ45 Ports; (2) 10GbE SFP+	
Expansion Slots	(1) x16 full-height, (2) x8 low profile PCIe slots (in default configuration)	
USB(s)	Rear (2) USB 3.0, Front (2) USB 2.0, Internal (1) USB 3.0	
Video Outputs	(1) VGA	
Remote Management	iDRAC Basic	
Manufacturer	PELCO	
Warranty	5-Year, On-site, NBD, Keep Your Hard Drive Warranty	
MECHANICAL		
Form Factor	2U Rackmount	
Rack Support	Sliding Rack Rail with Cable Management Arm	
Hard Drive Bays	(12) 3.5" Hot Swappable Bays & (2) M.2 SSD Slots	
Hard Drives Supported	PCIe NVMe & SATA	
Power Supply(s)	(2) 750W (100-240VAC) 80 Plus Platinum	
Power Information	Input Power 330W / 1126 BTU/h - Max Potential 650W / 2178 BTU/h	
Operating Temperature	(Min) 50°F - (Max) 95°F [(Min) 10°C - (Max) 35° C]	
Operating Humidity	5 ~ 90% (non-condensing)	
Dimensions (WxDxH)	19" (482.6mm) x 28.15" (646mm) x 3.4" (86.8mm)	
Max. Weight	65.43 lbs. (29.68 kg)	
MODEL		
	RECORDING THROUGHPUT	PLAYBACK THROUGHPUT
VXS2-T: 1Gb	Up to 700 Mbps	Up to 175 Mbps
VXS2-T: 10Gb	Up to 1000 Mbps	Up to 175 Mbps

Pelco, Inc
625 W. Alluvial Ave., Fresno, California 93711 United States
(800) 289-9100 Tel
(800) 289-9150 Fax
+1 (559) 292-1981 International Tel
+1 (559) 348-1120 International Fax
www.pelco.com

Pelco, the Pelco logo, and other trademarks associated with Pelco products referred to in this publication are trademarks of Pelco, Inc. or its affiliates. ONVIF and the ONVIF logo are trademarks of ONVIF Inc. All other product names and services are the property of their respective companies. Product specifications and availability are subject to change without notice.