

Acknowledgment Letter



SPECIFICATION FOR APPROVAL

CUSTOMER: **Shenzhen Yixunda Technology Co., Ltd**

CUST P/N: **10.0110.1967 Heating shrink tubing**

FINE P/N: **G45-6.8UH single coil 0.08 * 24P * 2-10TS**

DESC: **Diameter 43.5MMX5.0MMX0.8MM slotted**

DATE: **May 23, 2024**

Version:

A.0



PREPARED BY	CHECKED BY	APPROVED BY	CUSTOMER APPROVE
Huang Yanming	Ning Yuan'an	Huang Jinhua	

Dongguan Xilian Gancheng Technology Co., Ltd

Factory address: 8th floor, Building 2, Sanjia High tech Industrial Park, No.
123 Junfa Road, Dongkeng Town, Dongguan City

TEL: 0769-82989159


FAX: 0769-82989159

E-mail: aming198204@163.com

SPECIFICATION

DESC	Φ20.5x40-6.8uH-0.08x24PX2P-160mm	Rev: A.0	CUST:	XXX
			CUST P/N:	

one、DIMENSION:(mm)




A	43.5±0.5
B	20.5±1
C	39±1.0
D	160±3
E	3±2
F	1.4±0.3

Note:

1. Cross outgoing line;
2. Wrap 8mm (ref) wide high-temperature adhesive paper 1-2Ts around the outlet position;
3. The coil is covered with circular hard magnetic plates with slots, with a magnetic plate size of 43.5 ± 0.5 mm, an inner hole of 5.0mm, and a thickness of 0.8 ± 0.1 mm.
4. Lead heating shrink tubing

two、SCHEMATIC DIAGRAM:



three、Winding Specification:

NO.	TERMINAL	WIRE	Turns	Winding Direction
1	S F	Hot air line 0.08 * 24PX2	10Ts	CCW

four、ELECTRICAL CHARACTERISTICS:

TEMPERATURE:25±10°C, RELATIVE HUMIDITY:65±20%

NO.	ITEM	TERMINAL	SPECIFICATION	TEST FREQUENCY	TEST EQUIPMENTS
1	IND.	S-F	$3.8\mu\text{H} \pm 20\%$ individual coil	100KHz/1.0V	LCZ METER 1062B
2	IND.	S-F	$6.8\mu\text{H} + 10\%$ magnetic disk	100KHz/1.0V	LCZ METER 1062B
3	DCR	S-F	$\leq 90\text{m}\Omega$	100KHz/1.0V	LCZ METER 502B
4	Q	S-F	≥ 39	100KHz/1.0V	LCZ METER 502B

PREPARED BY/DATE	CHECKED BY/DATE
Huang Yanming May 23, 2024	Huang Jinhua May 23, 2024