ThinkCentre M720 Tiny 10T8000X++

Region EMEA

Machine Type

10T8

TopSeller

No

Processor

Core i5-8400T (6C, 1.7 / 3.3GHz, 9MB)

vPro No

Graphics

Integrated Intel UHD Graphics 630

Monitor Cable

None

Memory 8GBx1

Storage

256GB SSD M.2 PCIe NVMe Opal

Optical None

WLAN + Bluetooth

Intel 3165 ac, 1x1 + BT4.2

Ethernet Integrated

Optional Rear Ports

VGA + Serial

Extension Card

None

Kensington Cable Lock

None

Adapter Cage

Adapter Cage

Toolless Chassis Screw

Toolless Chassis Screw

Speaker

1.5Wx1

Dust Filter

Dust Filter

VESA Mount

VESA Mount

Stand

None

Keyboard / Mouse

USB / USB

Power Supply

65W 88% Adapter

TUV Low Noise

None

Operating System

Windows 10 Pro 64

Warranty

3-year, Onsite

End of Support

Jul 26, 2024

Ann Date (mm/yy)

06/18

Note:

Country Code "US" is for United States, "++" is for EMEA countries (e.g. AD - Saudi, Arabia, AT - Austria, BM - Bulgaria, etc.), "xx" is for EAST countries (e.g. BM - Bulgaria, CX - Hungary, CY - Cyprus, etc.), and "**" is for MEA countries (e.g. AD - Saudi, Arabia, ED - Egypt, EQ - Sweden, etc.). Please be aware that the EMEA/ EAST/MEA models listed above might not be available in all countries



www.lenovo.com

This publication was developed for products and services offered in the United States and E.M.E.A countries. Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area. Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. Lenovo provides this publication "as is" without warranty of any kind, either express or implied, including the implied warranties of merchantability or ftness for a particular purpose.



http://psref.lenovo.com

Visit psref website for the latest version of Product Specifications Reference.
© Lenovo. 2018. All rights reserved.



ThinkCentre M720 Tiny Platform Specifications

Droosss	Intol® Colores® 1	lond!	or Oth O	n later of	20x0TM :0 /:5 /:3 5	Drog = = = =	Monographic	Intol Anthrop Man	nant Taskers I	O (Intel ANT 40)		
Processor		Intel® Celeron®, Intel Pentium®, or 8th Generation Intel Core™ i3 / i5 / i7 Processor Cores / Frequency Cores Memory Support Integrated						Intel Active Management Technology 12 (Intel AMT 12) Discrete TPM 2.0, TCG Certified				
	Processor	Cores / Threads	Frequency Base/Max(GHz)	Cache	(Up to)	Graphics	Security features	S • Security slot (in rear for optional • Bo		Boot sequence of		
	Celeron G4900T	2/2	2.9G	2 MB	DDR4-2400	UHD 610		Kensington® Micros	Saver® cable)	 Boot without key 	yboard and mouse	
	Pentium Gold G5400T	2/4	3.1G	4 MB	DDR4-2400	UHD 610		Chassis intrusion sPower-on password		 Individual USB p Smart USB prote 	port disablement tection, allows keyboard/	
	Pentium Gold G5500T	2/4	3.2G	4 MB	DDR4-2400	UHD 630		 Power-on password Administrator pass 			tection, allows keyboard/ cks all storage devices	
	Core i3-8100T	4/4	3.1G	6 MB	DDR4-2400	UHD 630		Hard disk password				
	Core i3-8300T	4/4	3.2G	8 MB	DDR4-2400	UHD 630		Some: Lenovo Callio				
	Core i5-8400T	6/6	1.7G / 3.3G	9 MB	DDR4-2666	UHD 630]	Some: Lenovo Tradit	litional Keyboard (U	USB connector), blac	ıck	
	Core i5-8500T	6/6	2.1G / 3.5G	9 MB	DDR4-2666	UHD 630	Mouse	Some: Lenovo Callid Some: Lenovo Callid	ope Wouse /IICD /	DOME (2.4GHZ VIA U	ום receiver), black	
	Core i5-8600T	6/6	2.3G / 3.7G	9 MB	DDR4-2666	UHD 630	1	Some: Lenovo Finge	erprint Mouse (US	SB connector), Windo	lows Hello support, blac	
	Core i7-8700T	6/12	2.4G / 4.0G	12 MB	DDR4-2666	UHD 630	1[Some: Lenovo Callic	ope Wireless Mous	se (2.4GHz via USE	3 receiver), black	
	32GB max, DDR4-266		260-pin SO-DIMI	vi socke.	rts, non-ECC,	i		Tiny (1L), black color				
	dual-channel capable * System automatically		lown for the proc	essors	with lower memor	ry controller		 Toolless chanssis c 	open (need optiona	al toolless chanssis	screw)	
Storage		,	· · · · · · · · · · · · · · · · · · ·			, 23.16.0116.	┥	Toolless HDD, SSDOptional dust filter		น		
· ·	Some: Hard Drive / SATA 6.0Gb/s, 2.5", 5400 rpm or 7200 rpm Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5"							one 2.5" bay for HDD	D/SSD, one PCIe 3	3.0 x8 slot (low-profit	ile), two M.2 slots (one	
	Some: M.2 SSD / PCI	Cle NVMe,	, PCle 3.0 x 4*, 3	32Gb/s	No.0.0 - 0 - 100 -	6		for WLAN, one for M.	1.2 SSD), 2.5" HDL	D/SSD and PCIe car	rd are mutually exclusive	
	* 128GB SSD M.2 (2242) PCIe NVMe only supports PCIe 3.0 x 2, 16Gb/s Some: Intel Optane™ Memory (not support Celeron / Pentium Processor), M.2							i	Dimension	ns (WxDxH)	Weight (Approx.)	
Optical	Some: Intel Optane ¹ Some: DVD-ROM, slir	m (9.0mm	n), via USB exter	rnal OD	D box	∪1, 1VI.∠ 1		Tiny only	7.05" X 7.2	.20" X 1.36"	2.91 lb (1.32 kg),	
·	Some: DVD Burner (D	Some: DVD Burner (DVD±RW), slim (9.0mm), via USB external ODD box								.9mm X 34.5mm	vary by config	
	One onboard SATA 6.0						1	With VESA mount &		.30" X 2.48"	3.66 lb (1.66 kg),	
Graphics	Intel HD Graphics 610 DisplayPort™, one HDI	10/630 in A	processor, uses	main m	emory, DirectX [®]	12, one		ODD box	188.4mm X 18t	5.38mm X 63mm	vary by config	
	or USB 3.1 Type-C Ge	n1 with D	VisplayPort function	ion), up	to 3 independent	displays:		Optional VESA moun			nd 100mm	
	Max resolution: 4096x2304 (DP)@60Hz; 4096x2304 (Type-C)@60Hz;							Optional system floor				
	4096x2	4096x2160 (onboard HDMI)@24Hz; 2048x1536 (VGA)@50Hz Optional DP to VGA dongle, DP to DVI-D dongle, DP to dual DP dongle (for Collage						Some: 65 watts AC/I				
Monitor cable	Display with intel integrated graphics), or DP to HDMI 1.4 dongle						7	Some: 90 watts AC/I	DC adapter, autos	sensing, 88% PSU		
	Intel R360 Chineat							Some: 135 watts AC	1 /			
) one USB 3.1 Gen1 (Always On and fast charge), one USB 3.1 Type-C Gen 1,						Limited warranty	Some: 1-year or 3-year, depot service / service upgrades available Some: 1-year or 3-year, limited onsite service / service upgrades available				
	one microphone (3.5mm), one headphone / microphone combo jack (3.5mm)								-	SELVICE / SELVICE	- apgrauco avalidDIE	
Rear ports (Std.)	2x USB 3.1 Gen2, 2x l	USB 3.1 (Gen1, 1x etherne	net (RJ-4:	45), 1x DisplayPor	rt, 1x HDMI		Preloaded operating Some: Windows® 10				
Rear ports (Opt.)	Two optional ports (mu	Two optional ports (mutually exclusive with PCIe card): Port 1 for VGA / 2nd DP / 2nd HDMI / serial / USB 3.1 Type-C Gen 1 with DP function); Port 2 for serial;						Some: Windows 10	O Home 64-bit			
	2nd HDMI / serial / US Optional ports via PCI							Preloaded application	ions (only some I	listed)		
	PCle x1	, Jui U. Z	O.I Gelli		(S	, viu		Lenovo VantageMicrosoft Office pro	eloaded.			
Audio support	Realtek ALC233VB2 / optional internal speaker (1.5 watt or 2 watt)							purchase a produc	ct key to activate			
	Some: 11ac wireless, M.2 Card, Realtek RTL8821CE (dual band),							 Cyberlink PowerDVD (only for models with DVD / DVD±RW) 		RW)		
	Wi-Fi + Bluetooth 4.2 combo adapter, 1x1							Cyberlink Power26LinkedIn	Cyberlink Power2GO (only for models with DVD±RW) LinkedIn			
	Some: 11ac wireless, M.2 Card, Realtek RTL8822BE (dual band), Wi-Fi + Bluetooth 4.2 combo adapter, 2x2					i			\ EDEATIM COLD	ting (North America	// ErP L ot 2 TOO	
	Some: 11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 3165, Wi-Fi + Bluetooth 4.2 combo adapter, 1x1							ENERGY STAR® 7.0, EPEAT™ Gold rating (North America), ErP Lot 3, TCO, TUV ultra low noise verified (coming soon, on some models), RoHS-compliant				
							MIL-SPEC test	MIL-STD-810G milita	ary certification (Lo	ow Pressure [Altitude	de], High Temperature,	
		Some: 11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 8265, Wi-Fi + Bluetooth 4.2 combo adapter, 2x2						Low Temperature, Te	emperature Shock,	Humidity, Sand and	d Dust, Vibration, Shock,	
Bluetooth	Some: Bluetooth 4.2 v	oour 4.∠ C wireless. r	integrated in Wi-	Fi + BT	combo adapter	i		Fungus, Solar Radiation)				
Ethernet	Gigabit ethernet, Intel Ethernet Connection I219-LM(Jacksonville), Wake on LAN® Some: Intel Ethernet Server Adapter I350-T4, gigabit ethernet, 4x RJ-45, PCIe x4						Accessories	For compatible accessories, please go to http://smartfind.lenovo.com				
Ethernet (Opt.)	Some: Intel Ethernet &	Server Aa	napter I350-T4, g	nigabit e.	tnernet, 4x RJ-45	o, PCle x4						
Inte: The specifica	ations above may not be a	available i	n all regions								Lenovo July 2018	











