

FCC and ISED Test Report

Apple Inc
Model: A2737

In accordance with FCC 47 CFR Part 15E, ISED RSS-247 and ISED RSS-GEN (5 GHz WLAN)

Prepared for: Apple Inc
One Apple Park Way
Cupertino, California
95014, USA



Add value.
Inspire trust.

FCC ID: BCGA2737 IC: 579C-A2737

COMMERCIAL-IN-CONFIDENCE

Document 75954422-12 Issue 01

SIGNATURE

A handwritten signature of Simon Bennett.

NAME	JOB TITLE	RESPONSIBLE FOR	ISSUE DATE
Simon Bennett	Director of Test Operations	Authorised Signatory	30 September 2022

Signatures in this approval box have checked this document in line with the requirements of TÜV SÜD document control rules.

ENGINEERING STATEMENT

The measurements shown in this report were made in accordance with the procedures described on test pages. All reported testing was carried out on a sample equipment to demonstrate limited compliance with FCC 47 CFR Part 15E, ISED RSS-247 and ISED RSS-GEN. The sample tested was found to comply with the requirements defined in the applied rules.

RESPONSIBLE FOR	NAME	DATE	SIGNATURE
Report Generation	Lauren Walters	30 September 2022	A handwritten signature of Lauren Walters.

FCC Accreditation
90987 Octagon House, Fareham Test Laboratory ISED Accreditation
12669A Octagon House, Fareham Test Laboratory

EXECUTIVE SUMMARY

A sample of this product was tested and found to be compliant with FCC 47 CFR Part 15E: 2020, ISED RSS-247: Issue 2 (2017-02) and ISED RSS-GEN: Issue 5 (2018-04) + A2 (2021-02) for the tests detailed in section 1.3.

The ILAC-MRA logo features a circular emblem with concentric arcs and the text "ILAC-MRA".	The UKAS Testing logo features a circular emblem with a crown and the text "UKAS TESTING".	DISCLAIMER AND COPYRIGHT This non-binding report has been prepared by TÜV SÜD with all reasonable skill and care. The document is confidential to the potential Client and TÜV SÜD. No part of this document may be reproduced without the prior written approval of TÜV SÜD. © 2022 TÜV SÜD. This report relates only to the actual item/items tested.
ACCREDITATION Our UKAS Accreditation does not cover opinions and interpretations and any expressed are outside the scope of our UKAS Accreditation. Results of tests not covered by our UKAS Accreditation Schedule are marked NUA (Not UKAS Accredited).		

TÜV SÜD
is a trading name of TUV SUD Ltd
Registered in Scotland at East Kilbride,
Glasgow G75 0QF, United Kingdom
Registered number: SC215164

TUV SUD Ltd is a
TÜV SÜD Group Company

Phone: +44 (0) 1489 558100
Fax: +44 (0) 1489 558101
www.tuvsgd.com/en

TÜV SÜD
Octagon House
Concorde Way
Fareham
Hampshire PO15 5RL
United Kingdom



Contents

1	Report Summary	2
1.1	Report Modification Record.....	2
1.2	Introduction.....	2
1.3	Brief Summary of Results	3
1.4	Product Information	4
1.5	Deviations from the Standard.....	6
1.6	EUT Modification Record	6
1.7	Test Location.....	7
2	Test Details	9
2.1	Restricted Band Edges.....	9
2.2	Emission Bandwidth	58
2.3	Maximum Conducted Output Power	165
2.4	Maximum Conducted Power Spectral Density.....	239
2.5	Authorised Band Edges	314
2.6	Spurious Radiated Emissions	382
2.7	Channel Move Time, Channel Closing Transmission Time and Non-Occupancy Period	420
3	Measurement Uncertainty	431



1 Report Summary

1.1 Report Modification Record

Alterations and additions to this report will be issued to the holders of each copy in the form of a complete document.

Issue	Description of Change	Date of Issue
1	First Issue	30 September 2022

Table 1

1.2 Introduction

Applicant	Apple Inc
Manufacturer	Apple Inc
Model Number(s)	A2737
Serial Number(s)	MW5QG9Q771, DY36RV992R, QQRXMCWXL5 and XPMX940350
Hardware Version(s)	REV 1.0
Software Version(s)	20J43040n, 20J42560n & 20J8378
Number of Samples Tested	4
Test Specification/Issue/Date	FCC 47 CFR Part 15E: 2020 ISED RSS-247: Issue 2 (2017-02) ISED RSS-GEN: Issue 5 (2018-04) + A2 (2021-02)
Order Number	540246998
Start of Test	06-April-2022
Finish of Test	23-September-2022
Name of Engineer(s)	Colin Brain, Thomas Randall, Ian Hart, Mohammad Malik, Taha Shafique, Daniel Cameron and Stefan Gilfedder, Faisal Malyar, James Woods, Elliot Callender, Nicolae Mihailiuc and Danial Shafique
Related Document(s)	ANSI C63.10 (2013) ANSI C63.10 (2020) KDB 662911 D01 v02r01 FCC KDB 789033 D02 v02 KDB 905462 D02 v02



1.3 Brief Summary of Results

A brief summary of the tests carried out in accordance with FCC 47 CFR Part 15E, ISED RSS-247 and ISED RSS-GEN is shown below.

Section	Specification Clause			Test Description	Result	Comments/Base Standard
	Part 15E	RSS-247	RSS-GEN			
Configuration and Mode: 5 GHz WLAN						
-	15.203	-	-	Antenna Requirement	N/T	The device complies with the provisions of this section, as it uses permanently attached integral antennas.
2.1	15.205	-	8.10	Restricted Band Edges	Pass	
2.2	15.407 (a)	6.2	-	Emission Bandwidth	Pass	
2.3	15.407 (a)	6.2	-	Maximum Conducted Output Power	Pass	
2.4	15.407 (a)	6.2	-	Maximum Conducted Power Spectral Density	Pass	
2.5	15.407 (b)	6.2	-	Authorised Band Edges	Pass	
2.6	15.407 (b) and 15.209	6.2	6.13 and 8.9	Spurious Radiated Emissions	Pass	
2.7	15.407 (h)(2)(iii)(iv)	6.3.2(c)(d)(e)	-	Channel Move Time, Channel Closing Transmission Time and Non-Occupancy Period	Pass	
Configuration and Mode: 5 GHz WLAN - Client to Client						
2.7	15.407 (h)(2)(iii)(iv)	6.3.2(c)(d)(e)	-	Channel Move Time, Channel Closing Transmission Time and Non-Occupancy Period	Pass	

Table 2



1.4 Product Information

1.4.1 Technical Description

The equipment under test was an Apple TV Set Top Box with Bluetooth® and IEEE 802.11 a/b/g/n/ac/ax Wi-Fi capabilities in the 2.4GHz and 5GHz bands.

1.4.2 Test Modes

The EUT's 5 GHz 802.11 radio supported Single Input/Single Output (SISO) and 2x2 MIMO (Multiple Input/Multiple Output) modes. 802.11a supports 20 MHz bandwidth only. 802.11n supported 20 MHz and 40 MHz bandwidths and 802.11ac, and ax supported 20 MHz, 40 MHz and 80 MHz bandwidths.

802.11a mode supported SISO operation only. 802.11n, ac and ax supported SISO, Cyclic Delay Diversity (CDD) and Space Division Multiplexing (SDM) modes. The EUT supported 802.11ax Single User (SU) and Multi-User (MU-MIMO) with all Resource Unit (RU) sizes from 26 subcarriers, up to the maximum allowed, dependent on channel bandwidth other than in U-NII-2A and U-NII-2C where RU-26 is not supported.

The EUT uses different output powers per core dependent on how many cores are used. The EUT also uses different power tables for Cyclic Delay Diversity (CDD) and Space Division Multiplexing (SDM) modes. It uses the same conducted power across all cores in any given mode, but due to the different antenna gains the radiated powers per core differ.

US and CA country codes changed the power table used for U-NII band 1. Therefore U-NII-1 channels were tested using both power settings for each country's respective limits.

After preliminary investigations were performed to find worst-case operation, the EUT was tested in the following modes, unless otherwise specified.

SISO Modes (5 GHz Core 1 for U-NII-1 / 2C and 5 GHz Core 0 for U-NII-2A / 3):

- 802.11a – 12 Mbps
- 802.11n HT20 – MCS2
- 802.11n HT40 – MCS2
- 802.11ac VHT80 – MCS2x1
- 802.11ax HE20 SU – MCS2x1
- 802.11ax HE40 SU – MCS2x1
- 802.11ax HE80 SU – MCS2x1
- 802.11ax HE20 MU RU26/52/106 – MCS2x1

2x2 MIMO Modes (Core 0+1 for U-NII-1 / 2A / 2C / 3):

- 802.11n HT20 - CDD (MCS2) and SDM (MCS10)
- 802.11n HT40 - CDD (MCS2), SDM (MCS10)
- 802.11ac VHT80 – CDD (MCS2x1), SDM (MCS2x2)
- 802.11ax HE20 SU – CDD (MCS2x1) and SDM (MCS2x2)
- 802.11ax HE40 SU – CDD (MCS2x1) and SDM (MCS2x2)
- 802.11ax HE80 SU – CDD (MCS2x1) and SDM (MCS2x2)
- 802.11ax HE20 MU RU26/52/106 – CDD (MCS2x1) and SDM (MCS2x2)

*Note: The RU offset for bottom and middle channels were placed in the lowest position and on the top channel, the offset was placed in the upper most position.

Band Edge testing was performed for all modulation types and the worst cases reported.



Reduced output power is used on the narrower 802.11ax multi-user (MU) modes to meet PSD and Band Edge limits. Therefore, only single user (SU) modes are reported for output power tests since these are always worst-case. All SU modes are reported for PSD and applicable MU modes of RU sizes of 26 to 106 subcarriers.



1.4.3 Test Setup

For conducted tests the EUT antennas were disconnected and replaced with U.FL to SMA test cables to enable conducted testing on each core. The loss of these test cables were known and compensated for in any conducted measurements.

For all testing except DFS the EUT was put into a continuous transmit test mode with the chipset manufacturer's test commands via a script running in the EUTs terminal application. The EUT then transmitted the required type of packeted 802.11 data frames of fixed length, containing the standard headers and with pseudo-random data content, ensuring the measured signals were representative and contained all the symbols at the highest power control level.

The test setup used for DFS is described in the test result section of the present document.

1.4.4 Antenna Gain Table

Antenna Port	Frequency Range (MHz)	Peak Gain (dBi)	Conducted Cable Loss (dB)
Core 0	5150 to 5250	-0.19	1.00
	5250 to 5350	1.74	1.10
	5470 to 5725	2.30	1.20
	5725 to 5850	2.37	1.20
Core 1	5150 to 5250	0.58	1.00
	5250 to 5350	1.67	1.10
	5470 to 5725	2.65	1.20
	5725 to 5850	1.77	1.20

Table 3

1.5 Deviations from the Standard

No deviations from the applicable test standard were made during testing.

1.6 EUT Modification Record

The table below details modifications made to the EUT during the test programme.

The modifications incorporated during each test are recorded on the appropriate test pages.

Modification State	Description of Modification still fitted to EUT	Modification Fitted By	Date Modification Fitted
Model: A2737, Serial Number: MW5QG9Q771			
0	As supplied by the customer	Not Applicable	Not Applicable
Model: A2737, Serial Number: DY36RV992R			
0	As supplied by the customer	Not Applicable	Not Applicable
Model: A2737, Serial Number: QQRXMCWXL5			
0	As supplied by the customer	Not Applicable	Not Applicable
Model: A2737, Serial Number: XPMX940350			
0	As supplied by the customer	Not Applicable	Not Applicable

Table 4



1.7 Test Location

TÜV SÜD conducted the following tests at our Fareham Test Laboratory.

Test Name	Name of Engineer(s)	Accreditation
Configuration and Mode: 5 GHz WLAN		
Restricted Band Edges	Colin Brain, Thomas Randall, Ian Hart, Mohammad Malik and Taha Shafique	UKAS
Emission Bandwidth	Daniel Cameron	UKAS
Maximum Conducted Output Power	Daniel Cameron	UKAS
Maximum Conducted Power Spectral Density	Daniel Cameron	UKAS
Authorised Band Edges	Colin Brain, Thomas Randall, Ian Hart, Mohammad Malik, Taha Shafique	UKAS
Spurious Radiated Emissions	Faisal Malyar, Taha Shafique, Elliot Callender, Danial Shafique, Mohammad Malik, Colin Brain, Ian Hart, Thomas Randall	UKAS
Channel Move Time, Channel Closing Transmission Time and Non-Occupancy Period	Stefan Gilfedder	UKAS
Configuration and Mode: 5 GHz WLAN - Client to Client		
Channel Move Time, Channel Closing Transmission Time and Non-Occupancy Period	Stefan Gilfedder	UKAS

Table 5

Office Address:

TÜV SÜD
Octagon House
Concorde Way
Fareham
Hampshire
PO15 5RL
United Kingdom



TÜV SÜD conducted the following tests at our Concorde Park Test Laboratory.

Test Name	Name of Engineer(s)	Accreditation
Configuration and Mode: 5 GHz WLAN		
Spurious Radiated Emissions	Ian Hart, Mohammad Malik, Faisal Malyar, James Woods, Nicolae Mihailiuc, Colin Brain and Thomas Randall	UKAS

Table 6

Office Address:

TÜV SÜD
Concorde Park
Concorde Way
Fareham
Hampshire
PO15 5FG
United Kingdom



2 Test Details

2.1 Restricted Band Edges

2.1.1 Specification Reference

FCC 47 CFR Part 15E, Clause 15.205
ISED RSS-GEN, Clause 8.10

2.1.2 Equipment Under Test and Modification State

A2737, S/N: QQRXMCWXL5 - Modification State 0

2.1.3 Date of Test

06-April-2022 to 11-May-2022

2.1.4 Test Method

The test was performed in accordance with ANSI C63.10, clause 6.10.5.

Restricted Band Edge measurements were performed with the device operating in SISO and MIMO, across the various modes supported by the device.

The measurements displayed within this report have been limited to those modes which have been shown to be worst case.

Where duty cycle corrections were required for average results, these are included in the result tables but are not shown on the plots.

Further measurements are held on file by TÜV SÜD and are available if required.

2.1.5 Environmental Conditions

Ambient Temperature	21.2 - 24.1 °C
Relative Humidity	26.2 - 50.7 %



2.1.6 Test Results

5 GHz WLAN

20 MHz Bandwidth (SISO)

Mode	Data Rate/ MCS	Resource Size	Resource Index	TX Frequency (MHz)	Band Edge Frequency (MHz)	Peak Level (dB μ V/m)	Average Level (dB μ V/m)
802.11a, Core 1	12 Mbps	-	-	5180	5150	66.73	51.21
802.11n HT20, Core 1	MCS 4	-	-	5180	5150	67.34	51.29
802.11ax HE20, Core 1	MCS 2x1	SU	-	5180	5150	65.82	51.19
802.11ax HE20, Core 1	MCS 11x1	26	0	5180	5150	55.03	42.78
802.11a, Core 1	12 Mbps	-	-	5320	5350	67.95	51.38
802.11n HT20, Core 1	MCS 4	-	-	5320	5350	67.52	51.42
802.11ax HE20, Core 1	MCS 2x1	SU	-	5320	5350	65.51	51.36
802.11ax HE20, Core 1	MCS 11x1	52	40	5320	5350	58.60	46.12
802.11a, Core 1	54 Mbps	-	-	5500	5460	62.93	48.75
802.11n HT20, Core 1	MCS 7	-		5500	5460	66.93	48.98
802.11ax HE20, Core 1	MCS 11x1	SU	-	5500	5460	67.45	49.19
802.11ax HE20, Core 1	MCS 11x1	52	37	5500	5460	57.71	46.14

Table 7 - SISO Restricted Band Edge Results




Figure 1 - 802.11a, Core 1 - 5180 MHz, Band Edge Frequency 5150 MHz




Figure 2 - 802.11n HT20, Core 1 - 5180 MHz, Band Edge Frequency 5150 MHz




Figure 3 - 802.11ax HE20, Core 1, SU - 5180 MHz, Band Edge Frequency 5150 MHz




Figure 4 - 802.11ax HE20, Core 1, 26-0 - 5180 MHz, Band Edge Frequency 5150 MHz




Figure 5 - 802.11a, Core 1 - 5320 MHz, Band Edge Frequency 5350 MHz




Figure 6 - 802.11n HT20, Core 1 - 5320 MHz, Band Edge Frequency 5350 MHz




Figure 7 - 802.11ax HE20, Core 1, SU - 5320 MHz, Band Edge Frequency 5350 MHz




Figure 8 - 802.11ax HE20, Core 1, 52-40 - 5320 MHz, Band Edge Frequency 5350 MHz




Figure 9 - 802.11a, Core 1 - 5500 MHz, Band Edge Frequency 5460 MHz




Figure 10 - 802.11n HT20, Core 1 - 5500 MHz, Band Edge Frequency 5460 MHz




Figure 11 - 802.11ax HE20, Core 1, SU - 5500 MHz, Band Edge Frequency 5460 MHz





Figure 12 - 802.11ax HE20, Core 1, 52-37 - 5500 MHz, Band Edge Frequency 5460 MHz




20 MHz Bandwidth (2TX MIMO)

Mode	Modulation Coding Scheme	Resource size	Resource Index	Frequency (MHz)	Band Edge Frequency (MHz)	Peak Level (dB μ V/m)	Average Level (dB μ V/m)
802.11n HT20 CDD, Cores 0-1	MCS 2	-	-	5180	5150	65.25	51.49
802.11n HT20 SDM, Cores 0-1	MCS 12	-	-	5180	5150	66.44	51.45
802.11ax HE20 CDD Cores 0-1	MCS 4x1	SU	-	5180	5150	66.72	51.43
802.11ax HE20 CDD, Cores 0-1	MCS 11x1	26	0	5180	5150	57.55	44.72
802.11ax HE20 SDM, Cores 0-1	MCS 4x2	SU	-	5180	5150	66.43	51.20
802.11ax HE20 SDM, Cores 0-1	MCS 11x2	26	0	5180	5150	56.78	44.71
802.11n HT20 CDD, Cores 0-1	MCS 2	-	-	5320	5350	66.20	51.17
802.11n HT20 SDM, Cores 0-1	MCS 12	-	-	5320	5350	66.31	51.26
802.11ax HE20 CDD, Cores 0-1	MCS 11x1	SU	-	5320	5350	67.79	51.28
802.11ax HE20 CDD, Cores 0-1	MCS 11x1	52	40	5320	5350	58.83	46.19
802.11ax HE20 SDM, Cores 0-1	MCS 2x2	SU	-	5320	5350	64.22	51.32
802.11ax HE20 SDM, Cores 0-1	MCS 11x2	52	40	5320	5350	59.44	46.29
802.11n HT20 CDD, Cores 0-1	MCS 7	-	-	5500	5460	66.68	49.28
802.11n HT20 SDM, Cores 0-1	MCS 15	-	-	5500	5460	65.09	49.25
802.11ax HE20 CDD, Cores 0-1	MCS 4x1	SU	-	5500	5460	63.83	49.23
802.11ax HE20 CDD, Cores 0-1	MCS 11x1	52	37	5500	5460	58.03	45.98
802.11ax HE20 SDM, Cores 0-1	MCS 11x2	SU	-	5500	5460	65.18	48.90
802.11ax HE20 SDM, Cores 0-1	MCS 11x2	52	37	5500	5460	57.65	46.08


Table 8 - MIMO 2TX Restricted Band Edge Results




**Figure 13 - 802.11n HT20 CDD, Cores 0-1 - 5180 MHz
Band Edge Frequency 5150 MHz**




**Figure 14 - 802.11n HT20 SDM, Cores 0-1 - 5180 MHz
Band Edge Frequency 5150 MHz**




**Figure 15 - 802.11ax HE20 CDD, Cores 0-1 SU - 5180 MHz
Band Edge Frequency 5150 MHz**




**Figure 16 - 802.11ax HE20 CDD, Cores 0-1, 26-0 - 5180 MHz
Band Edge Frequency 5150 MHz**




**Figure 17 - 802.11ax HE20 SDM, Cores 0-1, SU - 5180 MHz
Band Edge Frequency 5150 MHz**




**Figure 18 - 802.11ax HE20 SDM, Cores 0-1, 26-0 - 5180 MHz
Band Edge Frequency 5150 MHz**




**Figure 19 - 802.11n HT20 CDD, Cores 0-1 - 5320 MHz
Band Edge Frequency 5350 MHz**




**Figure 20 - 802.11n HT20 SDM, Cores 0-1 - 5320 MHz
Band Edge Frequency 5350 MHz**




**Figure 21 - 802.11ax HE20 CDD, Cores 0-1, SU - 5320 MHz
Band Edge Frequency 5350 MHz**




**Figure 22 - 802.11ax HE20 CDD, Cores 0-1, 52-40 - 5320 MHz
Band Edge Frequency 5350 MHz**




**Figure 23 - 802.11ax HE20 SDM, Cores 0-1, SU - 5320 MHz
Band Edge Frequency 5350 MHz**




**Figure 24 - 802.11ax HE20 SDM, Cores 0-1, 52-40 - 5320 MHz
Band Edge Frequency 5350 MHz**




**Figure 25 - 802.11n HT20 CDD, Cores 0-1 - 5500 MHz
Band Edge Frequency 5460 MHz**




**Figure 26 - 802.11n HT20 SDM, Cores 0-1 - 5500 MHz
Band Edge Frequency 5460 MHz**




**Figure 27 - 802.11ax HE20 CDD, Cores 0-1, SU- 5500 MHz
Band Edge Frequency 5460 MHz**



**Figure 28 - 802.11ax HE20 CDD, Cores 0-1, 52-37 - 5500 MHz
Band Edge Frequency 5460 MHz**



**Figure 29 - 802.11ax HE20 SDM, Cores 0-1, SU- 5500 MHz
Band Edge Frequency 5460 MHz**




**Figure 30 - 802.11ax HE20 SDM, Cores 0-1, 52-37 - 5500 MHz
Band Edge Frequency 5460 MHz**




40 MHz Bandwidth (SISO)

Mode	Data Rate/ MCS	Resource Size	Resource Index	TX Frequency (MHz)	Band Edge Frequency (MHz)	Peak Level (dB μ V/m)	Average Level (dB μ V/m)
802.11n HT40, Core 1	MCS 4	-	-	5190	5150	67.87	51.21
802.11ax HE40, Core 1	MCS 2x1	SU	-	5190	5150	65.19	51.23
802.11ax HE40, Core 1	MCS 11x1	26	0	5190	5150	53.99	42.65
802.11n HT40, Core 1	MCS 4	-	-	5310	5350	67.60	51.45
802.11ax HE40, Core 1	MCS 2x1	SU	-	5310	5350	64.85	51.24
802.11ax HE40, Core 1	MCS 11x1	52	44	5310	5350	64.84	45.60
802.11n HT40, Core 1	MCS 7	-	-	5510	5460	67.90	51.28
802.11ax HE40, Core 1	MCS 2x1	SU	-	5510	5460	67.37	51.39
802.11ax HE40, Core 1	MCS 11x1	52	37	5510	5460	57.14	44.72


Table 9 - SISO Restricted Band Edge Results




**Figure 31 - 802.11n HT40, Core 1 - 5190 MHz
Band Edge Frequency 5150 MHz**




**Figure 32 - 802.11ax HE40, Core 1, SU - 5190 MHz
Band Edge Frequency 5150 MHz**




**Figure 33 - 802.11ax HE40, Core 1, 26-0 - 5190 MHz
Band Edge Frequency 5150 MHz**




**Figure 34 - 802.11n HT40, Core 1 - 5310 MHz
Band Edge Frequency 5350 MHz**




**Figure 35 - 802.11ax HE40, Core 1, SU - 5310 MHz
Band Edge Frequency 5350 MHz**




**Figure 36 - 802.11ax HE40, Core 1, 52-44 - 5310 MHz
Band Edge Frequency 5350 MHz**



**Figure 37 - 802.11n HT40, Core 1 - 5510 MHz
Band Edge Frequency 5460 MHz**



**Figure 38 - 802.11ax HE40, Core 1, SU - 5510 MHz
Band Edge Frequency 5460 MHz**




**Figure 39 - 802.11ax HE40, Core 1, 52-37- 5510 MHz
Band Edge Frequency 5460 MHz**




40 MHz Bandwidth (2TX MIMO)

Mode	Data Rate/ MCS	Resource Size	Resource Index	TX Frequency (MHz)	Band Edge Frequency (MHz)	Peak Level (dB μ V/m)	Average Level (dB μ V/m)
802.11n HT40 CDD, Cores 0-1	MCS 2	-	-	5190	5150	64.08	51.27
802.11n HT40 SDM, Cores 0-1	MCS 10	-	-	5190	5150	65.00	51.32
802.11ax HE40 CDD, Cores 0-1	MCS 2x1	SU	-	5190	5150	62.76	50.70
802.11ax HE40 CDD, Cores 0-1	MCS 11x1	26	0	5190	5150	54.90	43.44
802.11ax HE40 SDM, Cores 0-1	MCS11x2	SU	-	5190	5150	67.90	51.21
802.11ax HE40 SDM, Cores 0-1	MCS 11x2	26	0	5190	5150	55.41	43.59
802.11n HT40 CDD, Cores 0-1	MCS 2	-	-	5310	5350	64.00	51.03
802.11n HT40 SDM, Cores 0-1	MCS 10	-	-	5310	5350	65.33	51.45
802.11ax HE40 CDD, Cores 0-1	MCS 2x1	SU	-	5310	5350	63.81	51.36
802.11ax HE40 CDD, Cores 0-1	MCS 11x1	52	44	5310	5350	62.35	45.37
802.11ax HE40 SDM, Cores 0-1	MCS 2x2	SU	-	5310	5350	63.51	51.36
802.11ax HE40 SDM, Cores 0-1	MCS 11x2	52	44	5310	5350	63.83	45.67
802.11n HT40 CDD, Cores 0-1	MCS 2	-	-	5510	5460	66.33	51.27
802.11n HT40 SDM, Cores 0-1	MCS 15	-	-	5510	5460	68.29	51.39
802.11ax HE40 CDD, Cores 0-1	MCS 4x1	SU	-	5510	5460	67.91	51.28
802.11ax HE40 CDD, Cores 0-1	MCS 11x1	52	37	5510	5460	57.46	45.51
802.11ax HE40 SDM, Cores 0-1	MCS 11x2	SU	-	5510	5460	67.16	51.48
802.11ax HE40 SDM, Cores 0-1	MCS 11x2	52	37	5510	5460	56.83	45.20


Table 10 – MIMO 2TX Restricted Band Edge Results




**Figure 40 - 802.11n HT40 CDD Cores 0-1 - 5190 MHz
Band Edge Frequency 5150 MHz**




**Figure 41 - 802.11n HT40 SDM Cores 0-1 - 5190 MHz
Band Edge Frequency 5150 MHz**




**Figure 42 - 802.11ax HE40 CDD, Cores 0-1, SU - 5190 MHz
Band Edge Frequency 5150 MHz**




**Figure 43 - 802.11ax HE40 CDD, Cores 0-1, 26-0 - 5190 MHz
Band Edge Frequency 5150 MHz**




**Figure 44 802.11ax HE40 SDM, Cores 0-1, SU - 5190 MHz
Band Edge Frequency 5150 MHz**




**Figure 45 - 802.11ax HE40 SDM, Cores 0-1, 26-0 - 5190 MHz
Band Edge Frequency 5150 MHz**




**Figure 46 - 802.11n HT40 CDD, Cores 0-1 - 5310 MHz
Band Edge Frequency 5350 MHz**




**Figure 47 - 802.11n HT40 SDM, Cores 0-1 - 5310 MHz
Band Edge Frequency 5350 MHz**




**Figure 48 - 802.11ax HE40 CDD, Cores 0-1, SU - 5310 MHz
Band Edge Frequency 5350 MHz**




**Figure 49 - 802.11ax HE40 CDD, Cores 0-1, 52-44 - 5310 MHz
Band Edge Frequency 5350 MHz**




**Figure 50 - 802.11ax HE40 SDM, Cores 0-1, SU - 5310 MHz
Band Edge Frequency 5350 MHz**




**Figure 51 - 802.11ax HE40 SDM, Cores 0-1, 52-44 5310 MHz
Band Edge Frequency 5350 MHz**




**Figure 52 - 802.11n HT40 CDD, Cores 0-1 - 5510 MHz
Band Edge Frequency 5460 MHz**




**Figure 53 - 802.11n HT40 SDM, Cores 0-1 - 5510 MHz
Band Edge Frequency 5460 MHz**




**Figure 54 - 802.11ax HE40 CDD, Cores 0-1, SU - 5510 MHz
Band Edge Frequency 5460 MHz**



**Figure 55 - 802.11ax HE40 CDD, Cores 0-1, 52-37 - 5510 MHz
Band Edge Frequency 5460 MHz**



**Figure 56 - 802.11ax HE40 SDM, Cores 0-1, SU - 5510 MHz
Band Edge Frequency 5460 MHz**



**Figure 57 - 802.11ax HE40 SDM, Cores 0-1, 52-37 - 5510 MHz
Band Edge Frequency 5460 MHz**