

EAP620-HD

TP-LINK

WiFi hotspot 6

Frequency 2.4 and 5 GHz Wave 2.0

Support 802.11 ax/ac/n/g/b

Transmission speed up to 1800 Mbps

Antenna 2x2 of 4 and 5 dBi



TP-LINK

Dual Band 802.11ax/ac/b/g/n Wifi Access Point 2,4 and 5 GHz

Double band AX1800

Allows connections up to 574 Mbps in 2.4GHz and 1201 Mbps in 5GHz

MultiSSID

Orthogonal Multiuser Modulation OFDMA

PoE 802.3at

Manageable Omada

Temperature range from 0 to 40°C

Ceiling or wall mounting

Mounting kit and PoE power supply included

Specifications

Wireless standard	WiFi 6 - 802.11 ax/ac/n/g/g/b
Transmission speed	Up to 1800 Mbps
Frequencies	2.4GHz & 5GHz
Maximum power transmission	25 dBm
Integrated antenna	Internal antennas 2x 4 dBi and 2x 5 Omnidirectional dBi at 2.4 GHz and 5 GHz
Operating modes	Wireless Access Point, Repeater, Gateway, WISP
Security	WEP/WPA2/WPA3/SSID hidden/filtered by MAC and IP, Wireless isolation between clients
SSIDs	Up to 8 SSID in 2.4 GHz and 8 SSID in 5 GHz
Management	Omada
Interface	1 Port RJ45 Gigabit Ethernet 10/100/1000Mbps
Power	PoE 802.3at or passive PoE 24 VDC, 10.5 W
Operating temperature	0 °C ~ + 40 °C
Dimensions	243 (H) x 243 (W) x 64 (D) mm