

15. FCC MAXIMUM PERMISSIBLE EXPOSURE (MPE)

15.1 Standard Applicable

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

This is a Mobile device, the MPE is required.

According to §1.1310 and §2.1093 RF exposure is calculated.

Limits for Maximum Permissive Exposure (MPE)

Frequency Range	Electric Field	Magnetic Field	Power Density	Averaging Time
(MHz)	Strength (V/m)	Strength (A/m)	(mW/cm ²)	(minute)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-15000	1	/	1.0	30

F = frequency in MHz

* = Plane-wave equipment power density

Note:

Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

S=PG/4πR2

Where: S = Power density

P = Power input to antenna

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna

*Note: BT / WLAN 2.4G / WLAN 5G will transmit together.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the parameter of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



15.2 Maximum Permissible Exposure (MPE) Evaluation (Worst Case)

802.11n HT20 Main

СН	Frequency (MHz)	TOTAL POWER (dBm)	TOTAL POWER (mW)		REQUIRED LIMIT (dBm)		RESULT
36	5180	10.08	10.186		23.98		PASS
44	5220	10.06	10.139	23.98		PASS	
48	5240	10.04	10.093	23.98		PASS	
52	5260	10.06	10.139	23.98	or 11+10log(B) =	25.31	PASS
60	5300	10.09	10.209	23.98	or 11+10log(B) =	25.31	PASS
64	5320	9.95	9.886	23.98	or 11+10log(B) =	25.49	PASS
100	5500	9.87	9.705	23.98	or 11+10log(B) =	25.62	PASS
116	5580	10.07	10.162	23.98	or 11+10log(B) =	25.48	PASS
140	5700	9.81	9.572	23.98	or 11+10log(B) =	25.33	PASS
149	5745	10.01	10.023		30		PASS
157	5785	10.09	10.209	30		PASS	
165	5825	10.02	10.046	30 PA		PASS	

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms_and_conditions.htm</u> and, for elec-tronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms_e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is any term performed with any term performant is unauthorized alteration, forgery or falsification of the content or ap-nearcance at this document is unaverted to the fullest extent of the law. pearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號 SGS Taiwan Ltd.



MPE Prediction (802.11n_HT20 5150~5250)

Max. output power including tune-up tolerancel:	10.08	(dBm)		
Max. output power including tune-up tolerancel:	10.185914	(mW)		
Duty cycle:	86.19	(%)		
Maximum Pav :	8.7792392	(mW)		
Peak Antenna gain (Maximum):	2	(dBi)		
Peak Antenna gain (linear):	1.5848932	(numeric)		
Prediction distance:	20	(cm)		
Prediction frequency:	5180	(MHz)		
MPE limit for uncontrolled exposure at prediction	1	(mW/cm2)		
Power density at predication frequency at 20 (cm)	0.003	(mW/cm^2)		
Measurement Result				
The predicted power density level at 20 cm is 0.003 mW/cm2.				
This is below the uncontrolled exposure limit of 1 mW/cm2 at 5180MHz.				

MPE Prediction (802.11n_HT20 5250~5350)

Max. output power including tune-up tolerancel:	10.09	(dBm)		
Max. output power including tune-up tolerancel:	10.209395	(mW)		
Duty cycle:	86.19	(%)		
Maximum Pav :	8.7994774	(mW)		
Peak Antenna gain (Maximum):	2	(dBi)		
Peak Antenna gain (linear):	1.5848932	(numeric)		
Prediction distance:	20	(cm)		
Prediction frequency:	5300	(MHz)		
MPE limit for uncontrolled exposure at prediction	1	(mW/cm2)		
Power density at predication frequency at 20 (cm)	0.003	(mW/cm^2)		
Measurement Result				
The predicted power density level at 20 cm is 0.003 mW/cm2.				
This is below the uncontrolled exposure limit of 1 mW/cm2 at 5300MHz.				

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms_and_conditions.htm</u> and, for elec-tronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms_e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is any term performed except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law



MPE Prediction (802.11n_HT20 5470~5725)

Max. output power including tune-up tolerancel:	10.07	(dBm)		
Max. output power including tune-up tolerancel:	10.162487	(mW)		
Duty cycle:	86.19	(%)		
Maximum Pav :	8.7590475	(mW)		
Peak Antenna gain (Maximum):	2	(dBi)		
Peak Antenna gain (linear):	1.5848932	(numeric)		
Prediction distance:	20	(cm)		
Prediction frequency:	5580	(MHz)		
MPE limit for uncontrolled exposure at prediction	1	(mW/cm2)		
Power density at predication frequency at 20 (cm)	0.003	(mW/cm^2)		
Measurement Result				
The predicted power density level at 20 cm is 0.003 mW/cm2.				
This is below the uncontrolled exposure limit of 1 mW/cm2 at 5580MHz.				

MPE Prediction (802.11n_HT20 5725~5850)

Max. output power including tune-up tolerancel:	10.09	(dBm)		
Max. output power including tune-up tolerancel:	10.209395	(mW)		
Duty cycle:	86.19	(%)		
Maximum Pav :	8.7994774	(mW)		
Peak Antenna gain (Maximum):	2	(dBi)		
Peak Antenna gain (linear):	1.5848932	(numeric)		
Prediction distance:	20	(cm)		
Prediction frequency:	5785	(MHz)		
MPE limit for uncontrolled exposure at prediction	1	(mW/cm2)		
Power density at predication frequency at 20 (cm)	0.003	(mW/cm^2)		
Measurement Result				
The predicted power density level at 20 cm is 0.003 mW/cm2.				
This is below the uncontrolled exposure limit of 1 mW/cm2 at 5785MHz.				

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms_and_conditions.htm</u> and, for elec-tronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms_e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is any term performed except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law