



Build Summary

\$69,783
Estimated Net Price

S Series

SVL75-3

*** EQUIPMENT IN STANDARD MACHINE ***

FEATURES

Vertical Lift Path Loader Frame
Standard Front Quick Coupler, Float Standard
Hydraulic Quick Coupler Option
Loader Boom Lock
Open ROPS & Air Conditioned ROPS/FOPS
Cab Models
High Back, Adjustable, Vinyl, Suspension Seat
2" Retractable Seat Belt and 2-Piece Seat Bar
12V Electric Outlet
17.4 gpm Auxiliary Hydraulics standard, 29.3
gpm Option
Direct To Tank Return Line
Rigid Mounted Undercarriage, 4 Lower Track
Rollers
Rubber Tracks, 12.6" Standard, 15" Optional
Two Speed Travel System
Automatic Wet Disk Parking Brake
Kubota 4 Hydraulic Pump Load Sensing
System
2 Gear, 2 Variable Displacement Pumps
Hydraulic Joystick Controls
ISO Operating Pattern
Hand And Foot Throttle Controls
Electronic Travel Torque Management
Automatic Glow Plugs
Key Switch Stop/Start System
Self Bleed Fuel System
2 Front and 2 Rear Working Lights
Hour Meter, Engine Temperature and Fuel
Gauges and Warning Lights
Horn and Backup Alarm
Lockable Fuel Cap
Bolt On Grab Handles to enter machine

BASIC UNITS

SVL75-3, 12.6" Rubber Tracks,
Open ROPS/FOPS Cab
Mechanical Quick Coupler

ENGINE

V3307 Kubota CR-TE4, Tier 4 Diesel Engine
4 Cylinder, 4 Cycle, Turbo Charged
74.3 Gross HP @ 2400 rpm

DIMENSIONS

Cab Height 82.0"
Width (without attachment) 65.9"
Width with wide track option (without attachment)
68.3"
Length (without attachment) 109.0"
Length of Track on Ground 56.5"

OPERATIONAL DIMENSIONS

Operating Weight*, SVL75H, 12.6" Rubber Tracks,
Open ROPS/FOPS Cab, Mechanical Quick Coupler
9,039 lbs.
Rated Operating Capacity (@ 35% of Tipping Load)
2,300 lbs.
Rated Operating Capacity (ROC) @ 35% of Tipping
Load complies with ISO 14397-1 and SAE J 818 for
crawler loaders
Rated Operating Capacity (ROC) @ 50% of Tipping
Load 3,285 lbs.
Tipping Load 6,570 lbs.
Auxiliary Hydraulics Flow 17.4 gpm
Travel Speed (Low / High) 4.7 / 7.1 mph
Reach @ Maximum Height 41.7"
Height to Hinge Pin 119.1"
Ground Pressure 5.6 psi.
Traction Force 9,678 lbf.

* Includes operator's weight, 175 lbs.

STANDARD EQUIPMENT INCLUDED

SVL75-3 12.6" TRK/CNPY/MECH Q.A.

| | |
|------------------|----------|
| Base Model Price | \$67,618 |
|------------------|----------|

KUBOTA ADD-ONS

| | |
|------------------------------------------|------------|
| 68" HVY DUTY /LW PRF/LONG FLR/C EDGE PNF | AP-HD68LLC |
| \$2,165 | |

PRICING SUMMARY

| | |
|--------------------|------------------------|
| Base Model | \$67,618 |
| Kubota Add-Ons | + \$2,165 |
| Land Pride Add-Ons | + \$0 |
| Tax | See Dealer for Pricing |
| Freight | See Dealer for Pricing |
| KTAC PDI | See Dealer for Pricing |
| Labor | See Dealer for Pricing |
| Assembly | See Dealer for Pricing |
| Total MSRP | \$69,783 |

| | |
|---------------------|----------|
| Estimated Net Price | \$69,783 |
|---------------------|----------|

This List Price configuration program is for informational purposes only. Price on this sales quote is an estimate and is subject to being increased. Payment assumes the MSRP of your selected equipment and accessories, the length of term you have selected and any applicable special A.P.R. program. Not Included: *Taxes, shipping; handling, surcharges, assembly charges, destination, freight and/or delivery charges.