POWER	
AC adapter input	100-240V ~ 50/60Hz 0.4A
AC adapter output	12V = 1.2A

HARDWARE FEATURES	
Processor	Quad-core CPU
Interface	2 LAN/WAN Gigabit Ethernet Ports
Button	1 Reset button on the underside
External Power Supply	12 V/1.2 A
Dimensions	Φ4.7 in. x 1.5 in. (Φ120 mm x 38 mm)
Antenna	4 internal antennas per Deco unit
Bluetooth version	4.2 and above

<u> </u>	
WIRELESS FEATURES	
Wireless Standards	IEEE 802.11 ac/n/a 5 GHz, IEEE 802.11 b/g/n 2.4 GHz
Frequency	2.4 GHz and 5 GHz
Signal Rate	400 Mbps on 2.4 GHz 867 Mbps on 5 GHz
Transmit Power	FCC: <30 dBm CE: <20 dBm (2.4 GHz) <23 dBm (5 GHz)
Wireless Security	WPA-PSK/WPA2-PSK
Advanced Functions	 Router/ Access Point Mode Optional Ethernet Backhaul TP-Link Mesh Technology: MU-MIMO Auto Path Selection Self-Healing AP Steering Band Steering Beamforming

SOFTWARE FEATURES	
Quality of Service	WMM
IPv6	Support
WAN Type	Dynamic IP/Static IP/PPPoE
Management	Local Management, Remote Management
DHCP	Server, Client
Port Forwarding	Support
Access Control	Blacklist
Firewall Security	SPI Firewall

SOFTWARE FEATURES	
Protocols	Supports IPv4 and IPv6
Advanced Features	Homecare: Antivirus Parental Controls Quality of Service
Advanced Functions	Speedtest Monthly Usage Reports Auto FW Update Expand for more deco
Guest Network	2.4 GHz guest network * 1 5 GHz guest network * 1
Beamforming	Support
APP	Easy setup by Deco App

OTHERS	
Certification	CE, FCC, IC, NCC, BSMI, IDA, RCM, JPA, JRF, VCCI, KC, RoHS
Package Contents	 Deco M5 (3-pack): Deco units RJ45 Ethernet Cable Power Adapters Deco M5 (1-pack): Deco unit RJ45 Ethernet Cable Power Adapter
Smartphone/Tablet Requirements	iOS 9.0 or later Android 4.4 or later Bluetooth 4.0 or later
Environment	Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing