

## POWER

**AC adapter input** 100-240V ~ 50/60Hz 0.4A

**AC adapter output** 12V = 1.2A

## HARDWARE FEATURES

**Processor** Quad-core CPU

**Interface** 2 LAN/WAN Gigabit Ethernet Ports

**Button** 1 Reset button on the underside

**External Power Supply** 12 V/1.2 A

**Dimensions** Φ4.7 in. x 1.5 in. (Φ120 mm x 38 mm)

**Antenna** 4 internal antennas per Deco unit

**Bluetooth version** 4.2 and above

## WIRELESS FEATURES

**Wireless Standards** IEEE 802.11 ac/n/a 5 GHz, IEEE 802.11 b/g/n 2.4 GHz

**Frequency** 2.4 GHz and 5 GHz

**Signal Rate** 400 Mbps on 2.4 GHz  
867 Mbps on 5 GHz

**Transmit Power** FCC: <30 dBm  
CE: <20 dBm (2.4 GHz)  
<23 dBm (5 GHz)

**Wireless Security** WPA-PSK/WPA2-PSK

- Router/ Access Point Mode
- Optional Ethernet Backhaul
- TP-Link Mesh Technology:

MU-MIMO

**Advanced Functions** Auto Path Selection  
Self-Healing  
AP Steering  
Band Steering  
Beamforming

## SOFTWARE FEATURES

**Quality of Service** WMM

**IPv6** Support

**WAN Type** Dynamic IP/Static IP/PPPoE

**Management** Local Management, Remote Management

**DHCP** Server, Client

**Port Forwarding** Support

**Access Control** Blacklist

**Firewall Security** SPI Firewall

**Protocols** Supports IPv4 and IPv6

## SOFTWARE FEATURES

	Homecare:
<b>Advanced Features</b>	Antivirus
	Parental Controls
	Quality of Service
	Speedtest
<b>Advanced Functions</b>	Monthly Usage Reports
	Auto FW Update
	Expand for more deco
<b>Guest Network</b>	2.4 GHz guest network * 1
	5 GHz guest network * 1
<b>Beamforming</b>	Support
<b>APP</b>	Easy setup by Deco App

## OTHERS

<b>Certification</b>	CE, FCC, IC, NCC, BSMI, IDA, RCM, JPA, JRF, VCCI, KC, RoHS
	● Deco M5 (3-pack): 3 Deco units 1 RJ45 Ethernet Cable 3 Power Adapters
<b>Package Contents</b>	● Deco M5 (1-pack): 1 Deco unit 1 RJ45 Ethernet Cable 1 Power Adapter
<b>Smartphone/Tablet Requirements</b>	iOS 8.0 or later Android 4.3 or later Bluetooth 4.0 or later
<b>Environment</b>	Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing