Product	Description	Fixed/ Modular	Assembly Label Location	Minimum SW Requirement
7150 Series				
DCS-7150S-24-F	Arista 7150S, 24x10GbE (SFP+) switch, front-to-rear air, 2xAC, 2xC13-C14 cords	1RU	Rear between fans	4.16.6M
DCS-7150S-24-R	Arista 7150S, 24x10GbE (SFP+) switch, rear-to-front air, 2xAC, 2xC13-C14 cords	1RU	Rear between fans	4.16.6M
DCS-7150S-24#	Arista 7150S, 24x10GbE (SFP+) switch, 2xC13-C14 cords. Requires 2 PSU & 4 fans sold separately	1RU	Rear between fans	4.16.6M
DCS-7150S-24-CL#	Arista 7150S, 24x10GbE (SFP+), with clock, 2xC13-C14 cords. Requires 2 PSU & 4 fans sold separately	1RU	Rear between fans	4.16.6M
DCS-7150S-24-CLD#	Arista 7150S, 24x10GbE (SFP+), with SSD and clock, 2xC13-C14 cords. Requires 2 PSU & 4 fans sold separately	1RU	Rear between fans	4.16.6M
DCS-7150S-52-CL-F	Arista 7150S, 52x10GbE (SFP+) switch with clock, front-to-rear air, 2xAC, 2xC13-C14 cords	1RU	Rear between fans	4.16.6M
DCS-7150S-52-CL-R	Arista 7150S, 52x10GbE (SFP+) switch with clock, rear-to-front air, 2xAC, 2xC13-C14 cords	1RU	Rear between fans	4.16.6M
DCS-7150S-52-CL#	Arista 7150S, 52x10GbE (SFP+), with clock, 2xC13-C14 cords. Requires 2 PSU & 4 fans sold separately	1RU	Rear between fans	4.16.6M
DCS-7150S-52-CLD#	Arista 7150S, 52x10GbE (SFP+), with SSD and clock, 2xC13-C14 cords. Requires 2 PSU & 4 fans sold separately	1RU	Rear between fans	4.16.6M
DCS-7150S-64-CL-F	Arista 7150S, 48x10GbE (SFP+) & 4xQSFP+ switch with clock, front-to-rear air, 2xAC, 2xC13-C14 cords	1RU	Rear between fans	4.16.6M
DCS-7150S-64-CL-R	Arista 7150S, 48x10GbE (SFP+) & 4xQSFP+ switch with clock, rear-to-front air, 2xAC, 2xC13-C14 cords	1RU	Rear between fans	4.16.6M
DCS-7150S-64-CL#	Arista 7150S, 48x10GbE (SFP+), & 4xQSFP+ with clock, 2xC13-C14 cords. Requires 2 PSU & 4 fans sold separately	1RU	Rear between fans	4.16.6M
DCS-7150S-64-CLD#	Arista 7150S, 48x10GbE (SFP+), & 4xQSFP+ with SSD and clock, 2xC13-C14 cords. Requires 2 PSU & 4 fans sold separately	1RU	Rear between fans	4.16.6M
7050X Series				
DCS-7050QX-32-F	Arista 7050, 32xQSFP+ switch, front-to-rear air, 2xAC, 2xC13-C14 cords	1RU	Rear between fans	4.16.6M
DCS-7050QX-32-R	Arista 7050, 32xQSFP+ switch, rear-to-front air, 2xAC, 2xC13-C14 cords	1RU	Rear between fans	4.16.6M
DCS-7050QX-32#	Arista 7050, 32xQSFP+ switch, no fans, no psu, 2 x C13-C14 cords	1RU	Rear between fans	4.16.6M
DCS-7050QX-32S-F	Arista 7050X, 32xQSFP+ & 4xSFP+ switch, front-to- rear airflow and dual 460W AC power supplies	1RU	Rear between fans	4.16.6M

Product	Description	Fixed/ Modular	Assembly Label Location	Minimum SW Requirement
DCS-7050QX-32S-R	Arista 7050X, 32xQSFP+ & 4xSFP+ switch, rear-to-front airflow and dual 460W AC power supplies	1RU	Rear between fans	4.16.6M
DCS-7050QX-32S#	Arista 7050X, 32xQSFP+ & 4xSFP+ switch, no fans, no psu (requires fans and psu)	1RU	Rear between fans	4.16.6M
DCS-7050QX-32S-D#	Arista 7050X, 32xQSFP+ & 4xSFP+ switch, SSD, no fans, no psu (requires fans and psu)	1RU	Rear between fans	4.16.6M
DCS-7050SX-128-F	Arista 7050, 96x10GbE (SFP+) & 8xQSFP+ switch, front-to-rear air, 2xAC, 2xC13-C14 cords	2RU	Rear pull-out tab	4.16.6M
DCS-7050SX-128-R	Arista 7050, 96x10GbE (SFP+) & 8xQSFP+ switch, rear-to-front air, 2xAC, 2xC13-C14 cords	2RU	Rear pull-out tab	4.16.6M
DCS-7050SX-128#	Arista 7050, 96x10GbE (SFP+) & 8xQSFP+ switch, no fans, no psu, 2 x C13-C14 cords	2RU	Rear pull-out tab	4.16.6M
DCS-7050SX-128-D#	Arista 7050, 96x10GbE (SFP+) & 8xQSFP+ switch, SSD, no fans, no psu, 2 x C13-C14 cords	2RU	Rear pull-out tab	4.16.6M
DCS-7050SX-64-F	Arista 7050X, 48x10GbE (SFP+) & 4xQSFP+ switch, front-to-rear air, 2xAC, 2xC13-C14 cords	1RU	Rear between fans	4.16.6M
DCS-7050SX-64-R	Arista 7050X, 48x10GbE (SFP+) & 4xQSFP+ switch, rear-to-front air, 2xAC, 2xC13-C14 cords	1RU	Rear between fans	4.16.6M
DCS-7050SX-64#	Arista 7050X, 48x10GbE (SFP+) & 4xQSFP+ switch, 2xC13-C14 cords. Requires 2 PSU & 4 fans sold separately	1RU	Rear between fans	4.16.6M
DCS-7050SX-64-D#	Arista 7050X, 48x10GbE (SFP+) & 4xQSFP+ switch, SSD, 2xC13-C14 cords. Requires 2 PSU & 4 fans sold separately	1RU	Rear between fans	4.16.6M
DCS-7050SX-72-F	Arista 7050X, 48x10GbE (SFP+) & 6x40GbE (2xMXP) switch, front-to-rear air, 2xAC, 2xC13-C14 cords	1RU	Rear between fans	4.16.6M
DCS-7050SX-72-R	Arista 7050X, 48x10GbE (SFP+) & 6x40GbE (2xMXP) switch, rear-to-front air, 2xAC, 2xC13-C14 cords	1RU	Rear between fans	4.16.6M
DCS-7050SX-72#	Arista 7050X, 48x10GbE (SFP+) & 6x40GbE (2xMXP) switch, 2xC13-C14 cords. Requires 2 PSU & 4 fans sold separately	1RU	Rear between fans	4.16.6M
DCS-7050SX-72-D#	Arista 7050X, 48x10GbE (SFP+) & 6x40GbE (2xMXP) switch,SSD, 2xC13-C14 cords. Requires 2 PSU & 4 fans sold separately	1RU	Rear between fans	4.16.6M
DCS-7050SX-96-F	Arista 7050X, 48x10GbE (SFP+) & 12x40GbE (4xMXP) switch, front-to-rear air, 2xAC, 2xC13-C14 cords	1RU	Rear between fans	4.16.6M
DCS-7050SX-96-R	Arista 7050X, 48x10GbE (SFP+) & 12x40GbE (4xMXP) switch, rear-to-front air, 2xAC, 2xC13-C14 cords	1RU	Rear between fans	4.16.6M

Product	Description	Fixed/ Modular	Assembly Label Location	Minimum SW Requirement
DCS-7050SX-96#	Arista 7050X, 48x10GbE (SFP+) & 12x40GbE (4xMXP) switch, 2xC13-C14 cords. Requires 2 PSU & 4 fans sold separately	1RU	Rear between fans	4.16.6M
DCS-7050SX-96-D#	Arista 7050X, 48x10GbE (SFP+) & 12x40GbE (4xMXP) switch,SSD, 2xC13-C14 cords. Requires 2 PSU & 4 fans sold separately	1RU	Rear between fans	4.16.6M
DCS-7050TX-128-F	Arista 7050X, 96x10GbE (1/10GBASE-T) & 8xQSFP+ switch, front-to-rear air, 2xAC, 2xC13-C14 cords	2RU	Rear pull-out tab	4.16.6M
DCS-7050TX-128-R	Arista 7050X, 96x10GbE (1/10GBASE-T) & 8xQSFP+ switch, rear-to-front air, 2xAC, 2xC13-C14 cords	2RU	Rear pull-out tab	4.16.6M
DCS-7050TX-128#	Arista 7050X, 96x10GbE (1/10GBASE-T) & 8xQSFP+ switch, no fans, no psu (requires fan and psu sold separately)	2RU	Rear pull-out tab	4.16.6M
DCS-7050TX-128-D#	Arista 7050X, 96x10GbE (1/10GBASE-T) & 8xQSFP+ switch, SSD, no fans, no psu (requires fan and psu sold separately)	2RU	Rear pull-out tab	4.16.6M
DCS-7050TX-48-F	Arista 7050X, 32xRJ45 (1/10GBASE-T) & 4xQSFP+ switch, front-to-rear air, 2xAC, 2xC13-C14 cords	1RU	Rear between fans	4.16.6M
DCS-7050TX-48-R	Arista 7050X, 32xRJ45 (1/10GBASE-T) & 4xQSFP+ switch, rear-to-front air, 2xAC, 2xC13-C14 cords	1RU	Rear between fans	4.16.6M
DCS-7050TX-48#	Arista 7050X, 32xRJ45 (1/10GBASE-T) & 4xQSFP+ switch, 2xC13-C14 cords. Requires 2 PSU & 4 fans sold separately	1RU	Rear between fans	4.16.6M
DCS-7050TX-48-D#	Arista 7050X, 32xRJ45 (1/10GBASE-T) & 4xQSFP+ switch,SSD, 2xC13-C14 cords. Requires 2 PSU & 4 fans sold separately	1RU	Rear between fans	4.16.6M
DCS-7050TX-64-F	Arista 7050X, 48xRJ45 (1/10GBASE-T) & 4xQSFP+ switch, front-to-rear air, 2xAC, 2xC13-C14 cords	1RU	Rear between fans	4.16.6M
DCS-7050TX-64-R	Arista 7050X, 48xRJ45 (1/10GBASE-T) & 4xQSFP+ switch, rear-to-front air, 2xAC, 2xC13-C14 cords	1RU	Rear between fans	4.16.6M
DCS-7050TX-64#	Arista 7050X, 48xRJ45 (1/10GBASE-T) & 4xQSFP+ switch, 2xC13-C14 cords. Requires 2 PSU & 4 fans sold separately	1RU	Rear between fans	4.16.6M
DCS-7050TX-64-D#	Arista 7050X, 48xRJ45 (1/10GBASE-T) & 4xQSFP+ switch, SSD, 2xC13-C14 cords. Requires 2 PSU & 4 fans sold separately	1RU	Rear between fans	4.16.6M
DCS-7050TX-72-F	Arista 7050X, 48x10GbE (1/10GBASE-T) & 6x40GbE (2xMXP) switch, front-to-rear air, 2xAC, 2xC13-C14 cords	1RU	Rear between fans	4.16.6M
DCS-7050TX-72-R	Arista 7050X, 48x10GbE (1/10GBASE-T) & 6x40GbE (2xMXP) switch, rear-to-front air, 2xAC, 2xC13-C14 cords	1RU	Rear between fans	4.16.6M

Product	Description	Fixed/ Modular	Assembly Label Location	Minimum SW Requirement
DCS-7050TX-72#	Arista 7050X, 48x10GbE (1/10GBASE-T) & 6x40GbE (2xMXP) switch, no fans, no psu (requires fan and psu)	1RU	Rear between fans	4.16.6M
DCS-7050TX-72-D#	Arista 7050X, 48x10GbE (1/10GBASE-T) & 6x40GbE (2xMXP) switch, SSD, no fans, no psu (requires fan and psu)	1RU	Rear between fans	4.16.6M
DCS-7050TX-96-F	Arista 7050X, 48x10GbE (1/10GBASE-T) & 12x40GbE (4xMXP) switch, front-to-rear air, 2xAC, 2xC13-C14 cords	1RU	Rear between fans	4.16.6M
DCS-7050TX-96-R	Arista 7050X, 48x10GbE (1/10GBASE-T) & 12x40GbE (4xMXP) switch, rear-to-front air, 2xAC, 2xC13-C14 cords	1RU	Rear between fans	4.16.6M
DCS-7050TX-96#	Arista 7050X, 48x10GbE (1/10GBASE-T) & 12x40GbE (4xMXP) switch, no fans, no psu (requires fan and psu)	1RU	Rear between fans	4.16.6M
DCS-7050TX-96-D#	Arista 7050X, 48x10GbE (1/10GBASE-T) & 12x40GbE (4xMXP) switch, SSD, no fans, no psu (requires fan and psu)	1RU	Rear between fans	4.16.6M
DCS-7050SX-72Q-F	Arista 7050X, 48x10GbE (SFP+) & 6x40GbE QSFP+ switch, front-to-rear air, 2xAC, 2xC13-C14 cords	1RU	Rear between fans	4.16.6M
DCS-7050SX-72Q-R	Arista 7050X, 48x10GbE (SFP+) & 6x40GbE QSFP+ switch, rear-to-front air, 2xAC, 2xC13-C14 cords	1RU	Rear between fans	4.16.6M
DCS-7050SX-72Q#	Arista 7050X, 48x10GbE (SFP+) & 6x40GbE QSFP+ switch, no fans, no psu, 2 x C13-C14 cords	1RU	Rear between fans	4.16.6M
DCS-7050TX-72Q-F	Arista 7050X, 48xRJ45 (1/10GBASE-T) & 6x40GbE QSFP+ switch, front-to-rear air, 2xAC, 2xC13-C14 cords	1RU	Rear between fans	4.16.6M
DCS-7050TX-72Q-R	Arista 7050X, 48xRJ45 (1/10GBASE-T) & 6x40GbE QSFP+ switch, rear-to-front air, 2xAC, 2xC13-C14 cords	1RU	Rear between fans	4.16.6M
DCS-7050TX-72Q#	Arista 7050X, 48xRJ45 (1/10GBASE-T) & 6x40GbE QSFP+ switch, no fans, no psu, 2 x C13-C14 cords	1RU	Rear between fans	4.16.6M
DCS-7250QX-64-F	Arista 7250, 64xQSFP+ switch, front-to-rear air, 2xAC, 2xC13-C14 cords	2RU	Rear pull-out tab	4.16.6M
DCS-7250QX-64-R	Arista 7250, 64xQSFP+ switch, rear-to-front air, 2xAC, 2xC13-C14 cords	2RU	Rear pull-out tab	4.16.6M
DCS-7250QX-64#	Arista 7250, 64xQSFP+ switch, no fans, no psu, 2 x C13-C14 cords	2RU	Rear pull-out tab	4.16.6M
DCS-7250QX-64-D#	Arista 7250, 64xQSFP+ switch, SSD, no fans, no psu, 2 x C13-C14 cords	2RU	Rear pull-out tab	4.16.6M
7010 Series	•	•	-	
DCS-7010T-48-F	Arista 7010T, 48x RJ45 (100/1000), 4 x SFP+ (1/10GbE) switch, front to rear air, 2x AC, 2xC13-C14 cords	1RU	Rear	4.16.6M

Product	Description	Fixed/ Modular	Assembly Label Location	Minimum SW Requirement
DCS-7010T-48-R	Arista 7010T, 48x RJ45 (100/1000), 4 x SFP+ (1/10GbE) switch, rear to front air, 2x AC, 2xC13-C14 cords	1RU	Rear	4.16.6M
DCS-7010T-48-DC-F	Arista 7010T, 48x 10/100/1000 RJ45 & 4 x SFP+ (1/10GbE) switch, front to rear air, 2xDC PSU	1RU	Rear	4.16.6M
DCS-7010T-48-DC-R	Arista 7010T, 48x 10/100/1000 RJ45 & 4 x SFP+ (1/10GbE) switch, rear to front air, 2xDC PSU	1RU	Rear	4.16.6M
7060X Series				
DCS-7060CX-32S-F	Arista 7060X, 32x100GbE QSFP & 2xSFP+ switch, front-to-rear air, 2xAC, 2xC13-C14 cords	1RU	Rear between fans	4.16.6FX- 7060X
DCS-7060CX-32S-R	Arista 7060X, 32x100GbE QSFP & 2xSFP+ switch, rear-to-front air, 2xAC, 2xC13-C14 cords	1RU	Rear between fans	4.16.6FX- 7060X
DCS-7060CX-32S#	Arista 7060X, 32x100GbE QSFP & 2xSFP+ switch, configurable fans and psu, 2 x C13-C14 cords	1RU	Rear between fans	4.16.6FX- 7060X
DCS-7260CX-64-F	Arista 7260X, 64x100GbE QSFP & 2xSFP+ switch, front-to-rear air, 2xAC, 2xC19-C20 cords	2RU	Rear pull-out tab	4.16.6FX- 7060X
DCS-7260CX-64-R	Arista 7260X, 64x100GbE QSFP & 2xSFP+ switch, rear-to-front air, 2xAC, 2xC19-C20 cords	2RU	Rear pull-out tab	4.16.6FX- 7060X
DCS-7260CX-64#	Arista 7260X, 64x100GbE QSFP & 2xSFP+ switch, no fans, no psu, 2 x C19-C20 cords	2RU	Rear pull-out tab	4.16.6FX- 7060X
DCS-7260QX-64-F	Arista 7260X, 64x40GbE QSFP+ & 2xSFP+ switch, front-to-rear air, 2xAC, 2xC13-C14 cords	2RU	Rear pull-out tab	4.16.6FX- 7060X
DCS-7260QX-64-R	Arista 7260X, 64x40GbE QSFP+ & 2xSFP+ switch, rear-to-front air, 2xAC, 2xC13-C14 cords	2RU	Rear pull-out tab	4.16.6FX- 7060X
DCS-7260QX-64#	Arista 7260X, 64x40GbE QSFP+ & 2xSFP+ switch, no fans, no psu, 2 x C13-C14 cords	2RU	Rear pull-out tab	4.16.6FX- 7060X
7280E Series				
DCS-7280SE-64-F	Arista 7280E, 48x10GbE (SFP+) & 4x40GbE QSFP+ switch, front-to-rear air, 2x AC and 2xC13-C14 cords	1RU	Rear between fans	4.16.6M
DCS-7280SE-64-R	Arista 7280E, 48x10GbE (SFP+) & 4x40GbE QSFP+ switch, rear-to-front air, 2x AC and 2xC13-C14 cords	1RU	Rear between fans	4.16.6M
DCS-7280SE-64#	Arista 7280E, 48x10GbE (SFP+) & 4x40GbE QSFP+ switch, 2xC13-C14 cords. Requires 2 PSU and 4 fans sold separately	1RU	Rear between fans	4.16.6M
DCS-7280SE-68-F	Arista 7280E, 48x10GbE (SFP+) & 2x100GbE QSFP100 switch, front-to-rear air, 2x AC and 2xC13-C14 cords	1RU	Rear between fans	4.16.6M

Product	Description	Fixed/ Modular	Assembly Label Location	Minimum SW Requirement
DCS-7280SE-68-R	Arista 7280E, 48x10GbE (SFP+) & 2x100GbE QSFP100 switch, rear-to-front air, 2x AC and 2xC13-C14 cords	1RU	Rear between fans	4.16.6M
DCS-7280SE-68#	Arista 7280E, 48x10GbE (SFP+) & 2x100GbE QSFP100 switch, 2xC13-C14 cords. Requires 2 PSU and 4 fans sold separately	1RU	Rear between fans	4.16.6M
DCS-7280SE-72-F	Arista 7280E, 48x10GbE (SFP+) & 2x100GbE MXP switch, front-to-rear air, 2x AC and 2xC13-C14 cords	1RU	Rear between fans	4.16.6M
DCS-7280SE-72-R	Arista 7280E, 48x10GbE (SFP+) & 2x100GbE MXP switch, rear-to-front air, 2x AC and 2xC13-C14 cords	1RU	Rear between fans	4.16.6M
DCS-7280SE-72#	Arista 7280E, 48x10GbE (SFP+) & 2x100GbE MXP switch, 2xC13-C14 cords. Requires 2 PSU and 4 fans sold separately	1RU	Rear between fans	4.16.6M
7280R Series				
DCS-7280SR-48C6-F	Arista 7280R, 48x10GbE (SFP+) & 6x100GbE QSFP switch, front to rear air, 2x AC and 2xC13-C14 cords	1RU	Rear between fans	4.16.6FX- 7500R
DCS-7280SR-48C6-R	Arista 7280R, 48x10GbE (SFP+) & 6x100GbE QSFP switch, rear to front air, 2x AC and 2xC13-C14 cords	1RU	Rear between fans	4.16.6FX- 7500R
DCS-7280SR-48C6#	Arista 7280R, 48x10GbE (SFP+) & 6x100GbE QSFP switch, configurable fans and psu, 2xC13-C14 cords	1RU	Rear between fans	4.16.6FX- 7500R
DCS-7280TR-48C6-F	Arista 7280R, 48x10GbE RJ45 (1/10G) & 6x100GbE QSFP switch, front to rear air, 2x AC and 2xC13-C14 cords	1RU	Rear between fans	4.16.6FX- 7500R
DCS-7280TR-48C6-R	Arista 7280R, 48x10GbE RJ45 (1/10G) & 6x100GbE QSFP switch, rear to front air, 2x AC and 2xC13-C14 cords	1RU	Rear between fans	4.16.6FX- 7500R
DCS-7280TR-48C6#	Arista 7280R, 48x10GbE RJ45 (1/10G) & 6x100GbE QSFP switch, configurable fans and psu, 2xC13-C14 cords	1RU	Rear between fans	4.16.6FX- 7500R
DCS-7280CR-48-F	Arista 7280R, 48x100GbE QSFP and 8x40GbE QSFP+ switch, front to rear air, 2 x AC and 2 x C19-C20 cords	2RU	Rear pull-out tab	4.16.6FX- 7500R
DCS-7280CR-48#	Arista 7280R, 48x100GbE QSFP and 8x40GbE QSFP+ switch, configurable fans and psu, 2 x C19-C20 cords	2RU	Rear pull-out tab	4.16.6FX- 7500R
DCS-7280CR-48-D#	Arista 7280R, 48x100GbE QSFP and 8x40GbE QSFP+ switch, SSD, configurable fans and psu, 2 x C19-C20 cords	2RU	Rear pull-out tab	4.16.6FX- 7500R
DCS-7280QR-C36-F	Arista 7280R, 24x40GbE QSFP+ & 12x100GbE QSFP switch, front to rear air, 2x AC and 2xC13-C14 cords	1RU	Rear pull-out tab	4.16.6FX- 7500R

Product	Description	Fixed/ Modular	Assembly Label Location	Minimum SW Requirement
DCS-7280QR-C36-R	Arista 7280R, 24x40GbE QSFP+ & 12x100GbE QSFP switch, rear to front air, 2x AC and 2xC13-C14 cords	1RU	Rear pull-out tab	4.16.6FX- 7500R
DCS-7280QR-C36#	Arista 7280R, 24x40GbE QSFP+ & 12x100GbE QSFP switch, configurable fans and psu, 2xC13-C14 cords	1RU	Rear pull-out tab	4.16.6FX- 7500R
7300 Series				
DCS-7308-CH	Arista 7308 empty chassis, 2 supervisor slots, 8 linecard slots, 4 fabric module slots	Modular	Front	4.16.6M
DCS-7304-CH	Arista 7304 empty chassis, 2 supervisor slots, 4 linecard slots, 4 fabric module slots	Modular	Front	4.16.6M
DCS-7316-CH	Arista 7316 empty chassis, 2 supervisor slots, 16 linecard slots, 4 fabric module slots	Modular	Front	4.16.6M
DCS-7300-SUP	Supervisor module for 7300 Series chassis	Modular	Left side	4.16.6M
DCS-7300-SUP-D	Supervisor module for 7300 Series chassis, &SSD	Modular	Left side	4.16.6M
DCS-7300X-32Q-LC	Arista 7300X32-port 40GbE QSFP+linecard(spare)	Modular	Left Ejector	4.16.6M
DCS-7300X-64S-LC	Arista 7300X 48-port 10GbE SFP+ & 4 port 40GbE QSFP+linecard(spare)	Modular	Left Ejector	4.16.6M
DCS-7300X-64T-LC	Arista 7300X48-port RJ45 10GBASE-T & 4 port 40GbE QSFP+linecard(spare)	Modular	Left Ejector	4.16.6M
DCS-7304X-FM-F	Fabric-X (integrated fans) module for 7304 chassis, required for slots 1-4. Front-to-rear air	Modular	Ejector Lever	4.16.6M
DCS-7304X-FM-R	Fabric-X (integrated fans) module for 7304 chassis, required for slots 1-4. Front-to-rear air	Modular	Ejector Lever	4.16.6M
DCS-7308X-FM-F	Fabric-X (integrated fans) module for 7308 chassis, required for slots 1-4. Front-to-rear air	Modular	Ejector Lever	4.16.6M
DCS-7308X-FM-R	Fabric-X (integrated fans) module for 7308 chassis, required for slots 1-4. Rear-to-front air	Modular	Ejector Lever	4.16.6M
DCS-7316X-FM-F	Fabric-X (integrated fans) module for 7316 chassis, required for slots 1-4. Front-to-rear air	Modular	Ejector Lever	4.16.6M
DCS-7316X-FM-R	Fabric-X (integrated fans) module for 7316 chassis, required for slots 1-4. Rear-to-front air	Modular	Ejector Lever	4.16.6M
DCS-7320X-32C-LC	Arista 7320X-32C linecard for 7300X Series, 32 port 100GbE QSFP (Configurable)	Modular	Left Ejector	4.16.6FX- 7060X
DCS-7324X-FM-F	7320X Fabric (integrated fans) module for 7304 chassis, required for slots 1-4. Front-to-rear air	Modular	Front, bottom left corner	4.16.6FX- 7060X
DCS-7328X-FM-F	7320X Fabric (integrated fans) module for 7308 chassis, required for slots 1-4. Front-to-rear air	Modular	Front, bottom left corner	4.16.6FX- 7060X
7500 Series				
DCS-7500E-SUP	Supervisor module for 7500E series chassis	Modular	Left Ejector	4.16.6M
DCS-7504E-FM	Fabric-E (integrated fan) Module for 7504-E Chassis, required for fabric slots 1-6	Modular	Handle	4.16.6M
DCS-7508E-FM	Fabric-E (integrated fan) Module for 7508-E Chassis, required for fabric slots 1-6	Modular	Handle	4.16.6M
DCS-7500E-12CM-LC	12 x SR10 Embedded (MPO) wire-speed linecard for 7500E Series (Spare)	Modular	Left Ejector	4.16.6M

Product	Description	Fixed/ Modular	Assembly Label Location	Minimum SW Requirement
DCS-7500E-12CQ-LC	12 x 100GbE QSFP wire-speed linecard for 7500E Series (Spare)	Modular	Left Ejector	4.16.6M
DCS-7500E-36Q-LC	36 port 40GbE QSFP+ wire-speed linecard for 7500E Series (spare)	Modular	Left Ejector	4.16.6M
DCS-7500E-48S-LC	48 port 10GbE SFP+ wire-speed linecard for 7500E Series (spare)	Modular	Left Ejector	4.16.6M
DCS-7500E-48T-LC	48 port RJ45 10GBASE-T wire-speed linecard for 7500E Series (spare)	Modular	Left Ejector	4.16.6M
DCS-7500E-6C2-LC	6-port 100GbE CFP2 wire-speed linecard for 7500E Series	Modular	Left Ejector	4.16.6M
DCS-7500E-6CFPX-LC	6 x 100GbE DWDM Coherent CFP2 wire-speed linecard with MACSec encryption for 7500E Series (Spare)	Modular	Left Ejector	4.16.6M
DCS-7500E-72S-LC	48 port 10GbE SFP+ & 2 x SR10 Embedded (MPO) wire-speed linecard for 7500E Series (spare)	Modular	Left Ejector	4.16.6M
DCS-7504-CH	Arista 7504 empty chassis. 2 Supervisor slots, 8 Linecard slots, 6 Fabric Module slots	Modular	Front	4.16.6M
DCS-7508-CH	Arista 7508 switch empty chassis. 2 Supervisor slots, 8 Linecard slots, 6 Fabric Module slots	Modular	Front	4.16.6M
DCS-7504N-CH	Arista 7504N empty chassis, 2 Supervisor slots, 4 line card slots, 6 Fabric Module slots, AC or DC option	Modular	Front	4.16.6M
DCS-7508N-CH	Arista 7508N empty chassis, 2 Supervisor slots, 8 line card slots, 6 Fabric Module slots, AC or DC option	Modular	Front	4.16.6M
DCS-7504R-FM	7500R Series Fabric (integrated fan) Module for 7504 Chassis, required for fabric slots 1-6	Modular	Handle	4.16.6FX- 7500R
DCS-7508R-FM	7500R Series Fabric (integrated fan) Module for 7508 Chassis, required for fabric slots 1-6	Modular	Handle	4.16.6FX- 7500R
DCS-7500-SUP2	Supervisor-2 module for 7500 Series (spare)	Modular	Left Ejector	4.16.6FX- 7500R
DCS-7500R-36CQ-LC	7500R Series 36 port 100GbE QSFP100 wirespeed line card (spare)	Modular	Left Ejector	4.16.6FX- 7500R
DCS-7500R-36Q-LC	7500R Series 36 port 40GbE QSFP100 wirespeed line card (spare)	Modular	Left Ejector	4.16.6FX- 7500R
DCS-7500R-48S2CQ-LC	7500R Series 48 port 1/10GbE SFP+ and 2 port 100GbE QSFP wirespeed line card (spare)	Modular	Left Ejector	4.16.6FX- 7500R