

Exposure Calculation Report

Apple Inc. Model: A2615

In accordance with FCC CFR 47 Part 1.1310 and
Canada Safety Code 6

Prepared for: Apple Inc
One Apple Way, Cupertino
California, 95014, USA



Add value.
Inspire trust.

COMMERCIAL-IN-CONFIDENCE

FCC ID: BCGA2615

IC: 579C-A2615

Document 75952325-17 Issue: 01

SIGNATURE

A handwritten signature in blue ink that reads 'Russell'.

NAME	JOB TITLE	RESPONSIBLE FOR	ISSUE DATE
Matt Russell	Senior Engineer	Authorised Signatory	04 February 2022

Signatures in this approval box have checked this document in line with the requirements of TÜV SÜD document control rules.

EXECUTIVE SUMMARY

The calculation of exposure for this product was found to be compliant at a minimum distance of 20 cm with FCC CFR 47 Part 1.1310 and Canada safety Code 6 assuming continuous exposure of 6 minutes or more. If alternative antennas are used with greater gains, the distance must be recalculated.

DISCLAIMER AND COPYRIGHT

This non-binding report has been prepared by TÜV SÜD with all reasonable skill and care. The document is confidential to the potential Client and TÜV SÜD. No part of this document may be reproduced without the prior written approval of TÜV SÜD. © 2022 TÜV SÜD.

TÜV SÜD
is a trading name of TUV SUD Ltd
Registered in Scotland at East Kilbride,
Glasgow G75 0QF, United Kingdom
Registered number: SC215164

TUV SUD Ltd is a
TÜV SÜD Group Company

Phone: +44 (0) 1489 558100
Fax: +44 (0) 1489 558101
www.tuvsud.com/en

TÜV SÜD
Octagon House
Concorde Way
Fareham
Hampshire PO15 5RL
United Kingdom



Contents

1	Report Summary	2
1.1	Report Modification Record.....	2
1.2	Introduction.....	2
1.3	Brief Summary of Results	3
1.4	Product Information	4
2	Assessment Details	5
2.1	Assessment Method.....	5
2.2	Individual Antenna Port Exposure Results.....	6
2.3	Combined Antenna Port RF Exposure Results.....	7
2.4	Far Field Region Boundary Results	14
2.5	Uncertainty	14
Annex A	Regional Requirements.....	A.2



1 Report Summary

1.1 Report Modification Record

Alterations and additions to this report will be issued to the holders of each copy in the form of a complete document.

Issue	Description of Change	Date of Issue
1	First Issue	04 February 2022

Table 1

1.2 Introduction

Applicant	Apple Inc
Manufacturer	Apple Inc
Model Number(s)	A2615
Hardware Version(s)	Rev 1.0
Software Version(s)	21C23
Specification/Issue/Date	<ul style="list-style-type: none">• FCC 47 CFR Part 1.1310: 2021• ISED Canada: Health Canada Safety Code 6:2015
Order Number	0540220896
Date	20.05.21
Related Document(s)	<ul style="list-style-type: none">• FCC 47 CFR Part 1.1307: 2021• OET65:97 Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields• IEEE C95.3:2002 IEEE Recommended Practice for Measurements and Computations of Radio Frequency Electromagnetic Fields with Respect to Human Exposure to Such Fields, 100 kHz–300 GHz



1.3 Brief Summary of Results

The wireless device described within this report was compliant with the restrictions related to human exposure to electromagnetic fields for both general public and worker/occupational exposures at the minimum compliance distances calculated.

The calculations shown in this report were made in accordance with the procedures specified in the applied test specification(s).

1.3.1 Compliance Boundary

Regional Requirement	Configuration	Calculated minimum compliance boundary (m) (rounded up to nearest 0.1 m)	
		Worker/Occupational	General Public
FCC	5.0 GHz WLAN + 2.4GHz WLAN	0.2	0.2
FCC	5.0 GHz WLAN + Bluetooth	0.2	0.2
FCC	5.0 GHz WLAN + 2.4GHz WLAN + Bluetooth	0.2	0.2
CANADA	5.0 GHz WLAN + 2.4GHz WLAN	0.2	0.2
CANADA	5.0 GHz WLAN + Bluetooth	0.2	0.2
CANADA	5.0 GHz WLAN + 2.4GHz WLAN + Bluetooth	0.2	0.2

Table 2 – Compliance Boundary Calculation Results

Note: The calculated minimum compliance distances were less than that stated in Table 2, however the assessment method of RF exposure calculation described in Section 2 is applicable only to separation distances of 0.2 m or more, therefore a minimum separation distance of 0.2 m is required.



1.4 Product Information

1.4.1 Technical Description

The Equipment Under Test (EUT) was a desktop computer with Bluetooth, Bluetooth Low Energy and 802.11 a/b/g/n/ac/ax WLAN capabilities in the 2.4 GHz and 5 GHz bands.

1.4.2 Transmitter Description

The following radio access technologies and frequency bands are supported by the equipment under test.

Radio Access Technology	Antenna Port	Frequency Band (MHz)	Minimum Frequency (MHz)	Output Power (dBm)	Duty Cycle (%)
Bluetooth	1	2402-2480	2402.0	16.00	100.0
2.4GHz WLAN	1	2412-2472	2412.0	22.50	100.0
5.0GHz WLAN	1	5180-5825	5180.0	21.00	100.0

Table 3 – Transmitter Description

Note: Transmitter power includes upper bounds of uncertainty therefore maximum values are used in accordance with Section 2.5.

1.4.3 Antenna Description

The following antennas are supported by the equipment under test.

Antenna No	Radio Access Technology	Antenna Model	Gain (dBi)	Antenna length (cm)
1	Bluetooth/2.4GHz WLAN	WF1	2.2	6.82
1	5.0GHz WLAN	WF1	3.3	6.82
2	Bluetooth/2.4GHz WLAN	WF2	1.4	6.82
2	5.0GHz WLAN	WF2	0.14	6.82
3	Bluetooth	WF3	1.7	6.82

Table 4 – Antenna description

In the case of more than one type of antenna being supported by the equipment, the calculation is based on the maximum of the antenna gains. If other antennas can be used that have greater gains, the minimum separation distances will need to be recalculated.

Note: Antenna gain includes upper bounds of uncertainty therefore maximum values are used in accordance with Section 2.5.

1.4.4 Equipment Configuration

Scenario 1 - 5.0 GHz WLAN + 2.4GHz WLAN

Scenario 2 - 5.0 GHz WLAN + Bluetooth

Scenario 3 - 5.0 GHz WLAN + 2.4GHz WLAN + Bluetooth



2 Assessment Details

2.1 Assessment Method

The assessment method is by calculation of the power density S , electric field strength E , magnetic field strength H or magnetic flux density B .

The calculation uses the spherical model applicable under far field conditions.

$$S = E \times H = \frac{E^2}{\eta} = H^2 \times \eta = \frac{P \times G_i}{4 \times \pi \times r^2}$$

Where:

η - Impedance of free space (377 ohm in far field)

P – Average transmitter power W ($P_{av} = P_{max} \times \text{Duty Cycle}$)

G_i – Antenna gain ratio relative to isotropic

r – Separation distance m

The magnetic flux density is related to the magnetic field strength by a constant:

$$B = \mu_o \times H$$

Where:

μ_o – Permeability of free space $4 \times \pi \text{ E-7 H/m}$

This assessment assumes that exposure is continuous for 6 minutes or more in accordance with the averaging time required by the exposure standards at the stated minimum compliance boundary separation distance. Exposures of less than 6 minutes at other separation distances are not addressed by this report.

This assessment method of RF exposure is applicable to separation distances of 20 cm or more. Separation distances of less than 20 cm require a Specific Absorption Rate (SAR) assessment.

The far field region boundary depends on the frequency and wavelength and also on the antenna dimension. The boundary of the far field region is calculated below to demonstrate the validity of using the spherical model.

The result is compared to the limits in Annex A to determine compliance or to calculate the required compliance distance. The calculation is based on the lowest frequency in each band as the most onerous requirement as the limits increase with frequency for frequencies above 10-50 MHz (dependent on region).



2.2 Individual Antenna Port Exposure Results

2.2.1 Calculation of Compliance Distance

The frequencies shown in the tables below have been chosen based on the lowest possible frequency that the EUT can transmit. A full list of the regional requirements is shown in Annex A.

Regional Requirement	Antenna Port	RAT	Frequency (MHz)	Minimum Calculated Compliance Boundary (m) at Limit for:			
				S Power Density	E Field	H Field	B Field
FCC	1	Bluetooth	2402.0	0.0103	N/A	N/A	N/A
FCC	1	2.4GHz WLAN	2412.0	0.0217	N/A	N/A	N/A
FCC	1	5.0GHz WLAN	5180.0	0.0207	N/A	N/A	N/A
CANADA	1	Bluetooth	2402.0	0.0129	0.0129	0.0129	N/A
CANADA	1	2.4GHz WLAN	2412.0	0.0272	0.0272	0.0272	N/A
CANADA	1	5.0GHz WLAN	5180.0	0.0215	0.0215	0.0215	N/A

Table 5 – Calculation of Compliance Distance Worker/Occupational

The calculations show that the EUT complies with the worker/occupational exposure levels described in in the listed specifications in Annex A at the point of investigation, a minimum distance of 0.0272 m. However the assessment method of RF exposure calculation described in Section 2 is applicable only to separation distances of 0.2 m or more, therefore a minimum separation distance of 0.2 m is required.

Regional Requirement	Antenna Port	RAT	Frequency (MHz)	Minimum Calculated Compliance Boundary (m) at Limit for:			
				S Power Density	E Field	H Field	B Field
FCC	1	Bluetooth	2402.0	0.0229	N/A	N/A	N/A
FCC	1	2.4GHz WLAN	2412.0	0.0485	N/A	N/A	N/A
FCC	1	5.0GHz WLAN	5180.0	0.0463	N/A	N/A	N/A
CANADA	1	Bluetooth	2402.0	0.0313	0.0313	0.0313	N/A
CANADA	1	2.4GHz WLAN	2412.0	0.0662	0.0662	0.0662	N/A
CANADA	1	5.0GHz WLAN	5180.0	0.0487	0.0487	0.0487	N/A

Table 6 – Calculation of Compliance Distance General Public

The calculations show that the EUT complies with the general public exposure levels described in in the listed specifications in Annex A at the point of investigation, a minimum distance of 0.0662 m. However the assessment method of RF exposure calculation described in Section 2 is applicable only to separation distances of 0.2 m or more, therefore a minimum separation distance of 0.2 m is required.



The following table shows the regional requirements for the frequencies used in the RF exposure calculation. A full list of the requirements is shown in Annex A.

Regional Requirement	Frequency (MHz)	Worker/Occupational Limit				General Public Limit			
		S Power Density (W/m ²)	E Field (V/m)	H Field (A/m)	B Field (μT)	S Power Density (W/m ²)	E Field (V/m)	H Field (A/m)	B Field (μT)
FCC	2402	50.00	N/A	N/A	N/A	10.00	N/A	N/A	N/A
FCC	2412	50.00	N/A	N/A	N/A	10.00	N/A	N/A	N/A
FCC	5180	50.00	N/A	N/A	N/A	10.00	N/A	N/A	N/A
CANADA	2402	31.64	109.21	0.2897	N/A	5.35	44.91	0.1191	N/A
CANADA	2412	31.70	109.32	0.2900	N/A	5.37	44.97	0.1193	N/A
CANADA	5180	46.46	132.34	0.3511	N/A	9.05	58.40	0.1549	N/A

Table 7 – Limits

2.3 Combined Antenna Port RF Exposure Results

As the frequency of operation for each transmitter is not the same, in order to evaluate compliance with the limit which is dependent on frequency, the fractional exposure value is calculated: The calculated S power density is divided by the limit to get a fractional exposure value. The calculated E and H fields are divided by the limit and squared to get a fractional exposure value. The summation of the fractional RF exposure results for each transmitter provides the combined result. Any values less than one are compliant with the limit. The compliance boundary distance has been calculated to ensure the summation is ≤ 1 .

Calculations are made on an Excel spreadsheet and numbers may not add up exactly due to rounding.



2.3.1 Configuration 1 – 5.0 GHz WLAN + 2.4GHz WLAN

FCC OET 65 specifies the method of summation in clause; Multiple-Transmitter Sites and Complex Environments; with results as follows:

Antenna Port	RAT	Frequency (MHz)	Calculated RF exposure level at minimum compliance boundary of 0.0300 m as a fraction of the limit			
			S Power Density	E Field	H Field	B Field
			Summation for simultaneous exposure; value to be <1			
1	2.4GHz WLAN	2412.0	0.5219	N/A	N/A	N/A
1	5.0GHz WLAN	5180.0	0.4760	N/A	N/A	N/A
Summation			0.9979	N/A	N/A	N/A

Table 8 - FCC Worker/Occupational Combined Exposure

The calculations show that the EUT complies with the worker/occupational exposure levels described in in the listed specifications in Annex A at the point of investigation, a minimum distance of 0.0300 m. However the assessment method of RF exposure calculation described in Section 2 **Error! Reference source not found.** is applicable only to separation distances of 0.2 m or more, therefore a minimum separation distance of 0.2 m is required.

Antenna Port	RAT	Frequency (MHz)	Calculated RF exposure level at minimum compliance boundary of 0.0670 m as a fraction of the limit			
			S Power Density	E Field	H Field	B Field
			Summation for simultaneous exposure; value to be <1			
1	2.4GHz WLAN	2412.0	0.5229	N/A	N/A	N/A
1	5.0GHz WLAN	5180.0	0.4768	N/A	N/A	N/A
Summation			0.9997	N/A	N/A	N/A

Table 9 – FCC General Public Combined Exposure

The calculations show that the EUT complies with the general public exposure levels described in in the listed specifications in Annex A at the point of investigation, a minimum distance of 0.0670 m. However the assessment method of RF exposure calculation described in Section 2 **Error! Reference source not found.** is applicable only to separation distances of 0.2 m or more, therefore a minimum separation distance of 0.2 m is required.



CANADA Health Canada Safety Code 6 specifies the method of summation in clause 2.2.1 Note 6 with results as follows:

Antenna Port	RAT	Frequency (MHz)	Calculated RF exposure level at minimum compliance boundary of 0.0347 m as a fraction of the limit			
			S Power Density	E Field	H Field	B Field
			Summation for simultaneous exposure; value to be <1			
1	2.4GHz WLAN	2412.0	0.6152	0.6152	0.6152	N/A
1	5.0GHz WLAN	5180.0	0.3829	0.3829	0.3829	N/A
Summation			0.9981	0.9981	0.9981	N/A

Table 10 – CANADA Worker/Occupational Combined Exposure

The calculations show that the EUT complies with the worker/occupational exposure levels described in in the listed specifications in Annex A at the point of investigation, a minimum distance of 0.0347 m. However the assessment method of RF exposure calculation described in Section 2 is applicable only to separation distances of 0.2 m or more, therefore a minimum separation distance of 0.2 m is required.

Antenna Port	RAT	Frequency (MHz)	Calculated RF exposure level at minimum compliance boundary of 0.0821 m as a fraction of the limit			
			S Power Density	E Field	H Field	B Field
			Summation for simultaneous exposure; value to be <1			
1	2.4GHz WLAN	2412.0	0.6487	0.6488	0.6487	N/A
1	5.0GHz WLAN	5180.0	0.3509	0.3509	0.3509	N/A
Summation			0.9996	0.9997	0.9996	N/A

Table 11 – CANADA General Public Combined Exposure

The calculations show that the EUT complies with the general public exposure levels described in in the listed specifications in Annex A at the point of investigation, a minimum distance of 0.0821 m. However the assessment method of RF exposure calculation described in Section 2 is applicable only to separation distances of 0.2 m or more, therefore a minimum separation distance of 0.2 m is required.



2.3.2 Configuration 2 – 5.0 GHz WLAN + Bluetooth

FCC OET 65 specifies the method of summation in clause; Multiple-Transmitter Sites and Complex Environments; with results as follows:

Antenna Port	RAT	Frequency (MHz)	Calculated RF exposure level at minimum compliance boundary of 0.0231 m as a fraction of the limit			
			S Power Density	E Field	H Field	B Field
			Summation for simultaneous exposure; value to be <1			
1	Bluetooth	2402.0	0.1971	N/A	N/A	N/A
1	5.0GHz WLAN	5180.0	0.8028	N/A	N/A	N/A
Summation			0.9998	N/A	N/A	N/A

Table 12 - FCC Worker/Occupational Combined Exposure

The calculations show that the EUT complies with the worker/occupational exposure levels described in in the listed specifications in Annex A at the point of investigation, a minimum distance of 0.0231 m. However the assessment method of RF exposure calculation described in Section 2 is applicable only to separation distances of 0.2 m or more, therefore a minimum separation distance of 0.2 m is required.

Antenna Port	RAT	Frequency (MHz)	Calculated RF exposure level at minimum compliance boundary of 0.0517 m as a fraction of the limit			
			S Power Density	E Field	H Field	B Field
			Summation for simultaneous exposure; value to be <1			
1	Bluetooth	2402.0	0.1971	N/A	N/A	N/A
1	5.0GHz WLAN	5180.0	0.8029	N/A	N/A	N/A
Summation			1.0000	N/A	N/A	N/A

Table 13 – FCC General Public Combined Exposure

The calculations show that the EUT complies with the general public exposure levels described in in the listed specifications in Annex A at the point of investigation, a minimum distance of 0.0517 m. However the assessment method of RF exposure calculation described in Section 2 is applicable only to separation distances of 0.2 m or more, therefore a minimum separation distance of 0.2 m is required.



CANADA Health Canada Safety Code 6 specifies the method of summation in clause 2.2.1 Note 6 with results as follows:

Antenna Port	RAT	Frequency (MHz)	Calculated RF exposure level at minimum compliance boundary of 0.0251 m as a fraction of the limit			
			S Power Density	E Field	H Field	B Field
			Summation for simultaneous exposure; value to be <1			
1	Bluetooth	2402.0	0.2648	0.2648	0.2648	N/A
1	5.0GHz WLAN	5180.0	0.7347	0.7347	0.7347	N/A
Summation			0.9996	0.9995	0.9995	N/A

Table 14 – CANADA Worker/Occupational Combined Exposure

The calculations show that the EUT complies with the worker/occupational exposure levels described in in the listed specifications in Annex A at the point of investigation, a minimum distance of 0.0251 m. However the assessment method of RF exposure calculation described in Section 2 is applicable only to separation distances of 0.2 m or more, therefore a minimum separation distance of 0.2 m is required.

Antenna Port	RAT	Frequency (MHz)	Calculated RF exposure level at minimum compliance boundary of 0.0579 m as a fraction of the limit			
			S Power Density	E Field	H Field	B Field
			Summation for simultaneous exposure; value to be <1			
1	Bluetooth	2402.0	0.2931	0.2931	0.2931	N/A
1	5.0GHz WLAN	5180.0	0.7062	0.7063	0.7062	N/A
Summation			0.9993	0.9994	0.9993	N/A

Table 15 – CANADA General Public Combined Exposure

The calculations show that the EUT complies with the general public exposure levels described in in the listed specifications in Annex A at the point of investigation, a minimum distance of 0.0579 m. However the assessment method of RF exposure calculation described in Section 2 is applicable only to separation distances of 0.2 m or more, therefore a minimum separation distance of 0.2 m is required.



2.3.3 Configuration 3 – 5.0 GHz WLAN + 2.4GHz WLAN + Bluetooth

FCC OET 65 specifies the method of summation in clause; Multiple-Transmitter Sites and Complex Environments; with results as follows:

Antenna Port	RAT	Frequency (MHz)	Calculated RF exposure level at minimum compliance boundary of 0.0317 m as a fraction of the limit			
			S Power Density	E Field	H Field	B Field
			Summation for simultaneous exposure; value to be <1			
1	Bluetooth	2402.0	0.1046	N/A	N/A	N/A
1	2.4GHz WLAN	2412.0	0.4674	N/A	N/A	N/A
1	5.0GHz WLAN	5180.0	0.4263	N/A	N/A	N/A
Summation			0.9983	N/A	N/A	N/A

Table 16 - FCC Worker/Occupational Combined Exposure

The calculations show that the EUT complies with the worker/occupational exposure levels described in in the listed specifications in Annex A at the point of investigation, a minimum distance of 0.0317 m. However the assessment method of RF exposure calculation described in Section 2 is applicable only to separation distances of 0.2 m or more, therefore a minimum separation distance of 0.2 m is required.

Antenna Port	RAT	Frequency (MHz)	Calculated RF exposure level at minimum compliance boundary of 0.0708 m as a fraction of the limit			
			S Power Density	E Field	H Field	B Field
			Summation for simultaneous exposure; value to be <1			
1	Bluetooth	2402.0	0.1048	N/A	N/A	N/A
1	2.4GHz WLAN	2412.0	0.4680	N/A	N/A	N/A
1	5.0GHz WLAN	5180.0	0.4268	N/A	N/A	N/A
Summation			0.9996	N/A	N/A	N/A

Table 17 – FCC General Public Combined Exposure

The calculations show that the EUT complies with the general public exposure levels described in in the listed specifications in Annex A at the point of investigation, a minimum distance of 0.0708 m. However the assessment method of RF exposure calculation described in Section 2 is applicable only to separation distances of 0.2 m or more, therefore a minimum separation distance of 0.2 m is required.



CANADA Health Canada Safety Code 6 specifies the method of summation in clause 2.2.1 Note 6 with results as follows:

Antenna Port	RAT	Frequency (MHz)	Calculated RF exposure level at minimum compliance boundary of 0.0370 m as a fraction of the limit			
			S Power Density	E Field	H Field	B Field
			Summation for simultaneous exposure; value to be <1			
1	Bluetooth	2402.0	0.1214	0.1214	0.1214	N/A
1	2.4GHz WLAN	2412.0	0.5411	0.5411	0.5411	N/A
1	5.0GHz WLAN	5180.0	0.3368	0.3367	0.3368	N/A
Summation			0.9993	0.9992	0.9993	N/A

Table 18 – CANADA Worker/Occupational Combined Exposure

The calculations show that the EUT complies with the worker/occupational exposure levels described in the listed specifications in Annex A at the point of investigation, a minimum distance of 0.0370 m. However the assessment method of RF exposure calculation described in Section 2 is applicable only to separation distances of 0.2 m or more, therefore a minimum separation distance of 0.2 m is required.

Antenna Port	RAT	Frequency (MHz)	Calculated RF exposure level at minimum compliance boundary of 0.0879 m as a fraction of the limit			
			S Power Density	E Field	H Field	B Field
			Summation for simultaneous exposure; value to be <1			
1	Bluetooth	2402.0	0.1271	0.1271	0.1271	N/A
1	2.4GHz WLAN	2412.0	0.5662	0.5663	0.5662	N/A
1	5.0GHz WLAN	5180.0	0.3063	0.3063	0.3063	N/A
Summation			0.9996	0.9997	0.9996	N/A

Table 19 – CANADA General Public Combined Exposure

The calculations show that the EUT complies with the general public exposure levels described in the listed specifications in Annex A at the point of investigation, a minimum distance of 0.0879 m. However the assessment method of RF exposure calculation described in Section 2 is applicable only to separation distances of 0.2 m or more, therefore a minimum separation distance of 0.2 m is required.



2.4 Far Field Region Boundary Results

The far field region boundary calculation result is shown in Table 20:

Near Field / Far Field Boundary (Ref: FCC 1.1307(b)(3)(i)(C), Technical Guide for Interpretation and Compliance Assessment of Health Canada's Radiofrequency Exposure Guidelines 7.1)			
RAT Name	Frequency MHz	Reactive Near Field Boundary (Wave Impedance Dependent)	Far Field Boundary (Antennas on axis)
		$\lambda/2\pi$ (m)	$2D^2/\lambda$ (m)
Bluetooth	2402.0	0.0199	0.0745
2.4GHz WLAN	2412.0	0.0198	0.0748
5.0GHz WLAN	5180.0	0.0092	0.1606

Table 20 – Far Field Boundary (FCC, CANADA)

The table below shows the maximum calculated near field / far field region boundaries.

The compliance boundary of 0.2 m is in the far field region and therefore, the approach described in section 2.1 is valid.

Field Region	Reactive Near Field Region	Radiating Near Field Region	Far Field Region
Maximum Boundary	<0.0199 m	0.0199 m – 0.1606 m	> 0.1606 m
Validity of Regions	Spherical model potential under-estimate: SAR assessment required	Spherical model over-estimate and conservative	Spherical model valid
Compliance Boundary Location	N/A	N/A	0.2 m

Table 21 – Assessment Method Validity

2.5 Uncertainty

The basic computation formulas presented in section 2.1 are conservative formulas for the estimation of RF field strength or power density.

No uncertainty estimations are required when using these formulas but there is clear guidance on where and when these formulas are applicable. For the estimate of S, E or H to be conservative, the transmitter power P and antenna gain G_i values shall be the upper bounds of uncertainty therefore maximum values are used.

The spherical formula is valid under far field conditions which are established in section 2.4.



ANNEX A

REGIONAL REQUIREMENTS



Frequency Range (MHz)	Power Density (mW/cm ²) Note 1	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)
0 - 0.3	-	-	-
0.3 - 3	100	614	1.63
3 - 30	900/f ²	1842/f	4.89/f
30 - 300	1	61.4	0.163
300 - 1500	f/300	-	-
1500 - 100000	5	-	-

Table A.1 – FCC CFR 47 Pt.1.1310 Worker/Occupational Limits

Frequency Range (MHz)	Power Density (mW/cm ²) Note 1	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)
0 - 0.3	-	-	-
0.3 - 3	100	614	1.63
3 - 30	180/f ²	824/f	2.19/f
30 - 300	0.2	27.5	0.073
300 - 1500	f/1500	-	-
1500 - 100000	1	-	-

Table A.2 – FCC CFR 47 Pt.1.1310 General Public Limits

Note 1: The calculations and limits presented in this report for power density are in units of W/m². The conversion factor is; 1 mW/cm² = 10 W/m².

Frequency Range (MHz)	Power Density (W/m ²)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)
10 - 20	10	61.4	0.163
20 - 48	44.72/f ^{0.5}	129.8/f ^{0.25}	0.3444/f ^{0.25}
48 - 100	6.455	49.33	0.1309
100 - 6000	0.6455*f ^{0.5}	15.60*f ^{0.25}	0.04138*f ^{0.25}
6000 - 150000	50	137	0.364

Table A.3 – Health Canada Safety Code 6 Worker/Occupational Limits

Frequency Range (MHz)	Power Density (W/m ²)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)
10 - 20	2	27.46	0.0728
20 - 48	8.944/f ^{0.5}	58.07/f ^{0.25}	0.1540/f ^{0.25}
48 - 300	1.291	22.06	0.05852
300 - 6000	0.02619*f ^{0.6834}	3.142*f ^{0.3417}	0.008335*f ^{0.3417}
6000 - 15000	10	61.4	0.163

Table A.4 – Health Canada Safety Code 6 General Public Limits