



# Xitanium LED downlight and spotlight drivers

## Xitanium 32W/m 0.7A 46V SC 230V

Xitanium LED drivers are leading the way in terms of reliability

### Product data

General Information	
Lighting Technology	LED
Operating and Electrical	
Output Current Ripple (Max)	4 %
Output Current (Max)	700 mA
Open Circuit Voltage (DC) (Max)	60 V
Output Power (Max)	32.2 W
Output Power (Min)	21.7 W
Output Current (Min)	700 mA
Output Voltage (Max)	46 V
Output Voltage (Min)	31 V
System characteristics	
Central DC Operation	No
YellowDot ready	No
Temperature	
T-Case Lifetime (Max)	75 °C
T-Case Maximum (Max)	75 °C

Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Product Length	97 mm
Housing	Mini 97x43x30 2p2p
Overall length	97.2 mm
Overall width	43 mm
Overall height	30 mm
Dimensions (Height x Width x Depth)	30 x 43 x 97 mm
Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Isolation Classification	Class I and Class II
Approval Marks	CE marking CB Certificate ENEC certificate CCC certificate RCM compliance
Output Current Set Options	Preset Current
Protection class IEC	Safety class I/II
Product Data	
Order product name	Xitanium 32W/m 0.7A 46V SC 230V

Xitanium LED downlight and spotlight drivers

Full product name	Xitanium 32W/m 0.7A 46V SC 230V
Full product code	871869970223600
Order code	929002105106
Material Nr. (12NC)	929002105106
Numerator - Quantity Per Pack	1

EAN/UPC - Product/Case	8718699702236
Numerator - Packs per outer box	50
EAN/UPC - Case	8718699702243

