ThinkCentre M720 Tiny 10T700AXGE

Product

ThinkCentre M720 Tiny

Region

WE

Country/Region

Germany

Machine Type

10T7

TopSeller

TopSeller

Processor

Intel Core i3-9100T (4C / 4T, 3.1 / 3.7GHz, 6MB)

Chipset

Intel B360 Chipset

Graphics

Integrated Intel UHD Graphics 630

Memory

1x 4GB DDR4-2666

Storage

1x 256GB SSD 2.5" SATA6Gb/s Opal

Optane Memory

None

Optical

None

Speaker

1.5Wx1

Ethernet

Integrated 100/1000M

WLAN + Bluetooth

Intel 3165 11ac, 1x1 + BT4.2

Optional Rear Ports

None

Chassis Intrusion Switch

Chassis Intrusion Switch

Kensington Cable Lock

None

Adapter Cage

None

Toolless Chassis Screw

None

Dust Filter

None

VESA Mount

VESA Mount

Color

Black

Stand

None

Keyboard

USB Traditional Keyboard, German

Mouse

USB Calliope Mouse

Power Supply

65W 88% Adapter

TUV Low Noise

None

Monitor Cable

None

System Management

None

Operating System

None

Bundled Software

None

Base Warranty

3-year, Onsite

Bundled Service

None

End of Support

2025-08-02

Announce Date

2019-07-02

Recommended Services

Best

4Y Premier Support Upgrade from 3Y Onsite (5WS0T36207)

Rottor

3Y Premier Support Upgrade from 3Y Onsite (5WS0U26647)

Good

5Y Onsite upgrade from 3Y Onsite (5WS0D81042)

WWW.LENOVO.COM

Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area.

Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. Lenovo provides this publication "as is" without warranty of any kind, either express or implied, including the implied warranties of merchantability or fitness for a particular purpose.



https://psref.lenovo.com

Visit psref website for the latest version of Product Specifications Reference.
© Lenovo, 2019. All rights reserved.



ThinkCentre M720 Tiny Platform Specifications

							I				
Processor	Intel® Celeron®, Intel Pentium®, or 8th / 9th Gen Intel Core™ i3 / i5 / i7 / i9 Processor							None Discrete TRM 2.0. TCC Contified			
	Processor	Cores / Threads	Frequency Base/Max(GHz)	Cache	Memory Support (Up to)	Integrated Graphics	Security chip Security features	Discrete TPM 2.0, TCG Certified Security slot (in rear for optional Boot sequence control			
	Celeron G4900T	2/2	2.9G	2 MB	DDR4-2400	UHD 610		Kensington® MicroSaver® cable) • Boot without keyboard and m			yboard and mouse
	Pentium Gold G5400T	2/4	3.1G	4 MB	DDR4-2400	UHD 610		 Chassis intrusion switch Power-on password Individual USB port disableme Smart USB protection, allows 		ection allows keyboard/	
	Pentium Gold G5500T	2/4	3.2G	4 MB	DDR4-2400	UHD 630		Administrator passy	vord	mouse only. bloc	cks all storage devices
	Core i3-8100T	4/4	3.1G	6 MB	DDR4-2400	UHD 630	<u> </u>	Hard disk password	t		
	Core i3-8300T	4/4	3.2G	8 MB	DDR4-2400	UHD 630		Some: Lenovo Calliope Keyboard (USB connector), black			
	Core i5-8400T	6/6	1.7G / 3.3G	9 MB	DDR4-2666	UHD 630		Some: Lenovo Tradit	tional Keyboard (L	USB connector), bla	ick
	Core i5-8500T	6/6	2.1G / 3.5G	9 MB	DDR4-2666	UHD 630	Mouse	Some: Lenovo Calliope Wireless Keyboard (2.4GHz via USB receiver), black Some: Lenovo Calliope Mouse (USB connector), black Some: Lenovo Fingerprint Mouse (USB connector), Windows Hello support, black Some: Lenovo Calliope Wireless Mouse (2.4GHz via USB receiver), black			ואכע receiver), black
	Core i5-8600T	6/6	2.3G / 3.7G	9 MB	DDR4-2666	UHD 630					ows Hello support, black
	Core i7-8700T	6/12	2.4G / 4.0G	12 MB	DDR4-2666	UHD 630					3 receiver), black
	Core i3-9100T	4/4	3.1G / 3.7G	6 MB	DDR4-2400 DDR4-2400	UHD 630 UHD 630	Mechanical	Tiny (1L), black color	Tiny (1L), black color; metal case Toolless chassis open (need optional toolless chassis screw)		
	Core i3-9300T	6/6	3.2G / 3.8G 1.8G / 3.4G	8 MB 9 MB	DDR4-2400 DDR4-2666	UHD 630		 Toolless chassis op 			
	Core i5-9400T Core i5-9500T	6/6	1.8G / 3.4G 2.2G / 3.7G	9 MB	DDR4-2666 DDR4-2666	UHD 630	1	 Toolless HDD, SSD 	Toolless HDD, SSD, memory removal		
	Core i5-9600T	6/6	2.2G / 3.7G 2.3G / 3.9G	9 MB	DDR4-2666 DDR4-2666	UHD 630	1	 Optional dust filter one 2.5" bay for HDD 	/SSD one PCIe 3	3 0 x8 slot (low-profi	le) two M 2 slots (one
	Core i5-96001 Core i7-9700T	8/8	2.3G / 3.9G 2.0G / 4.3G	12 MB	DDR4-2666 DDR4-2666	UHD 630	1	one 2.5" bay for HDD/SSD, one PCIe 3.0 x8 slot (low-profile), two M for WLAN, one for M.2 SSD), 2.5" HDD/SSD and PCIe card are muti		rd are mutually exclusive	
	Core i9-9900T	8/16	2.1G / 4.4G	16 MB	DDR4-2666	UHD 630	1			ns (WxDxH)	Weight (Approx.)
Memory	32GB max, DDR4-266 dual-channel capable		·				1	Tiny only	7.05" X 7.	.20" X 1.36" .9mm X 34.5mm	2.91 lb (1.32 kg), vary by config
Storage	* System automaticall Some: Hard Drive / S	ATA 6.00	àb/s, 2.5", 5400 r	pm or 7		ry controller	r <u> </u> -	With VESA mount & ODD box		.30" X 2.48" 5.38mm X 63mm	3.66 lb (1.66 kg), vary by config
	Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Some: M.2 SSD / PCIe NVMe, PCIe 3.0 x 4*, 32Gb/s * 128GB SSD M.2 (2242) PCIe NVMe only supports PCIe 3.0 x 2, 16Gb/s Some: Intel Optane™ Memory (not support Celeron / Pentium Processor), M.2 Some: DVD-ROM, slim (9.0mm), via USB external ODD box Some: DVD Burner (DVD±RW), slim (9.0mm), via USB external ODD box One onboard SATA 6.0Gb/s connector						VESA mount Floor Stand	Optional VESA mount bracket kit, supports VESA 75mm and 100mm Optional system floor stand for vertical orientation			
Optical							Power supply	Some: 65 watts AC/DC adapter, autosensing, 88% PSU Some: 90 watts AC/DC adapter, autosensing, 88% PSU Some: 135 watts AC/DC adapter, autosensing, 88% PSU			
Onboard SATA											
Graphics	Intel HD Graphics 610/630 in processor, uses main memory, DirectX [®] 12, one DisplayPort™, one HDMI, one optional video port (2nd HDMI, VGA, 2nd DP, or USB 3.1 Type-C Gen1 with DisplayPort function), up to 3 independent displays; <i>Max resolution:</i> 4096x2304 (DP) @ 60Hz; 4096x2304 (Type-C) @ 60Hz;						Limited warranty	ty Some: 1-year or 3-year, depot service / service upgrades available Some: 1-year or 3-year, limited onsite service / service upgrades available			
							Preload	Preload Preloaded operating system Some: Windows® 10 Pro 64-bit			
						อรถผ _ื ว		Some: Windows 10			
Monitor cable	4096x2160 (onboard HDMI)@24Hz; 2048x1536 (VGA)@50Hz Optional DP to VGA dongle, DP to DVI-D dongle, DP to dual DP dongle (for Collage Display with intel integrated graphics), or DP to HDMI 1.4 dongle							Preloaded applications (only some listed) Lenovo Vantage			
Chipset	Intel B360 Chipset						1	Microsoft Office pre			
		lwave On	and fast charge) one l	ISB 3.1 Type C.C	†	 purchase a product key to activate Cyberlink PowerDVD (only for models with DVD / DVD±RW) 			RW)	
Rear ports* (Std.)	Front ports* (Std.) one USB 3.1 Gen1 (Always On and fast charge), one USB 3.1 Type-C Gen 1, one microphone (3.5mm), one headphone / microphone combo jack (3.5mm) Rear ports* (Std.) 2x USB 3.1 Gen2, 2x USB 3.1 Gen1, 1x ethernet (RJ-45), 1x DisplayPort, 1x HDMI							Cyberlink PowerDVD (only for models with DVD / DVD±RW) Cyberlink Power2GO (only for models with DVD±RW) LinkedIn			
Rear ports* (Opt.	r ports* (Opt.) Two optional ports (mutually exclusive with PCIe card): Port 1 for VGA / 2nd DP / 2nd HDMI / serial / USB 3.1 Type-C Gen 1 with DP function); Port 2 for serial; Optional ports via PCIe card: 2x USB 3.1 Gen1 via PCIe x1, 4x serial (9-pin) via PCIe x1 * Depending on many factors, actual data transfer speed may be lower than theoretical speed						Environment	ENERGY STAR® 7.0, EPEAT™ Gold rating (North America), ErP Lot 3, TCO, TUV ultra low noise verified (coming soon, on some models), RoHS-compliant			
							MIL-SPEC test	Low Temperature, Temperature Shock, Humidity, Sand and Dust, Vibration, Shock,			
Audio support		tek ALC233VB2 / optional internal speaker (1.5 watt or 2 watt)				1	Fungus, Solar Radiat	,			
WLAN	Some: 11ac wireless, M.2 Card, Realtek RTL8821CE (dual band), Wi-Fi + Bluetooth 4.2 combo adapter, 1x1						Accessories	For compatible accessories, please go to http://smartfind.lenovo.com			
	Some: 11ac wireless, Wi-Fi + Blueto	Some: 11ac wireless, M.2 Card, Realtek RTL8822BE (dual band), Wi-Fi + Bluetooth 4.2 combo adapter, 2x2									
	Some: 11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 3165, Wi-Fi + Bluetooth 4.2 combo adapter, 1x1 Some: 11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 8265, Wi-Fi + Bluetooth 4.2 combo adapter, 2x2 Some: Bluetooth 4.2 wireless, integrated in Wi-Fi + BT combo adapter Gigabit ethernet, Intel Ethernet Connection 1219-V (Jacksonville), Wake on LAN®										
Bluetooth Ethernet											
Ethernet (Opt.)	Some: Intel Ethernet S			jigabit e	thernet, 4x RJ-45	o, PCle x4					Longvo Jung 2010
Note: The enecified	P 1	91 1 1									











