ThinkStation P330 Tiny 30CF0037GE

Product

ThinkStation P330 Tiny

Region

WE

Country/Region

Germany

Machine Type

30CF

TopSeller

TopSeller

Processor

Intel Core i5-9500T 6C/6T/2.2GHz/9MB/35W/DDR4-2666

Integrated Graphics

Intel UHD Graphics 630

Discrete Graphics

1x NVIDIA Quadro P620 2GB

Monitor Cable

None

Chipset

Intel Q370

HDD Controller

Onboard Intel AHCI

Memory

1x 8GB SO-DIMM DDR4-2666 Non-ECC

Internal Disk Drive

None

M.2 SSD Drive

1x 256GB SSD M.2 PCIe NVMe Opal

Optane Memory

None

Optical

None

Ethernet

1x GbE RJ-45

WLAN + Bluetooth

None

Chassis Intrusion Switch

Chassis Intrusion Switch

Optional Rear Ports

None

Cable Lock

Cable Lock

Dust Filter

None

Adapter Cage

None

Toolless Chassis Screw

None

Mounting

None

Stand

None

Keyboard

USB Traditional Keyboard, Germany

Mouse

USB Calliope Mouse

Power Supply

135W 88% Adapter

TUV Low Noise

None

System Management

Intel vPro with AMT 12

Operating System

Windows 10 Pro 64, German

Bundled Software

None

Base Warranty

3-year, Onsite

Bundled Service

None

EAN/UPC

0194552104948

End of Support

2025-09-06

Announce Date

2019-08-06

Recommended Services

Best

3Y Premier Support Upgrade from 3Y Onsite (5WS0U26646)

Rette

4Y Premier Support Upgrade from 3Y Onsite (5WS0T36136)

Good

5Y Premier Support Upgrade from 3Y Onsite (5WS0T36135)

WWW.LENOVO.COM

Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area.

Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. Lenovo provides this publication "as is" without warranty of any kind, either express or implied, including the implied warranties of merchantability or fitness for a particular purpose.



https://psref.lenovo.com

Visit psref website for the latest version of Product Specifications Reference.
© Lenovo, 2020. All rights reserved.



ThinkStation P330 Tiny Platform Specifications - I of II

Components				P • • • • • • • • • • • • • • • • • • •			Components	Specification
Components	Specification 1L. Optional VESA mount bracket kit, supports VESA 75mm and 100mm.					00mm		One PCIe slot via specific riser card:
	Optional floor stand for vertical orientation.						Expansion slots	PCIe 3.0 x16 (negotiable link width x8) and low profile for discrete graphics
Form factor	Optional tool-less chassis open. Optional dust filter							card;
								PCIe 3.0 x4 and low profile for i350-T4 adapter and quad COM ports adapter
Dimensions	Height: 179 mm (7.0 in). Width: 36.5 mm (1.437 in). Depth: 182.9 mm (7.2 in)						Graphics	65W or 62W processor models supports processor graphics only.
Weight	Maximum configuration: 3.08 lb (1.4kg)							35W processor models come with processor graphics plus a discrete graphics
Recommended	Lenovo recommends ThinkVision P series monitors for best display performance							adapter Integrated Intel UHD Graphics 630. Works along with discrete graphics to
monitors	and productivity							support multi-display
	Supports one of the following:							One of the following discrete graphics cards on 35W processor models:
Processor	Processor Number	Cores	Threads	Base Frequency	Cache TDP Memory Types	Processor Graphics	Graphics - Discrete	Adapter Cores Memory Pow- Connectors
	Core i9-9900T	8	16	2.1GHz	16MB 35WDDR4-2666	Intel UHD Graphics 630	graphics card	er
	Core i7-9700T	8	8	2.0GHz	12MB 35WDDR4-2666	Intel UHD		Quadro P1000 640 4GB GDDR5 47W 4x miniDP
	Core i5-9600T	6	6	2.3GHz	9MB 35WDDR4-2666	Graphics 630 Intel UHD	Storage controllers	Integrated Intel SATA AHCI controller in chipset, 6Gbps SATA, one onboard SATA port for 2.5" HDD
						Graphics 630 Intel UHD	Internal storage bay	Up to one 2.5" HDD on models without discrete graphics card
	Core i5-9600	6	6	3.1GHz	9MB 65WDDR4-2666	Graphics 630	Disks	2.5" HDD supports up to 1TB, 6Gbps SATA, 7.2K or 5.4K
	Core i5-9500T	6	6	2.2GHz	9MB 35WDDR4-2666	Intel UHD Graphics 630	M.2 slot for SSD	Two onboard M.2 slots for M.2 SSD, one for M.2 2280 SSD, one for M.2 2280 or 2242 SSD
	Core i5-9500	6	6	3.0GHz	9MB 65WDDR4-2666	Intel UHD Graphics 630	M.2 SSD	M.2 2280 SSD supports up to 1TB each, PCle 3.0 x4, NVMe, optional Opal.
	Core i5-9400T	6	6	1.8GHz	9MB 35WDDR4-2666	Intel UHD Graphics 630		M.2 2242 SSD supports up to 128GB, PCIe 3.0 x2, NVMe Up to one 16GB Optane memory per system. Optane memory must work with
	Core i5-9400	6	6	2.9GHz	9MB 65WDDR4-2666	Intel UHD Graphics 630		a 2.5" HDD One dedicated M.2 2230 slot for optional Wi-Fi card, supports one of the
	Core i3-9320	4	4	3.7GHz	8MB 62WDDR4-2400	Intel UHD	M.2 slot for Wi-Fi and Bluetooth	following:
	Core i3-9300T	4	4	3.2GHz	8MB 35WDDR4-2400	Graphics 630 Intel UHD		Intel Wireless-AC 9560, 2x2, 2.4GHz/5GHz (160MHz channels), 802.11ac, Bluetooth 5, up to 1.73Gbps.
	Core i3-9300	4	4	3.7GHz	8MB 62WDDR4-2400	Graphics 630 Intel UHD		Intel Wireless-AC 8265, 2x2, 2.4GHz/5GHz, 802.11ac, Bluetooth 4.2, up to 867Mbps.
	Core i3-9100T	4	4	3.1GHz	6MB 35WDDR4-2400	Graphics 630 Intel UHD	Wi-Fi antenna	Note: Wi-Fi card, or specific functions of Wi-Fi- card may not be supported in some countries Optional Tiny 2.4GHz/5GHz SMA antenna kit
		4	4	3.6GHz	6MB 65WDDR4-2400	Graphics 630 Intel UHD	Optical	Optional one 9.0mm optical drive via optical drive kit, DVD-ROM or DVD±RW. VESA mount is required
	Core i3-9100					Graphics 630 Intel UHD	Media reader	None. Using USB adapter
	Core i7-8700T	6	12	2.4GHz	12MB 35WDDR4-2666	Graphics 630 Intel UHD	Security features Intel vPro	One onboard GbE port via integrated gigabit ethernet Intel i219LM, supports Wake-on-LAN. Optional Intel i350-T4 for 4x GbE ports, using PCIe slot
	Core i7-8700	6	12	3.2GHz	12MB 65WDDR4-2666	Graphics 630 Intel UHD		Power-on and admin password. Trusted Platform Module, TCG 2.0 compliant.
	Core i5-8600T	6	6	2.3GHz	9MB 35WDDR4-2666	Graphics 630		Chassis intrusion switch. Optional Kensington lock Supports vPro on models with the following processors: Core i7-8700T, Core
	Core i5-8600	6	6	3.1GHz	9MB 65WDDR4-2666	Intel UHD Graphics 630		i7-8700, Core i5-8600T, Core i5-8600, Core i5-8500T, Core i5-8500. vPro also requires Wireless-AC 9560 if Wi-Fi is needed
	Core i5-8500T	6	6	2.1GHz	9MB 35WDDR4-2666	Intel UHD Graphics 630	Systems	Intel Active Management Technology 12 on vPro models,
	Core i5-8500	6	6	3.0GHz	9MB 65WDDR4-2666	Intel UHD Graphics 630	management	Intel Standard Manageability on other models US models comes with 3-year limited onsite service with 9x5/NBD.
	Core i5-8400T	6	6	1.7GHz	9MB 35WDDR4-2666	Intel UHD Graphics 630	Base warranty	1 or 3-year limited onsite service with 9x5/NBD in EMEA or other GEOs
	Core i5-8400	6	6	2.8GHz	9MB 65WDDR4-2666	Intel UHD Graphics 630	HD Audio	Intel HD Audio interface with Realtek ALC233 Codec 1x USB 3.1 Gen 1 Type A (charging). 1x USB 3.1 Gen 1 Type-C. 1x Mic-in. 1x
	Core i3-8300T	4	4	3.2GHz	8MB 35WDDR4-2400	Intel UHD Graphics 630	Tront standard ports	Combo jack 2x USB 3.1 Gen 2 Type A. 2x USB 3.1 Gen 1 Type-A. 1x RJ-45. 1x DP.
	Core i3-8300	4	4	3.7GHz	8MB 62WDDR4-2400	Intel UHD Graphics 630	rtear staridard ports	1x HDMI
	Core i3-8100T	4	4	3.1GHz	6MB 35WDDR4-2400	Intel UHD Graphics 630		Up to two optional rear ports via punch out cable. Port 1 supports one of the following:
	Core i3-8100	4	4	3.6GHz	6MB 65WDDR4-2400	Intel UHD Graphics 630	Optional rear ports -	1x USB 3.1 Gen 1 Type-C, also supports DP function. 1x COM.
Chipset	Intel Q370 Chipset via punch out cable 1x VGA.							
Memory	2 DIMM sockets. DDR4-2666. SoDIMM. Non-ECC							1x HDMI.
Memory Capacity	64GB (2x 32GB)							Port 2 supports one COM
<u> </u>								

ThinkStation P330 Tiny Platform Specifications - II of II

Components	Specification
Optional rear ports - via PCIe adapter	Supports one of the following: 4x miniDP with Quadro P620 or P1000, 35W processor models only 2x USB 3.1 Gen 1. 4x RJ-45 GbE with Intel I350-T4. 4x COM Note: Punch out cable and PCIe adapter are mutually exclusive
Temperature	Operating: 50 °F to 95 °F (10 °C to 35 °C) Non operating (with package): -40 °F to 140 °F (-40 °C to 60 °C)
Altitude	Operating: -15.2 m (-50 ft) to 3048 m (10 000 ft). Storage: -15.2 m (-50 ft) to 10, 668 m (35 000 ft)
Humidity	Operating: 20%~80%, non-condensing Storage (with package): 20%~90%, non-condensing
MIL-SPEC	Certified
Environmental certification	RoHS-compliant. GREENGUARD. EPEAT Silver rating and ENERGY STAR 7 qualified
Power supply	Supports one 135W power adaper, 100V - 240V, 88% PSU
ISV certifications	Please visit www.thinkworkstations.com/isv-certifications/







