



Features and Benefits

Design

Touch control with SteelTouch™ Buttons for Easier Operation of the Oven

Performance

- 12 Specialized Cooking Modes Gourmet Cooking Made Easy
- . Custom Cooking Modes: Pizza, Pie, Warm and Proof
- Genuine European Convection for Even Baking Results on Multiple Racks
- Temperature Conversion for Convection Cooking
- Meat Probe Takes Guesswork out of Cooking
- Fast Preheat Reduces Preheat Time

Efficiency

EcoClean™ 2-Hour Self-Clean Cycle

Convenience


- Two Oven Lights to Better Monitor Cooking Progress
- Timer with Cook Time and Delay Start Function
- Extra Large Door Window for Easy Monitoring of Cooking Process
- Star-K certified. 100°-450° F

Capacity


- . Large Capactiy at 4.1 Cu Ft.
- Recessed 8 Pass Broil Element for Increased Capacity and Safety

Notes: All height, width and depth dimensions are shown in inches. *Please refer to installation instructions prior to making cutout. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details. Applicable product warranty can be foundin a ccompanying product literature or you may contact your account manager for further details.






measurements in inches (mm)




measurements in inches (mm)




Top View

* For single ovens installed into a wall cabinet, the junction box may be located above or beneath the unit within reach of the power cord.

measurements in inches (mm)





measurements in inches (mm)

Cooking method primary cavity	3rd element convection, Convection Bake, Convection Broil, Convection Roast, Conventional heat, Dough proving setting, Half width variable grill, Pizza setting, Sabbath function, Top heating, 1/3 bottom heat., warming
Cleaning system - primary cavity	Self Clean
	^
Interior Lights - primary cavity	2
Interior Lights - primary cavity Pull-out system	2
	Alarm, Off, On, timer
Pull-out system	_
Pull-out system Timer settings	Alarm, Off, On, timer
Pull-out system Timer settings	Alarm, Off, On, timer 3 x Oven racks /
Pull-out system Timer settings	Alarm, Off, On, timer 3 x Oven racks / upper, 1 x Temperature
Pull-out system Timer settings Included accessories	Alarm, Off, On, timer 3 x Oven racks / upper, 1 x Temperature probe /upper

Technical Specification

Microwave Wattages (W)
Drawer wattage (W)

(W)

Features

тостинови оросиновичения	
UPC code	825225907053
Product color	Stainless steel
Alternative colors available	
Energy source	Electric
Watts (W)	5000
Current (A)	30
Volts (V)	240/208
Frequency (Hz)	60
Approval certificates	CSA
Power Cord Length	50"
Plug type	fixed connection, no plug
Required cutout size (HxWxD) (in)	27" - 28 5/8" x
	25 1/2" x 23 1/2"
Product packaging dimensions (HxWxD) (in)	31 1/4" x 34" x 31 1/2"
Net weight (lbs)	174
Gross weight (lbs)	193

Notes: All height, width and depth dimensions are shown in inches. *Please refer to installation instructions prior to making cutout. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details. Applicable product warranty can be foundin a ccompanying product literature or you may contact your account manager for further details.

For more information on our entire line of products, go to boschappliances.com or call 1-800-944-2904.

Copyright ©2014 BSH Home Appliances Corporation. All rights reserved. Bosch is a registered trademark of Robert Bosch GmbH.