

# RF Exposure Report

**FCC ID: 2AXV6ACY2WH**

## RF Exposure Measurement

The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The gain of the antennas used in the product is extracted from the Antenna data sheets provided and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis Transmission formula is far field assumption, the calculated result of that is an over-prediction for near field power density. It is taken as worst case to specify the safety range.

## RF Exposure Limit

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of the human exposure to radio-frequency (RF) radiation as specified in 1.1307 (b)

| Frequency Range (MHz)                                 | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm <sup>2</sup> ) |
|---|-------------------------------|-------------------------------|-------------------------------------|
| Limits for Occupational / controlled Exposures        |                               |                               |                                     |
| 300 - 1500  | --                            | --                            | F/300                               |
| 1500 – 100000   | --                            | --                            | 5.0                                 |
| Limits for General population / Uncontrolled Exposure |                               |                               |                                     |
| 300 - 1500  | --                            | --                            | F/1500                              |
| 1500 – 100000   | --                            | --                            | 1.0                                 |

Limits for Maximum Permissible Exposure (MPE)

F= Frequency in MHz

## Friss Formula

Friss Transmission Formula:  $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

$G$  = gain of antenna in linear scale

$\pi$  = 3.1416

$R$  = Distance between observation point and the center of radiator in cm

If we know the maximum gain of the antenna and the total output power to the antenna, through calculation, we will know MPE value at distance 20cm.

## EUT Operation condition

EUT was enabled to transmit and receive at lowest, middle and highest channels.

## Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. Warning statement to the user for keeping at least 20cm or more separation distance from the antenna should be included in the User manual. So, this device is classified as Mobile device.

## 2.4G WIFI

|           |                            |
|-----------|----------------------------|
| Mode      | 802.11b/g/n20:2412-2462MHz |
| Detector  | AV                         |
| 802.11b   | 18.5±1dBm                  |
| 802.11g   | 21±1dBm                    |
| 802.11n20 | 21±1dBm                    |

**ANT Gain (G) :3dBi (gain of antenna in linear scale=1.995)**

| Protocol   | ANT Gain(gain of antenna in linear scale) | Channel Frequency (MHz) | Output Power to Antenna | Output Power to Antenna (mW) | Power Density (mW/cm <sup>2</sup> ) | Limit (mW/cm <sup>2</sup> ) |
|------------|---|-------------------------|-------------------------|------------------------------|-------------------------------------|-----------------------------|
| 802.11 b   | 1.995                                     | 2412                    | 19.5                    | 89.1251                      | 0.03539                             | 1                           |
| 802.11 g   | 1.995                                     | 2412                    | 22                      | 158.4893                     | 0.06294                             | 1                           |
| 802.11 n20 | 1.995                                     | 2412                    | 22                      | 158.4893                     | 0.06294                             | 1                           |
|            |   |                         |                         |                              |                                     |                             |

According to the maximum gain of the antenna and the total output power to the antenna, through calculation, we will know max MPE value 0.06294 at distance 20cm. This is less than the limit 1. So SAR testing is not required.