

# TEST REPORT

of

FCC Part 15 Subpart C §15.247  
IC RSS-247 Issue 2 and RSS-Gen Issue 5

FCC ID: 2ATQS-MKB420  
IC Certification: 27424-MKB420

Equipment Under Test : Mokibo Folio Keyboard Case

Model Name : MKB420

Variant Model Name(s) : Refer to the page 3

Applicant : Mokibo, Inc.

Manufacturer : Mokibo, Inc.

Date of Receipt : 2022.12.12

Date of Test(s) : 2022.12.13 ~ 2023.01.04

Date of Issue : 2023.01.04

In the configuration tested, the EUT complied with the standards specified above. This test report does not assure KOLAS accreditation.

- 1) The results of this test report are effective only to the items tested.
- 2) The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received.
- 3) This test report cannot be reproduced, except in full, without prior written permission of the Company.
- 4) The data marked ※ in this report was provided by the customer and may affect the validity of the test results.

We are responsible for all the information of this test report except for the data(※) provided by the customer.

Tested by:

  
Taek Kim

Technical  
Manager:

  
Jinhyoung Cho

**SGS Korea Co., Ltd. Gunpo Laboratory**



**SGS Korea Co., Ltd.**

4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807  
Tel. +82 31 428 5700 / Fax. +82 31 427 2370  
<http://www.sgsgroup.kr>

Report Number: F690501-RF-RTL003683

Page: 2 of 27

# INDEX

## Table of contents

1. General Information -----	3
2. Transmitter Radiated Spurious Emissions -----	8
3. Antenna Requirement -----	27

## 1. General Information

### 1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

- 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- Designation number: KR0150

All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx>.

Phone No. : +82 31 688 0901

Fax No. : +82 31 688 0921

### 1.2. Details of Applicant

Applicant : Mokibo, Inc.

Address : 303, 46, Dallaenae-ro, Sujeong-gu, Seongnam-si, Gyeonggi-do, South Korea, 13449

Contact Person : Cho, Eun-hyung

Phone No. : +82 10 3260 1213

### 1.3. Details of Manufacturer

Company : Same as applicant

Address : Same as applicant

### 1.4. Description of EUT

<b>Kind of Product</b>	Mokibo Folio Keyboard Case
<b>Model Name</b>	MKB420
<b>Variant Model Names</b>	MKB420-A11, MKB420-A12
<b>Serial Number</b>	Radiated: 003, 004
<b>Power Supply</b>	DC 3.7 V
<b>Frequency Range</b>	2 402 MHz ~ 2 480 MHz (Bluetooth Low Energy)
<b>Modulation Technique</b>	GFSK
<b>Number of Channels</b>	40 channels (Bluetooth Low Energy)
<b>Antenna Type</b>	SMD Antenna
<b>Antenna Gain*</b>	1.5 dBi
<b>H/W Version</b>	0.5
<b>S/W Version</b>	0.2.7
<b>FVIN</b>	N/A

## 1.5. Declaration by the Manufacturer

The Bluetooth version of the EUT is 5.1 and 37, 255 bytes of PHY 1M are supported.

## 1.6. Test Equipment List

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Interval	Cal. Due
Signal Generator	R&S	SMA100B	106887	Oct. 13, 2022	Annual	Oct. 13, 2023
Signal Generator	R&S	SMBV100A	255834	May 25, 2022	Annual	May 25, 2023
Spectrum Analyzer	Agilent	N9020A	MY53421758	Aug. 26, 2022	Annual	Aug. 26, 2023
High Pass Filter	Wainwright Instrument GmbH	WHKX3.0/18G-6SS	21	Jun. 09, 2022	Annual	Jun. 09, 2023
High Pass Filter	Wainwright Instrument GmbH	WHNX7.5/26.5G-6SS	15	May 31, 2022	Annual	May 31, 2023
Low Pass Filter	Mini-Circuits	NLP-1200+	V 8979400903-2	Feb. 10, 2022	Annual	Feb. 10, 2023
Preamplifier	H.P.	8447F	2944A03909	Aug. 04, 2022	Annual	Aug. 04, 2023
Signal Conditioning Unit	R&S	SCU-18	10117	Jun. 13, 2022	Annual	Jun. 13, 2023
Preamplifier	TESTEK	TK-PA1840H	130016	Jan. 10, 2022	Annual	Jan. 10, 2023
Loop Antenna	Schwarzbeck Mess-Elektronik	FMZB 1519	1519-039	Aug. 23, 2021	Biennial	Aug. 23, 2023
Bilog Antenna	Schwarzbeck Mess-Elektronik	VULB 9163	01126	Feb. 07, 2022	Annual	Feb. 07, 2023
Horn Antenna	R&S	HF906	100326	Feb. 18, 2022	Annual	Feb. 18, 2023
Horn Antenna	Schwarzbeck Mess-Elektronik	BBHA 9170	9170-540	Nov. 30, 2022	Annual	Nov. 30, 2023
EMI Test Receiver	R&S	ESU26	100109	Jan. 18, 2022	Annual	Jan. 18, 2023
Turn Table	Innco systems GmbH	DS 1200 S	N/A	N.C.R.	N/A	N.C.R.
Controller	Innco systems GmbH	CONTROLLER CO3000-4P	CO3000/963/383 30516/L	N.C.R.	N/A	N.C.R.
Antenna Mast	Innco systems GmbH	MA4640-XP-ET	MA4640/536/383 30516/L	N.C.R.	N/A	N.C.R.
Anechoic Chamber	SY Corporation	L x W x H (9.6 m x 6.4 m x 6.6 m)	N/A	N.C.R.	N/A	N.C.R.
Coaxial Cable	RFONE	MWX221-NMSNMS (4 m)	J1023142	Oct. 04, 2022	Semi-Annual	Apr. 04, 2023
Coaxial Cable	Qualwave Inc.	QA500-18-NN-10 (10 m)	22200114	Oct. 04, 2022	Semi-Annual	Apr. 04, 2023

## 1.7. Summary of Test Results

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part15 Subpart C, RSS-247 Issue 2, RSS-Gen Issue 5			
Section in FCC	Section in IC	Test Item(s)	Result
15.205(a) 15.209 15.247(d)	RSS-247 Issue 2 5.5 RSS-Gen Issue 5 8.9	Transmitter Radiated Spurious Emissions	Complied
15.247(a)(2)	RSS-247 Issue 2 5.2(a) RSS-Gen Issue 5 6.7	6 dB Bandwidth & 99 % Bandwidth	N/A <sup>1)</sup>
15.247(b)(3)	RSS-247 Issue 2 5.4(d)	Maximum Peak Conducted Output Power	N/A <sup>1)</sup>
15.247(e)	RSS-247 Issue 2 5.2(b)	Power Spectral Density	N/A <sup>1)</sup>
15.207	RSS-Gen Issue 5 8.8	AC Power Line Conducted Emission	N/A <sup>1)</sup>

### Note;

1) These test items have been tested in the approved model test report. As a case of adding variant models, Only the radiation test was performed.

- Model name : MKB420
- Test report Number : F690501-RF-RTL002347-3
- Issue date : 2022.08.30
- Test Laboratory : SGS Korea Co., Ltd.

## 1.8. Test Procedure(s)

The measurement procedures described in the American National Standard of Procedure for Compliance Testing of unlicensed Wireless Devices (ANSI C63.10-2013) and the guidance provided in KDB 558074 D01 15.247 Meas Guidance v05r02 were used in the measurement of the DUT.

## 1.9. Sample Calculation

Where relevant, the following sample calculation is provided:

### 1.9.1. Radiation Test

Field strength level (dB $\mu$ V/m) = Measured level (dB $\mu$ V) + Antenna factor (dB) + Cable loss (dB) - Amplifier gain (dB) + Duty factor (dB)

## 1.10. Information of software for test

- Using the software of nRF Connect (Version 3.6.1) to testing of EUT.

### 1.11. Test Report Revision

Revision	Report number	Date of Issue	Description
0	F690501-RF-RTL003683	2023.01.04	Initial

### 1.12. Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Parameter	Uncertainty	
Radiated Emission, 9 kHz to 30 MHz	H	3.40 dB
	V	3.40 dB
Radiated Emission, below 1 GHz	H	4.50 dB
	V	5.10 dB
Radiated Emission, above 1 GHz	H	3.70 dB
	V	3.90 dB

All measurement uncertainty values are shown with a coverage factor of  $k=2$  to indicate a 95 % level of confidence.

### 1.13. Conclusion of Worst-Case (Bluetooth 5.1)

Modulation	Mode	Frequency (MHz)	Packet length (Byte)	Peak Power (dBm)
GFSK	PHY 1M	2 402	37	<u>5.86</u>
			255	5.85

### 1.14. Description of Variant Models

Model Name	Description
MKB420	- Basic Model
MKB420-A11	- Exterior size changed to 11 inches.
MKB420-A12	- Exterior size changed to 12 inches.

#### Note;

All the test were performed with Variant models(MKB420-A11, MKB420-A12).

### 1.15. Duty Cycle of EUT


Regarding to KDB 558074 D01 15.247 Meas Guidance v05r02, 6, the maximum duty cycles of all modes were investigated and set the spectrum analyzer as below;  
 Set RBW ≥ OBW if possible; otherwise, set RBW to the largest available value. Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are > 50/T and the number of sweep points across duration T exceeds 100.

Duty Cycle (%)	Correction factor (dB)
61.90	2.08

#### Remark;

1. Duty Cycle (%) = (Tx on time / Tx on + off time) x 100
2. Correction Factor (dB) = 10 log (1 / Duty Cycle)

#### - Test plot




## 2. Transmitter Radiated Spurious Emissions.


### 2.1. Test Setup

#### 2.1.1. Transmitter Radiated Spurious Emissions

The diagram below shows the test setup that is utilized to make the measurements for emission from 9 kHz to 30 MHz emissions.




The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz Emissions.





The diagram below shows the test setup that is utilized to make the measurements for emission. The spurious emissions were investigated from 1 GHz to the 10<sup>th</sup> harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.



## 2.2. Limit

### 2.2.1. FCC

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emission which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to §15.209(a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ( $\mu\text{V/m}$ )	Measurement Distance (Meters)
0.009-0.490	2 400/F(kHz)	300
0.490-1.705	24 000/F(kHz)	30
1.705-30.0	30	30
30-88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3

\*\* Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§15.231 and 15.241.

### 2.2.2. IC

According to RSS-247 Issue 2, 5.5, in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

According to RSS-Gen Issue 5, 8.9, except where otherwise indicated in the applicable RSS, radiated emissions shall comply with the field strength limits shown in table 5 and table 6. Additionally, the level of any transmitter unwanted emission shall not exceed the level of the transmitter's fundamental emission.

**Table 5 – General Field Strength Limits at frequencies above 30 MHz**

Frequency (MHz)	Field Strength ( $\mu\text{V/m}$ at 3 m)
30-88	100
88-216	150
216-960	200
Above 960	500

**Table 6 – General Field Strength Limits at frequencies below 30 MHz**

Frequency	Magnetic Field Strength (H-Field) ( $\mu\text{A/m}$ )	Measurement Distance (meters)
9-490 kHz <sup>1</sup>	6.37/F (F in kHz)	300
490-1 705 kHz	63.7/F (F in kHz)	30
1.705-30 MHz	0.08	30

**Note<sup>1</sup>:** The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

## 2.3. Test Procedures

Radiated emissions from the EUT were measured according to the dictates in section 11.11 & 11.12 of ANSI C63.10-2013 and only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

### 2.3.1. Test Procedures for emission below 30 MHz

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. Then antenna is a loop antenna is fixed at one meter above the ground to determine the maximum value of the field strength. Both parallel and perpendicular of the antenna are set to make the measurement.
3. For each suspected emission, the EUT was arranged to its worst case and then the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test-receiver system was set to average or quasi peak detect function and Specified Bandwidth with Maximum Hold Mode.

### 2.3.2. Test Procedures for emission from above 30 MHz

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site below 1 GHz and 1.5 meters above the ground at a 3 meter anechoic chamber test site above 1 GHz. The table was rotated 360 degrees to determine the position of the highest radiation.
2. During performing radiated emission below 1 GHz, the EUT was set 3 meters away from the interference receiving antenna, which was mounted on the top of a variable-height antenna tower. During performing radiated emission above 1 GHz, the EUT was set 3 meter away from the interference-receiving antenna.
3. The antenna is a bi-log antenna, a horn antenna and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. For measurements below 1 GHz resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.
6. For measurements Above 1 GHz resolution bandwidth is set to 1 MHz, the video bandwidth is set to 3 MHz for peak measurements and as applicable for average measurements.

### 1. Unwanted Emissions into Non-Restricted Frequency Bands

- The Reference Level Measurement refer to section 11.11.2

Set analyzer center frequency to DTS channel center frequency, SPAN  $\geq 1.5$  times the DTS bandwidth, the RBW = 100 kHz and VBW  $\geq 3 \times$  RBW, Detector = Peak, Sweep time = Auto couple, Trace = Max hold.

- Unwanted Emissions Level Measurement refer to section 11.11.3

Set the center frequency and span to encompass frequency range to be measured, the RBW = 100 kHz and VBW  $\geq 3 \times$  RBW, Detector = Peak, Sweep time = Auto couple, Trace = Max hold.

### 2. Unwanted Emissions into Restricted Frequency Bands

- Peak Power measurement procedure refer to section 11.12.2.4

Set RBW = as specified in Table 9, VBW  $\geq 3 \times$  RBW, Detector = Peak, Sweep time = auto, Trace = Max hold.

**Table 9 – RBW as a function of frequency**

Frequency	RBW
9 kHz to 150 kHz	200 Hz to 300 Hz
0.15 MHz to 30 MHz	9 kHz to 10 kHz
30 MHz to 1 000 MHz	100 kHz to 120 kHz
> 1 000 MHz	1 MHz

If the peak – detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

- Average Power measurements procedure refer to section 11.12.2.5.2

The EUT shall be configured to operate at the maximum achievable duty cycle.

Measure the duty cycle D of the transmitter output signal as described in section 11.6.

Set RBW = 1 MHz, VBW  $\geq 3 \times$  RBW, Detector = RMS, if span / (# of points in sweep)  $\leq (RBW/2)$ .

Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied then the detector mode shall be set to peak.

Averaging type = power (i.e., RMS).

As an alternative the detector and averaging type may be set for linear voltage averaging.

Some instruments require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used. Sweep time = auto, Perform a trace average of at least 100 traces.

A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:

- 1) If power averaging (rms) mode was used in step f), then the applicable correction factor is  $[10 \log (1 / D)]$ , where D is the duty cycle.

### 3. Definition of DUT Axis.

The test orthogonal plan of EUT was investigated with three axis described in the test setup photo.

The X-axis was worst-case, all radiated testing of EUT was performed with **X-axis**.

## 2.4. Test Results

Ambient temperature : (23 ± 1) °C  
Relative humidity : 47 % R.H.

### 2.4.1. Radiated Spurious Emission below 1 000 MHz

The frequency spectrum from 9 MHz to 1 000 MHz was investigated. All reading values are peak values.



#### - Variant Model (MKB420-A11)

Radiated Emissions			Ant	Correction Factors		Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP + CL (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
33.92	47.20	Peak	V	16.58	-27.75	36.03	40.00	3.97
76.17	43.30	Quasi Peak	V	13.27	-27.18	29.39	40.00	10.61
112.90	44.90	Peak	V	17.12	-26.83	35.19	43.50	8.31
135.08	48.30	Peak	H	14.09	-26.61	35.78	43.50	7.72
195.35	44.60	Peak	V	17.14	-26.38	35.36	43.50	8.14
327.06	39.40	Peak	H	19.78	-25.51	33.67	46.00	12.33
Above 400.00	Not detected	-	-	-	-	-	-	-

#### Remark;

1. Spurious emissions for all channels were investigated and almost the same below 1 GHz.
2. Reported spurious emissions are in **PHY 1M / 37 bytes / Middle channel** as worst case among other channels.
3. Radiated spurious emission measurement as below.  
(Actual = Reading + AF + AMP + CL)
4. According to §15.31(o), emission levels are not report much lower than the limits by over 20 dB.

### - Test plots




**- Variant Model (MKB420-A12)**

Radiated Emissions			Ant	Correction Factors		Total	Limit	
Frequency (MHz)	Reading (dB $\mu$ V)	Detect Mode	Pol.	AF (dB/m)	AMP + CL (dB)	Actual (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
33.64	47.50	Peak	V	16.53	-27.75	36.28	40.00	3.72
73.25	47.70	Peak	V	14.13	-27.19	34.64	40.00	5.36
115.56	43.40	Peak	H	16.79	-26.82	33.37	43.50	10.13
183.22	48.00	Peak	V	15.60	-26.45	37.15	43.50	6.35
282.08	40.20	Peak	H	18.78	-25.80	33.18	46.00	12.82
480.04	33.10	Peak	H	22.70	-26.06	29.74	46.00	16.26
Above 500.00	Not detected	-	-	-	-	-	-	-

**Remark;**

1. Spurious emissions for all channels were investigated and almost the same below 1 GHz.
2. Reported spurious emissions are in **PHY 1M / 37 bytes / Middle channel** as worst case among other channels.
3. Radiated spurious emission measurement as below.  
(Actual = Reading + AF + AMP + CL)
4. According to §15.31(o), emission levels are not report much lower than the limits by over 20 dB.

**- Test plot**





### 2.4.2. Radiated Spurious Emission above 1 000 MHz

The frequency spectrum above 1 000 MHz was investigated. All reading values are peak and average values.

#### - Variant Model (MKB420-A11)

Low Channel (2 402 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
*2 310.00	15.14	Peak	H	27.80	6.37	-	49.31	74.00	24.69
*2 310.00	5.43	Average	H	27.80	6.37	2.08	41.68	54.00	12.32
*2 318.26	17.20	Peak	H	27.80	6.36	-	51.36	74.00	22.64
*2 338.17	6.08	Average	H	27.80	6.39	2.08	42.35	54.00	11.65
*2 390.00	15.75	Peak	H	28.04	6.63	-	50.42	74.00	23.58
*2 390.00	5.72	Average	H	28.04	6.63	2.08	42.47	54.00	11.53

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
*4 804.34	49.58	Peak	V	32.62	-35.59	-	46.61	74.00	27.39
7 206.87	53.83	Peak	V	35.73	-33.03	-	56.53	74.00	17.47
*12 011.01	41.94	Peak	H	38.50	-31.32	-	49.12	74.00	24.88
Above 12 100.00	Not detected	-	-	-	-	-	-	-	-

Middle Channel (2 440 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
*4 880.30	47.45	Peak	V	32.86	-35.66	-	44.65	74.00	29.35
*7 320.59	51.19	Peak	V	36.04	-32.49	-	54.74	74.00	19.26
*7 319.50	44.95	Average	V	36.04	-32.48	2.08	<b>50.59</b>	54.00	3.41
*12 198.78	41.29	Peak	H	38.40	-29.06	-	50.63	74.00	23.37
Above 12 200.00	Not detected	-	-	-	-	-	-	-	-

High Channel (2 480 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB $\mu$ V)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	DF (dB)	Actual (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
*2 483.50	16.67	Peak	H	28.13	6.35	-	51.15	74.00	22.85
*2 483.50	6.04	Average	H	28.13	6.35	2.08	42.60	54.00	11.40
*2 491.05	18.73	Peak	H	28.12	6.34	-	53.19	74.00	20.81
*2 495.35	6.14	Average	H	28.11	6.33	2.08	42.66	54.00	11.34
*2 500.00	17.08	Peak	H	28.10	6.32	-	51.50	74.00	22.50
*2 500.00	6.16	Average	H	28.10	6.32	2.08	42.66	54.00	11.34

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB $\mu$ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
*4 960.46	51.49	Peak	V	33.00	-35.54	-	48.95	74.00	25.05
*7 439.38	47.91	Peak	V	36.00	-32.30	-	51.61	74.00	22.39
*12 398.76	41.31	Peak	H	38.40	-27.63	-	52.08	74.00	21.92
Above 12 400.00	Not detected	-	-	-	-	-	-	-	-

**- Variant Model (MKB420-A12)**

Low Channel (2 402 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB $\mu$ V)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	DF (dB)	Actual (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
*2 310.00	15.32	Peak	V	27.80	6.37	-	49.49	74.00	24.51
*2 310.00	5.35	Average	V	27.80	6.37	2.08	41.60	54.00	12.40
*2 320.22	17.66	Peak	V	27.80	6.36	-	51.82	74.00	22.18
*2 376.18	6.12	Average	V	27.96	6.51	2.08	42.67	54.00	11.33
*2 390.00	16.28	Peak	V	28.04	6.63	-	50.95	74.00	23.05
*2 390.00	5.68	Average	V	28.04	6.63	2.08	42.43	54.00	11.57

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB $\mu$ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
*4 803.60	58.71	Peak	H	32.61	-35.59	-	55.73	74.00	18.27
*4 803.72	53.46	Average	H	32.61	-35.59	2.08	<b>52.56</b>	54.00	1.44
7 206.72	54.75	Peak	H	35.73	-33.03	-	57.45	74.00	16.55
Above 7 300.00	Not detected	-	-	-	-	-	-	-	-

Middle Channel (2 440 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB $\mu$ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
*4 879.45	53.69	Peak	H	32.86	-35.66	-	50.89	74.00	23.11
*7 319.96	51.73	Peak	H	36.04	-32.48	-	55.29	74.00	18.71
*7 319.50	45.28	Average	H	36.04	-32.48	2.08	50.92	54.00	3.08
Above 7 400.00	Not detected	-	-	-	-	-	-	-	-

High Channel (2 480 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
*2 483.50	16.11	Peak	V	28.13	6.35	-	50.59	74.00	23.41
*2 483.50	5.52	Average	V	28.13	6.35	2.08	42.08	54.00	11.92
*2 490.41	17.48	Peak	V	28.12	6.34	-	51.94	74.00	22.06
*2 493.65	6.51	Average	V	28.11	6.33	2.08	43.03	54.00	10.97
*2 500.00	16.16	Peak	V	28.10	6.32	-	50.58	74.00	23.42
*2 500.00	5.88	Average	V	28.10	6.32	2.08	42.38	54.00	11.62

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
*4 960.57	52.63	Peak	H	33.00	-35.54	-	50.09	74.00	23.91
*7 440.04	48.70	Peak	H	36.00	-32.30	-	52.40	74.00	21.60
Above 7 500.00	Not detected	-	-	-	-	-	-	-	-


**Remarks;**

1. "\*" means the restricted band.
2. Measuring frequencies from 1 GHz to the 10<sup>th</sup> harmonic of highest fundamental frequency.
3. Radiated emissions measured in frequency above 1 000 MHz were made with an instrument using peak/average detector mode.
4. Actual = Reading + AF + CL + (DF) or Reading + AF + AMP + CL + (DF).
5. According to § 15.31(o), emission levels are not reported much lower than the limits by over 20 dB.
6. The maximized peak measured value complies with the average limit, to perform an average measurement is unnecessary.
7. AF = Antenna Factor, CL = Cable Loss, DF = Duty Correction Factor.


- Test plots

- Variant Model (MKB420-A11)


Low channel band edge (Peak)




Low channel band edge (Average)




Low channel 2<sup>nd</sup> Harmonics (Peak)




Low channel 3<sup>rd</sup> Harmonics (Peak)




Low channel 5<sup>th</sup> Harmonics (Peak)




Middle channel 2<sup>nd</sup> Harmonics (Peak)



Middle channel 3<sup>rd</sup> Harmonics (Peak)




Middle channel 3<sup>rd</sup> Harmonics (Average)




Middle channel 5<sup>th</sup> Harmonics (Peak)




High channel band edge (Peak)




High channel band edge (Average)




High channel 2<sup>nd</sup> Harmonics (Peak)



High channel 3<sup>rd</sup> Harmonics (Peak)




High channel 5<sup>th</sup> Harmonics (Peak)




**- Variant Model (MKB420-A12)**


Low channel band edge (Peak)




Low channel band edge (Average)




Low channel 2<sup>nd</sup> Harmonics (Peak)



Low channel 2<sup>nd</sup> Harmonics (Average)




Low channel 3<sup>rd</sup> Harmonics (Peak)






Middle channel 2<sup>nd</sup> Harmonics (Peak)




Middle channel 3<sup>rd</sup> Harmonics (Peak)




Middle channel 3<sup>rd</sup> Harmonics (Average)




High channel band edge (Peak)




High channel band edge (Average)



High channel 2<sup>nd</sup> Harmonics (Peak)



High channel 3<sup>rd</sup> Harmonics (Peak)



### **3. Antenna Requirement**

#### **3.1. Standard Applicable**

For intentional device, according to FCC 47 CFR Section §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. And according to FCC 47 CFR Section §15.247(b) if transmitting antennas of directional gain greater than 6 dB i are used, the power shall be reduced by the amount in dB that the gain of the antenna exceeds 6 dB i.

#### **3.2. Antenna Connected Construction**

Antenna used in this product is SMD antenna with gain of 1.5 dB i.

**- End of the Test Report -**