

# FCC ID: 2AB7K-T2103

## RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposure</b>				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f <sup>2</sup>	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz \* = Plane-wave equivalent power density

## MPE Calculation Method

Friis transmission formula:  $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

$P_d$  = Power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

$G$  = Numeric gain of the antenna relative to isotropic antenna

$\pi$  = 3.14115926

$R$  = distance between observation point and center of the radiator in cm (20cm)

$P_d$  the limit of MPE, 1mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

## Measurement Result

### WIFI:

Operation Frequency: WIFI 802.11b/g/n HT20: 2412-2462MHz,  
HT40:2422-2452MHz

Power density limited: 1mW/ cm<sup>2</sup>

Antenna Type: PCB Antenna;

WIFI antenna gain: 4dBi (ANT A);

R=20cm

$mW=10^{(dBm/10)}$

antenna gain Numeric= $10^{(dBi/10)}=10^{(4/10)}=2.51$

Channel Freq. (MHz)	modulation	conducted power	Tune-up power	Max		Antenna	Evaluation result at 20cm	Power density Limits
		(dBm)	(dBm)	tune-up power		Gain	Power density(mW/cm <sup>2</sup> )	(mW/cm <sup>2</sup> )
		Ant A	Ant A	(dBm)	(mW)	Numeric		
2412	802.11b	15	15±1	16	39.810717	2.51	0.01988	1
2437		15.6	15±1	16	39.810717	2.51	0.01988	1
2462		16	15±1	16	39.810717	2.51	0.01988	1
2412	802.11g	10.4	11±1	12	15.848932	2.51	0.00791	1
2437		11	11±1	12	15.848932	2.51	0.00791	1
2462		11.5	11±1	12	15.848932	2.51	0.00791	1
2412	802.11n H20	9.2	10±1	11	12.589254	2.51	0.00629	1
2437		9.6	10±1	11	12.589254	2.51	0.00629	1
2462		9.9	10±1	11	12.589254	2.51	0.00629	1
2422	802.11n H40	9.4	10±1	11	12.589254	2.51	0.00629	1
2437		9.6	10±1	11	12.589254	2.51	0.00629	1
2452		9.7	10±1	11	12.589254	2.51	0.00629	1

### Conclusion:

For the max result : 0.01988≤ 1.0 for 1g SAR, No SAR is required.

*Jason chen*

**Signature:**

**Date:** 2017-06-09

NAME AND TITLE (Please print or type): Jason Chen/Manager

**COMPANY** (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen 518126P.R. China.