

# ACER COMMERCIAL TOP SELLER LCD LINEUP

## VALUE



Model	V227Q BBI	V227Q BBMIPX	V247Y ABI	V247Y ABIPX	V277 BIX
Part#	UM.WV7AA.B01	UM.WV7AA.B03	UM.QV7AA.A01	UM.QV7AA.A02	UM.HV7AA.009
Display size (ratio)	22" wide	22" wide	23.8" wide	23.8" wide	27" wide
Max resolution	1920 x 1080	1920 x 1080	1920 x 1080	1920 x 1080	1920 x 1080
Brightness	250 cd/m <sup>2</sup>	250 cd/m <sup>2</sup>	250 cd/m <sup>2</sup>	250 cd/m <sup>2</sup>	250 cd/m <sup>2</sup>
Response time (typical)	4ms gray-to-gray	4ms gray-to-gray	4ms gray-to-gray	4ms gray-to-gray	4ms gray-to-gray
Signal connectors (cables included)	HDMI <sup>®</sup> 1.4	HDMI <sup>®</sup> 1.4, DisplayPort <sup>™</sup> 1.2	HDMI <sup>®</sup> 1.4	HDMI <sup>®</sup> 1.4	VGA, HDMI <sup>®</sup> 1.4, Audio out with one VGA cable
Signal connectors (no cables)	VGA	VGA, audio-in, audio-out	VGA	VGA, DisplayPort <sup>™</sup>	HDMI <sup>®</sup> 1.4
Integrated Speakers	n/a	2 x 2.0W	n/a	n/a	n/a
Height Adjustment	n/a	n/a	n/a	n/a	n/a
VESA Mount Supported	100 x 100	100 x 100	100 x 100	100 x 100	100 x 100



Model	V277 BMIPX	V277U BMIPX
Part#	UM.HV7AA.001	UM.HV7AA.003
Display size (ratio)	27" wide	27" wide
Max resolution	1920 x 1080	2560 x 1440
Brightness	250 cd/m <sup>2</sup>	350 cd/m <sup>2</sup>
Response time (typical)	4ms gray-to-gray	4ms gray-to-gray
Signal connectors (cables included)	VGA, DisplayPort <sup>™</sup> , audio-in and audio-out with one cable	DisplayPort <sup>™</sup> 1.2
Signal connectors (no cables)	HDMI <sup>®</sup> 1.4	Audio-out, two HDMI <sup>®</sup>
Integrated Speakers	2 x 2.0W	2 x 2.0W
Height Adjustment	n/a	n/a
VESA Mount Supported	100 x 100	100 x 100



# ACER COMMERCIAL TOP SELLER LCD LINEUP

## MAINSTREAM



Model	B227Q BMIPRZX	B247Y BMIPRZX	B277 BMIPRZX	B277U BMIIPPRZX	B287K BMIIPPRZX
Part#	UM.WB7AA.001	UM.QB7AA.001	UM.HB7AA.001	UM.HB7AA.003	UM.PB7AA.001
Display size (ratio)	21.5" wide	23.8" wide	27" wide	27" wide	28" wide
Max resolution	1920 x 1080	1920 x 1080	1920 x 1080	2560 x 1440	3840 x 2160
Brightness	250 cd/m <sup>2</sup>	250 cd/m <sup>2</sup>	250 cd/m <sup>2</sup>	350 cd/m <sup>2</sup>	300 cd/m <sup>2</sup>
Response time (typical)	4ms gray-to-gray	4ms gray-to-gray	4ms gray-to-gray	4ms gray-to-gray	4ms gray-to-gray
Signal connectors (cables included)	VGA, DisplayPort™ 1.2, USB 3.0 hub (one up, four down)	VGA, DisplayPort™ 1.2, USB 3.0 hub (one up, four down)	VGA, DisplayPort™ 1.2, USB 3.0 hub (one up, four down)	DisplayPort™ 1.2, two HDMI® with one cable, USB 3.0 hub (one up, four down) with one cable	Two HDMI®, USB3.0x4 (1up 4down)
Signal connectors (no cables)	HDMI®, audio-in, audio-out, speaker	HDMI®, audio-in, audio-out, speaker	HDMI®, audio-in, audio-out, speaker	Mini DisplayPort™	Mini DisplayPort™, DisplayPort(1.2), audio-out, Speaker
Integrated Speakers	2 x 2.0W	2 x 2.0W	2 x 2.0W	2 x 2.0W	2 x 2.0W
Height Adjustment	120mm	120mm	120mm	120mm	120mm
VESA Mount Supported	100 x 100	100 x 100	100 x 100	100 x 100	100 x 100

## FLAGSHIP



Model	B248Y BEMIQPRCUX	CB273U BEMIPRUZX	CB322QK SEMIPRUZX	CB342CUR BMIIPHUZX	CB382CUR BMIIPHUZX
Part#	UM.QB8AA.001	UM.HB3AA.002	UM.JB2AA.003	UM.CB2AA.002	UM.TB2AA.001
Display size (ratio)	24" wide	27" wide	31.5" wide	34" wide	37.5" wide
Max resolution	1920 x 1080	2560 x 1440	3840 x 2160	3440x1440	3840x1600
Brightness	250 cd/m <sup>2</sup>	350 cd/m <sup>2</sup>	350 cd/m <sup>2</sup>	300 cd/m <sup>2</sup>	300 cd/m <sup>2</sup>
Response time (typical)	4ms gray-to-gray	1ms (VRB)	4ms gray-to-gray	1ms (VRB)	1ms (VRB)
Signal connectors (cables included)	HDMI®, USB 3.0 hub (one up, three down), Type-C (PD 100W)	HDMI®, USB 3.0 hub, Type-C (PD 90W)	Two HDMI® 2.0 (with one cable), Type-C (65W), two USB 3.0 (with one cable)	HDMI 2.0 x 2 (with one cable), Type-C (90W) x 1 (with one cable)	HDMI 2.0 x 2 (with one cable), Type-C (90W) x 1 (with one cable), USB 3.0 x 4 (with one cable)
Signal connectors (no cables)	DisplayPort™ 1.2, DP out, RJ45, Speaker, audio-out, USB-B (2up 4down), FHD webcam with microphone	DisplayPort™ 1.2	DisplayPort™ 1.2, USB-B (two up one down), RJ45, Audio out	DisplayPort, Audio out, USB 3.0 x 4, USB-B (2up 4down)	DP, Audio out
Integrated Speakers	2 x 2.0W	2 x 2.0W	2 x 2.0W	2 x 7W	2 x 7.0W
Height Adjustment	150mm	120mm	150mm	150mm	150mm
VESA Mount Supported	100 x 100	100 x 100	100 x 100	100 x 100	100 x 100