



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: U244-001-VGA-R

USB 2.0 to VGA Adapter



Highlights

- Add an additional VGA monitor through a single USB 2.0 port
- Supports Extended Desktop Display
- Supports video resolutions up to 1920 x 1080 (60Hz), 1080p (60Hz)
- Supports Aero themes in Windows
- Compatible with Windows 2000 and later, and Mac OS X 10.4 and later

Description

Tripp Lite's U244-001-VGA-R, USB to VGA Display Adapter, enables you to connect an additional monitor or projector to a computer/laptop USB 2.0 port. Up to six U244-001-VGA-R adapters can be used simultaneously, allowing the user to connect up to six additional monitors to a single computer. Once the installation is done, the computer screen appears on the add-on monitor(s) without the hassle of function keys to swap to a second monitor. The U244-001-VGA-R chip-set supports video resolutions up to 1920 x 1080 (60Hz), 1080p (60Hz). The U244-001-VGA-R is compatible with Windows 2000 and later, and Mac OS X 10.4 and later operating systems.

Applications

Office workstation

- View large spreadsheets across multiple screens
- Multitask more effectively without overlapping windows
- Edit on one screen while surfing the Internet for information on the other

On the road

- Do multiple screen presentations without bringing another computer
- Easily provide multiple screen exhibitions in a trade show

Graphics workstation

- Use second display for palettes/tools
- et a panoramic view of large documents

Editing workstation

- Type documents on one screen while viewing reference material on the other
- Compare two documents simultaneously across two screens

Financial analysis

- Have one monitor per data stream
- View charts and live data at the same time

Entertainment

- View videos/TV on one screen and reviews on the other
- Get additional perspectives when playing games

System Requirements

- USB 2.0 port
- Computer running Windows 2000 or later, or an Intel-based Mac running OS X 10.4 or later. Power PC-based Macs are not supported.

- Supports Surface Pro tablets running Windows 8 Pro and Surface Pro 2 tablets running Windows 8.1 Pro
- VGA monitor

Computer requirements when using 1 to 2 display adapters:

- 1.2GHz Single-Core CPU
- 512MB memory

Computer requirements when using 3 display adapters:

- 1.8GHz Single-Core CPU
- 1GB memory

Computer requirements when using 4 to 6 display adapters:

- 1.6GHz Core-Duo CPU
- 1GB memory

Note: Only 1 added monitor can support DVD playback. In order to support DVD playback, your computer must meet the following requirements:

- 2.0GHz Core-Duo CPU
- 1GB memory
- Adapter screen resolution must be set to 800 x 600 with 16-bit color



Package Includes

- U244-001-VGA-R USB to VGA display adapter
- 3 ft. USB Cable
- Quick Start Guide
- Driver CD with Owner's Manual

Features

- Add an additional VGA monitor through a single USB 2.0 port
- Hot pluggable; add or remove a monitor without the need for a system reboot
- Use up to six adapters simultaneously, adding up to six additional monitors to a single computer
- View large spreadsheets across multiple screens by extending video amongst all monitors
- Play video on one monitor while working on another
- Do multiple screen presentations from a laptop computer
- Bus powered...no external power adapter needed
- Features 128MB DDR SDRAM of memory
- Supports video resolutions up to 1920 x 1080 (60Hz), 1080p (60Hz)
- Supports Aero themes in Windows
- Compatible with Windows 2000 and later, and Mac OS X 10.4 and later
- Supports Surface Pro tablets running Windows 8 Pro and Surface Pro 2 tablets running Windows 8.1 Pro

Specifications

OVERVIEW	
Display Style	Adapter
CONNECTIONS	
Connector A	 USB MINI-B 5-PIN (FEMALE)
Connector B	 HD15 (FEMALE)
WARRANTY	

**Product Warranty Period
(Worldwide)**

1-year limited warranty

Related Items

Optional Products

Related Model	Description	Qty.
P502-003	3-ft. SVGA/VGA Monitor Cable with RGB Coax (HD15 M/M)	1
P502-006	6-ft. SVGA/VGA Monitor Cable with RGB Coax (HD15 M/M)	1
P502-010	10-ft. SVGA/VGA Monitor Cable with RGB Coax (HD15 M/M)	1
U244-001-R	USB2.0 to DVI and VGA Adapter	1
U244-001-HDMI-R	USB2.0 to HDMI Adapter	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=4917.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.