



# Vehicle Recovery and Fleet Management

Maximize efficiency. Minimize risks. Manage assets.



## AT10

### HIGHLIGHTS

The AT10 tracker is a real-time vehicle tracking system designed for vehicle recovery, fleet management, and more..

#### IT'S RELIABLE

The ultra-thin yet durable AT10 is a high-performance cellular tracking device designed for vehicle financing, vehicle tracking, lot management, theft recovery, or other fleet applications. With an integrated GNSS receiver, the AT10 includes an LTE Cat-M (or NB-IoT) modem for wireless data communication. The built in high performance antennas for both cellular radio and GNSS receivers make installation easy.

#### IT'S SIMPLE

No programming skills required; the AT10 comes with easy-to-configure application software and an extended AT command set. Reports can be triggered periodically or in response to events such as motion, speeding, harsh acceleration and braking, geo-fence violations, and battery status. Notifications can be sent for vehicle towing, battery removal, and more.

#### IT'S FUNCTIONAL

The AT10 interface supports serial communication with external terminals and devices, as well as IO options dedicated to ignition, starter inhibit, and buzzer.

A built in 3-axis accelerometer enables motion detection and monitoring of driver behavior. An internal Lithium-Ion backup battery allows for continuous operation for up to 4 hours when the device is disconnected from the main power. An optional buzzer alert system for driver warnings is available inside the unit.

- LTE Cat-M1, NB-IoT & GPRS
- Integrated cellular and GNSS antenna
- LED status indicators for GNSS and network registration
- Integrated accelerometer for monitoring vehicle status & driver behavior
- I/O options for starter inhibit, ignition, and buzzer
- BLE5.0 support, low power consumption
- Rechargeable backup battery
- SMS, UDP, TCP, FTP & MQTT
- Up to 16 Geo-fences (polygons and circles)
- Over the air configuration and firmware update
- Extended AT Command set for flexible and easy configuration
- Small size and easy installation
- OPTIONAL FEATURES
  - Internal Buzzer

*The application firmware is flexible and can be customized to be compatible with your existing server at special request.*



## Specifications:

### CELLULAR

- LTE Cat-M1, NB-IoT
- LTE-FDD Bands : 1/2/3/4/5/8/12/13/17/18/19/20/25/26/28
- LTE-TDD B39 (For Cat.M1 only)
- GSM:850/900/1800/1900
- Integrated high performance antenna

### GNSS

- GPS, GLONASS, Beidou & Galileo
- Tracking Sensitivity : -161 dBm
- Acquisition Sensitivity : -146 dBm
- Location Accuracy : < 2.5CEP

### BATTERY INFORMATION

- Type : Li-ION
- Capacity : 80mAh @ 3.7V
- Battery Life : Up to 4hours @ hibernation mode, 1 report per hour.(depends on the LTE signal strength and how many reports per hour)

### ENVIRONMENTAL

- Operation Temperature: -30°C to +75°C without Battery
- Operation Temperature: -20°C to +60°C With Battery
- Storage Temperature: -40°C to +85°C

### ELECTRICAL

- Operating Voltage: 8V – 36V
- Over voltage protected
- Over current protected with resettable fuse
- Power Consumption:
  - ✓ GPS Acquisition : ~ 48mA @ 12V
  - ✓ GPS Tracking/Reporting : ~ 74mA @ 12V
  - ✓ Sleep mode : < 1mA @12V

### BLUETOOTH

- BLE 5.0, low power consumption

### PHYSICAL

- Dimensions: 85.5 x 47.5 x 12.5 mm
- Internal Cellular and GPS Antennas
- Weight : ~80g

### INTERFACE CONNECTORS

- Cable Harness :
  - 10-Pin built-in flat Cable
  - ✓ PWR, GND (\*2)
  - ✓ UART (RX/TX) (\*2)
  - ✓ I/Os : Ignition, starter inhibit (Sink current 500mA Relay driver) and GPIOs (\*6)

### APPROVALS

- FCC 47 CFR Part 22, and Part 24
- PTCRB & Carrier Approved

## Asiatelco Technologies Inc. (ATEL)

**Asiatelco** is the leading provider of wireless terminal products to its value customers worldwide. Its innovative products and solutions are widely used for reliable broadband access, IoT/M2M applications and voice communication with 4G LTE, 3G & 2G wireless technologies. ATEL's sales and marketing are globally positioned. It has become globally well-known company in the wireless industry due to its excellent products, solutions and services.. For more information, contact Asiatelco Technologies Inc.

#### FCC Regulations:

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
  - Increase the separation between the equipment and receiver.
  - Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
  - Consult the dealer or an experienced radio/ TV technician for help.
- Changes or modifications not expressly approved by the manufacturer could void the user's authority to operate the equipment.