# FRIGIDAIRE

**Electrical Specifications** 

### FFAD5033W1E

#### **Available Colors : White**

Version: 03/20

### Dehumidifier

High Humidity 50 Pint Capacity Dehumidifier



## **Product Specifications**

### **Functions**

24-Hour On/Off Timer	Yes
Auto Restart	Yes
Auto Shut-Off	Yes
Continuous Drain Operation	Yes
Dehumidifier	
Air CFM (High)	229
Air CFM (Low)	167
Air CFM (Med)	194
Container Capacity (Pints)	16.9
Container Full Indication	Yes
Digital Humidity Readout	Yes
Fan Speeds - Fan	3
Filter Access	Rear of Unit
Filter Check Indicator	Yes
Filter Type	Easy-to-Clean Washable Filter
Low Temperature Operation	Yes
Motor RPM (High)	1160
Motor RPM (Low)	880
Motor RPM (Med)	980
Noise Level dB (High)	51
Noise Level dB (Low)	47
Noise Level dB (Med)	49

Electrical opecifications		
Amps	5.2	
Plug Type	LCDI 5-15P	
Power Cord Length	6'	
Voltage Rating	115	
Watts	545	
Certifications & Approvals		
ENERGY STAR® Certified	Yes	
Energy Efficiency Verification	Yes	
ISTA 6	Yes	
UL Listed	Yes	
cUL Listed	Yes	
Controls		
Control Type	Electronic	
Performance		
DOE Rating	Yes	
Dehumidification - Pints per Day	50	
Dimensions		
Depth	12.19"	
Height	24.25"	
Width	15.96"	
General Specifications		
Prop 65 Label	Yes	
Refrigerant Type	R410a	
Stack Height	6	
40 HQ Stuffing Quantity	663	
Warranty - Labor	1 yr Full	

Note: For planning purposes only. Always consult local and national electric, gas and plumbing code Refer to Product Installation Guide for detailed installation instructions on the web at frigidaire.com / frigidaire Specifications subject to change. Accessories information available on the web at frigidaire.com / frigidaire

USA + 10200 David Taylor Drive + Charlotte, NC 28262 + 1-800-FRIGIDAIRE + frigidaire.com CANADA + 5855 Terry Fox Way + Mississauga, ON L5V 3E4 + 1-800-265-8352 + frigidaire.ca

FRIGIDAIRE -