

Declaration of Electromagnetic Field Health Compliance

To whom it may concern,

As to the product **eBox-S** made by Huawei Technologies Co., Ltd., we declare that it complies with the Basic restrictions/Reference levels for electric, magnetic and electromagnetic fields as specified in following standards(s):

Nr.	Standard
1	47CFR FCC Part 1 (10-1-13 Edition) & OET Bulletin 65
2	RSS-102 (Issue4, March 2010)

The compliance is demonstrated based on the following calculation model assessment:

- The power density according to far-field model is:

$$S = \frac{P \times G_{(\theta, \phi)}}{4 \times \pi \times R^2}$$

Where:

P = input power of the antenna.

G = antenna gain relative to an isotropic antenna.

θ, ϕ = elevation and azimuth angles.

R = distance from the antenna to the point of investigation.

- For single or multiple RF sources, the calculated power density should comply with following:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

Where:

S_i = the power density when the f is i .

$S_{Limit,i}$ = the reference level requirement for power density when f is i .

- The calculation of the power density or safe distance is:

NOTE 1: The RF exposure evaluation is base on the far-field and the radiation exposure is over-estimated.

NOTE 2: The maximum output power level is taken into account as a worst case for the purpose of the calculation of power density or safe distance.


NOTE 3: The minimum antenna feed cable loss (assumed no cable loss) is taken into account as a worst case for the purpose of the calculation of power density or safe distance.

NOTE 4: The maximum antenna radiation exposure orientation and maximum antenna gain is taken into account as a worst case for the purpose of the calculation of power density or safe distance.

RF Source	Calculation
RF Source #1 (IEEE 802.15.4)	f = 2400 to 2483.5 MHz
	$S_{Limit,i}$ = 10 W/m ²
	P = 0.0008 W (= -1.0 dBm, measured max peak value)

RF Source	Calculation
	$G_{(\theta,\phi)} = 3.388 (= 5.3 \text{ dBi, rated max})$ $\theta, \phi = \text{The worst condition is considered, i.e. the max } G \text{ is used.}$ $R \geq 0.2 \text{ m}$ $S_i \leq \frac{P \times G_{(\theta,\phi)}}{4 \times \pi \times R^2} = 0.005 \text{ W/m}^2$ $\frac{S_i}{S_{Limit,i}} \leq 0.005$
RF Source(s) Combination	$\sum_i \frac{S_i}{S_{Limit,i}} \leq 0.0005 \text{ (Less than 1, so complied)}$
NOTE:	Actually, the exposure can be considered as “low power / inherently compliant” without testing based on that the emissions is limited to a level that cannot exceed the basic restriction.

Person responsible for making this declaration:



Zhang Weimin

RF Engineer, EMC Lab

Reliability Laboratory of Huawei Technologies Co., Ltd.

September 22, 2014